

Estimation of Greenhouse Gas Emissions

Recommended Methods for Selected Stationary Source Categories

Last Updated February 3, 2014



Iowa Department of Natural Resources
Air Quality Bureau
7900 Hickman Rd, Suite 1
Windsor Heights, IA 50324

Contact:
Marnie Stein
515-725-9555 - Marnie.Stein@dnr.iowa.gov

Table of Contents

Table of Contents.....	3
Table of Figures.....	4
Acronyms and Key Terms.....	5
Chapter 1: Introduction	6
Chapter 2: Emissions Estimation Methods.....	7
Chapter 3: Stationary Fossil Fuel Combustion Sources	10
Chapter 4: CO ₂ , CH ₄ , and N ₂ O Emissions from Industrial and Other Source Categories.....	15
Chapter 5: Fluorinated Gases (HFC, PFC, and SF ₆).....	17
Chapter 6: Converting to Carbon Dioxide Equivalent (CO ₂ e)	19
References	21
Glossary.....	22
Appendix A – Units of Measure Conversions	25
Appendix B – 40 CFR 98 Subparts.....	26

Table of Figures

Table 1 – Tiers in 40 CFR 98 Subpart C	10
Table 2 - Default CO ₂ Emission Factors and High Heat Values for Various Types of Fuel	11
Table 3 - Default CH ₄ and N ₂ O Emission Factors for Various Types of Fuel	13
Table 4 – Recommended Emission Estimated Methods for Industrial and Other Source Categories.....	15
Table 5 – Recommended Emission Estimation Methods for HFC, PFC, and SF ₆	17
Table 6 - Global Warming Potentials of Common Greenhouse Gases	19

Acronyms and Key Terms

ASTM	American Society for Testing and Materials
CEM	Continuous Emissions Monitor
CH ₄	Methane
CO	Carbon Monoxide
CO ₂	Carbon Dioxide
CO ₂ e	Carbon Dioxide Equivalent
DNR	Iowa Department of Natural Resources
DSCFM	Dry Standard Cubic Feet per Minute
EIIP	Emission Inventory Improvement Program
EPA	Environmental Protection Agency
GHG	Greenhouse Gas
GHGRP	Greenhouse Gas Reporting Program
GWP	Global Warming Potential
HAP	Hazardous Air Pollutant
HFC	Hydrofluorocarbons
HFE	Hydrofluorinated ethers
IAC	Iowa Administrative Code
IPCC	Intergovernmental Panel on Climate Change
LBS	Pounds
LPG	Liquefied Petroleum Gas
MMBtu	Million British Thermal Units
MMcf	Million Cubic Feet
MMscf	Million Standard Cubic Feet
mtCO ₂ e	Metric Tons of Carbon Dioxide Equivalent
NACAA	National Association of Clean Air Agencies
N ₂ O	Nitrous Oxide
NF ₃	Nitrogen Trifluoride
NO _x	Nitrogen Oxides
PFC	Perfluorocarbons
PSD	Prevention of Significant Deterioration
SCF	Standard Cubic Feet
SF ₆	Sulfur Hexafluoride
STAAPA/ALAPCO	State and Territorial Air Pollution Program Administrators/Association of Local Air Pollution Control Officers (now known as NACAA)

Chapter 1: Introduction

Purpose

This document provides guidance for estimating greenhouse gas emissions from select stationary sources. It is intended to reflect the most recent information on data sources, emission factors, and methods that are consistent with EPA guidance. There are several different chemicals considered greenhouse gases. 567 IAC 20.2 defines greenhouse gas as meaning:

- Carbon dioxide (CO₂)
- Methane (CH₄)
- Nitrous oxide (N₂O)
- Hydrofluorocarbons (HFC)
- Perfluorocarbons (PFC)
- Sulfur hexafluoride (SF₆)

Emission estimate methods discussed in this document consider stationary source emissions only. It does not cover emissions from fuel suppliers or any sources such as vehicle miles traveled, offsite waste disposal, or electricity consumption.

This document does not mandate the use of specific estimation methods, but recommends appropriate emission factors and estimation methods. It is intended to be a living document which the DNR plans to periodically update to incorporate new or updated emission factors and methods as they become available. Suggest uses of the document by facilities may include:

- Calculating actual emissions to determine if a facility is subject to the federal Greenhouse Gas Reporting Program (GHGRP).
- Calculating potential emissions for Iowa DNR construction permit applications.
- Calculating potential emissions to evaluate program applicability for permit programs such as Title V and Prevention of Significant Deterioration (PSD).

To stay informed of important updates, please visit the [Air Quality Bureau's webpage](#). Additionally, you may wish to subscribe to the "IAirTech" list serve, which delivers regulatory news, program updates, and technical guidance directly to your email. To subscribe, send a blank E-mail to: join-iairtech@lists.ia.gov. The subject line should remain blank.

Chapter 2: Emissions Estimation Methods

This chapter provides a general overview of available methods for estimating emissions. For greenhouse gas emissions, EPA states that the estimation methods prescribed in the federal [Mandatory Reporting of Greenhouse Gases](#)¹ rule (also known as the Greenhouse Gas Reporting Program (GHGRP)) should be used as a primary reference in emissions inventories and permit applications.² This document is consistent with EPA's recommendation and discusses estimation methods for specific source categories in Chapters 3, 4, and 5 of this document. Additional resources for estimation methods are listed at the end of this chapter.

When selecting the method used to calculate emissions, it is important to understand the difference between potential and actual emissions. In general, **potential emissions** reflect the emissions that will occur if an emission unit is operated at its maximum design rate for an entire year (8,760 hours). Federal enforceable limits may be used to reduce the calculated potential emissions. Examples of federally enforceable limits found in permits include restrictions on the amount of fuel burned, hours operated, or raw material processed. **Actual emissions** are the actual rate of pollutant emissions from an emission unit calculated using the emission unit's actual operating hours, production rates, and quantities of materials processed, stored, or combusted for the calendar year. Please refer to the definitions of both potential to emit and actual emissions from 567 IAC 22.100 located in the glossary of this document. Examples of both potential and actual emission calculations can be found on pages 13 – 14 of this document.

General Hierarchy

Emissions must be based on the best possible method and may vary between source categories. In general, DNR recommends that greenhouse gas emissions be calculated using the same hierarchy of estimation methods as used for criteria and hazardous air pollutants. The methods listed below are in order of decreasing accuracy. Supporting documentation that allows DNR to recreate your calculations should be included for any calculations that cannot be easily verified. Please note that CEM data and stack tests are measures of actual emissions during a specific time period.

1. **Continuous Emissions Monitoring (CEM)** systems directly measure pollutant concentrations in the exhaust stack 24 hours a day. This is the most accurate method for determining actual emissions.

¹ §40 CFR 98.

² See "Resources for Estimating Greenhouse Gas Emissions" on <http://www.epa.gov/nsr/ghgresources.html>.

Most likely used for: CO₂ emissions from utilities, Portland cement plants, large combustion units, or other units with CEMs.

2. A **Stack Test** measures the concentration of pollutants in the exhaust stack during the test period. Stack test data can provide an accurate source-specific emission rate for many different processes and pollutants.

Most likely used for: CO₂ emissions from combustion sources and other process-related CO₂ emissions from specific source categories.

3. **Material Balance or Mass Balance** can only be used on specific types of emission units. Information must first be gathered on process rates, material used, and material properties (usually from **material safety data sheets** (MSDS)). By combining this information with the knowledge of the process, an emission estimation can be made.

Most likely used for: SF₆, HFC, and PFC emissions.

4. **Emission Factors** are the basis for many calculations. Emission factors represent industry averages and show the relationship between emissions and a measure of production. Emission factors for select industries and processes, as well as reference sources for additional information, are provided in this document.

Most likely used for: CO₂, CH₄, and N₂O emissions from fossil fuel combustion.

5. **Vendor Supplied Factors** may be used if a more preferred method is not available. This data may be used to calculate emissions if the manufacturer's data is based on approved stack testing and no significant changes have been made to the emission unit. Supporting documentation must be submitted to show how the estimation was made.
6. **Engineering Estimation** is allowed if a more preferred method is not available. Some processes may have no published guidance regarding the estimation of emissions. In these cases, the estimation must be the best possible assessment given the amount of data available. Supporting documentation must be submitted to show how the estimation was made.

Other Greenhouse Gas-Specific Resources

EPA has published a list on its New Source Review Website

(<http://www.epa.gov/nsr/ghgresources.html>) of resources that may prove useful to sources and permitting authorities in identifying, characterizing and estimating greenhouse gas emissions. The list includes:

- [Mandatory Reporting of Greenhouse Gases](#)
- [ENERGY STAR Industrial Sector Energy Guides and Plant Energy Performance Indicators \(benchmarks\)](#)
- [US EPA National Greenhouse Gas Inventory](#)
- [EPA's Climate Leaders Protocols](#)
- EPA's Voluntary Partnerships for Greenhouse Gas Reductions:
 - [Landfill Methane Outreach Program](#)
 - [CHP Partnership Program](#)
 - [Green Power Partnership](#)
 - [Coal bed Methane Outreach Program](#)
 - [Natural Gas STAR Program](#)
 - [Voluntary Aluminum Industrial Partnership](#)
- [SF₆ Emission Reduction Partnership for the Magnesium Industry](#)
- [PFC Reduction/Climate Partnership for the Semiconductor Industry](#)

Other sources include:

- [The Climate Registry Reporting Protocols](#)
- [The Greenhouse Gas Protocol Initiative](#)

Chapter 3: Stationary Fossil Fuel Combustion Sources

CO₂, N₂O, and CH₄ are all emitted from the combustion of fossil fuels from stationary sources. CO₂ is formed from the oxidation of the fuel carbon, CH₄ is a production of incomplete combustion, and N₂O is formed by oxygen-nitrogen reactions. DNR recommends that emissions of these pollutants be calculated using the estimation methods and emission factors in the federal Greenhouse Gas Reporting Program (GHGRP) in 40 CFR 98 Subpart C. This subpart includes four methods (called tiers) for calculating actual GHG emissions from stationary fossil fuel combustion sources:

Table 1 – Tiers in 40 CFR 98 Subpart C

Tier	Method
Tier 4	Calculate emissions using CEMs data.
Tier 3	Calculates emissions from solid and liquid fuels using annual average carbon content from fuel sampling and an annual average molecular weight for gaseous fuels.
Tier 2	Calculates emissions using an annual average high heat value (HHV) from fuel sampling and a default emission factor.
Tier 1	Calculates emissions using a default HHV and a default emission factor.

DNR does not require use of a specific tier method, but **actual** greenhouse gas emissions from stationary fossil fuel combustion should be calculated in a similar approach:

1. CEMs data. If not available then,
2. Stack test data. If not available then,
3. Fuel sampling data and a default emission factor. If not available then,
4. A default HHV and a default emission factor.

Potential greenhouse gas emissions should be calculated using the maximum design rate of the emission unit in conjunction with any federally enforceable permit limits and:

1. Fuel sampling data and a default emission factor. If not available then,
2. A default HHV and a default emission factor.

If using a default HHV or default emission factor to calculate potential or actual greenhouse gas emissions, use the value listed in Table C-1 and C-2 of 40 CFR 98 Subpart C. These tables have been included in this document for convenience as Tables 2 and 3. Conversions for units of measure can be found in Appendix A of this document. The DNR has also developed a spreadsheet-based calculation tool using these emission factors called "[Stationary Fossil Fuel Combustion Tool.xls](#)" that can be used to calculate both potential and actual emissions.

The 40 CFR 98 Subpart C CO₂ emission factors assume 100% of the carbon in the fuel is converted to CO₂. They are comparable to emission factors found in WebFIRE and to the emission factors that DNR used on its GHG reporting spreadsheets for 2007 – 2009, but vary slightly because of differences in the high heating values used to generate the emission factors. The 40 CFR 98 Subpart C CH₄ and N₂O emission factors are from Intergovernmental Panel on Climate Change (IPCC) estimation guidelines and are more conservative than their corresponding CH₄ and N₂O emission factors in AP-42 and WebFIRE, which are based on test data.

Table 2 - Default CO₂ Emission Factors and High Heat Values for Various Types of Fuel³

Fuel Type	Default High Heat Value (HHV)	Default CO ₂ emission factor	
		kg CO ₂ /MMBtu	lb CO ₂ /MMBtu ⁵
Coal and Coke	MMBtu/ton ⁴	kg CO ₂ /MMBtu	lb CO ₂ /MMBtu ⁵
Anthracite	25.09	103.69	228.60
Bituminous	24.93	93.28	205.65
Subbituminous	17.25	97.17	214.22
Lignite	14.21	97.72	215.44
Coal Coke	24.80	113.67	250.60
Mixed (Commercial sector)	21.39	94.27	207.83
Mixed (Industrial coking)	26.28	93.90	207.01
Mixed (Industrial sector)	22.35	94.67	208.71
Mixed (Electric Power sector)	19.73	95.52	210.59
Natural Gas	MMBtu/scf	kg CO ₂ /MMBtu	lb CO ₂ /MMBtu
(Weighted U.S. Average)	1.026 x 10 ⁻³	53.06	116.98
Petroleum Products	MMBtu/gallon	kg CO ₂ /MMBtu	lb CO ₂ /MMBtu
Distillate Oil No. 1	0.139	73.25	161.49
Distillate Oil No. 2	0.138	73.96	163.05
Distillate Oil No. 4	0.146	75.04	165.43
Residual Fuel Oil No. 5	0.140	72.93	160.78
Residual Fuel Oil No. 6	0.150	75.10	165.57
Used Oil	0.138	74.00	163.14
Kerosene	0.135	75.20	165.79
Liquefied petroleum gases (LPG)	0.092	61.71	136.05
Propane	0.091	62.87	138.60
Propylene	0.091	67.77	149.41
Ethane	0.068	59.60	131.40
Ethanol	0.084	68.44	150.88
Ethylene	0.058	65.96	145.22
Isobutane	0.099	64.94	143.17
Isobutylene	0.103	68.86	151.81

³ From Table C-1 of 40 CFR 98 Subpart C as amended on November 29, 2013 and effective on January 1, 2014.

⁴ Table C-1 of 40 CFR 98 Subpart C uses the term “short ton”, which DNR refers to throughout this document as “ton”.

⁵ Table C-1 of 40 CFR 98 lists only the kg/MMBtu emission factors. DNR has converted them to lb/MMBtu for convenience using a conversion of 1 kg = 2.20462 lbs.

Table 2 (continued)

Petroleum Products	MMBtu/gallon	kg CO₂/MMBtu	lb CO₂/MMBtu
Isobutylene	0.103	68.86	151.81
Butane	0.103	64.77	142.79
Butylene	0.105	68.72	151.50
Naphtha (<401 deg F)	0.125	68.02	149.96
Natural Gasoline	0.110	66.88	147.44
Other Oil (>401 deg F)	0.139	76.22	168.04
Pentanes Plus	0.110	70.02	154.37
Petrochemical Feedstocks	0.125	71.02	156.57
Petroleum Coke	0.143	102.41	225.78
Special Naphtha	0.125	72.34	159.48
Unfinished Oils	0.139	74.54	164.33
Heavy Gas Oils	0.148	74.92	165.17
Lubricants	0.144	74.27	163.74
Motor Gasoline	0.125	70.22	154.81
Aviation Gasoline	0.120	69.25	152.67
Kerosene-Type Jet Fuel	0.135	72.22	159.22
Asphalt and Road Oil	0.158	75.36	166.14
Crude Oil	0.138	74.54	164.33
Other fuels - solid	MMBtu/ ton⁶	kg CO₂/MMBtu	lb CO₂/MMBtu
Municipal Solid Waste (MSW)	9.95	90.7	200.11
Tires	28.00	85.97	189.53
Plastics	38.00	75.00	165.35
Petroleum Coke	30.00	102.41	225.78
Other fuels - gaseous	MMBtu/scf	kg CO₂/MMBtu	lb CO₂/MMBtu
Blast Furnace Gas	0.092 x 10 ⁻³	274.32	604.77
Coke Oven Gas	0.599 x 10 ⁻³	46.85	103.29
Propane Gas	2.516 x 10 ⁻³	61.46	135.50
Fuel Gas ⁷	1.388 x 10 ⁻³	59.00	130.07
Biomass fuels - solid	MMBtu/ton	kg CO₂/MMBtu	lb CO₂/MMBtu
Wood and Wood Residuals (dry basis)	17.48	93.80	206.79
Agricultural Byproducts	8.25	118.17	260.52
Peat	8.00	111.84	246.56
Solid Byproducts	10.39	105.51	232.61
Biomass Fuels - gaseous	MMBtu/scf	kg CO₂/MMBtu	lb CO₂/MMBtu
Landfill Gas	0.485 x10 ⁻³	52.07	114.79
Other Biomass Gases	0.655 x10 ⁻³	52.07	114.79
Biomass Fuels - liquid	MMBtu/gallon	kg CO₂/MMBtu	lb CO₂/MMBtu
Ethanol	0.084	68.44	150.88
Biodiesel (100%)	0.128	73.84	162.79
Rendered Animal Fat	0.125	71.06	156.66
Vegetable Oil	0.120	81.55	179.79

⁶ Table C-1 of 40 CFR 98 Subpart C uses the term “short ton”, which DNR refers to throughout this document as “ton”.

Table 3 - Default CH₄ and N₂O Emission Factors for Various Types of Fuel⁷

Fuel Type	Default CH ₄ Emission Factor		Default N ₂ O Emission Factor	
	kg CH ₄ /MMBtu	lb CH ₄ /MMBtu ⁸	kg N ₂ O/MMBtu	lb N ₂ O/MMBtu ⁹
Coal and Coke (All fuel types in Table C-1)	1.1 x 10 ⁻⁰²	2.4 x 10 ⁻⁰²	1.6 x 10 ⁻⁰³	3.5 x 10 ⁻⁰³
Natural Gas	1.0 x 10 ⁻⁰³	2.2 x 10 ⁻⁰³	1.0 x 10 ⁻⁰⁴	2.2 x 10 ⁻⁰⁴
Petroleum (All fuel types in Table C-1)	3.0 x 10 ⁻⁰³	6.6 x 10 ⁻⁰³	6.0 x 10 ⁻⁰⁴	1.3 x 10 ⁻⁰³
Fuel Gas	3.0 x 10 ⁻⁰³	6.6 x 10 ⁻⁰³	6.0 x 10 ⁻⁰⁴	1.3 x 10 ⁻⁰³
Municipal Solid Waste	3.2 x 10 ⁻⁰²	7.1 x 10 ⁻⁰²	4.2 x 10 ⁻⁰³	9.3 x 10 ⁻⁰³
Tires	3.2 x 10 ⁻⁰²	7.1 x 10 ⁻⁰²	4.2 x 10 ⁻⁰³	9.3 x 10 ⁻⁰³
Blast Furnace Gas	2.2 x 10 ⁻⁰⁵	4.9 x 10 ⁻⁰⁵	1.0 x 10 ⁻⁰⁴	2.2 x 10 ⁻⁰⁴
Coke Oven Gas	4.8 x 10 ⁻⁰⁴	1.1 x 10 ⁻⁰³	1.0 x 10 ⁻⁰⁴	2.2 x 10 ⁻⁰⁴
Biomass Fuels – Solid (All fuel types in Table C-1, except wood and wood residuals)	3.2 x 10 ⁻⁰²	7.1 x 10 ⁻⁰²	4.2 x 10 ⁻⁰³	9.3 x 10 ⁻⁰³
Biomass Fuels – Gaseous (All fuel types in Table C-1)	3.2 x 10 ⁻⁰³	7.1 x 10 ⁻⁰³	6.3 x 10 ⁻⁰⁴	1.4 x 10 ⁻⁰³
Biomass Fuels – Liquid (All fuel types in Table C-1)	1.1 x 10 ⁻⁰³	2.4 x 10 ⁻⁰³	1.1 x 10 ⁻⁰⁴	2.4 x 10 ⁻⁰⁴

Examples

Example 1

Calculate the actual CO₂, CH₄, and N₂O emissions from a natural gas boiler that combusted 25,500,000 standard cubic feet (scf) of natural gas in a given year. No CEMS, stack test, or fuel sampling data is available.⁹

$$\text{CO}_2 = \frac{25,500,000 \text{ scf}}{\text{year}} \times \frac{1.026 \times 10^{-03} \text{ MMBtu}}{\text{scf}} \times \frac{116.98 \text{ lbs. CO}_2}{\text{MMBtu}} \times \frac{\text{ton}}{2,000 \text{ lbs.}} = 1,530.27 \text{ tons CO}_2$$

$$1,530.27 \text{ tons CO}_2 \times \frac{0.90718 \text{ metric tons}}{\text{ton}} = 1,388.23 \text{ metric tons CO}_2$$

⁷ From Table C-1 of 40 CFR 98 Subpart C as amended on November 29, 2013 and effective on January 1, 2014.

⁸ Table C-2 of 40 CFR 98 Subpart C lists only the kg/MMBtu emission factors. DNR has converted them to lb/MMBtu for convenience using a conversion of 1 kg = 2.20462 lbs.

⁹ The example equations include conversions from tons to metric tons as examples for those facilities subject to the US EPA GHGRP, which requires reporting in units of metric tons.

$$\text{CH}_4 = \frac{25,500,000 \text{ scf}}{\text{year}} \times \frac{1.026 \times 10^{-3} \text{ MMBtu}}{\text{scf}} \times \frac{2.2 \times 10^{-03} \text{ lbs. CH}_4}{\text{MMBtu}} \times \frac{\text{ton}}{2,000 \text{ lbs.}} = 0.029 \text{ tons CH}_4$$

$$0.029 \text{ tons CH}_4 \times \frac{0.90718 \text{ metric tons}}{\text{ton}} = 0.026 \text{ metric tons CH}_4$$

$$\text{N}_2\text{O} = \frac{25,500,000 \text{ scf}}{\text{year}} \times \frac{1.026 \times 10^{-3} \text{ MMBtu}}{\text{scf}} \times \frac{2.2 \times 10^{-04} \text{ lbs. N}_2\text{O}}{\text{MMBtu}} \times \frac{\text{ton}}{2,000 \text{ lbs.}} = 0.0029 \text{ tons N}_2\text{O}$$

$$0.0029 \text{ tons N}_2\text{O} \times \frac{0.90718 \text{ metric tons}}{\text{ton}} = 0.0026 \text{ metric tons N}_2\text{O}$$

Example 2

Calculate the potential CO₂, CH₄, and N₂O emissions from a generator that has a maximum hourly rated capacity of 75 gallons per hour of residual fuel oil #6.

$$\text{CO}_2 = \frac{75 \text{ gallons}}{\text{hour}} \times \frac{0.150 \text{ MMBtu}}{\text{gallons}} \times \frac{165.57 \text{ lbs. CO}_2}{\text{MMBtu}} \times \frac{8,760 \text{ hours}}{\text{year}} \times \frac{\text{ton}}{2,000 \text{ lbs.}} = \frac{8,158.46 \text{ tons CO}_2}{\text{year}}$$

$$8,158.46 \text{ tons CO}_2 \times \frac{0.90718 \text{ metric tons}}{\text{ton}} = 7,401.19 \text{ metric tons CO}_2$$

$$\text{CH}_4 = \frac{75 \text{ gallons}}{\text{hour}} \times \frac{0.150 \text{ MMBtu}}{\text{gallons}} \times \frac{6.6 \times 10^{-03} \text{ lbs. CH}_4}{\text{MMBtu}} \times \frac{8,760 \text{ hours}}{\text{year}} \times \frac{\text{ton}}{2000 \text{ lbs.}} = \frac{0.33 \text{ tons CH}_4}{\text{year}}$$

$$0.33 \text{ tons CH}_4 \times \frac{0.90718 \text{ metric tons}}{\text{ton}} = 0.30 \text{ metric tons CH}_4$$

$$\text{N}_2\text{O} = \frac{75 \text{ gallons}}{\text{hour}} \times \frac{0.150 \text{ MMBtu}}{\text{gallons}} \times \frac{1.3 \times 10^{-03} \text{ lbs. CH}_4}{\text{MMBtu}} \times \frac{8,760 \text{ hours}}{\text{year}} \times \frac{\text{ton}}{2000 \text{ lbs.}} = \frac{0.06 \text{ tons N}_2\text{O}}{\text{year}}$$

$$0.06 \text{ tons N}_2\text{O} \times \frac{0.90718 \text{ metric tons}}{\text{ton}} = 0.05 \text{ metric tons N}_2\text{O}$$

To learn how to convert the greenhouse gas emissions in units of carbon dioxide equivalents (CO₂e), please see Chapter 6 of this document.

Chapter 4: CO₂, CH₄, and N₂O Emissions from Industrial and Other Source Categories

Greenhouse gases are also emitted from several stationary source categories (other than fossil fuel combustion) that may currently operate in Iowa. If CEMS or stack test data is not available, the estimation methods in the [federal Greenhouse Gas Reporting Program \(GHGRP\)](#) in 40 CFR 98 should be used. However, some exceptions are noted below. In general, GHG emissions from stationary fossil fuel combustion sources in these source categories should be calculated using GHGRP - 40 CFR 98.30 (Subpart C) unless the industry-specific GHGRP subpart contains another method be used. Table 4 below includes only source categories that DNR assumes currently operate in Iowa. A full list of the source categories covered by the federal GHGRP in 40 CFR 98 is included in this document as Appendix B.

Table 4 – Recommended Emission Estimated Methods for Industrial and Other Source Categories

Source Categories	Recommended Estimation Method
Ammonia Manufacturing	GHGRP - 40 CFR 98.70 (Subpart G)
Brick Manufacturing	GHGRP - 40 CFR 98.30 (Subpart C) ¹⁰
Cement Production	GHGRP - 40 CFR 98.80 (Subpart H)
Electricity Generation	GHGRP - 40 CFR 98.40 (Subpart D)
Ethanol Fermentation	GHG Emissions Estimation Methodology for Selected Biogenic Source Categories . ¹¹
Glass Production	GHGRP - 40 CFR 98.140 (Subpart N)
Gypsum Manufacturing	GHGRP - 40 CFR 98.30 (Subpart C) ¹²
Hot Mix Asphalt Plants	GHGRP - 40 CFR 98.30 (Subpart C) ¹³
Iron and Steel Production	GHGRP - 40 CFR 98.170 (Subpart Q)
Industrial Waste Landfills	<ul style="list-style-type: none"> • GHGRP - 40 CFR 98.460 (Subpart TT) • See also GHG Emissions Estimation Methodology for Selected Biogenic Source Categories.¹⁴
Industrial Wastewater Treatment	<ul style="list-style-type: none"> • GHGRP - 40 CFR 98.350 (Subpart II) • See also GHG Emissions Estimation Methodology for Selected Biogenic Source Categories.¹⁵
Lime Manufacturing	GHGRP - 40 CFR 98.190 (Subpart S)
Miscellaneous Uses of Carbonate ¹⁶	GHGRP - 40 CFR 98.210 (Subpart U)

¹⁰ No process GHG emissions emitted. GHGs are emitted from fossil fuels combusted in the kiln and dryer.

¹¹ RTI International. *GHG Emissions Estimation Methodology for Selected Biogenic Source Categories* (2010): 4-1 – 4-6. < <http://www.epa.gov/ttnchie1/efpac/ghg/index.html>>. >.

¹² No process GHG emissions emitted. GHGs are emitted from fossil fuels combusted in the calciner and dryer.

¹³ No process GHG emissions emitted. GHGs are emitted from fossil fuels combusted in the dryer and hot oil heater.

¹⁴ RTI International 2-1 – 2-14.

¹⁵ RTI International 3-1 – 3-12.

¹⁶ This includes greenhouse gas emissions from soda ash used in corn wet milling.

Table 4 (continued)

Source Categories	Recommended Estimation Method
Municipal Solid Waste Landfills	<ul style="list-style-type: none"> • LandGEM¹⁷ • See also GHG Emissions Estimation Methodology for Selected Biogenic Source Categories.¹⁸
Nitric Acid Production	GHGRP - 40 CFR 98.220 (Subpart V)
Petrochemical Production	GHGRP - 40 CFR 98.240 (Subpart X)
Petroleum and Natural Gas Systems	GHGRP - 40 CFR 98.230 (Subpart W)
Pulp and Paper Manufacturing	GHGRP - 40 CFR 98.270 (Subpart AA)
Wastewater Treatment	<ul style="list-style-type: none"> • See Industrial Wastewater Treatment above. • See also GHG Emissions Estimation Methodology for Selected Biogenic Source Categories.¹⁹

Biogenic Emissions

Emissions estimation methods for biogenic sources are included for reference only. On July 1, 2011 EPA issued a rulemaking deferring permitting requirements for carbon dioxide emissions from biomass-fired and other biogenic sources until July 21, 2014.

Then on July 12, 2013, the U.S. Court of Appeals for the D.C. Circuit vacated EPA’s “Deferral Rule” for biogenic carbon dioxide emissions, holding that the agency was not authorized under the Clean Air Act to temporarily exempt such emissions from the Prevention of Significant Deterioration (PSD) and Title V permitting programs. However, the Court has not issued the formal mandate vacating the rule, so the deferral is still in place at this time.

¹⁷ United States Environmental Protection Agency. *Landfill Gas Emissions Model (LandGEM), version 3.02* (2005). <http://www.epa.gov/ttn/catc/products.html#software>.

¹⁸ RTI International. *GHG Emissions Estimation Methodology for Selected Biogenic Source Categories* (2010): 2-1 – 2-14. <http://www.epa.gov/ttnchie1/efpac/ghg/index.html> >.>.

¹⁹ RTI International 3-1 – 3-12.

Chapter 5: Fluorinated Gases (HFC, PFC, and SF₆)

The 1990 Clean Air Act Amendments and the Montreal Protocol phase out the use of ozone depleting substances, and hydrofluorocarbons (HFCs) are currently used as an alternative. Some perfluorocarbons (PFCs) are currently used as well, but on a much smaller scale.²⁰ Sulfur hexafluoride (SF₆) is used primarily by electric utilities in transmission and distribution, accounting for approximately 80% of worldwide use of SF₆.²¹ It is also used in semiconductor manufacturing and can also be used in thermal, sound, and high voltage insulation. Table 5 below only includes source categories the DNR assumes currently operate in Iowa. A full list of the source categories covered by the federal GHGRP in 40 CFR 98 is included in this document as Appendix B.

Table 5 – Recommended Emission Estimation Methods for HFC, PFC, and SF₆

Source Categories	Recommended Estimation Method
Electronics Manufacturing	GHGRP – 40 CFR 98.90 (Subpart I)
Electric Transmission and Distribution Equipment – Manufacture Of	GHGRP - 40 CFR 98.450 (Subpart SS)
Electric Transmission and Distribution Equipment – Use Of	GHGRP - 40 CFR 98.300 (Subpart DD)
Magnesium Production	GHGRP – 40 CFR 98.200 (Subpart T)
Substitutes for Ozone-Depleting Substances <ul style="list-style-type: none"> • Aerosols • Fire extinguishing equipment • Fire suppression and explosion protection • Foam production • Insulation – high voltage, sound, thermal • Refrigeration and air conditioning • Solvent cleaning • Sterilization 	Mass Balance Equation – see below

Mass Balance Estimation Method

Actual emissions of HFC, PFC, and SF₆, also known as F-gas emissions, from substitutes of ozone depleting substances should be using a mass balance equation that derives emissions from a facility's inventory of F-gases, subtracting the quantity consumed and quantity recovered as shown in Equation 4 below.

²⁰ Ashford et al, 2006 *IPCC Guidelines for National Greenhouse Gas Inventories, Chapter 7: Emissions of Fluorinated Substitutes for Ozone Depleting Substances* (2006): 7.7. < http://www.ipcc-nggip.iges.or.jp/public/2006gl/pdf/3_Volume3/V3_7_Ch7_ODS_Substitutes.pdf>

²¹ STAPPA/ALAPCO and the United States Environmental Protection Agency, *EIIP Volume VIII Chapter 6: Methods for Estimating Non-Energy Greenhouse Gas Emissions from Industrial Processes* (2004): p. 6.4-26.

Equation 4:

$$\textit{Emissions (lbs.)} = \textit{Quantity Added (lbs.)} - \textit{Quantity Consumed (lbs.)} - \textit{Quantity Recovered (lbs.)}$$

Global Warming Potentials

Fluorinated gases have high global warming potentials (GWPs), values used to compare the abilities of different greenhouse gases to trap heat in the atmosphere. GWPs are further discussed in Chapter 6 of this document.

Chapter 6: Converting to Carbon Dioxide Equivalent (CO₂e)

As discussed in Chapter 5, the potency of various greenhouse gases can vary and are indicated by the pollutants' GWP. Greenhouse gas emissions are typically converted to a unit of measure called carbon dioxide equivalent (CO₂e) that allows for better comparison of the impact of different greenhouse gases. CO₂e is calculated by multiplying the mass amount of each greenhouse gas by its GWP and then summing the resulting value. CO₂e should be calculated using Equation 5 below:

Equation 5:

$$\text{tons CO}_2\text{e} = \sum_{i=0}^n \text{GHGi} \times \text{GWP}_i$$

Where:

GHG_i = Mass emissions of each greenhouse gas

GWP_i = Global warming potential for each greenhouse gas

n = the number of greenhouse gases emitted

Example:

Calculate the greenhouse gas emissions in units of carbon dioxide equivalent from a generator that has the potential to emit 8,158.46 tons CO₂, 0.33 tons CH₄, and 0.06 tons N₂O per year.

$$\text{tons CO}_2\text{e} = (8,158.46 \times 1) + (0.33 \times 21) + (0.06 \times 310) = 8,183.99$$

When calculating CO₂e, the GWP value published in 40 CFR Part 98, Subpart A, Table A-1 as of October 30, 2009 should be used per the definition of "subject to regulation" in 567 IAC 22.100. On November 29, 2013 EPA finalized changes to many of the GWP values in 40 CFR Part 98, Subpart A, Table A-1, but the new values have not been adopted in to the Iowa Administrative Code (IAC) at this time. The global warming potentials of some common greenhouse gases are included in Table 6 for convenience.

Table 6 - Global Warming Potentials of Common Greenhouse Gases²²

Common Name	Name	Chemical Formula	CAS Number	GWP (100 year)
	Carbon dioxide	CO ₂	124-38-9	1
	Methane	CH ₄	74-82-8	21
	Nitrous Oxide	N ₂ O	10024-97-2	310
HFC-23	trifluoromethane	CHF ₃	75-46-7	11,700
HFC-32	difluoroethane	CH ₂ F ₂	75-10-5	650
HFC-41	fluoromethane	CH ₃ F	593-53-3	150
HFC-43-10mee	1,1,1,2,2,3,4,5,5,5-decafluoropentane	CF ₃ CHFCHF ₂ CF ₃	138495-42-8	1,300

²² 40 CFR Part 98, Subpart A, Table A-1 as of October 20, 2009.

Table 6 (continued)

Common Name	Name	Chemical Formula	CAS Number	GWP (100 year)
HFC-125	pentafluoroethane	C ₂ HF ₅	354-33-6	2,800
HFC-134	1,1,2,2-tetrafluoroethane	C ₂ H ₂ F ₄	359-35-3	1,000
HFC-134a	1,1,1,2-tetrafluoroethane	CH ₂ FCF ₃	811-97-2	1,300
HFC-143	1,1,2-trifluoroethane	C ₂ H ₃ F ₃	430-66-0	300
HFC-143a	1,1,1-trifluoroethane	C ₂ H ₃ F ₃	420-46-2	3,800
HFC-152	1,2-difluoroethane	CH ₂ FCH ₂ F	624-72-6	53
HFC-152a	1,1-difluoroethane	CH ₃ CHF ₂	75-37-6	140
HFC-161	fluoroethane	CH ₃ CH ₂ F	353-36-6	12
HFC-227ea	1,1,1,2,3,3,3-heptafluoropropane	CH ₃ HF ₇	431-89-0	2,900
HFC-236cb	1,1,1,2,2,3-hexafluoropropane	CH ₂ FCF ₂ CF ₃	677-56-5	1,340
HFC-236ea	1,1,1,2,3,3-hexafluoropropane	CHF ₂ CHFCF ₃	431-63-0	1,370
HFC-236fa	1,1,1,3,3,3-hexafluoropropane	C ₃ H ₂ F ₆	690-39-1	6,300
HFC-245ca	1,1,2,2,3-pentafluoropropane	C ₃ H ₃ F ₅	679-86-7	560
HFC-245fa	1,1,1,3,3-pentafluoropropane	CHF ₂ CH ₂ CF ₃	460-73-1	1,030
HFC-365mfc	1,1,1,3,3-pentafluorobutane	CH ₃ CF ₂ CH ₂ CF ₃	406-58-6	794
PFC-14	perfluoromethane	CF ₄	75-73-0	6,500
PFC-116	perfluoroethane	C ₂ F ₆	76-16-4	9,200
PFC-218	perfluoropropane	C ₃ F ₈	76-19-7	7,000
PFC-3-1-10	perfluorobutane	C ₄ F ₁₀	355-25-9	7,000
PFC-318	perfluorocyclobutane	C-C ₄ F ₈	115-25-3	8,700
PFC-4-1-12	perfluoropentane	C ₅ F ₁₂	678-26-2	7,500
PFC-5-1-14	perfluorohexane	C ₆ F ₁₄	355-42-0	7,400
SF ₆	Sulfur hexafluoride	SF ₆	2551-62-4	23,900

References

Ashford et al., 2006 IPCC Guidelines for National Greenhouse Gas Inventories, Chapter 7: Emissions of Fluorinated Substitutes for Ozone Depleting Substances, 2006. <http://www.ipcc-nggip.iges.or.jp/public/2006gl/pdf/3_Volume3/V3_7_Ch7_ODS_Substitutes.pdf>

RTI International, GHG Emissions Estimation Methodology for Selected Biogenic Source Categories, 2010. <<http://www.epa.gov/ttnchie1/efpac/ghg/index.html>>.

STAPPA/ALAPCO and the United States Environmental Protection Agency, Emission Inventory Improvement Program (EIIP) Volume VIII: Greenhouse Gases, 2004. <<http://www.epa.gov/ttn/chief/eiip/techreport/>>.

United States Environmental Protection Agency, AP-42 Compilation of Air Pollutant Emission Factors, Volume 1, Fifth Edition, 1995. <<http://www.epa.gov/ttn/chief/ap42/index.html>>.

United States Environmental Protection Agency, Landfill Gas Emissions Model (LandGEM), version 3.02, 2005. <<http://www.epa.gov/ttn/catc/products.html#software>>.

United States Environmental Protection Agency, WebFIRE - Factor Information Retrieval (FIRE) Data System, 2005. <<http://cfpub.epa.gov/webfire/>>.

Glossary

Actual emissions means the actual rate of emissions of a pollutant from an emissions unit, as determined in accordance with the following:

1. In general, actual emissions as of a particular date shall equal the average rate, in tons per year, at which the unit actually emitted the pollutant during a two-year period which immediately precedes that date and which is representative of normal source operations. The director may allow the use of a different time period upon a demonstration that it is more representative of normal source operations. Actual emissions shall be calculated using the unit's actual operating hours, production rates, and types of materials processed, stored or combusted during the selected time period. Actual emissions for acid rain affected sources are calculated using a one-year period.
2. Lacking specific information to the contrary, the director may presume that source-specific allowable emissions for the unit are equivalent to the actual emissions of the unit.
3. For any emissions unit which has not begun normal operations on a particular date, actual emissions shall equal the potential to emit of the unit on that date.
4. For purposes of calculating early reductions of hazardous air pollutants, actual emissions shall not include excess emissions resulting from a malfunction or from startups and shutdowns associated with a malfunction.

Actual emissions for purposes of determining fees shall be the actual emissions calculated over a period of one year.

Biogenic - Produced by living organisms or biological processes. Examples of biogenic greenhouse gas emissions are CO₂ emissions from trees, vegetation, decomposition of solid waste, etc.

Carbon Dioxide (CO₂) - A naturally occurring gas that is also a byproduct of burning fossil fuels and biomass, other industrial processes, and land-use changes.

Continuous Emission Monitor (CEM) – Equipment that measures the concentration or emission rate of a gas or particulate matter using analyzer measurements and a conversion equation, graph, or computer program. Installation and operation of a CEM may be required by EPA or DNR in order to determine compliance with specific standards. Operation of a CEM must meet performance specifications, certification procedures, and recordkeeping and reporting requirements as specified in applicable regulations.

Emission Factor – The relationship between the amount of pollution produced and the amount of raw material processed. For example – pounds of CO₂ emitted per ton of coal combusted.

Fluorinated Gases "F-Gases" - Gases sometimes used as substitutes for ozone depleting substances. HFC, PFC, and SF₆ are "F-gases" and are emitted from a variety of industrial processes. "F-gases" are

commonly emitted in smaller quantities, but are important because they have high global warming potentials (GWP).

Global Warming Potential (GWP) – Values used to compare the abilities of different greenhouse gases to trap heat in the atmosphere. It is the radiative forcing that results from the addition of 1 kilogram (2.2 pounds) of a gas to the atmosphere, compared to an equal mass of carbon dioxide, which has a global warming potential of 1. The higher the GWP, the more heat the specific gas can keep in the atmosphere.

Greenhouse Gas (GHG) – Any gas that absorbs and re-emits infrared radiation into the atmosphere. Greenhouse gases include carbon dioxide (CO₂), methane (CH₄), nitrous oxide (N₂O), sulfur hexafluoride (SF₆), hydrofluorocarbons (HFC), and perfluorocarbons (PFC).

Hydrofluorocarbons (HFC) – A group of human-made chemicals composed of one or two carbon atoms and varying numbers of hydrogen and fluorine atoms.

Hydrofluorinated ethers (HFE) – A group of refrigerant gases that have been developed as alternatives to chlorofluorocarbons and hydrofluorocarbons (HFC).

Mass Balance - A process of estimating emissions using knowledge of the process, process rate, material used, and material properties.

Methane (CH₄) – A colorless, flammable, odorless hydrocarbon that is a greenhouse gas.

Nitrogen Trifluoride (NF₃) – A high-GWP gas used in the manufacture of flat panel televisions, computer displays and other products.

Nitrous Oxide (N₂O) – A greenhouse gas formed from soil cultivation practices, especially the use of commercial and organic fertilizers, fossil fuel combustion, nitric acid production, and biomass burning.

Perfluorocarbons (PFC) – A group of human-made chemicals composed of carbon and fluorine. PFC have no commercial uses and are emitted as a byproduct of aluminum smelting and semiconductor manufacturing.

Potential to emit means the maximum capacity of a stationary source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored, or processed, shall be treated as part of its

design if the limitation is enforceable by the administrator. This term does not alter or affect the use of this term for any other purposed under the Act, or the term “capacity factors” as used in Title IV of the Act or regulations relating to acid rain.

For the purposes of determining potential to emit for country grain elevators, the provisions set forth in 567 – subrule 22.10(2) shall apply.

For purposes of calculating potential to emit for emergency generators, “maximum capacity” means one of the following:

1. 500 hours of operation annually, if the generator has actually been operated less than 500 hours per year for the past five years;
2. 8,760 hours of operating annually, if the generator has actually been operated more than 500 hours in one of the past five years; or
3. The number of hours specified in a state or federally enforceable limit.

Stack Test – A test that measures the concentration of pollutants in the exhaust stack. Measurements are performed following procedures specified and developed by the US EPA and/or Iowa DNR. Such testing is required by DNR to be conducted by various stationary sources to determine compliance with applicable air emission limits.

Sulfur Hexafluoride (SF₆) – A greenhouse gas used primarily to insulate high-voltage equipment and to assist in the manufacturing of cable cooling systems.

Appendix A – Units of Measure Conversions²³

To convert from	To	Multiply by
Kilograms (kg)	Pounds (lbs)	2.20462
Pounds (lbs)	Kilograms (kg)	0.45359
Pounds (lbs)	Metric tons	4.53592×10^{-4}
Short tons (referred to in this document as “tons”)	Pounds (lbs)	2,000
Short tons (referred to in this document as “tons”)	Metric tons	0.90718
Metric tons	Short tons	1.10231
Metric tons	Kilograms (kg)	1,000
Cubic meters (m ³)	Cubic feet (ft ³)	35.31467
Cubic feet (ft ³)	Cubic meters (m ³)	0.028317
Gallons (liquid, US)	Liters (l)	3.78541
Liters (l)	Gallons (liquid, US)	0.26417
Barrels of Liquid Fuel (bbl)	Cubic meters (m ³)	0.15891
Cubic meters (m ³)	Barrels of Liquid Fuel (bbl)	6.289
Barrels of Liquid Fuel (bbl)	Gallons (liquid, US)	42
Gallons (liquid, US)	Barrels of Liquid Fuel (bbl)	0.023810
Gallons (liquid, US)	Cubic meters (m ³)	0.0037854
Liters (l)	Cubic meters (m ³)	0.001
Feet (ft)	Meters (m)	0.3048
Meters (m)	Feet (ft)	3.28084
Miles (mi)	Kilometers (km)	1.60934
Kilometers (km)	Miles (mi)	0.62137
Square feet (ft ²)	Acres	2.29568×10^{-5}
Square meters (m ²)	Acres	2.47105×10^{-4}
Square miles (mi ²)	Square kilometers (km ²)	2.58999
Degrees Celsius (°C)	Degrees Fahrenheit (°F)	$^{\circ}\text{C} = (5/9) \times (^{\circ}\text{F} - 32)$
Degrees Fahrenheit (°F)	Degrees Celsius (°C)	$^{\circ}\text{F} = (9/5) \times ^{\circ}\text{C} + 32$
Degrees Celsius (°C)	Kelvin (K)	$\text{K} = ^{\circ}\text{C} + 273.15$
Kelvin (K)	Degrees Rankine (°R)	1.8
Joules	Btu	9.47817×10^{-4}
Btu	MMBtu	1×10^{-6}
Pascals (Pa)	Inches of Mercury (inHg)	2.95334×10^{-4}
Inches of Mercury (inHg)	Pounds per square inch (psi)	0.49110
Pounds per square inch (psi)	Inches of Mercury (inHg)	2.03625

²³ Table A-2 to Subpart A of 40 CFR 98

Appendix B – 40 CFR 98 Subparts²⁴

Rule Section	Subpart		Initial Reporting Year
98.10	A	General Provisions	2010
98.20	B	Reserved	
98.30	C	General Stationary Fuel Combustion Sources	2010
98.40	D	Electricity Generation	2010
98.50	E	Adipic Acid Production	2010
98.60	F	Aluminum Production	2010
98.70	G	Ammonia Manufacturing	2010
98.80	H	Cement Production	2010
98.90	I	Electronics Manufacturing	2010
98.100	J	Ethanol Production	N/A
98.110	K	Ferrous Alloy Production	2010
98.120	L	Fluorinated Gas Production	2011
98.130	M	Food Processing	N/A
98.140	N	Glass Production	2010
98.150	O	HCFC-22 Production and HF-23 Destruction	2010
98.160	P	Hydrogen Production	2010
98.170	Q	Iron and Steel Production	2010
98.180	R	Lead Production	2010
98.190	S	Lime Manufacturing	2010
98.200	T	Magnesium Production	2011
98.210	U	Miscellaneous Uses of Carbonate	2010
98.220	V	Nitric Acid Production	2010
98.230	W	Petroleum and Natural Gas Systems	2011
98.240	X	Petrochemical Production	2010
98.250	Y	Petroleum Refineries	2010
98.260	Z	Phosphoric Acid Production	2010
98.270	AA	Pulp and Paper Manufacturing	2010
98.280	BB	Silicon Carbide Production	2010
98.290	CC	Soda Ash Manufacturing	2010
98.300	DD	Use of Electric Transmission and Distribution Equipment	2011
98.310	EE	Titanium Dioxide Production	2010
98.320	FF	Underground Coal Mines	2011
98.330	GG	Zinc Production	2010
98.340	HH	Municipal Solid Waste Landfills	2010
98.350	II	Industrial Wastewater Treatment	2011

²⁴ <http://www.epa.gov/climatechange/emissions/subpart.html>

40 CFR 98 Subparts (continued)

Rule Section	Subpart	Rule Section	Initial Reporting Year
98.360	JJ	Manure Management NOTE: EPA will not be implementing subpart JJ of Part 98. The FY 2013 House Subcommittee Report Section 421 contains a provision prohibiting the expenditure of funds for this purpose.	N/A
98.370	KK	Suppliers of Coal	N/A
98.380	LL	Suppliers of Coal-based Liquid Fuels	2010
98.390	MM	Suppliers of Petroleum Products	2010
98.400	NN	Suppliers of Natural Gas and Natural Gas Liquids	2010
98.410	OO	Suppliers of Industrial Greenhouse Gases	2010
98.420	PP	Suppliers of Carbon Dioxide	2010
98.430	QQ	Imports and Exports of Equipment Pre-charged with Fluorinated GHGs or Containing Fluorinated GHGs in Closed-cell Foams	2011
98.440	RR	Carbon Dioxide Injection and Geologic Sequestration	2011
98.450	SS	Manufacture of Electric Transmission and Distribution Equipment	2011
98.460	TT	Industrial Waste Landfills	2011
98.470	UU	Injection of Carbon Dioxide	2011

Appendix C – Document Revision History

<u>Date</u>	<u>Revision(s) Made</u>
Fall 2007	First versions of document posted.
03/17/11	Document updated to recommend use of federal GHG Reporting Program emission factors and federal Mandatory Reporting Rule subparts. Stationary Fossil Fuel Combustion Calculation Tool created.
01/09/12	Hyperlinks updated.
09/09/13	Contact phone number changed.
02/03/14	Font size increased, global warming potentials language updated, biogenic emissions language updated, and revision history added. Emission factors in Table 2 and Table 3 and calculation examples updated to match emission factors in Table C-1 of 40 CFR 98 Subpart C as amended on November 29, 2013 and effective on January 1, 2014.