

**Iowa Department of Natural Resources  
Title V Operating Permit**

**Name of Permitted Facility: Andersons Denison Ethanol, LLC**  
**Facility Location: 2404 West Highway 30, Denison, IA 51442**  
**Air Quality Operating Permit Number: 14-TV-011**  
**Expiration Date: August 14, 2019**  
**Permit Renewal Application Deadline: February 14, 2019**

**EIQ Number: 92-4602**  
**Facility File Number: 24-01-007**

---

**Responsible Official**

**Name: Mike Schrum**  
**Title: Plant Manager**  
**Mailing Address: 2404 West Highway 30, Denison, IA 51442**  
**Phone #: (712) 263-2676**

**Permit Contact Person for the Facility**

**Name: Jackie Roberts**  
**Title: Compliance and Safety Administrator**  
**Mailing Address: 2404 West Highway 30, Denison, IA 51442**  
**Phone #: (712) 263-2676**

---

This permit is issued in accordance with 567 Iowa Administrative Code Chapter 22, and is issued subject to the terms and conditions contained in this permit.

**For the Director of the Department of Natural Resources**

---

Lori Hanson, Supervisor of Air Operating Permits Section

Date

# Table of Contents

<b>I. Facility Description and Equipment List .....</b>	<b>4</b>
<b>II. Plant - Wide Conditions.....</b>	<b>6</b>
<b>III. Emission Point Specific Conditions .....</b>	<b>10</b>
<b>IV. General Conditions.....</b>	<b>76</b>
G1. Duty to Comply	
G2. Permit Expiration	
G3. Certification Requirement for Title V Related Documents	
G4. Annual Compliance Certification	
G5. Semi-Annual Monitoring Report	
G6. Annual Fee	
G7. Inspection of Premises, Records, Equipment, Methods and Discharges	
G8. Duty to Provide Information	
G9. General Maintenance and Repair Duties	
G10. Recordkeeping Requirements for Compliance Monitoring	
G11. Evidence used in establishing that a violation has or is occurring.	
G12. Prevention of Accidental Release: Risk Management Plan Notification and Compliance Certification	
G13. Hazardous Release	
G14. Excess Emissions and Excess Emissions Reporting Requirements	
G15. Permit Deviation Reporting Requirements	
G16. Notification Requirements for Sources That Become Subject to NSPS and NESHAP Regulations	
G17. Requirements for Making Changes to Emission Sources That Do Not Require Title V Permit Modification	
G18. Duty to Modify a Title V Permit	
G19. Duty to Obtain Construction Permits	
G20. Asbestos	
G21. Open Burning	
G22. Acid Rain (Title IV) Emissions Allowances	
G23. Stratospheric Ozone and Climate Protection (Title VI) Requirements	
G24. Permit Reopenings	
G25. Permit Shield	
G26. Severability	
G27. Property Rights	
G28. Transferability	
G29. Disclaimer	
G30. Notification and Reporting Requirements for Stack Tests or Monitor Certification	
G31. Prevention of Air Pollution Emergency Episodes	
G32. Contacts List	
<b>V. Appendix – Links to Standards .....</b>	<b>90</b>

## Abbreviations

acfm.....	actual cubic feet per minute
CFR.....	Code of Federal Regulation
CE .....	control equipment
CEM.....	continuous emission monitor
°F.....	degrees Fahrenheit
EIQ.....	emissions inventory questionnaire
EP.....	emission point
EU .....	emission unit
gr./dscf .....	grains per dry standard cubic foot
gr./100 cf.....	grains per one hundred cubic feet
IAC.....	Iowa Administrative Code
IDNR.....	Iowa Department of Natural Resources
MVAC.....	motor vehicle air conditioner
NAICS.....	North American Industry Classification System
NSPS.....	new source performance standard
ppmv .....	parts per million by volume
lb./hr .....	pounds per hour
lb./MMBtu .....	pounds per million British thermal units
SCC.....	Source Classification Codes
scfm.....	standard cubic feet per minute
SIC.....	Standard Industrial Classification
TPY.....	tons per year
USEPA.....	United States Environmental Protection Agency

## Pollutants

PM.....	particulate matter
PM <sub>10</sub> .....	particulate matter ten microns or less in diameter
SO <sub>2</sub> .....	sulfur dioxide
NO <sub>x</sub> .....	nitrogen oxides
VOC.....	volatile organic compound
CO.....	carbon monoxide
HAP.....	hazardous air pollutant

# I. Facility Description and Equipment List

Facility Name: Andersons Denison Ethanol, LLC

Permit Number: 14-TV-011

Facility Description: Fuel-Grade Ethyl Alcohol Manufacturing (SIC 2869)

---

## Equipment List

---

Emission Point Number	Emission Unit Number	Emission Unit Description	DNR Construction Permit Number
S10	P50a	Slurry Tank	04-A-642-S3
		Liquefaction Tank #1 and #2	
		Beer Column	
		Stripper	
		Rectifier	
		Evaporator System	
		Whole Stillage Tank	
		Thin Stillage Tank	
		Syrup Tank	
		Molecular Sieve #1, #2, and 3	
		Process Condensate Tank	
		200 Proof Condenser	
		Yeast Tank	
	Centrifuge # 1		
	P50b	Centrifuge # 2	
	P50c	Centrifuge # 3	
	P50d	Centrifuge # 4	
P50e	Centrifuge # 5		
P50f	Centrifuge # 6		
P10a	DDGS Dryer #1		
P10b	DDGS Dryer #2		
19a	S19a	Grain Receiving	None
19b	S19b	Tunnel Belt Conveyor	None
20a	Tank A	Grain Storage Tank A	06-A-318-S2
20b	Tank B	Grain Storage Tank B	06-A-319-S2
20c	Tank C	Grain Storage Tank C	06-A-320-S2
20d	Tank D	Grain Storage Tank D	04-A-640-S3
20e	Tank E	Grain Storage Tank E	04-A-641-S2
20f	Tank F	Grain Storage Silo F	06-A-321-S3
20g	Tank G	Grain Storage Silo G	06-A-322-S3

<b>Emission Point Number</b>	<b>Emission Unit Number</b>	<b>Emission Unit Description</b>	<b>DNR Construction Permit Number</b>
S30	P30	Hammermills	04-A-643-S3
S40	P40a	Fermenter #1	04-A-644-S5
	P40b	Fermenter #2	
	P40c	Fermenter #3	
	P40d	Fermenter #5	
	P40e	Fermenter #4 and Beer Well	
S70	P70	DDGS Cooler	04-A-645-S3
S90	P90	DDGS Loading	04-A-646-S2
SEP11	EU11	Biomethanator Flare	04-A-647-S1
SEP22	EU22	Truck Loadout Flare	04-A-648-S2
S23	P54	Ethanol Rail Loadout	06-A-323-S3
F15	F15	Grain Handling Fugitives	06-A-810-S1
F20	F20	MWDGS Storage/Loadout	12-A-563
F70	F70	Fire Water Pump	12-A-564
F80	F80	Cooling Tower	06-A-324
F100	F100	Haul Roads	06-A-325-S5
F110	F110	VOC Emissions	07-A-1541-S1
GD2	GD2	Grain Dryer	06-A-809-S2
T61	T61	Denatured EtOH Storage Tank	04-A-649
T62	T62	Denatured EtOH Storage Tank	04-A-650
T63	T63	200 Proof Ethanol Storage Tank	04-A-651
T64	T64	Denaturant Storage Tank	04-A-652-S1
T65	T65	190 Proof Ethanol Storage Tank	04-A-653

## II. Plant-Wide Conditions

Facility Name: Andersons Denison Ethanol, LLC  
Permit Number: 14-TV-011

Permit conditions are established in accord with 567 Iowa Administrative Code rule 22.108

---

### Permit Duration

The term of this permit is: 5 years  
Commencing on: August 15, 2014  
Ending on: August 14, 2019

Amendments, modifications and reopenings of the permit shall be obtained in accordance with 567 Iowa Administrative Code rules 22.110 - 22.114. Permits may be suspended, terminated, or revoked as specified in 567 Iowa Administrative Code Rules 22.115.

---

### Emission Limits

*Unless specified otherwise in the Source Specific Conditions, the following limitations and supporting regulations apply to all emission points at this plant:*

#### Pollutant: Single HAP

Emission Limit: 9.4 tons/yr (Plant-wide limit)

Authority for Requirement: DNR Construction Permits 04-A-642-S3, 04-A-644-S5,  
04-A-645-S3, 04-A-649, 04-A-650, 04-A-651, 04-A-652-S1,  
04-A-653

#### Pollutant: Total HAP

Emission Limit: 24.4 tons/yr (Plant-wide limit)

Authority for Requirement: DNR Construction Permits 04-A-642-S3, 04-A-644-S5,  
04-A-645-S3, 04-A-649, 04-A-650, 04-A-651, 04-A-652-S1,  
04-A-653

### Reporting and Recordkeeping

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

A. Plant-wide, record the HAP emissions (in tons) for each HAP and total HAPs per twelve-month rolling period.

Authority for Requirement: 567 IAC 22.108(3)

Opacity (visible emissions): 40% opacity

Authority for Requirement: 567 IAC 23.3(2)"d"

Sulfur Dioxide (SO<sub>2</sub>): 500 parts per million by volume

Authority for Requirement: 567 IAC 23.3(3)"e"

Particulate Matter:

No person shall cause or allow the emission of particulate matter from any source in excess of the emission standards specified in this chapter, except as provided in 567 – Chapter 24. For sources constructed, modified or reconstructed after July 21, 1999, the emission of particulate matter from any process shall not exceed an emission standard of 0.1 grain per dry standard cubic foot of exhaust gas, except as provided in 567 – 21.2(455B), 23.1(455B), 23.4(455B) and 567 – Chapter 24.

For sources constructed, modified or reconstructed prior to July 21, 1999, the emission of particulate matter from any process shall not exceed the amount determined from Table I, or amount specified in a permit if based on an emission standard of 0.1 grain per standard cubic foot of exhaust gas or established from standards provided in 23.1(455B) and 23.4(455B).

Authority for Requirement: 567 IAC 23.3(2)"a"

Fugitive Dust: Attainment and Unclassified Areas - A person shall take reasonable precautions to prevent particulate matter from becoming airborne in quantities sufficient to cause a nuisance as defined in Iowa Code section 657.1 when the person allows, causes or permits any materials to be handled, transported or stored or a building, its appurtenances or a construction haul road to be used, constructed, altered, repaired or demolished, with the exception of farming operations or dust generated by ordinary travel on unpaved roads. Ordinary travel includes routine traffic and road maintenance activities such as scarifying, compacting, transporting road maintenance surfacing material, and scraping of the unpaved public road surface. (the preceding sentence is State Only) All persons, with the above exceptions, shall take reasonable precautions to prevent the discharge of visible emissions of fugitive dusts beyond the lot line of the property on which the emissions originate. The public highway authority shall be responsible for taking corrective action in those cases where said authority has received complaints of or has actual knowledge of dust conditions which require abatement pursuant to this subrule. Reasonable precautions may include, but not be limited to, the following procedures.

1. Use, where practical, of water or chemicals for control of dusts in the demolition of existing buildings or structures, construction operations, the grading of roads or the clearing of land.
2. Application of suitable materials, such as but not limited to asphalt, oil, water or chemicals on unpaved roads, material stockpiles, race tracks and other surfaces which can give rise to airborne dusts.
3. Installation and use of containment or control equipment, to enclose or otherwise limit the emissions resulting from the handling and transfer of dusty materials, such as but not limited to grain, fertilizer or limestone.
4. Covering, at all times when in motion, open-bodied vehicles transporting materials likely to give rise to airborne dusts.
5. Prompt removal of earth or other material from paved streets or to which earth or other material has been transported by trucking or earth-moving equipment, erosion by water or other means.

6. Reducing the speed of vehicles traveling over on-property surfaces as necessary to minimize the generation of airborne dusts.

Authority for Requirement: 567 IAC 23.3(2)"c"

---

#### **40 CFR 60 Subpart A Requirements**

This facility is an affected source and these *General Provisions* apply to the facility. The affected units are EP S10, EP S40, EP SEP22, EP S23, EP F110, EP T61, EP T62, EP T63, EP T64, and EP T65.

See Appendix for a link to the Standard.

Applicable requirements are incorporated in the Emission Point Specific conditions.

Authority for Requirements: 40 CFR 60 Subpart A  
567 IAC 23.1(2)

#### **40 CFR 60 Subpart Db Requirements**

This facility is subject to Standards of Performance for *Industrial Commercial Institutional Steam Generating Units*. The affected unit is EP S10.

See Appendix for a link to the Standard.

Authority for Requirements: 40 CFR 60 Subpart Db  
567 IAC 23.1(2) "ccc"

#### **40 CFR 60 Subpart Kb Requirements**

This facility is subject to Standards of Performance for *Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels)* for Which Construction, Reconstruction, or Modification Commenced after July 23, 1984. The affected units are EP T61, EP T62, EP T63, EP T64, and EP T65.

See Appendix for a link to the Standard.

Authority for Requirements: 40 CFR 60 Subpart Kb  
567 IAC 23.1(2) "ddd"

#### **40 CFR 60 Subpart VV Requirements**

This facility is subject to Standards of Performance for *Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry*. The affected units are equipment in VOC service and any applicable devices and systems (as defined in 40 CFR 60.481) in the entire facility, which include EP S10, EP S40, EP SEP22, EP S23, EP F110, EP T61, EP T62, EP T63, EP T64, and EP T65. The owner or operator shall comply with the applicable requirements in 40 CFR 60.480 through 60.489, including recordkeeping requirements in 40 CFR 60.486 and reporting requirements in 40 CFR 60.487.

See Appendix for a link to the Standard.

Authority for Requirements: 40 CFR 60 Subpart VV  
567 IAC 23.1(2) "nn"

**40 CFR 63 Subpart ZZZZ Requirements**

This facility is subject to National Emission Standards for Hazardous Air Pollutants for *Stationary Reciprocating Internal Combustion Engines* (RICE NESHAP). The affected unit is EP F70.

See Appendix for a link to the Standard.

Authority for Requirements: 40 CFR 63 Subpart ZZZZ  
567 IAC 23.1(4) "cz"

**40 CFR 63 Subpart BBBBBB Requirements**

This facility is subject to National Emission Standards for Hazardous Air Pollutants for *Source Category: Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities*. The affected unit is EP SEP22 and F110.

See Appendix for a link to the Standard.

### III. Emission Point-Specific Conditions

Facility Name: Andersons Denison Ethanol, LLC  
 Permit Number: 14-TV-011

#### Emission Point ID Number: S10

##### Associated Equipment

Associated Emission Unit ID Numbers: P50a, P50b, P50c, P50d, P50e, P50f, P10a, P10b  
 Emissions Control Equipment ID Number: C10  
 Emissions Control Equipment Description: Thermal Oxidizer (125 MMBtu/hr)  
 Continuous Emissions Monitors ID Numbers: None

EU	Emission Unit Description	Maximum Capacity
P50a	Slurry Tank	16,000 gallons
	Liquefaction Tank #1 and #2	50,000 gallons (each)
	Beer Column	500 gal/min
	Stripper	65 gal/min
	Rectifier	9600 gal/hr
	Evaporator System	66,500 sq. ft. (8 evaporators)
	Whole Stillage Tank	500 gal/min
	Thin Stillage Tank	146,000 gallons
	Syrup Tank	50,000 gallons
	Molecular Sieve #1, #2, and 3	130 gal/min (each)
	Process Condensate Tank	264 gallons
	200 Proof Condenser	22.5 sq. ft.
	Yeast Tank	234 sq. ft.
	Centrifuge # 1	8100 -15,000 lb/hr (each)
P50b	Centrifuge # 2	
P50c	Centrifuge # 3	
P50d	Centrifuge # 4	
P50e	Centrifuge # 5	
P50f	Centrifuge # 6	
P10a	DDGS Dryer #1	37.6 tons/hr, 42 MMBtu/hr
P10b	DDGS Dryer #2	37.6 tons/hr, 42 MMBtu/hr

## **Applicable Requirements**

### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: DNR Construction Permit 04-A-642-S3  
567 IAC 23.3(2) "d"

<sup>(1)</sup> An exceedance of the indicator opacity of "No Visible Emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM<sub>10</sub>)

Emission Limit(s): 6.88 lb/hr

Authority for Requirement: DNR Construction Permit 04-A-642-S3

Pollutant: Particulate Matter (PM)

Emission Limit(s): 6.88 lb/hr; 0.1 gr/dscf

Authority for Requirement: DNR Construction Permit 04-A-642-S3  
567 IAC 23.4(7)

Pollutant: Sulfur Dioxide (SO<sub>2</sub>)

Emission Limit(s): 8.48 lb/hr

Authority for Requirement: DNR Construction Permit 04-A-642-S3  
567 IAC 23.3(3)

Pollutant: Nitrogen Oxides (NO<sub>x</sub>)

Emission Limit(s): 25.0 lb/hr; 0.10 lb/MMBtu

Authority for Requirement: DNR Construction Permit 04-A-642-S3  
40 CFR 60 Subpart Db

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 6.88 lb/hr

Authority for Requirement: DNR Construction Permit 04-A-642-S3

Pollutant: Carbon Monoxide (CO)

Emission Limit(s): 20.56 lb/hr

Authority for Requirement: DNR Construction Permit 04-A-642-S3

Pollutant: Single HAP

Emission Limit(s): 9.4 tons/yr <sup>(2)</sup><sup>(3)</sup>

Authority for Requirement: DNR Construction Permit 04-A-642-S3

Pollutant: Total HAP

Emission Limit(s): 1.36 lb/hr <sup>(2)</sup>; 24.4 tons/yr <sup>(3)</sup>

Authority for Requirement: DNR Construction Permit 04-A-642-S3

<sup>(2)</sup> Specific HAPs of concern are acrolein at 0.20 lb/hr, acetaldehyde at 0.175 lb/hr, formaldehyde at 0.20 lb/hr and methanol at 0.34 lb/hr. HAP emission limits established to maintain potential emissions of the facility below “major source” thresholds for the purposes of NESHAP applicability as defined in 40 CFR Part 63.2.

<sup>(3)</sup> Plant-wide limit on HAP emissions to keep the facility an area source for NESHAP.

### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **Operating Limits**

- A. The owner or operator shall follow the applicable standards of Subpart VV, 40 CFR 60.480 through 60.489.
- B. The owner or operator shall follow the applicable standards of Subpart Db, 40 CFR 60.40b through 60.49b.
- C. The thermal oxidizer shall maintain a temperature (3 hour average) during operation of within + / -50 degrees Fahrenheit of the average temperature of the oxidizer recorded during the most recent performance test which demonstrated compliance with the emission limits, and shall be operated at all times the dryers or distillation equipment is being used.
- D. For the CEMS or PEMS, record the total air flow from the emission point.
- E. The dryer/thermal oxidizer system shall combust only natural gas and/or process off-gases.
- F. The control equipment shall be inspected and maintained according to manufacturer's recommendations.
- G. Plant-wide, MWDGS/DDGS Production shall not exceed 421,767 tons per rolling twelve (12) month rolling period.

#### **Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

- A. The owner or operator shall keep hourly records of the operating temperatures of the thermal oxidizer, and record all three-hour periods (during actual operations) during which the average temperature of the thermal oxidizer is more than 50 degrees Fahrenheit above or below the average temperature of the oxidizer during its most recent performance test which demonstrated compliance with the emission limits.
- B. The owner or operator shall keep records as required in 40 CFR 60.486, and reports as required in 40 CFR 60.487.
- C. The owner or operator shall keep records of control equipment inspections and repairs.
- D. The owner or operator shall record and maintain records of the amounts of each fuel combusted during each day, and calculate the annual capacity factor on a 12 month rolling average basis with a new annual capacity factor calculated at the end of each calendar month, as required in 40 CFR 60.49b(d). The annual capacity factor is defined as the ratio between

the actual heat input to a steam generating unit during a calendar year, and the potential heat input had it been operated for 8,760 hours during a calendar year at the maximum steady state design heat input capacity.

- E. Record on an hourly basis the air flow rate from the emission point.
- F. The owner or operator shall maintain records of the following information for each steam generating unit operating day, as required in 40 CFR 60.49b(g). This information shall also be submitted in a report, as required in 40 CFR 60.49b(i).
  - a. Calendar date
  - b. Average hourly nitrogen oxides emission (as NO<sub>2</sub>) rates measured or predicted.
  - c. 30-day average nitrogen oxides emission rates calculated at the end of each steam generating unit operating day from the measured hourly nitrogen oxide emission rates for the preceding 30 steam generating unit operating days.
  - d. Identification of the steam generating unit operating days when the calculated 30-day average nitrogen oxides emission rates are in excess of the emission standard, with the reason for such excess emissions as well as a description of corrective actions taken.
  - e. Identification of the steam generating unit operating days for which pollutant data have not been obtained, including reasons for not obtaining sufficient data and a description of corrective actions taken.
  - f. Identification of the times when emission data have been excluded from the calculation of average emission rates and the reasons for excluding data.
  - g. Identification of "F" factor used for calculations, method of determination, and type of fuel combusted.
  - h. Identification of the times when the pollutant concentrations exceeded the full span of the continuous monitoring system.
  - i. Description of any modifications to the continuous monitoring system that could affect the ability of the CMS to comply with Performance Specification 2 or 3.
  - j. Results of daily CEMS drift tests and quarterly accuracy assessments as required under 40 CFR Appendix F, Procedure 1.
- G. The owner or operator shall determine the amount of MWDGS/DDGS for each month of operation, and determine the cumulative amount of MWDGS/DDGS on a rolling-12-month basis for each month of operation.

Authority for Requirement: DNR Construction Permit 04-A-642-S3

### **NSPS and NESHAP Applicability**

These emission units are subject to Subparts A (General Provisions) and Subpart Db - Standards of Performance for *Industrial-Commercial-Institutional Steam Generating Units* of the New Source Performance Standards (NSPS). Additionally, the facility (Plant Number 24-01-007) is subject to NSPS Subpart VV - Standards of Performance for *Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry*.

Authority for Requirement: DNR Construction Permit 04-A-642-S3

## **Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 125  
Stack Opening, (inches, dia.): 72  
Exhaust Flow Rate (acfm): 89,000  
Exhaust Temperature (°F): 205  
Discharge Style: Vertical unobstructed  
Authority for Requirement: DNR Construction Permit 04-A-642-S3

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

## **Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

### **Stack Testing:**

Pollutant – Opacity  
Test Method - 40 CFR 60, Appendix A, Method 9  
Stack Test to be Completed by – Once every 3 years  
Authority for Requirement – DNR Construction Permit 04-A-642-S3

Pollutant – Particulate Matter (PM<sub>10</sub>)  
Test Method - 40 CFR 51, Appendix M, 201A with 202  
Stack Test to be Completed by – August 14, 2017  
Authority for Requirement: 567 IAC 22.108(3)

Pollutant – Particulate Matter (PM)<sup>(3)</sup>  
Test Method - 40 CFR 60, Appendix A, Method 5  
40 CFR 51, Appendix M, Method 202  
Stack Test to be Completed by – Once every 3 years  
Authority for Requirement – DNR Construction Permit 04-A-642-S3

Pollutant – VOC<sup>(1)(3)</sup>  
Test Method - 40 CFR 60, Appendix A, Method 25A  
Stack Test to be Completed by – Once every 3 years  
Authority for Requirement – DNR Construction Permit 04-A-642-S3

Pollutant – Single HAP<sup>(2)</sup>  
Test Method - 40 CFR 60, Appendix A, Method 18  
Stack Test to be Completed by – August 14, 2017  
Authority for Requirement – 567 IAC 22.108(3)

Pollutant – Total HAP  
Test Method - 40 CFR 60, Appendix A, Method 18  
Stack Test to be Completed by – August 14, 2017  
Authority for Requirement – 567 IAC 22.108(3)

- (1) VOC compliance testing may be determined using the worst case of either Method 25A or the sum of the Method 320 results.
- (2) Acrolein, acetaldehyde, formaldehyde and methanol shall be tested for specifically.
- (3) Stack testing shall be conducted once every three years with a minimum of 12 months between testing. If a stack test exceeds 95% of appropriate emission limitation, then testing shall revert to annual until 4 consecutive tests are less than 95% of the appropriate emissions limitation.

*The owner of this equipment or the owner's authorized agent shall provide written notice to the Director, not less than 30 days before a required stack test or performance evaluation of a continuous emission monitor. Results of the test shall be submitted in writing to the Director in the form of a comprehensive report within 6 weeks of the completion of the testing. 567 IAC 25.1(7)*

**Continuous Emissions Monitoring:**

Compliance with the nitrogen oxide emission limits of this permit shall be continuously demonstrated by the owner/operator through the use of a CEMS or PEMS. Therefore, the facility shall install, calibrate, maintain, and operate a CEMS or PEMS for measuring nitrogen oxides emissions discharged to the atmosphere and record the output of the system in lb/hr. This output shall be calculated as a 3-hour rolling average. The system shall be designed to meet the 40 CFR 60, Appendix B, Performance Specification 2 (PS2) and Performance Specification 6 (PS6) requirements. The specifications of 40 CFR Appendix F (Quality Assurance/Quality Control) shall apply. The monitor span shall be between 0 and 100 ppmv. Appendix F requirements shall be supplemented with a quarterly notice to the Department with the dates of the quarterly cylinder gas audits and annual relative accuracy test audit.

The CEMS or PEMS required by this permit shall be operated and data recorded during all periods of operation of the boiler (HRSG) except for CEM breakdowns and repairs. Data is recorded during calibration checks, and zero and span adjustments.

Authority for Requirement: DNR Construction Permit 04-A-642-S3

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP 19a, EP 19b**

### Associated Equipment

Associated Emission Unit ID Numbers: EU S19a, EU S19b  
Emissions Control Equipment ID Number: C19a, C19b  
Emissions Control Equipment Description: Baghouse  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: EU S19a, EU S19b  
Emission Unit Description: Grain Receiving by Truck (EU S19a),  
Tunnel Belt Conveyor (EU S19b)  
Raw Material/Fuel: Grain  
Rated Capacity: 45,000 bu/hr (receiving), 7,500 bu/hr (conveyor)

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from these emission points shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2)"d"

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.1 gr/dscf

Authority for Requirement: 567 IAC 23.4 (7)

#### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **Operating Limits**

Maintain baghouses (C19a and C19b) according to manufacturer specifications and maintenance schedule.

#### **Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

- A. Record the amount of corn received in bushels on a monthly basis. Calculate and record rolling 12-month totals.
- B. Maintain a record of all inspections/maintenance and any action resulting from the

inspection/maintenance of baghouses (C19a and C19b).

Authority for Requirement: 567 IAC 22.108(3)

**Compliance Plan**

*The owner/operator of this equipment shall comply with the applicable requirements listed.*

With the exception listed below, this point is in compliance with all applicable requirements and shall continue to comply with all such requirements. For those applicable requirements which will become effective during the permit term, this source will comply with such requirements in a timely manner.

**Exception**

*For this point to come into compliance, a construction permit is required for the emission unit vented through this point.*

**Condition**

*The permittee shall apply for a construction permit from the Iowa Department of Natural Resources within six (6) months of the issuance date of this permit. This point will be in compliance at the time the construction permit for the unit venting through this point is issued.*

Authority for Requirement: 567 IAC 22.108(15)

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Stack Testing at EP S19a:**

Pollutant – Particulate Matter (PM)  
Stack Test to be Completed by (Date) – August 14, 2017  
Test Method - 40 CFR 60, Appendix A Method 5  
40 CFR 51, Appendix M, Method 202  
Authority for Requirement – 567 IAC 22.108(3)

*The owner of this equipment or the owner’s authorized agent shall provide written notice to the Director, not less than 30 days before a required stack test or performance evaluation of a continuous emission monitor. Results of the test shall be submitted in writing to the Director in the form of a comprehensive report within 6 weeks of the completion of the testing. 567 IAC 25.1(7)*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**

Yes  No

*Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the applicable requirements.*

*Facility operation and maintenance plans are to be developed by the facility within six(6) months of the issuance date of this permit and the data pertaining to the plan maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.*

*Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.*

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP S20a, EP S20b, EP S20c, EP S20d, EP S20e**

Associated Equipment

<b>Emission Point</b>	<b>Associated Emission Unit ID Number</b>	<b>Emissions Control Equipment ID Number</b>	<b>Emissions Control Equipment Description</b>	<b>Construction Permit Number</b>
S20a	Tank A	CE S20a	Shaker Baghouse	06-A-318-S2
S20b	Tank B	CE S20b		06-A-319-S2
S20c	Tank C	CE S20c		06-A-320-S2
S20d	Tank D	CE S20d		04-A-640-S3
S20e	Tank E	CE S20e		04-A-641-S2

<b>EU</b>	<b>EU Description</b>	<b>Raw Material</b>	<b>Maximum Capacity (bushels)</b>
Tank A	Grain Storage Tank A	Grain	316,612
Tank B	Grain Storage Tank B		315,099
Tank C	Grain Storage Tank C		316,612
Tank D	Grain Storage Tank D		466,371
Tank E	Grain Storage Tank E		466,371

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from these emission points shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: DNR Construction Permit 06-A-318-S2, 06-A-319-S2, 06-A-320-S2, 04-A-640-S3, 04-A-641-S2  
567 IAC 23.3(2)"d"

<sup>(1)</sup> An exceedance of the indicator opacity of “No Visible Emissions” will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM<sub>10</sub>)

Emission Limit(s): 0.17 lb/hr

Authority for Requirement: DNR Construction Permit 06-A-318-S2, 06-A-319-S2,  
06-A-320-S2, 04-A-640-S3, 04-A-641-S2

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.17 lb/hr; 0.1 gr/dscf

Authority for Requirement: DNR Construction Permit 06-A-318-S2, 06-A-319-S2,  
06-A-320-S2, 04-A-640-S3, 04-A-641-S2  
567 IAC 23.4(7)

### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **Operating Limits**

- A. The owner or operator shall operate and maintain the control equipment accordance with the manufacture's specifications and instructions.
- B. The owner or operator shall conduct daily visible emissions observations of Emission Points EP S20a, EP S20b, EP S20c, EP S20d, and EP S20e. The observations shall only be conducted on days when the unit is in operation. If visible emissions are observed, the owner or operator of the affected facility must initiate corrective action within 24 hours to return the baghouse to normal operation, and it must be completed as soon as possible.

#### **Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

- A. The owner or operator shall maintain a copy of the manufacture's specifications and instructions that ensure proper operation of the control equipment.
- B. The permittee shall maintain a record of all inspections, maintenance, and repair and any action resulting from the inspection and maintenance of the control equipment.
- C. The permittee shall maintain a record of all daily visible emissions observations.
- D. The permittee shall maintain a record any corrective action taken if visible emissions are observed for this emission point, including the date and time the visible emissions were observed, the time corrective action was initiated and completed, and the corrective action taken.

Authority for Requirement: DNR Construction Permit 06-A-318-S2, 06-A-319-S2,  
06-A-320-S2, 04-A-640-S3, 04-A-641-S2

**Emission Point Characteristics**

*The emission points shall conform to the specifications listed in the table below.*

<b>EP Number</b>	<b>S20a, S20c *</b>	<b>S20b *</b>	<b>S20d, S20e</b>
Stack Height, (ft, from the ground)	90.9	90.7	97.5
Stack Opening, (inches, dia.)	23 x 8		
Exhaust Flow Rate (acfm)	2000		
Exhaust Temperature (°F)	Ambient		
Discharge Style	Horizontal		

\* These emission units also include 8 roof exhausters (each 24” x 24”) and 18 gravity vents (each 18” x 18”). All the exhaust points discharge horizontally.

Authority for Requirement: DNR Construction Permit 06-A-318-S2, 06-A-319-S2, 06-A-320-S2, 04-A-640-S3, 04-A-641-S2

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

*Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source’s compliance with the applicable requirements.*

*Facility operation and maintenance plans are to be developed by the facility within six(6) months of the issuance date of this permit and the data pertaining to the plan maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility’s implementation of its obligation to operate according to good air pollution control practice.*

*Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.*

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP S20f, EP S20g**

Associated Equipment

<b>Emission Point</b>	<b>Associated Emission Unit ID Number</b>	<b>Emissions Control Equipment ID Number</b>	<b>Emissions Control Equipment Description</b>	<b>Construction Permit Number</b>
S20f	Tank F	CE S20f	Shaker	06-A-321-S3
S20g	Tank G	CE S20g	Baghouse	06-A-322-S3

<b>EU</b>	<b>EU Description</b>	<b>Raw Material</b>	<b>Maximum Capacity (bushels)</b>
Tank F	Grain Storage Silo F	Grain	253,714
Tank G	Grain Storage Silo G		254,554

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from these emission points shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: DNR Construction Permit 06-A-321-S3, 06-A-322-S3  
567 IAC 23.3(2) "d"

<sup>(1)</sup> An exceedance of the indicator opacity of “No Visible Emissions” will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM<sub>10</sub>)

Emission Limit(s): 0.30 lb/hr

Authority for Requirement: DNR Construction Permit 06-A-321-S3, 06-A-322-S3

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.30 lb/hr; 0.1 gr/dscf

Authority for Requirement: DNR Construction Permit 06-A-321-S3, 06-A-322-S3  
567 IAC 23.4(7)

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

**Operating Limits**

- A. The owner or operator shall operate and maintain the control equipment accordance with the manufacture’s specifications and instructions.
- B. The owner or operator shall conduct daily visible emissions observations of Emission Points EP S20f and EP S20g. The observations shall only be conducted on days when the unit is in operation. If visible emissions are observed, the owner or operator of the affected facility must initiate corrective action within 24 hours to return the baghouse to normal operation, and it must be completed as soon as possible.

**Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

- A. The owner or operator shall maintain a copy of the manufacture’s specifications and instructions that ensure proper operation of the control equipment.
- B. The permittee shall maintain a record of all inspections, maintenance, and repair and any action resulting from the inspection and maintenance of the control equipment.
- C. The permittee shall maintain a record of all daily visible emissions observations.
- D. The permittee shall maintain a record any corrective action taken if visible emissions are observed for this emission point, including the date and time the visible emissions were observed, the time corrective action was initiated and completed, and the corrective action taken.

Authority for Requirement: DNR Construction Permit 06-A-321-S3, 06-A-322-S3

**Emission Point Characteristics**

*The emission points shall conform to the specifications listed in the table below.*

<b>EP Number</b>	<b>S20f and S20g</b>
Stack Height, (ft, from the ground)	120.6
Stack Opening, (inches, dia.)	23 x 3
Exhaust Flow Rate (acfm)	3450
Exhaust Temperature (°F)	Ambient
Discharge Style	Horizontal

Authority for Requirement: DNR Construction Permit 06-A-321-S3, 06-A-322-S3

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate

may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

*Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the applicable requirements.*

*Facility operation and maintenance plans are to be developed by the facility within six (6) months of the issuance date of this permit and the data pertaining to the plan maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.*

*Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.*

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP S30**

### Associated Equipment

Associated Emission Unit ID Numbers: P30  
Emissions Control Equipment ID Number: CE C30  
Emissions Control Equipment Description: Baghouse  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: P30  
Emission Unit Description: Hammermills  
Raw Material/Fuel: Grain  
Rated Capacity: One mill, 56.5 tons/hr; two mills, 70 tons/hr each

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: DNR Construction Permit 04-A-643-S3  
567 IAC 23.3(2) "d"

<sup>(1)</sup> An exceedance of the indicator opacity of 10% will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM<sub>10</sub>)

Emission Limit(s): 1.0 lb/hr

Authority for Requirement: DNR Construction Permit 04-A-643-S3

Pollutant: Particulate Matter (PM)

Emission Limit(s): 1.0 lb/hr; 0.1 gr/dscf

Authority for Requirement: DNR Construction Permit 04-A-643-S3  
567 IAC 23.4(7)

#### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **Operating Limits**

A. Maintain the baghouse according to the manufacturer's specifications.

## **Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

A. The owner or operator shall keep records of control equipment inspection and repair.

Authority for Requirement: DNR Construction Permit 04-A-643-S3

## **Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 40

Stack Opening, (inches, dia.): 26

Exhaust Flow Rate (acfm): 12,000

Exhaust Temperature (°F): 70

Discharge Style: Vertical unobstructed

Authority for Requirement: DNR Construction Permit 04-A-643-S3

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

## **Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

### **Stack Testing:**

Pollutant – Particulate Matter (PM<sub>10</sub>)

Stack Test to be Completed by (date) – August 14, 2017

Test Method - 40 CFR 51, Appendix M, 201A with 202

Authority for Requirement – 567 IAC 22.108(3)

Pollutant – Particulate Matter (PM)

Stack Test to be Completed by (date) – August 14, 2017

Test Method – 40 CFR 60, Appendix A, Method 5

40 CFR 51, Appendix M, Method 202

Authority for Requirement – 567 IAC 22.108(3)

*The owner of this equipment or the owner's authorized agent shall provide written notice to the Director, not less than 30 days before a required stack test or performance evaluation of a continuous emission monitor. Results of the test shall be submitted in writing to the Director in*

*the form of a comprehensive report within 6 weeks of the completion of the testing. 567 IAC 25.1(7)*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

*Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the applicable requirements.*

*Facility operation and maintenance plans are to be developed by the facility within six(6) months of the issuance date of this permit and the data pertaining to the plan maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.*

*Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.*

Authority for Requirement: 567 IAC 22.108(3)

## Emission Point ID Number: EP S40

### Associated Equipment

Associated Emission Unit ID Numbers: P40a – P40e

Emissions Control Equipment ID Number: C40

Emissions Control Equipment Description: Packed Bed CO<sub>2</sub> Scrubber

Continuous Emissions Monitors ID Numbers: None

---

EU	Emissions Unit Description	Raw Material/Fuel	Maximum Capacity
EU40a	Fermenter #1	Corn Mash	730,000 gallons (each)
EU40b	Fermenter #2		
EU40c	Fermenter #3		
EU40e	Fermenter #5		
	Fermenter #4		
EU40d	Beer Well	Beer	985,000 gallons

### Applicable Requirements

#### Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: DNR Construction Permit 04-A-644-S5  
567 IAC 23.3(2) "d"

<sup>(1)</sup> An exceedance of the indicator opacity of "No Visible Emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM<sub>10</sub>)

Emission Limit(s): 0.10 lb/hr

Authority for Requirement: DNR Construction Permit 04-A-644-S5

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.10 lb/hr; 0.1 gr/dscf

Authority for Requirement: DNR Construction Permit 04-A-644-S5  
567 IAC 23.3(2) "a"

Pollutant: Volatile Organic Compounds (VOC)  
Emission Limit(s): 12.0 lb/hr  
Authority for Requirement: DNR Construction Permit 04-A-644-S5

Pollutant: Single HAP  
Emission Limit(s): 9.4 tons/yr <sup>(2)(3)</sup>  
Authority for Requirement: DNR Construction Permit 04-A-644-S5

Pollutant: Total HAP  
Emission Limit(s): 2.80 lb/hr; 24.4 tons/yr <sup>(2)(3)</sup>  
Authority for Requirement: DNR Construction Permit 04-A-644-S5

<sup>(4)</sup> Specific HAP are acrolein at 0.31 lb/hr, acetaldehyde at 1.86 lb/hr, formaldehyde at 0.10 lb/hr and methanol at 0.31 lb/hr.

<sup>(5)</sup> Plant-wide limit on HAP emissions to keep the facility synthetic minor for any applicable NESHAP.

### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **Operating Limits**

- A. The owner or operator shall follow the applicable standards of Subpart VV, 40 CFR 60.480 through 60.489.
- B. The owner or operator shall inspect and maintain the control equipment according to manufacturer's recommendations.
- C. Total denatured ethanol production shall not exceed 65.00 million gallons per rolling twelve (12) month period.
- D. The minimum liquid feed rate to the scrubber shall be at least 90% of the average liquid feed rate observed during the most recent accepted compliance test which demonstrated compliance with all applicable emission limitations.
- E. The pressure drop across to the scrubber shall be maintained above 90% of the average pressure drop across the scrubber observed during the most recent accepted compliance test which demonstrated compliance with all applicable emission limitations.
- F. Any additive added to the scrubber liquid during the compliance testing to enhance the removal efficiency of the scrubber shall be added at the same rate that it was added for the most recent accepted compliance test which demonstrated compliance with all applicable emission limitations.

#### **Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

- A. The owner or operator shall keep records as required in 40 CFR 60.486, and reports as required in 40 CFR 60.487.

- B. The owner or operator shall keep records of control equipment inspections and repairs.
- C. The owner or operator shall determine the total amount of denatured ethanol produced for each month of operation and determine the cumulative amount of denatured ethanol produced on a rolling 12-month basis for each month of operation.
- D. Maintain a copy of the most recent compliance test report which showed compliance with all applicable emission limitations. This report shall include, but not be limited to, the emission rates observed during the testing, the average liquid feed rate to the scrubber during the testing, the average pressure drop across the scrubber during the testing, the average pH of the scrubber liquid during the testing, and the additive feed rate during the testing if additives are used. All excess emission reporting shall be conducted in accordance with 567 IAC 24.1(1).
- E. Install and continually operate a strip chart recorder or other device to continually record the scrubber liquid feed rate. All excess emission reporting shall be conducted in accordance with 567 IAC 24.1(1).
- F. Install and continually operate a strip chart recorder or other device to continually record the pressure drop across the scrubber. All excess emission reporting shall be conducted in accordance with 567 IAC 24.1(1).
- G. If an additive to the scrubber liquid is used and it is continually added to the scrubber liquid, install and continually operate a strip chart recorder or other device to continually record the additive feed rate. If an additive to the scrubber liquid is used and it is mixed with the scrubber liquid in a batch operation, record the time each batch is mixed as well as the amount of additive added to the scrubber liquid.

Authority for Requirement: DNR Construction Permit 04-A-644-S5

#### **NSPS and NESHAP Applicability**

These emission units are subject to Subparts A (*General Provisions*) and NSPS Subpart VV - Standards of Performance for *Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry*.

Authority for Requirement: DNR Construction Permit 04-A-644-S5

#### **Compliance Plan**

*The owner/operator of this equipment shall comply with the applicable requirements listed.*

With the exception listed below, this point is in compliance with all applicable requirements and shall continue to comply with all such requirements. For those applicable requirements which will become effective during the permit term, this source will comply with such requirements in a timely manner.

#### **Exception**

*For this point to come into compliance, a construction permit modification is required for the emission unit vented through this point.*

## **Condition**

*The permittee shall apply for a construction permit modification from the Iowa Department of Natural Resources within six (6) months of the issuance date of this permit. This point will be in compliance at the time the construction permit for the unit venting through this point is issued.*

Authority for Requirement: 567 IAC 22.108(15)

## **Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 45

Stack Opening, (inches, dia.): 20

Exhaust Flow Rate (scfm): 5100

Exhaust Temperature (°F): 75

Discharge Style: Vertical unobstructed

Authority for Requirement: DNR Construction Permit 04-A-644-S5

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the

emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

## **Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

### **Stack Testing:**

Pollutant – VOC <sup>(1)(3)</sup>

Stack Test to be Completed by – Once every 3 years

Test Method - 40 CFR 60, Appendix A, Method 25A

Authority for Requirement – DNR Construction Permit 04-A-644-S5

Pollutant – HAP <sup>(1)(2)</sup>

Stack Test to be Completed by – Once every 3 years

Test Method - 40 CFR 60, Appendix A, Method 18

Authority for Requirement – DNR Construction Permit 04-A-644-S5

<sup>(1)</sup> Stack testing shall be conducted once every three years with a minimum of 12 months between testing, and done between the months of June and September. If a stack test exceeds 95% of appropriate emission limitation, then testing shall revert to annual until 4 consecutive tests are less than 95% of the appropriate emissions limitation.

<sup>(2)</sup> Acrolein, acetaldehyde, formaldehyde and methanol shall be tested for specifically.

<sup>(3)</sup> VOC compliance testing may be determined using the worst case of either Method 25A or the sum of the Method 320 results.

*The owner of this equipment or the owner's authorized agent shall provide written notice to the Director, not less than 30 days before a required stack test or performance evaluation of a continuous emission monitor. Results of the test shall be submitted in writing to the Director in the form of a comprehensive report within 6 weeks of the completion of the testing. 567 IAC 25.1(7)*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP S70**

Associated Equipment

Associated Emission Unit ID Numbers: P70  
Emissions Control Equipment ID Number: C70  
Emissions Control Equipment Description: Baghouse  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: P70  
Emission Unit Description: DDGS Cooler  
Raw Material/Fuel: DDGS  
Rated Capacity: 18.15 tons/hr

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity  
Emission Limit(s): 40% <sup>(1)</sup>  
Authority for Requirement: DNR Construction Permit 04-A-645-S3  
567 IAC 23.3(2) "d"

<sup>(1)</sup> An exceedance of the indicator opacity of “No Visible Emissions” will require the owner or operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the Department may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM<sub>10</sub>)  
Emission Limit(s): 1.8 lb/hr  
Authority for Requirement: DNR Construction Permit 04-A-645-S3

Pollutant: Particulate Matter (PM)  
Emission Limit(s): 1.8 lb/hr; 0.1 gr/dscf  
Authority for Requirement: DNR Construction Permit 04-A-645-S3  
567 IAC 23.3(2)"a"

Pollutant: Volatile Organic Compounds (VOC)  
Emission Limit(s): 3.58 lb/hr  
Authority for Requirement: DNR Construction Permit 04-A-645-S3

Pollutant: Single HAP  
Emission Limit(s): 9.4 tons/yr <sup>(2)(3)</sup>  
Authority for Requirement: DNR Construction Permit 04-A-645-S3

Pollutant: Total HAP

Emission Limit(s): 0.35 lb/hr; 24.4 tons/yr <sup>(2) (3)</sup>

Authority for Requirement: DNR Construction Permit 04-A-645-S3

<sup>(2)</sup> Specific HAP are acrolein at 0.037 lb/hr, acetaldehyde at 0.046 lb/hr, formaldehyde at 0.061 lb/hr and methanol at 0.208 lb/hr.

<sup>(3)</sup> Plant-wide limit on HAP emissions to keep the facility synthetic minor for any applicable NESHAP.

### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **Operating Limits**

- A. The owner or operator shall follow the applicable standards of Subpart VV, 40 CFR 60.480 through 60.489.
- B. The owner or operator shall inspect and maintain the control equipment according to manufacturer's recommendations.
- C. Plant-wide, DDGS/MWDGS Production shall not exceed 421,767 tons per rolling twelve (12) month rolling period.

#### **Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

- A. The owner or operator shall keep records as required in 40 CFR 60.486, and reports as required in 40 CFR 60.487.
- B. The owner or operator shall keep records of control equipment inspections and repairs.
- C. The owner or operator shall determine the amount of DDGS/MWDGS for each month of operation, and determine the cumulative amount of DDGS/MWDGS on a rolling-12-month basis for each month of operation.

Authority for Requirement: DNR Construction Permit 04-A-645-S3

### **Compliance Plan**

*The owner/operator of this equipment shall comply with the applicable requirements listed.*

With the exception listed below, this point is in compliance with all applicable requirements and shall continue to comply with all such requirements. For those applicable requirements which will become effective during the permit term, this source will comply with such requirements in a timely manner.

#### **Exception**

*For this point to come into compliance, a construction permit modification is required for the emission unit vented through this point.*

## **Condition**

*The permittee shall apply for a construction permit modification from the Iowa Department of Natural Resources within six (6) months of the issuance date of this permit. This point will be in compliance at the time the construction permit for the unit venting through this point is issued.*

Authority for Requirement: 567 IAC 22.108(15)

## **Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 50

Stack Opening, (inches, dia.): 40

Exhaust Flow Rate (acfm): 30,000

Exhaust Temperature (°F): 68

Discharge Style: Vertical unobstructed

Authority for Requirement: DNR Construction Permit 04-A-645-S3

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

## **Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

### **Stack Testing:**

Pollutant – Particulate Matter (PM<sub>10</sub>)

Stack Test to be Completed by (date) – August 14, 2017

Test Method - 40 CFR 51, Appendix M, 201A with 202

Authority for Requirement – 567 IAC 22.108(3)

Pollutant – Particulate Matter (PM)

Stack Test to be Completed by (date) – August 14, 2017

Test Method – 40 CFR 60, Appendix A, Method 5

40 CFR 51, Appendix M, Method 202

Authority for Requirement – 567 IAC 22.108(3)

Pollutant – VOC <sup>(1)(2)</sup>

Stack Test to be Completed by – Once every 3 years

Test Method - 40 CFR 60, Appendix A, Method 25A

Authority for Requirement – DNR Construction Permit 04-A-645-S3

Pollutant – HAP <sup>(1)(3)</sup>

Stack Test to be Completed by – Once every 3 years

Test Method - According to DNR approved method

Authority for Requirement – DNR Construction Permit 04-A-645-S3

- (1) Testing of this stack shall be performed during the summer months and conducted in a manner to verify compliance with all emission limitations with all equipment operating in a worst case scenario. Stack testing shall be conducted once every three years with a minimum of 12 months between testing. If a stack test exceeds 95% of appropriate emission limitation, then testing shall revert to annual until 4 consecutive tests are less than 95% of the appropriate emissions limitation.
- (2) VOC compliance testing may be determined using the worst case of either Method 25A or the sum of the Method 320 results.
- (3) Acrolein, acetaldehyde, formaldehyde and methanol shall be tested for specifically. With the exception of acrolein, acetaldehyde, formaldehyde and methanol, any HAP whose emissions are below the detection limit shall be assumed to be zero.

*The owner of this equipment or the owner's authorized agent shall provide written notice to the Director, not less than 30 days before a required stack test or performance evaluation of a continuous emission monitor. Results of the test shall be submitted in writing to the Director in the form of a comprehensive report within 6 weeks of the completion of the testing. 567 IAC 25.1(7)*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

*Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the applicable requirements.*

*Facility operation and maintenance plans are to be developed by the facility within six(6) months of the issuance date of this permit and the data pertaining to the plan maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.*

*Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.*

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP S90**

Associated Equipment

Associated Emission Unit ID Numbers: P90  
Emissions Control Equipment ID Number: C90  
Emissions Control Equipment Description: Baghouse  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: P90  
Emission Unit Description: DDGS Loading  
Raw Material/Fuel: DDGS  
Rated Capacity: 250 tons/hr

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity  
Emission Limit(s): 40% <sup>(1)</sup>  
Authority for Requirement: DNR Construction Permit 04-A-646-S2  
567 IAC 23.3(2) "d"

<sup>(1)</sup> An exceedance of the indicator opacity of “No Visible Emissions” will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM<sub>10</sub>)  
Emission Limit(s): 0.37 lb/hr  
Authority for Requirement: DNR Construction Permit 04-A-646-S2

Pollutant: Particulate Matter (PM)  
Emission Limit(s): 0.37 lb/hr; 0.1 gr/dscf  
Authority for Requirement: DNR Construction Permit 04-A-646-S2  
567 IAC 23.4(7)

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

**Operating Limits**

- A. The control equipment shall be inspected and maintained according to manufacturer's recommendations.

### **Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

A. The owner or operator shall keep records of control equipment inspections and repairs.

Authority for Requirement: DNR Construction Permit 04-A-646-S2

### **Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 40

Stack Opening, (inches, dia.): 16

Exhaust Flow Rate (acfm): 5000

Exhaust Temperature (°F): Ambient

Discharge Style: Vertical unobstructed

Authority for Requirement: DNR Construction Permit 04-A-646-S2

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

### **Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

#### **Stack Testing:**

Pollutant – Particulate Matter (PM<sub>10</sub>)

Stack Test to be Completed by (date) – August 14, 2017

Test Method - 40 CFR 51, Appendix M, 201A with 202

Authority for Requirement – 567 IAC 22.108(3)

Pollutant – Particulate Matter (PM)

Stack Test to be Completed by (date) – August 14, 2017

Test Method – 40 CFR 60, Appendix A, Method 5

40 CFR 51, Appendix M, Method 202

Authority for Requirement – 567 IAC 22.108(3)

*The owner of this equipment or the owner's authorized agent shall provide written notice to the Director, not less than 30 days before a required stack test or performance evaluation of a continuous emission monitor. Results of the test shall be submitted in writing to the Director in*

*the form of a comprehensive report within 6 weeks of the completion of the testing. 567 IAC 25.1(7)*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

*Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the applicable requirements.*

*Facility operation and maintenance plans are to be developed by the facility within six(6) months of the issuance date of this permit and the data pertaining to the plan maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.*

*Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.*

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP SEP11**

### Associated Equipment

Associated Emission Unit ID Numbers: EU11  
Emissions Control Equipment ID Number: CE11  
Emissions Control Equipment Description: Flare  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: EU11  
Emission Unit Description: Biomethanator Flare  
Raw Material/Fuel: Methane/Natural Gas  
Rated Capacity: 3.2 MMBtu/hr

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: DNR Construction Permit 04-A-647-S1  
567 IAC 23.3(2) "d"

<sup>(1)</sup> An exceedance of the indicator opacity of "No Visible Emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.1 gr/dscf

Authority for Requirement: 567 IAC 23.3(2)"a"

Pollutant: Nitrogen Oxides (NO<sub>x</sub>)

Emission Limit(s): 0.22 lb/hr

Authority for Requirement: DNR Construction Permit 04-A-647-S1

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 0.17 lb/hr

Authority for Requirement: DNR Construction Permit 04-A-647-S1

Pollutant: Carbon Monoxide (CO)

Emission Limit(s): 1.2 lb/hr

Authority for Requirement: DNR Construction Permit 04-A-647-S1

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

**Operating Limits**

- A. The control equipment shall be inspected and maintained according to manufacturer's recommendations

**Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

- A. The owner or operator shall keep records of control equipment inspections and maintenance.

Authority for Requirement: DNR Construction Permit 04-A-647-S1

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 11

Stack Opening, (inches, dia.): 17

Exhaust Flow Rate (acfm): NA - Flare

Exhaust Temperature (°F): 1600

Discharge Style: Vertical unobstructed

Authority for Requirement: DNR Construction Permit 04-A-647-S1

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP SEP22**

### Associated Equipment

Associated Emission Unit ID Numbers: EU22  
Emissions Control Equipment ID Number: CE22  
Emissions Control Equipment Description: Flare  
Continuous Emissions Monitors ID Numbers: None

---

Emission Units vented through these Emission Points: EU22  
Emission Unit Description: Ethanol Truck Loadout  
Raw Material/Fuel: Ethanol  
Rated Capacity: 7.3 MMBtu/hr

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from these emission points shall not exceed the levels specified below.*

Pollutant: Opacity  
Emission Limit(s): 40%  
Authority for Requirement: 567 IAC 23.3(2)"d"

Pollutant: Particulate Matter (PM)  
Emission Limit(s): 0.1 gr/dscf  
Authority for Requirement: 567 IAC 23.3(2)"a"

Pollutant: Nitrogen Oxides (NO<sub>x</sub>)  
Emission Limit(s): 0.50 lb/hr  
Authority for Requirement: DNR Construction Permit 04-A-648-S2

Pollutant: Volatile Organic Compounds (VOC)  
Emission Limit(s): 6.17 tons/yr  
Authority for Requirement: DNR Construction Permit 04-A-648-S2

Pollutant: Carbon Monoxide (CO)  
Emission Limit(s): 2.70 lb/hr  
Authority for Requirement: DNR Construction Permit 04-A-648-S2

#### **NSPS and NESHAP Applicability**

The emission units are subject to the requirements/conditions of NSPS Subpart A-*General Provisions* and NSPS Subpart VV - Standards of Performance for *Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry* of the New Source Performance Standards (NSPS).

Authority for Requirement: DNR Construction Permit 04-A-648-S2

This facility is subject to NESHAP 40 CFR Part 63, Subpart BBBBBB – *National Emission Standards for Hazardous Air Pollutants for Source Category: Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities* (40 CFR §63.11080 through 40 CFR §63.11100).

Authority for Requirement: 567 IAC 22.108(3)

### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **Operating Limits**

- A. The owner or operator shall inspect and maintain the control equipment according to manufacturer's specifications.
- B. The owner or operator shall follow the applicable standards of Subpart VV, 40 CFR 60.480 through 60.489.
- C. The flare shall be operated per the requirements of NSPS Subpart A – 40 CFR Part 60.18 (i.e., smokeless design).
- D. The control equipment (flare) shall be used at all times product is loaded out by truck.
- E. The total amount of denatured ethanol loaded out plantwide shall not exceed 65,000,000 gallons per twelve-month rolling period.

#### **Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

- A. The owner or operator shall keep records of control equipment inspection and maintenance.
- B. The owner or operator shall keep records as required in 40 CFR 60.486, and reports as required in 40 CFR 60.487.
- C. For the first twelve (12) months of operation, the owner or operator shall determine the plantwide amount of product (denatured ethanol) loaded out each month. After the first twelve (12) months of operation, the owner or operator shall monthly record the amount of product loaded out plantwide and calculate the rolling 12-month total of product loaded out.

Authority for Requirement: DNR Construction Permit 04-A-648-S2

### **Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 36

Stack Opening, (inches, dia.): 30

Exhaust Flow Rate (acfm): NA – Flare

Exhaust Temperature (°F): 1600

Discharge Style: Vertical unobstructed

Authority for Requirement: DNR Construction Permit 04-A-648-S2

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate

may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP S23**

### Associated Equipment

Associated Emission Unit ID Numbers: P54  
Emissions Control Equipment ID Number: CE23  
Emissions Control Equipment Description: Flare  
Continuous Emissions Monitors ID Numbers: None

---

Emission Units vented through these Emission Points: P54  
Emission Unit Description: Ethanol Rail Loadout  
Raw Material/Fuel: Ethanol  
Rated Capacity: 60,000 gal/hr; 6.1 MMBtu/hr

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from these emission points shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: DNR Construction Permit 06-A-323-S3  
567 IAC 23.3(2)"d"

<sup>(1)</sup> An exceedance of the indicator opacity of 10% will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.1 gr/dscf

Authority for Requirement: 567 IAC 23.3(2)"a"

Pollutant: Sulfur Dioxide (SO<sub>2</sub>)

Emission Limit(s): 500 ppmv

Authority for Requirement: DNR Construction Permit 06-A-323-S3  
567 IAC 23.3(3) "e"

Pollutant: Nitrogen Oxides (NO<sub>x</sub>)

Emission Limit(s): 2.5 tons/yr

Authority for Requirement: DNR Construction Permit 06-A-323-S3

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 0.23 tons/yr

Authority for Requirement: DNR Construction Permit 06-A-323-S3

Pollutant: Carbon Monoxide (CO)

Emission Limit(s): 4.19 tons/yr

Authority for Requirement: DNR Construction Permit 06-A-323-S3

### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **Operating Limits**

- A. The facility may loadout to dedicated railcars only (i.e., no switch loading of railcars).
- B. The owner or operator shall follow the applicable standards of Subpart VV, 40 CFR 60.480 through 60.489.
- C. The flare shall be operated per the requirements of NSPS Subpart A – 40 CFR Part 60.18 (i.e., smokeless design).
- D. The total amount of denatured ethanol loaded out plantwide shall not exceed 65,000,000 gallons per twelve-month rolling period.

#### **Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

- A. The owner or operator shall keep records as required in 40 CFR 60.486, and reports as required in 40 CFR 60.487.
- B. For the first twelve (12) months of operation, the owner or operator shall determine the plantwide amount of product (denatured ethanol) loaded out each month. After the first twelve (12) months of operation, the owner or operator shall monthly record the amount of product loaded out plantwide and calculate the rolling 12-month total of product loaded out.
- C. The owner or operator shall keep records of control equipment inspection and repair.

Authority for Requirement: DNR Construction Permit 06-A-323-S3

#### **NSPS and NESHAP Applicability**

The emission units are subject to the requirements/conditions of NSPS Subpart A-*General Provisions* and NSPS Subpart VV - Standards of Performance for *Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry* of the New Source Performance Standards (NSPS).

Authority for Requirement: DNR Construction Permit 06-A-323-S3

#### **Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 35

Stack Opening, (inches, dia.): 42

Exhaust Flow Rate (acfm): 1000

Exhaust Temperature (°F): 1600

Discharge Style: Vertical unobstructed

Authority for Requirement: DNR Construction Permit 06-A-323-S3

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP F15**

Associated Equipment

Associated Emission Unit ID Numbers: F15  
Emissions Control Equipment ID Number: None  
Emissions Control Equipment Description: NA  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: F15  
Emission Unit Description: Grain Receiving Fugitives  
Raw Material/Fuel: Grain  
Rated Capacity: 45,000 bu/hr

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Fugitive Dust <sup>(1)</sup>

Emission Limit: No person shall allow, cause or permit any materials to be handled, transported or stored; or a building, its appurtenances or a construction haul road to be used, constructed, altered, repaired or demolished, without taking reasonable precautions to prevent a nuisance. All persons shall take reasonable precautions to prevent the discharge of visible emissions of fugitive dusts beyond the lot line of the property on which the emissions originate.

Authority for Requirement: DNR Construction Permit 06-A-810-S1  
567 IAC 23.3(2)"c"

<sup>(1)</sup> Opacity (visible emissions) at the lot line shall be 0%.

Pollutant: Particulate Matter (PM<sub>10</sub>)

Emission Limit(s): 0.79 tons/yr

Authority for Requirement: DNR Construction Permit 06-A-810-S1

Pollutant: Particulate Matter (PM)

Emission Limit(s): 1.78 tons/yr; 0.1 gr/dscf

Authority for Requirement: DNR Construction Permit 06-A-810-S1  
567 IAC 23.4(7)

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP F20**

Associated Equipment

Associated Emission Unit ID Numbers: F20  
Emissions Control Equipment ID Number: None  
Emissions Control Equipment Description: NA  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: F20  
Emission Unit Description: Modified Wet Distillers Grains (MWDGS) Storage Loadout  
Raw Material/Fuel: MWDGS  
Rated Capacity: 37.6 tons/hr

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Volatile Organic Compounds (VOC)  
Emission Limit(s): 0.74 tons/yr  
Authority for Requirement: DNR Construction Permit 12-A-563

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

**Operating Limits**

A. Plant-wide, DDGS/MWDGS production shall not exceed 421,767 tons per rolling twelve (12) month rolling period.

**Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

A. The owner or operator shall determine the amount of DDGS and MWDGS produced for each month of operation, and determine the cumulative amount of DDGS/MWDGS combined on a rolling-12-month basis for each month of operation.

Authority for Requirement: DNR Construction Permit 12-A-563

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**

Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**

Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: F70**

### Associated Equipment

Associated Emission Unit ID Numbers: F70  
Emissions Control Equipment ID Number: NA  
Emissions Control Equipment Description: None

---

Emission Unit vented through this Emission Point: F70  
Emission Unit Description: Fire Water Pump  
Raw Material/Fuel: Diesel  
Rated Capacity: 300 hp, 14 gal/hr

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity  
Emission Limit: 40% <sup>(1)</sup>  
Authority for Requirement: DNR Construction Permit 12-A-564  
567 IAC 23.3(2)"d"

<sup>(1)</sup> An exceedance of the indicator opacity of no visible emissions will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM<sub>10</sub>)  
Emission Limit: 0.66 lb/hr  
Authority for Requirement: DNR Construction Permit 12-A-564

Pollutant: Particulate Matter (PM)  
Emission Limit: 0.66 lb/hr; 0.1 gr/dscf  
Authority for Requirement: DNR Construction Permit 12-A-564  
567 IAC 23.3(2)"a"

Pollutant: SO<sub>2</sub>  
Emission Limit: 0.62 lb/hr; 500 ppmv  
Authority for Requirement: DNR Construction Permit 12-A-564  
567 IAC 23.3(3)

Pollutant: NO<sub>x</sub>  
Emission Limit: 9.3 lb/hr  
Authority for Requirement: DNR Construction Permit 12-A-564

Pollutant: VOC  
Emission Limit: 0.74 lb/hr  
Authority for Requirement: DNR Construction Permit 12-A-564

Pollutant: CO  
Emission Limit: 2.0 lb/hr  
Authority for Requirement: DNR Construction Permit 12-A-564

### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

### **Operating Limits**

- A. The unit is limited to operating a maximum of 500 hours per twelve month rolling period.
- B. This engine shall combust diesel fuel with a maximum sulfur content of 0. 5% by weight only.

### **Reporting & Record keeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

- A. At the end of each month, record the total hours of operation over the month of the unit.
- B. At the end of each month, record the total hours of operation over the previous twelve (12) months.
- C. The owner or operator shall either test the sulfur content of each diesel delivery or else have the fuel supplier certify the sulfur content for each delivery.

Authority for Requirement: DNR Construction Permit 12-A-564

### **NSPS and NESHAP Applicability**

This emergency engine is subject to 40 CFR 63 Subpart ZZZZ - National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines (RICE). According to 40 CFR 63.6590(a)(1)(iii) this compression ignition emergency engine, located at an area source, is an existing stationary RICE as it was constructed prior to June 12, 2006.

### **Compliance Date**

Per 63.6595(a)(1) you must comply with the provisions of Subpart ZZZZ that are applicable by May 3, 2013.

### **Fuel Requirements**

No requirements except (beginning January 1, 2015) if you own or operate an existing emergency compression ignited stationary engine with a site rating of more than 100 bhp and a displacement of less than 30 liters per cylinder that uses diesel fuel and operates or is contractually obligated to be available for more than 15 hours per calendar year for the purposes specified in 40 CFR 63.6640(f)(2)(ii) and (iii) or that operates for the purpose specified in

§63.6640(f)(4)(ii), you must use diesel fuel that meets the requirements in 40 CFR 80.510(b) for nonroad diesel fuel. Those requirements include a maximum sulfur content of 15 ppm (0.0015%) by weight and a minimum cetane index of 40 or a maximum aromatic content of 35 percent by volume. 40 CFR 63.6604(b).

Operation and Maintenance Requirements 40 CFR 63.6603, 63.6625, 63.6640 and Tables 2d and 6 to Subpart ZZZZ

1. Change oil and filter every 500 hours of operation or annually, whichever comes first. (See 63.6625(i) for the oil analysis option to extend time frame of requirements.)
2. Inspect air cleaner every 1000 hours of operation or annually, whichever comes first, and replace as necessary.
3. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.
4. Operate and maintain the stationary RICE and after-treatment control device (if any) according to the manufacturer's emission related written instructions or develop your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions.
5. Install a non-resettable hour meter if one is not already installed.
6. Minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes.

Operating Limits 40 CFR 63.6640(f)

1. Any operation other than emergency operation, maintenance and testing, emergency demand response and operation in non-emergency situations (*up to*) 50 hours per year is prohibited.
2. There is no time limit on the use of emergency stationary RICE in emergency situations.
3. You may operate your emergency stationary RICE up to 100 combined hours per calendar year for maintenance checks and readiness testing, emergency demand response and periods where there is a deviation of voltage or frequency of 5 percent or greater below standard voltage or frequency. See 40 CFR 63.6640(f)(2) for additional information and restrictions.
4. You may operate your emergency stationary RICE up to 50 hours per calendar year for non-emergency situations, but those 50 hours are counted toward the 100 hours of maintenance and testing and emergency demand response. Except as provided in 40 CFR 63.6640(f)(4)(i) and (ii), the 50 hours per year for non-emergency situations cannot be used for peak shaving or non-emergency demand response, or to generate income for a facility to supply power to an electric grid or otherwise supply power as part of a financial arrangement with another entity.

Recordkeeping Requirements 40 CFR 63.6655

1. Keep records of the maintenance conducted on the stationary RICE.
2. Keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. Document how many hours are spent for emergency operation,

including what classified the operation as emergency and how many hours are spent for non-emergency operation. See 40 CFR 63.6655(f) for additional information.

Notification and Reporting Requirements 40 CFR 63.6645, 63.6650 and Table 2d to Subpart ZZZZ

1. An initial notification is not required per 40 CFR 63.6645(a)(5)
2. A report may be required for failure to perform the work practice requirements on the schedule required in Table 2d. (See Footnote 2 of Table 2d for more information.)
3. If you own or operate an emergency stationary RICE with a site rating of more than 100 bhp that operates or is contractually obligated to be available for more than 15 hours per calendar year for the purposes specified in 40 CFR 63.6640(f)(2)(ii) and (iii) or that operates for the purpose specified in §63.6640(f)(4)(ii) , you must submit an annual report. (See 40 CFR 63.6650(h) for additional information.)

Authority for Requirement: 40 CFR 63 Subpart ZZZZ  
567 IAC 23.1(4)"cz"

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height (ft, from the ground): 9.5  
Stack Opening (inches, dia.): 5  
Exhaust Flow Rate (acfm): 1740  
Exhaust Temperature (°F): 770  
Discharge Style: Vertical unobstructed  
Authority for Requirement: DNR Construction Permit 12-A-564

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

**Monitoring Requirements**

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP F80**

### Associated Equipment

Associated Emission Unit ID Numbers: F80  
Emissions Control Equipment ID Number: None  
Emissions Control Equipment Description: NA  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: F80  
Emission Unit Description: Cooling Tower  
Raw Material/Fuel: Water  
Rated Capacity: 1,280,000 gal/hr

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity  
Emission Limit(s): 40%  
Authority for Requirement: 567 IAC 23.3(2)"d"

Pollutant: Particulate Matter (PM)  
Emission Limit(s): 0.1 gr/dscf  
Authority for Requirement: 567 IAC 23.3(2)"a"

#### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **Operating Limits**

A. The Total Dissolved Solids (TDS) Concentration in the cooling water shall not exceed 2,500 mg/l for any single sampling event.

#### **Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

A. The performance testing on the Total Dissolved Solids (TDS) concentration shall be completed at a minimum of once per calendar month.

Authority for Requirement: DNR Construction Permit 06-A-324

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP F100**

### Associated Equipment

Associated Emission Unit ID Numbers: F100  
Emissions Control Equipment ID Number: None  
Emissions Control Equipment Description: NA  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: EUF002  
Emission Unit Description: Fugitive Unpaved Roads  
Raw Material/Fuel: Fugitive Dust  
Rated Capacity: 10 VMT/hr

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity  
Emission Limit(s): <sup>(1)</sup>  
Authority for Requirement: DNR Construction Permit 06-A-325-S5  
567 IAC 23.3(2)"c"(1)

<sup>(1)</sup> The owner/operator shall take reasonable precautions to prevent the discharge of visible emissions of fugitive dusts beyond lot line of the property.

Pollutant: Particulate Matter (PM)  
Emission Limit(s): 35.13 tons/yr <sup>(2)</sup>  
Authority for Requirement: DNR Construction Permit 06-A-325-S5

Pollutant: Particulate Matter (PM<sub>10</sub>)  
Emission Limit(s): 7.03 tons/yr <sup>(2)</sup>  
Authority for Requirement: DNR Construction Permit 06-A-325-S5

<sup>(2)</sup> Particulate emission limit based on an average vehicle weight of 27.5 tons, silt content of 3.0 grams per square meter, maximum of 1.5 miles per truck trip, and the vehicle miles traveled during a 12-month rolling period. PM emission limit established to reduce potential emissions of the facility.

### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **Operating Limits**

- A. The haul roads shall be paved prior to receiving grain at the facility.
- B. Truck traffic on the haul road shall not exceed 10 mph. The speed limit shall be posted on the haul road.
- C. Any spills on the road shall be cleaned up immediately.

- D. Truck traffic emissions on the paved road shall be controlled by water flushing and sweeping [except as noted below] once per day.
  - a. If water flushing followed by sweeping cannot be accomplished because the ambient air temperature (as measured at the facility during daylight operating hours) will be less than 35<sup>0</sup> F (1.7<sup>0</sup> C) only sweeping is required. Water flushing and sweeping is not required for days of inclement weather.
  - b. Water flushing and sweeping need not occur when a rain gauge located at the site indicates that at least 0.2 inches of precipitation (water equivalent) has occurred within the preceding 24-hr time period or the paved road(s) will not be used on a given day.
  - c. Water flushing and sweeping need not occur if the plant does not receive any truck traffic that day (i.e. on a weekend).
- E. Silt load performance testing shall be required if the facility fails to record whether or not water flushing and sweeping was completed for three (3) consecutive days or for more than 36 days in any year. At that time, silt load performance testing shall be conducted quarterly. Testing shall be completed prior to water flushing and sweeping for that day. Provided the results demonstrate compliance with the PM & PM<sub>10</sub> ton per year emission limits, reduced frequency of testing may be requested after an additional 8 performance tests (i.e., 2 years of testing) have been completed.
- F. The PM and PM<sub>10</sub> emissions shall not exceed the emission limits in this permit per rolling twelve month period. Based on the total number of trucks the average Vehicle Miles Traveled (VMT) per truck shall be calculated for that month.

### **Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

- A. Record the frequency of water flushing and sweeping performed on the haul roads. If the roads are not swept due to weather, a written record must be kept on site outlining the conditions.
- B. If the facility fails to record the haul road management practices above, performance testing on the haul road surface silt loading shall be completed on a quarterly basis. For each performance test, silt loading sampling shall be done for at least 3 different locations. Performance testing shall be completed prior to water flushing and sweeping.
- C. The plant shall maintain a log for the haul roads that show the following:
  - a. The vehicle miles traveled (VMT) per truck and number of vehicles used to determine the VMT for that month;
  - b. Each day record whether or not water flushing and sweeping was accomplished. For days without water flushing and sweeping, record the circumstances (i.e. weather condition, equipment malfunction);
  - c. The amount of water applied and the areas treated; and,
  - d. The operator's initials.
- G. The owner/operator shall record the number of trucks that load/unload material on a monthly basis, and calculate and record the 12-month rolling total. If the average VMT per truck exceeds 1.5 miles, and/or the maximum number of trucks (i.e., total number of trips) used to

transport material to or from the facility exceeds 53,317 trucks per rolling 12-month period, the owner or operator shall calculate and update the PM and PM<sub>10</sub> twelve month rolling total emissions on a monthly basis using AP-42 Section 13.2.1 equation 2. The silt load used in the calculations shall be that measured in the last silt load test, or shall assumed to be 3.0 grams per square meter if the last silt load test is more than 4 months old.

Authority for Requirement: DNR Construction Permit 06-A-325-S5

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP F110**

### Associated Equipment

Associated Emission Unit ID Numbers: F110

Emissions Control Equipment ID Number: None

Emissions Control Equipment Description: Leak Detection and Repair (LDAR)

Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: F110

Emission Unit Description: VOC Emissions

Raw Material/Fuel: VOC

Rated Capacity: NA

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 9.54 tons/yr <sup>(1)</sup>

Authority for Requirement: DNR Construction Permit 07-A-1541-S1

<sup>(1)</sup> Limit established to restrict potential emissions below applicable Title V and PSD “major source” thresholds. This is a plant-wide limit for equipment leaks.

Pollutant: Total HAP

Emission Limit(s): 0.38 lb/hr <sup>(2)</sup>

Authority for Requirement: DNR Construction Permit 07-A-1541-S1

<sup>(2)</sup> Limit established to restrict potential emissions below applicable NESHAP “major source” thresholds. This is a plant-wide limit for equipment leaks.

#### **NSPS and NESHAP Applicability**

The emission units are subject to the requirements/conditions of NSPS Subpart A-*General Provisions* and NSPS Subpart VV - Standards of Performance for *Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry* of the New Source Performance Standards (NSPS).

Authority for Requirement: DNR Construction Permit 07-A-1541-S1

This facility is subject to NESHAP 40 CFR Part 63, Subpart BBBB – *National Emission Standards for Hazardous Air Pollutants for Source Category: Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities* (40 CFR §63.11080 through 40 CFR §63.11100).

Authority for Requirement: 567 IAC 22.108(3)

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

**Operating Limits**

- A. The VOC emissions from equipment leaks at this facility shall not exceed 9.54 tons per twelve (12) month rolling period, rolled monthly.
- B. The component count shall be documented as to the number and types of all components used including vacuum service components. Components include but are not limited to valves, pumps, compressor seals, flanges, etc. All components shall be tested initially including those of vacuum service; there is no de minimus level.
- C. The owner or operator shall follow the applicable standards of NSPS Subpart VV, 40 CFR 60.480 through 40 CFR 60.489.
- D. All emissions shall be recorded except those below detection limits.

**Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

- A. Determine the VOC emissions over the previous month from the facility using the calculation methods outlined in EPA’s document 453/R-95-017 titled Protocol for Equipment Leak Emission Estimates (page 2-11).
- B. At the end of each month, record the total VOC emissions over the previous twelve (12) months as determined in Condition A above.
- C. The owner or operator shall follow the applicable recordkeeping and reporting standards of Subpart VV, 40 CFR 60.486 and 60.487.

Authority for Requirement: DNR Construction Permit 07-A-1541-S1

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP GD2**

### Associated Equipment

Associated Emission Unit ID Numbers: GD2  
Emissions Control Equipment ID Number: None  
Emissions Control Equipment Description: NA  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: GD2  
Emission Unit Description: Grain Drying  
Raw Material/Fuel: Grain; Natural Gas  
Rated Capacity: 5000 bu/hr; 69.9 MMBtu/hr

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: DNR Construction Permit 06-A-809-S2  
567 IAC 23.3(2)"d"

<sup>(1)</sup> Visible emissions will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedence. If exceedences continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM<sub>10</sub>)

Emission Limit(s): 7.82 lb/hr

Authority for Requirement: DNR Construction Permit 06-A-809-S2

Pollutant: Particulate Matter (PM)

Emission Limit(s): 31.14 lb/hr; 0.1 gr/scf

Authority for Requirement: DNR Construction Permit 06-A-809-S2  
567 IAC 23.4(7)

Pollutant: Sulfur Dioxide (SO<sub>2</sub>)

Emission Limit(s): 0.04 lb/hr; 500 ppmv

Authority for Requirement: DNR Construction Permit 06-A-809-S2

Pollutant: Nitrogen Oxides (NO<sub>x</sub>)

Emission Limit(s): 6.09 lb/hr

Authority for Requirement: DNR Construction Permit 06-A-809-S2

Pollutant: Volatile Organic Compounds (VOC)  
Emission Limit(s): 0.33 lb/hr  
Authority for Requirement: DNR Construction Permit 06-A-809-S2

Pollutant: Carbon Monoxide (CO)  
Emission Limit(s): 5.2 lb/hr  
Authority for Requirement: DNR Construction Permit 06-A-809-S2

Pollutant: Total HAP  
Emission Limit(s): 0.34 tons/yr<sup>(2)</sup>  
Authority for Requirement: DNR Construction Permit 06-A-809-S2

<sup>(1)</sup> Emission limits established for the facility to remain 'synthetic' minor for NESHAP applicability. Estimated hexane emissions are 0.33 tpy, formaldehyde emissions are 0.014 tpy, and all other single HAP emissions are estimated to be less than 0.001 tpy.

### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **Operating Limits**

A. The unit is limited to operating a maximum of 6,000 hours per twelve month rolling period.

#### **Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

- A. At the end of each month, record the total hours of operation over the month of the unit.
- B. At the end of each month, record the total hours of operation over the previous twelve (12) months.

Authority for Requirement: DNR Construction Permit 06-A-809-S2

### **Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height (ft, from the ground): 48.5 – center of exhaust  
Stack Opening (sq. ft.): 460 and 663  
Exhaust Flow Rate (scfm): 282,000  
Exhaust Temperature (°F): 120  
Discharge Style: Horizontal  
Authority for Requirement: DNR Construction Permit 06-A-809-S2

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP T61 and EP T62**

### Associated Equipment

Associated Emission Unit ID Numbers: T61, T62  
Emissions Control Equipment ID Number: None  
Emissions Control Equipment Description: Internal Floating Roof  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: T61, T62  
Emission Unit Description: Denatured Ethanol Storage Tank  
Raw Material/Fuel: Denatured Ethanol  
Rated Capacity: 750,000 gallons each

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from these emission points shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: DNR Construction Permit 04-A-649, 04-A-650  
567 IAC 23.3(2)"d"

<sup>(1)</sup> An exceedance of the indicator opacity of no visible emissions will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Single HAP

Emission Limit(s): 9.4 tons/yr <sup>(3)</sup>

Authority for Requirement: DNR Construction Permit 04-A-649, 04-A-650

Pollutant: Total HAP

Emission Limit(s): 24.4 tons/yr <sup>(3)</sup>

Authority for Requirement: DNR Construction Permit 04-A-649, 04-A-650

<sup>(2)</sup> Plantwide limit, to remain minor for Title V and 112 (g).

#### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **Operating Limits**

A. The owner or operator shall follow the applicable standards of Subpart Kb, 40 CFR 60.112b(a)(1), and inspect as required in 50 CFR 60.113b(a).

**Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

- A. The owner or operator shall keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel for the lifetime of the source.
- B. The owner or operator shall follow the applicable recordkeeping and reporting standards of Subpart Kb, 40 CFR 60.115b through 60.116b.

Authority for Requirement: DNR Construction Permit 04-A-649, 04-A-650

**NSPS and NESHAP Applicability**

These storage tanks are subject to the following NSPS subparts:

Subpart A – *General Provisions*

Subpart Kb – *Standards of Performance for Volatile Organic Liquid Storage Vessels*

Authority for Requirement: DNR Construction Permit 04-A-649, 04-A-650

These storage tanks are subject to the following NSPS subpart:

Subpart VV – *Standards of Performance for Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry.*

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 61.7

Stack Opening, (inches, dia.): 10

Exhaust Flow Rate (scfm): NA – vent

Exhaust Temperature (°F): Ambient

Discharge Style: Downward

Authority for Requirement: DNR Construction Permit 04-A-649, 04-A-650

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**

Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## Emission Point ID Number: EP T63

### Associated Equipment

Associated Emission Unit ID Numbers: T63  
Emissions Control Equipment ID Number: None  
Emissions Control Equipment Description: Internal Floating Roof  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: T63  
Emission Unit Description: 200 Proof Ethanol Storage Tank  
Raw Material/Fuel: Ethanol  
Rated Capacity: 100,000 gallons

### Applicable Requirements

#### Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity  
Emission Limit(s): 40% <sup>(1)</sup>  
Authority for Requirement: DNR Construction Permit 04-A-651  
567 IAC 23.3(2)"d"

<sup>(1)</sup> An exceedance of the indicator opacity of no visible emissions will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Single HAP  
Emission Limit(s): 9.4 tons/yr <sup>(2)</sup>  
Authority for Requirement: DNR Construction Permit 04-A-651

Pollutant: Total HAP  
Emission Limit(s): 24.4 tons/yr <sup>(2)</sup>  
Authority for Requirement: DNR Construction Permit 04-A-651

<sup>(2)</sup> Plantwide limit, to remain minor for Title V and 112 (g).

#### Operational Limits & Requirements

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **Operating Limits**

A. The owner or operator shall follow the applicable standards of Subpart Kb, 40 CFR 60.112b(a)(1), and inspect as required in 50 CFR 60.113b(a).

**Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

- A. The owner or operator shall keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel for the lifetime of the source.
- B. The owner or operator shall follow the applicable recordkeeping and reporting standards of Subpart Kb, 40 CFR 60.115b through 60.116b.

Authority for Requirement: DNR Construction Permit 04-A-651

**NSPS and NESHAP Applicability**

These storage tanks are subject to the following NSPS subparts:

Subpart A – *General Provisions*

Subpart Kb – *Standards of Performance for Volatile Organic Liquid Storage Vessels*

Authority for Requirement: DNR Construction Permit 04-A-651

Subpart VV – *Standards of Performance for Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry.*

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 35.3

Stack Opening, (inches, dia.): 10

Exhaust Flow Rate (scfm): NA - vent

Exhaust Temperature (°F): Ambient

Discharge Style: Downward

Authority for Requirement: DNR Construction Permit 04-A-651

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**

Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP T64**

### Associated Equipment

Associated Emission Unit ID Numbers: T64  
Emissions Control Equipment ID Number: None  
Emissions Control Equipment Description: Internal Floating Roof  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: T64  
Emission Unit Description: Denaturant Storage Tank  
Raw Material/Fuel: Denaturant  
Rated Capacity: 100,000 gallons

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Single HAP  
Emission Limit(s): 9.4 tons/yr <sup>(1)</sup>  
Authority for Requirement: DNR Construction Permit 04-A-652-S1

Pollutant: Total HAP  
Emission Limit(s): 24.4 tons/yr <sup>(1)</sup>  
Authority for Requirement: DNR Construction Permit 04-A-652-S1

<sup>(1)</sup> Facility-wide limit imposed to keep the facility minor for Title V and 112(g).

#### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **Operating Limits**

A. The permit holder, owner and operator of the facility shall follow the applicable standards of Subpart Kb, 40 CFR 60.110b through 40 CFR 60.117b.

#### **Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

- A. The permit holder, owner and operator of the facility shall follow the applicable recordkeeping and reporting standards as required in 40 CFR 60.115b through 40 CFR 60.116b.
- B. The permit holder, owner and operator of the facility shall keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the

storage vessel for the lifetime of the source. Authority for Requirement: DNR Construction Permit 04-A-653

**NSPS and NESHAP Applicability**

These storage tanks are subject to the following NSPS subparts:

Subpart A – *General Provisions*

Subpart Kb – Standards of Performance for *Volatile Organic Liquid Storage Vessels*

Authority for Requirement: DNR Construction Permit 04-A-652-S1

Subpart VV – Standards of Performance for *Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry* for which Construction, Reconstruction, or Modification Commenced after November 7, 2006

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 35.3

Stack Opening, (inches, dia.): 10

Exhaust Flow Rate (scfm): NA - vent

Exhaust Temperature (°F): Ambient

Discharge Style: Downward

Authority for Requirement: DNR Construction Permit 04-A-652-S1

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP T65**

### Associated Equipment

Associated Emission Unit ID Numbers: T65  
Emissions Control Equipment ID Number: None  
Emissions Control Equipment Description: Internal Floating Roof  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: T65  
Emission Unit Description: 190 Proof Ethanol Storage Tank  
Raw Material/Fuel: Ethanol  
Rated Capacity: 100,000 gallons

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from these emission points shall not exceed the levels specified below.*

Pollutant: Opacity  
Emission Limit(s): 40% <sup>(1)</sup>  
Authority for Requirement: DNR Construction Permit 04-A-653  
567 IAC 23.3(2)"d"

<sup>(1)</sup> An exceedance of the indicator opacity of no visible emissions will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Single HAP  
Emission Limit(s): 9.4 tons/yr <sup>(3)</sup>  
Authority for Requirement: DNR Construction Permit 04-A-653

Pollutant: Total HAP  
Emission Limit(s): 24.4 tons/yr <sup>(3)</sup>  
Authority for Requirement: DNR Construction Permit 04-A-653

<sup>(3)</sup> Plantwide limit, to remain minor for Title V and 112 (g).

#### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **Operating Limits**

A. The owner or operator shall follow the applicable standards of Subpart Kb, 40 CFR 60.112b(a)(1), and inspect as required in 50 CFR 60.113b(a).

**Reporting and Recordkeeping**

*All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.*

- A. The owner or operator shall keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel for the lifetime of the source.
- B. The owner or operator shall follow the applicable recordkeeping and reporting standards of Subpart Kb, 40 CFR 60.115b through 60.116b.

Authority for Requirement: DNR Construction Permit 04-A-653

**NSPS and NESHAP Applicability**

These storage tanks are subject to the following NSPS subparts:

Subpart A – *General Provisions*

Subpart Kb – Standards of Performance for *Volatile Organic Liquid Storage Vessels*

Authority for Requirement: DNR Construction Permit 04-A-653

Subpart VV – Standards of Performance for *Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry.*

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point Characteristics**

*The emission points shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 35.3

Stack Opening, (inches, dia.): 10

Exhaust Flow Rate (scfm): NA - vent

Exhaust Temperature (°F): Ambient

Discharge Style: Downward

Authority for Requirement: DNR Construction Permit 04-A-653

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**

Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## IV. General Conditions

This permit is issued under the authority of the Iowa Code subsection 455B.133(8) and in accordance with 567 Iowa Administrative Code chapter 22.

### G1. Duty to Comply

1. The permittee must comply with all conditions of the Title V permit. Any permit noncompliance constitutes a violation of the Act and is grounds for enforcement action; for a permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application. *567 IAC 22.108(9)"a"*
2. Any compliance schedule shall be supplemental to, and shall not sanction noncompliance with, the applicable requirements on which it is based. *567 IAC 22.105 (2)"h"(3)*
3. Where an applicable requirement of the Act is more stringent than an applicable requirement of regulations promulgated under Title IV of the Act, both provisions shall be enforceable by the administrator and are incorporated into this permit. *567 IAC 22.108 (1)"b"*
4. Unless specified as either "state enforceable only" or "local program enforceable only", all terms and conditions in the permit, including provisions to limit a source's potential to emit, are enforceable by the administrator and citizens under the Act. *567 IAC 22.108 (14)*
5. It shall not be a defense for a permittee, in an enforcement action, that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. *567 IAC 22.108 (9)"b"*
6. For applicable requirements with which the permittee is in compliance, the permittee shall continue to comply with such requirements. For applicable requirements that will become effective during the permit term, the permittee shall meet such requirements on a timely basis. *567 IAC 22.108(15)"c"*

### G2. Permit Expiration

1. Except as provided in rule 567—22.104(455B), permit expiration terminates a source's right to operate unless a timely and complete application for renewal has been submitted in accordance with rule 567—22.105(455B). *567 IAC 22.116(2)*
2. To be considered timely, the owner, operator, or designated representative (where applicable) of each source required to obtain a Title V permit shall submit on forms or electronic format specified by the Department to the Air Quality Bureau, Iowa Department of Natural Resources, Air Quality Bureau, 7900 Hickman Rd, Suite #1, Windsor Heights, Iowa 50324, two copies (three if your facility is located in Linn or Polk county) of a complete permit application, at least 6 months but not more than 18 months prior to the date of permit expiration. An additional copy must also be sent to U.S. EPA Region VII, Attention: Chief of Air Permits, 11201 Renner Blvd., Lenexa, KS 66219. Additional copies to local programs or EPA are not required for application materials submitted through the electronic format specified by the Department. The application must include all emission points, emission units, air pollution control equipment, and monitoring devices at the facility. All emissions generating activities, including fugitive emissions, must be included. The definition of a complete application is as indicated in 567 IAC 22.105(2). *567 IAC 22.105*

### G3. Certification Requirement for Title V Related Documents

Any application, report, compliance certification or other document submitted pursuant to this permit shall contain certification by a responsible official of truth, accuracy, and completeness. All certifications shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete. *567 IAC 22.107 (4)*

#### **G4. Annual Compliance Certification**

By March 31 of each year, the permittee shall submit compliance certifications for the previous calendar year. The certifications shall include descriptions of means to monitor the compliance status of all emissions sources including emissions limitations, standards, and work practices in accordance with applicable requirements. The certification for a source shall include the identification of each term or condition of the permit that is the basis of the certification; the compliance status; whether compliance was continuous or intermittent; the method(s) used for determining the compliance status of the source, currently and over the reporting period consistent with all applicable department rules. For sources determined not to be in compliance at the time of compliance certification, a compliance schedule shall be submitted which provides for periodic progress reports, dates for achieving activities, milestones, and an explanation of why any dates were missed and preventive or corrective measures. The compliance certification shall be submitted to the administrator, director, and the appropriate DNR Field office. *567 IAC 22.108 (15)"e"*

#### **G5. Semi-Annual Monitoring Report**

By March 31 and September 30 of each year, the permittee shall submit a report of any monitoring required under this permit for the 6 month periods of July 1 to December 31 and January 1 to June 30, respectively. All instances of deviations from permit requirements must be clearly identified in these reports, and the report must be signed by a responsible official, consistent with 567 IAC 22.107(4). The semi-annual monitoring report shall be submitted to the director and the appropriate DNR Field office. *567 IAC 22.108 (5)*

#### **G6. Annual Fee**

1. The permittee is required under subrule 567 IAC 22.106 to pay an annual fee based on the total tons of actual emissions of each regulated air pollutant. Beginning July 1, 1996, Title V operating permit fees will be paid on July 1 of each year. The fee shall be based on emissions for the previous calendar year.
2. The fee amount shall be calculated based on the first 4,000 tons of each regulated air pollutant emitted each year. The fee to be charged per ton of pollutant will be available from the department by June 1 of each year. The Responsible Official will be advised of any change in the annual fee per ton of pollutant.
3. The following forms shall be submitted annually by March 31 documenting actual emissions for the previous calendar year.
  - a. Form 1.0 "Facility Identification";
  - b. Form 4.0 "Emissions unit-actual operations and emissions" for each emission unit;
  - c. Form 5.0 "Title V annual emissions summary/fee"; and
  - d. Part 3 "Application certification."
4. The fee shall be submitted annually by July 1. The fee shall be submitted with the following forms:
  - a. Form 1.0 "Facility Identification";
  - b. Form 5.0 "Title V annual emissions summary/fee";
  - c. Part 3 "Application certification."
5. If there are any changes to the emission calculation form, the department shall make revised forms available to the public by January 1. If revised forms are not available by January 1, forms from the previous year may be used and the year of emissions documented changed. The department shall calculate the total statewide Title V emissions for the prior calendar year and make this information available to the public no later than April 30 of each year.

6. Phase I acid rain affected units under section 404 of the Act shall not be required to pay a fee for emissions which occur during the years 1993 through 1999 inclusive.
7. The fee for a portable emissions unit or stationary source which operates both in Iowa and out of state shall be calculated only for emissions from the source while operating in Iowa.
8. Failure to pay the appropriate Title V fee represents cause for revocation of the Title V permit as indicated in 567 IAC 22.115(1)"d".

**G7. Inspection of Premises, Records, Equipment, Methods and Discharges**

Upon presentation of proper credentials and any other documents as may be required by law, the permittee shall allow the director or the director's authorized representative to:

1. Enter upon the permittee's premises where a Title V source is located or emissions-related activity is conducted, or where records must be kept under the conditions of the permit;
2. Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
3. Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
4. Sample or monitor, at reasonable times, substances or parameters for the purpose of ensuring compliance with the permit or other applicable requirements. *567 IAC 22.108 (15)"b"*

**G8. Duty to Provide Information**

The permittee shall furnish to the director, within a reasonable time, any information that the director may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee also shall furnish to the director copies of records required to be kept by the permit, or for information claimed to be confidential, the permittee shall furnish such records directly to the administrator of EPA along with a claim of confidentiality. *567 IAC 22.108 (9)"e"*

**G9. General Maintenance and Repair Duties**

The owner or operator of any air emission source or control equipment shall:

1. Maintain and operate the equipment or control equipment at all times in a manner consistent with good practice for minimizing emissions.
2. Remedy any cause of excess emissions in an expeditious manner.
3. Minimize the amount and duration of any excess emission to the maximum extent possible during periods of such emissions. These measures may include but not be limited to the use of clean fuels, production cutbacks, or the use of alternate process units or, in the case of utilities, purchase of electrical power until repairs are completed.
4. Schedule, at a minimum, routine maintenance of equipment or control equipment during periods of process shutdowns to the maximum extent possible. *567 IAC 24.2(1)*

**G10. Recordkeeping Requirements for Compliance Monitoring**

1. In addition to any source specific recordkeeping requirements contained in this permit, the permittee shall maintain the following compliance monitoring records, where applicable:
  - a. The date, place and time of sampling or measurements
  - b. The date the analyses were performed.
  - c. The company or entity that performed the analyses.
  - d. The analytical techniques or methods used.
  - e. The results of such analyses; and
  - f. The operating conditions as existing at the time of sampling or measurement.
  - g. The records of quality assurance for continuous compliance monitoring systems (including but not limited to quality control activities, audits and calibration drifts.)

2. The permittee shall retain records of all required compliance monitoring data and support information for a period of at least 5 years from the date of compliance monitoring sample, measurement report or application. Support information includes all calibration and maintenance records and all original strip chart recordings for continuous compliance monitoring, and copies of all reports required by the permit.

3. For any source which in its application identified reasonably anticipated alternative operating scenarios, the permittee shall:

- a. Comply with all terms and conditions of this permit specific to each alternative scenario.
- b. Maintain a log at the permitted facility of the scenario under which it is operating.
- c. Consider the permit shield, if provided in this permit, to extend to all terms and conditions under each operating scenario. *567 IAC 22.108(4), 567 IAC 22.108(12)*

**G11. Evidence used in establishing that a violation has or is occurring.**

Notwithstanding any other provisions of these rules, any credible evidence may be used for the purpose of establishing whether a person has violated or is in violation of any provisions herein.

1. Information from the use of the following methods is presumptively credible evidence of whether a violation has occurred at a source:

- a. A monitoring method approved for the source and incorporated in an operating permit pursuant to 567 Chapter 22;
- b. Compliance test methods specified in 567 Chapter 25; or
- c. Testing or monitoring methods approved for the source in a construction permit issued pursuant to 567 Chapter 22.

2. The following testing, monitoring or information gathering methods are presumptively credible testing, monitoring, or information gathering methods:

- a. Any monitoring or testing methods provided in these rules; or
- b. Other testing, monitoring, or information gathering methods that produce information comparable to that produced by any method in subrule 21.5(1) or this subrule. *567 IAC 21.5(1)-567 IAC 21.5(2)*

**G12. Prevention of Accidental Release: Risk Management Plan Notification and Compliance Certification**

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Act, the permittee shall notify the department of this requirement. The plan shall be filed with all appropriate authorities by the deadline specified by EPA. A certification that this risk management plan is being properly implemented shall be included in the annual compliance certification of this permit. *567 IAC 22.108(6)*

**G13. Hazardous Release**

The permittee must report any situation involving the actual, imminent, or probable release of a hazardous substance into the atmosphere which, because of the quantity, strength and toxicity of the substance, creates an immediate or potential danger to the public health, safety or to the environment. A verbal report shall be made to the department at (515) 281-8694 and to the local police department or the office of the sheriff of the affected county as soon as possible but not later than six hours after the discovery or onset of the condition. This verbal report must be followed up with a written report as indicated in 567 IAC 131.2(2). *567 IAC Chapter 131-State Only*

**G14. Excess Emissions and Excess Emissions Reporting Requirements**

1. Excess Emissions. Excess emission during a period of startup, shutdown, or cleaning of control equipment is not a violation of the emission standard if the startup, shutdown or cleaning is accomplished expeditiously and in a manner consistent with good practice for minimizing emissions. Cleaning of control equipment which does not require the shutdown of the process equipment shall be limited to one six-minute period per one-hour period. An incident of excess emission (other than an incident during startup, shutdown or cleaning of control equipment) is a violation. If the owner or operator of a source maintains that the incident of excess emission was due to a malfunction, the owner or operator must show that the conditions which caused the incident of excess emission were not preventable by reasonable maintenance and control measures. Determination of any subsequent enforcement action will be made following review of this report. If excess emissions are occurring, either the control equipment causing the excess emission shall be repaired in an expeditious manner or the process generating the emissions shall be shutdown within a reasonable period of time. An expeditious manner is the time necessary to determine the cause of the excess emissions and to correct it within a reasonable period of time. A reasonable period of time is eight hours plus the period of time required to shut down the process without damaging the process equipment or control equipment. A variance from this subrule may be available as provided for in Iowa Code section 455B.143. In the case of an electric utility, a reasonable period of time is eight hours plus the period of time until comparable generating capacity is available to meet consumer demand with the affected unit out of service, unless, the director shall, upon investigation, reasonably determine that continued operation constitutes an unjustifiable environmental hazard and issue an order that such operation is not in the public interest and require a process shutdown to commence immediately.

## 2. Excess Emissions Reporting

a. Initial Reporting of Excess Emissions. An incident of excess emission (other than an incident of excess emission during a period of startup, shutdown, or cleaning) shall be reported to the appropriate field office of the department within eight hours of, or at the start of the first working day following the onset of the incident. The reporting exemption for an incident of excess emission during startup, shutdown or cleaning does not relieve the owner or operator of a source with continuous monitoring equipment of the obligation of submitting reports required in 567-subrule 25.1(6). An initial report of excess emission is not required for a source with operational continuous monitoring equipment (as specified in 567-subrule 25.1(1) ) if the incident of excess emission continues for less than 30 minutes and does not exceed the applicable emission standard by more than 10 percent or the applicable visible emission standard by more than 10 percent opacity. The initial report may be made by electronic mail (E-mail), in person, or by telephone and shall include as a minimum the following:

- i. The identity of the equipment or source operation from which the excess emission originated and the associated stack or emission point.
- ii. The estimated quantity of the excess emission.
- iii. The time and expected duration of the excess emission.
- iv. The cause of the excess emission.
- v. The steps being taken to remedy the excess emission.
- vi. The steps being taken to limit the excess emission in the interim period.

b. Written Reporting of Excess Emissions. A written report of an incident of excess emission shall be submitted as a follow-up to all required initial reports to the department

within seven days of the onset of the upset condition, and shall include as a minimum the following:

- i. The identity of the equipment or source operation point from which the excess emission originated and the associated stack or emission point.
- ii. The estimated quantity of the excess emission.
- iii. The time and duration of the excess emission.
- iv. The cause of the excess emission.
- v. The steps that were taken to remedy and to prevent the recurrence of the incident of excess emission.
- vi. The steps that were taken to limit the excess emission.
- vii. If the owner claims that the excess emission was due to malfunction, documentation to support this claim. *567 IAC 24.1(1)-567 IAC 24.1(4)*

3. Emergency Defense for Excess Emissions. For the purposes of this permit, an “emergency” means any situation arising from sudden and reasonably unforeseeable events beyond the control of the source, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the source to exceed a technology-based emission limitation under the permit due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include non-compliance, to the extent caused by improperly designed equipment, lack of preventive maintenance, careless or improper operation or operator error. An emergency constitutes an affirmative defense to an action brought for non-compliance with technology based limitations if it can be demonstrated through properly signed contemporaneous operating logs or other relevant evidence that:

- a. An emergency occurred and that the permittee can identify the cause(s) of the emergency;
- b. The facility at the time was being properly operated;
- c. During the period of the emergency, the permittee took all reasonable steps to minimize levels of emissions that exceeded the emissions standards or other requirements of the permit; and
- d. The permittee submitted notice of the emergency to the director by certified mail within two working days of the time when the emissions limitations were exceeded due to the emergency. This notice fulfills the requirement of paragraph 22.108(5)"b." – See G15. This notice must contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken.

In any enforcement proceeding, the permittee seeking to establish the occurrence of an emergency has the burden of proof. This provision is in addition to any emergency or upset provision contained in any applicable requirement. *567 IAC 22.108(16)*

#### **G15. Permit Deviation Reporting Requirements**

A deviation is any failure to meet a term, condition or applicable requirement in the permit. Reporting requirements for deviations that result in a hazardous release or excess emissions have been indicated above (see G13 and G14). Unless more frequent deviation reporting is specified in the permit, any other deviation shall be documented in the semi-annual monitoring report and the annual compliance certification (see G4 and G5). *567 IAC 22.108(5)"b"*

#### **G16. Notification Requirements for Sources That Become Subject to NSPS and NESHAP Regulations**

During the term of this permit, the permittee must notify the department of any source that becomes subject to a standard or other requirement under 567-subrule 23.1(2) (standards of

performance of new stationary sources) or section 111 of the Act; or 567-subrule 23.1(3) (emissions standards for hazardous air pollutants), 567-subrule 23.1(4) (emission standards for hazardous air pollutants for source categories) or section 112 of the Act. This notification shall be submitted in writing to the department pursuant to the notification requirements in 40 CFR Section 60.7, 40 CFR Section 61.07, and/or 40 CFR Section 63.9. *567 IAC 23.1(2), 567 IAC 23.1(3), 567 IAC 23.1(4)*

### **G17. Requirements for Making Changes to Emission Sources That Do Not Require Title V Permit Modification**

1. Off Permit Changes to a Source. Pursuant to section 502(b)(10) of the CAAA, the permittee may make changes to this installation/facility without revising this permit if:

- a. The changes are not major modifications under any provision of any program required by section 110 of the Act, modifications under section 111 of the act, modifications under section 112 of the act, or major modifications as defined in 567 IAC Chapter 22.
- b. The changes do not exceed the emissions allowable under the permit (whether expressed therein as a rate of emissions or in terms of total emissions);
- c. The changes are not modifications under any provisions of Title I of the Act and the changes do not exceed the emissions allowable under the permit (whether expressed therein as a rate of emissions or as total emissions);
- d. The changes are not subject to any requirement under Title IV of the Act (revisions affecting Title IV permitting are addressed in rules 567—22.140(455B) through 567 - 22.144(455B));
- e. The changes comply with all applicable requirements.
- f. For each such change, the permitted source provides to the department and the administrator by certified mail, at least 30 days in advance of the proposed change, a written notification, including the following, which must be attached to the permit by the source, the department and the administrator:
  - i. A brief description of the change within the permitted facility,
  - ii. The date on which the change will occur,
  - iii. Any change in emission as a result of that change,
  - iv. The pollutants emitted subject to the emissions trade
  - v. If the emissions trading provisions of the state implementation plan are invoked, then Title V permit requirements with which the source shall comply; a description of how the emissions increases and decreases will comply with the terms and conditions of the Title V permit.
  - vi. A description of the trading of emissions increases and decreases for the purpose of complying with a federally enforceable emissions cap as specified in and in compliance with the Title V permit; and
  - vii. Any permit term or condition no longer applicable as a result of the change.

*567 IAC 22.110(1)*

2. Such changes do not include changes that would violate applicable requirements or contravene federally enforceable permit terms and conditions that are monitoring (including test methods), record keeping, reporting, or compliance certification requirements. *567 IAC 22.110(2)*

3. Notwithstanding any other part of this rule, the director may, upon review of a notice, require a stationary source to apply for a Title V permit if the change does not meet the requirements of subrule 22.110(1). *567 IAC 22.110(3)*

4. The permit shield provided in subrule 22.108(18) shall not apply to any change made pursuant to this rule. Compliance with the permit requirements that the source will meet using the emissions trade shall be determined according to requirements of the state implementation plan authorizing the emissions trade. *567 IAC 22.110(4)*
5. No permit revision shall be required, under any approved economic incentives, marketable permits, emissions trading and other similar programs or processes, for changes that are provided for in this permit. *567 IAC 22.108(11)*

#### **G18. Duty to Modify a Title V Permit**

##### 1. Administrative Amendment.

- a. An administrative permit amendment is a permit revision that does any of the following:
  - i. Correct typographical errors
  - ii. Identify a change in the name, address, or telephone number of any person identified in the permit, or provides a similar minor administrative change at the source;
  - iii. Require more frequent monitoring or reporting by the permittee; or
  - iv. Allow for a change in ownership or operational control of a source where the director determines that no other change in the permit is necessary, provided that a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new permittee has been submitted to the director.
- b. The permittee may implement the changes addressed in the request for an administrative amendment immediately upon submittal of the request. The request shall be submitted to the director.
- c. Administrative amendments to portions of permits containing provisions pursuant to Title IV of the Act shall be governed by regulations promulgated by the administrator under Title IV of the Act.

##### 2. Minor Title V Permit Modification.

- a. Minor Title V permit modification procedures may be used only for those permit modifications that satisfy all of the following:
  - i. Do not violate any applicable requirement;
  - ii. Do not involve significant changes to existing monitoring, reporting or recordkeeping requirements in the Title V permit;
  - iii. Do not require or change a case by case determination of an emission limitation or other standard, or an increment analysis;
  - iv. Do not seek to establish or change a permit term or condition for which there is no corresponding underlying applicable requirement and that the source has assumed in order to avoid an applicable requirement to which the source would otherwise be subject. Such terms and conditions include any federally enforceable emissions caps which the source would assume to avoid classification as a modification under any provision under Title I of the Act; and an alternative emissions limit approved pursuant to regulations promulgated under section 112(i)(5) of the Act;
  - v. Are not modifications under any provision of Title I of the Act; and
  - vi. Are not required to be processed as significant modification under rule 567 - 22.113(455B).

- b. An application for minor permit revision shall be on the minor Title V modification application form and shall include at least the following:
- i. A description of the change, the emissions resulting from the change, and any new applicable requirements that will apply if the change occurs;
  - ii. The permittee's suggested draft permit;
  - iii. Certification by a responsible official, pursuant to 567 IAC 22.107(4), that the proposed modification meets the criteria for use of minor permit modification procedures and a request that such procedures be used; and
  - iv. Completed forms to enable the department to notify the administrator and the affected states as required by 567 IAC 22.107(7).
- c. The permittee may make the change proposed in its minor permit modification application immediately after it files the application. After the permittee makes this change and until the director takes any of the actions specified in 567 IAC 22.112(4) "a" to "c", the permittee must comply with both the applicable requirements governing the change and the proposed permit terms and conditions. During this time, the permittee need not comply with the existing permit terms and conditions it seeks to modify. However, if the permittee fails to comply with its proposed permit terms and conditions during this time period, the existing permit terms and conditions it seeks to modify may be enforced against the facility.

### 3. Significant Title V Permit Modification.

Significant Title V modification procedures shall be used for applications requesting Title V permit modifications that do not qualify as minor Title V modifications or as administrative amendments. These include but are not limited to all significant changes in monitoring permit terms, every relaxation of reporting or recordkeeping permit terms, and any change in the method of measuring compliance with existing requirements. Significant Title V modifications shall meet all requirements of 567 IAC Chapter 22, including those for applications, public participation, review by affected states, and review by the administrator, as those requirements that apply to Title V issuance and renewal.

The permittee shall submit an application for a significant permit modification not later than three months after commencing operation of the changed source unless the existing Title V permit would prohibit such construction or change in operation, in which event the operation of the changed source may not commence until the department revises the permit. *567 IAC 22.111-567 IAC 22.113*

#### **G19. Duty to Obtain Construction Permits**

Unless exempted in 567 IAC 22.1(2) or to meet the parameters established in 567 IAC 22.1(1)"c", the permittee shall not construct, install, reconstruct or alter any equipment, control equipment or anaerobic lagoon without first obtaining a construction permit, or conditional permit, or permit pursuant to rule 567 IAC 22.8, or permits required pursuant to rules 567 IAC 22.4, 567 IAC 22.5, 567 IAC 31.3, and 567 IAC 33.3 as required in 567 IAC 22.1(1). A permit shall be obtained prior to the initiation of construction, installation or alteration of any portion of the stationary source or anaerobic lagoon. *567 IAC 22.1(1)*

#### **G20. Asbestos**

The permittee shall comply with 567 IAC 23.1(3)"a", and 567 IAC 23.2(3)"g" when activities involve asbestos mills, surfacing of roadways, manufacturing operations, fabricating, insulating, waste disposal, spraying applications, demolition and renovation operations (*567 IAC 23.1(3)"a"*); training fires and controlled burning of a demolished building (*567 IAC 23.2*).

## **G21. Open Burning**

The permittee is prohibited from conducting open burning, except as provided in 567 IAC 23.2. *567 IAC 23.2 except 23.2(3)"j"; 567 IAC 23.2(3)"j" - State Only*

## **G22. Acid Rain (Title IV) Emissions Allowances**

The permittee shall not exceed any allowances that it holds under Title IV of the Act or the regulations promulgated there under. Annual emissions of sulfur dioxide in excess of the number of allowances to emit sulfur dioxide held by the owners and operators of the unit or the designated representative of the owners and operators is prohibited. Exceedences of applicable emission rates are prohibited. "Held" in this context refers to both those allowances assigned to the owners and operators by USEPA, and those allowances supplementally acquired by the owners and operators. The use of any allowance prior to the year for which it was allocated is prohibited. Contravention of any other provision of the permit is prohibited. *567 IAC 22.108(7)*

## **G23. Stratospheric Ozone and Climate Protection (Title VI) Requirements**

1. The permittee shall comply with the standards for labeling of products using ozone-depleting substances pursuant to 40 CFR Part 82, Subpart E:
  - a. All containers in which a class I or class II substance is stored or transported, all products containing a class I substance, and all products directly manufactured with a class I substance must bear the required warning statement if it is being introduced into interstate commerce pursuant to § 82.106.
  - b. The placement of the required warning statement must comply with the requirements pursuant to § 82.108.
  - c. The form of the label bearing the required warning statement must comply with the requirements pursuant to § 82.110.
  - d. No person may modify, remove, or interfere with the required warning statement except as described in § 82.112.
2. The permittee shall comply with the standards for recycling and emissions reduction pursuant to 40 CFR Part 82, Subpart F, except as provided for MVACs in Subpart B:
  - a. Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to § 82.156.
  - b. Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to § 82.158.
  - c. Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to § 82.161.
  - d. Persons disposing of small appliances, MVACs, and MVAC-like appliances must comply with reporting and recordkeeping requirements pursuant to § 82.166. ("MVAC-like appliance" as defined at § 82.152)
  - e. Persons owning commercial or industrial process refrigeration equipment must comply with the leak repair requirements pursuant to § 82.156.
  - f. Owners/operators of appliances normally containing 50 or more pounds of refrigerant must keep records of refrigerant purchased and added to such appliances pursuant to § 82.166.
3. If the permittee manufactures, transforms, imports, or exports a class I or class II substance, the permittee is subject to all the requirements as specified in 40 CFR part 82, Subpart A, Production and Consumption Controls.
4. If the permittee performs a service on motor (fleet) vehicles when this service involves ozone-depleting substance refrigerant (or regulated substitute substance) in the motor vehicle air

conditioner (MVAC), the permittee is subject to all the applicable requirements as specified in 40 CFR part 82, Subpart B, Servicing of Motor Vehicle Air Conditioners. The term "motor vehicle" as used in Subpart B does not include a vehicle in which final assembly of the vehicle has not been completed. The term "MVAC" as used in Subpart B does not include the air-tight sealed refrigeration system used as refrigerated cargo, or system used on passenger buses using HCFC-22 refrigerant,

5. The permittee shall be allowed to switch from any ozone-depleting substance to any alternative that is listed in the Significant New Alternatives Program (SNAP) promulgated pursuant to 40 CFR part 82, Subpart G, Significant New Alternatives Policy Program. *40 CFR part 82*

#### **G24. Permit Reopenings**

1. This permit may be modified, revoked, reopened, and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition. *567 IAC 22.108(9)"c"*

2. Additional applicable requirements under the Act become applicable to a major part 70 source with a remaining permit term of 3 or more years. Revisions shall be made as expeditiously as practicable, but not later than 18 months after the promulgation of such standards and regulations.

a. Reopening and revision on this ground is not required if the permit has a remaining term of less than three years;

b. Reopening and revision on this ground is not required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions have been extended pursuant to 40 CFR 70.4(b)(10)(i) or (ii) as amended to May 15, 2001.

c. Reopening and revision on this ground is not required if the additional applicable requirements are implemented in a general permit that is applicable to the source and the source receives approval for coverage under that general permit. *567 IAC 22.108(17)"a"*, *567 IAC 22.108(17)"b"*

3. A permit shall be reopened and revised under any of the following circumstances:

a. The department receives notice that the administrator has granted a petition for disapproval of a permit pursuant to 40 CFR 70.8(d) as amended to July 21, 1992, provided that the reopening may be stayed pending judicial review of that determination;

b. The department or the administrator determines that the Title V permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of the Title V permit;

c. Additional applicable requirements under the Act become applicable to a Title V source, provided that the reopening on this ground is not required if the permit has a remaining term of less than three years, the effective date of the requirement is later than the date on which the permit is due to expire, or the additional applicable requirements are implemented in a general permit that is applicable to the source and the source receives approval for coverage under that general permit. Such a reopening shall be complete not later than 18 months after promulgation of the applicable requirement.

d. Additional requirements, including excess emissions requirements, become applicable to a Title IV affected source under the acid rain program. Upon approval by the administrator, excess emissions offset plans shall be deemed to be incorporated into the

permit.

e. The department or the administrator determines that the permit must be revised or revoked to ensure compliance by the source with the applicable requirements. *567 IAC 22.114(1)*

4. Proceedings to reopen and reissue a Title V permit shall follow the procedures applicable to initial permit issuance and shall effect only those parts of the permit for which cause to reopen exists. *567 IAC 22.114(2)*

5. A notice of intent shall be provided to the Title V source at least 30 days in advance of the date the permit is to be reopened, except that the director may provide a shorter time period in the case of an emergency. *567 IAC 22.114(3)*

#### **G25. Permit Shield**

1. The director may expressly include in a Title V permit a provision stating that compliance with the conditions of the permit shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that:

a. Such applicable requirements are included and are specifically identified in the permit; or

b. The director, in acting on the permit application or revision, determines in writing that other requirements specifically identified are not applicable to the source, and the permit includes the determination or a concise summary thereof.

2. A Title V permit that does not expressly state that a permit shield exists shall be presumed not to provide such a shield.

3. A permit shield shall not alter or affect the following:

a. The provisions of Section 303 of the Act (emergency orders), including the authority of the administrator under that section;

b. The liability of an owner or operator of a source for any violation of applicable requirements prior to or at the time of permit issuance;

c. The applicable requirements of the acid rain program, consistent with Section 408(a) of the Act;

d. The ability of the department or the administrator to obtain information from the facility pursuant to Section 114 of the Act. *567 IAC 22.108 (18)*

#### **G26. Severability**

The provisions of this permit are severable and if any provision or application of any provision is found to be invalid by this department or a court of law, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected by such finding. *567 IAC 22.108 (8)*

#### **G27. Property Rights**

The permit does not convey any property rights of any sort, or any exclusive privilege. *567 IAC 22.108 (9)"d"*

#### **G28. Transferability**

This permit is not transferable from one source to another. If title to the facility or any part of it is transferred, an administrative amendment to the permit must be sought consistent with the requirements of *567 IAC 22.111(1)*. *567 IAC 22.111 (1)"d"*

#### **G29. Disclaimer**

No review has been undertaken on the engineering aspects of the equipment or control equipment other than the potential of that equipment for reducing air contaminant emissions. *567 IAC 22.3(3)"c"*

### **G30. Notification and Reporting Requirements for Stack Tests or Monitor Certification**

The permittee shall notify the department's stack test contact in writing not less than 30 days before a required test or performance evaluation of a continuous emission monitor is performed to determine compliance with applicable requirements of 567 – Chapter 23 or a permit condition. Such notice shall include the time, the place, the name of the person who will conduct the test and other information as required by the department. If the owner or operator does not provide timely notice to the department, the department shall not consider the test results or performance evaluation results to be a valid demonstration of compliance with applicable rules or permit conditions. Upon written request, the department may allow a notification period of less than 30 days. At the department's request, a pretest meeting shall be held not later than 15 days prior to conducting the compliance demonstration. A testing protocol shall be submitted to the department no later than 15 days before the owner or operator conducts the compliance demonstration. A representative of the department shall be permitted to witness the tests. Results of the tests shall be submitted in writing to the department's stack test contact in the form of a comprehensive report within six weeks of the completion of the testing. Compliance tests conducted pursuant to this permit shall be conducted with the source operating in a normal manner at its maximum continuous output as rated by the equipment manufacturer, or the rate specified by the owner as the maximum production rate at which the source shall be operated. In cases where compliance is to be demonstrated at less than the maximum continuous output as rated by the equipment manufacturer, and it is the owner's intent to limit the capacity to that rating, the owner may submit evidence to the department that the source has been physically altered so that capacity cannot be exceeded, or the department may require additional testing, continuous monitoring, reports of operating levels, or any other information deemed necessary by the department to determine whether such source is in compliance.

Stack test notifications, reports and correspondence shall be sent to:

Stack Test Review Coordinator  
Iowa DNR, Air Quality Bureau  
7900 Hickman Road, Suite #1  
Windsor Heights, IA 50324  
(515) 725-9545

Within Polk and Linn Counties, stack test notifications, reports and correspondence shall also be directed to the supervisor of the respective county air pollution program.

*567 IAC 25.1(7)"a", 567 IAC 25.1(9)*

### **G31. Prevention of Air Pollution Emergency Episodes**

The permittee shall comply with the provisions of 567 IAC Chapter 26 in the prevention of excessive build-up of air contaminants during air pollution episodes, thereby preventing the occurrence of an emergency due to the effects of these contaminants on the health of persons.

*567 IAC 26.1(1)*

### **G32. Contacts List**

The current address and phone number for reports and notifications to the EPA administrator is:

Chief of Air Permits  
U.S. EPA Region 7  
Air Permits and Compliance Branch  
11201 Renner Blvd.  
Lenexa, KS 66219  
(913) 551-7020

The current address and phone number for reports and notifications to the department or the Director is:

Chief, Air Quality Bureau  
Iowa Department of Natural Resources  
7900 Hickman Road, Suite #1  
Windsor Heights, IA 50324  
(515) 725-9500

Reports or notifications to the DNR Field Offices or local programs shall be directed to the supervisor at the appropriate field office or local program. Current addresses and phone numbers are:

**Field Office 1**

909 West Main – Suite 4  
Manchester, IA 52057  
(563) 927-2640

**Field Office 3**

1900 N. Grand Ave.  
Spencer, IA 51301  
(712) 262-4177

**Field Office 5**

7900 Hickman Road, Suite #200  
Windsor Heights, IA 50324  
(515) 725-0268

**Polk County Public Works Dept.**

Air Quality Division  
5885 NE 14th St.  
Des Moines, IA 50313  
(515) 286-3351

**Field Office 2**

2300-15th St., SW  
Mason City, IA 50401  
(641) 424-4073

**Field Office 4**

1401 Sunnyside Lane  
Atlantic, IA 50022  
(712) 243-1934

**Field Office 6**

1023 West Madison Street  
Washington, IA 52353-1623  
(319) 653-2135

**Linn County Public Health**

Air Quality Branch  
501 13th St., NW  
Cedar Rapids, IA 52405  
(319) 892-6000

## V. Appendix

- A. 40 CFR 60 Subpart A – *General Provisions*  
<http://www.tceq.texas.gov/permitting/air/rules/federal/60/a/ahp.html>
- B. 40 CFR 60 Subpart Db – Standards of Performance for *Industrial-Commercial-Institutional Steam Generating Units*  
<http://www.ecfr.gov/cgi-bin/text-idx?c=ecfr&rgn=div6&view=text&node=40:7.0.1.1.1.1140> CFR 60
- C. 40 CFR 60 Subpart Kb – Standards of Performance for *Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels)* for Which Construction, Reconstruction, or Modification Commenced after July 23, 1984  
<http://www.tceq.texas.gov/permitting/air/rules/federal/60/kb/kbhp.html>
- D. 40 CFR 60 Subpart VV – Standards of Performance for *Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry*.  
<http://www.ecfr.gov/cgi-bin/text-idx?c=ecfr&rgn=div6&view=text&node=40:7.0.1.1.1.62>
- E. 40 CFR 63 Subpart ZZZZ – National Emission Standard for Hazardous Air Pollutants for *Stationary Reciprocating Internal Combustion Engines*  
<http://www.gpo.gov/fdsys/pkg/FR-2013-01-30/pdf/2013-01288.pdf>
- F. 40 CFR 63 SubpartBBBBBB – National Emission Standards for Hazardous Air Pollutants for Source Category: *Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities*  
<http://www.ecfr.gov/cgi-bin/text-idx?c=ecfr&rgn=div6&view=text&node=40:15.0.1.1.1.15#40:15.0.1.1.1.15.231.3>