

**Iowa Department of Natural Resources
Title V Operating Permit**

**Name of Permitted Facility: Southwest Iowa Renewable Energy
LLC**

Facility Location: 10868 189th Street, Council Bluffs, IA 51503

Air Quality Operating Permit Number: 14-TV-014-M001

Expiration Date: December 21, 2019

Permit Renewal Application Deadline: June 21, 2019

EIQ Number: 92-6062

Facility File Number: 78-01-110

Responsible Official

Name: Mr. Brian Cahill

Title: General Manager

Mailing Address: 10868 189th St, Council Bluffs, IA 51503

Phone #: 712-366-0392

Permit Contact Person for the Facility

Name: Ms. Brett Schulte

Title: Lab/Environmental Compliance Manager

Mailing Address: 10868 189th Street, Council Bluffs, IA 51503

Phone #: 712-352-5040

This permit is issued in accordance with 567 Iowa Administrative Code Chapter 22, and is issued subject to the terms and conditions contained in this permit.

For the Director of the Department of Natural Resources

Lori Hanson, Supervisor of Air Operating Permits Section

Date

Table of Contents

I. Facility Description and Equipment List	4
II. Plant - Wide Conditions.....	6
III. Emission Point Specific Conditions	10
IV. General Conditions.....	58
G1.Duty to Comply	
G2.Permit Expiration	
G3.Certification Requirement for Title V Related Documents	
G4.Annual Compliance Certification	
G5.Semi-Annual Monitoring Report	
G6.Annual Fee	
G7.Inspection of Premises, Records, Equipment, Methods and Discharges	
G8.Duty to Provide Information	
G9.General Maintenance and Repair Duties	
G10. Recordkeeping Requirements for Compliance Monitoring	
G11. Evidence used in establishing that a violation has or is occurring.	
G12. Prevention of Accidental Release: Risk Management Plan Notification and Compliance Certification	
G13. Hazardous Release	
G14. Excess Emissions and Excess Emissions Reporting Requirements	
G15. Permit Deviation Reporting Requirements	
G16. Notification Requirements for Sources That Become Subject to NSPS and NESHAP Regulations	
G17. Requirements for Making Changes to Emission Sources That Do Not Require Title V Permit Modification	
G18. Duty to Modify a Title V Permit	
G19. Duty to Obtain Construction Permits	
G20. Asbestos	
G21. Open Burning	
G22. Acid Rain (Title IV) Emissions Allowances	
G23. Stratospheric Ozone and Climate Protection (Title VI) Requirements	
G24. Permit Reopenings	
G25. Permit Shield	
G26. Severability	
G27. Property Rights	
G28. Transferability	
G29. Disclaimer	
G30. Notification and Reporting Requirements for Stack Tests or Monitor Certification	
G31. Prevention of Air Pollution Emergency Episodes	
G32. Contacts List	
V. Appendix: Links to Standards	72

Abbreviations

acfm.....	actual cubic feet per minute
CFR.....	Code of Federal Regulations
CE	control equipment
CEM.....	continuous emissions monitor
°F.....	degrees Fahrenheit
EIQ.....	emissions inventory questionnaire
EP	emission point
EU	emission unit
gr./dscf	grains per dry standard cubic foot
gr./100 cf.....	grains per one hundred cubic feet
IAC.....	Iowa Administrative Code
IDNR.....	Iowa Department of Natural Resources
MVAC.....	motor vehicle air conditioner
NAICS.....	North American Industry Classification System
NSPS	new source performance standard
NESHAP	National Emission Standards for Hazardous Air Pollutants
ppmv	parts per million by volume
lb./hr	pounds per hour
lb./MMBtu	pounds per million British thermal units
SCC	Source Classification Codes
scfm.....	standard cubic feet per minute
SIC	Standard Industrial Classification
TPY	tons per year
USEPA.....	United States Environmental Protection Agency

Pollutants

PM.....	particulate matter
PM ₁₀	particulate matter ten microns or less in diameter
SO ₂	sulfur dioxide
NO _x	nitrogen oxides
VOC	volatile organic compound
CO.....	carbon monoxide
HAP.....	hazardous air pollutant

I. Facility Description and Equipment List

Facility Name: Southwest Iowa Renewable Energy LLC

Permit Number: 14-TV-014-M001

Facility Description: Fuel Ethanol Manufacturing (SIC 2869)

Equipment List

Emission Point Number	Emission Unit Number	Emission Unit Description	DNR Construction Permit Number
EP-S10	EU-S10	DDGS Dryers 1 thru 6, Distillation	06-A-571-P6
EP-S12A	EU-S12A	Boiler #1	08-A-476-S2-P
EP-S12B	EU-S12B	Boiler #2	08-A-477-S2-P
EP-S20	EU-20A EU-20B EU-20C EU-20D EU-20E EU-20F	Grain Unloading	06-A-575-P2
EP-22	EU-22	Product Loadout	06-A-581-P1
EP-S30A	EU-30A	Hammermill	06-A-576-S1-P
EP-S30B	EU-30B	Hammermill	08-A-507-P
EP-S30C	EU-30C	Hammermill	08-A-508-P
EP-S30D	EU-30D	Hammermill	08-A-509-P
EP-S40	EU-40	Fermenters/Beer Well	06-A-577-P4
EP-S70	EU-70	DDGS Cooler	06-A-578-P1
EP-F80	EU-80	Cooling Tower 4 Cells	06-A-584-S1-P
EP-S90	EU-90	DDGS Loadout	06-A-579-S1-P
EP-EMERG	EU-EMERG	Emergency Fire Pump Generator	06-A-582-P
EP-F60	EU-F60	VOC Emissions from Equipment Leaks	06-A-583-P1
EP-F100	EU-F100	Hauling on Paved/Unpaved Roads	06-A-585-P
EP-T61	EU-T61	Denatured Ethanol Storage Tank	06-A-586-P
EP-T62	EU-T62	Denatured Ethanol Storage Tank	06-A-587-P
EP-T63	EU-T63	200 Proof Ethanol Storage Tank	06-A-588-P
EP-T64	EU-T64	Denaturant Storage Tank	06-A-589-P
EP-T65	EU-T65	190 Proof Ethanol Storage Tank	06-A-590-P

Insignificant Activities Equipment List

Insignificant Emission Unit Number	Insignificant Emission Unit Description
EU I10	Bulk Diesel Tank 500 - Gallon
EU I20	Bulk Unleaded Fuel Tank -500 Gallon

Insignificant Emission Unit Number	Insignificant Emission Unit Description
EU F60	Corn Oil Tricanter Fugitives
EU 22CO	Corn Oil Truck Loadout
TS-6851	Syrup Feed Tank, 3500 gal
TS-8901	Corn Oil Storage Tank, 9200 gal
TS-8902	Corn Oil Storage Tank, 9200 gal
TS-8903	Corn Oil Storage Tank, 9200 gal
TS-8904	Corn Oil Storage Tank, 9200 gal
TS-6852	Syrup Receiver Tank, 560 gal
TS-6853	Corn Oil Receiver Tank, 200 gal
TS-6854	Corn Oil Receiver Tank, 300 gal

II. Plant-Wide Conditions

Facility Name: Southwest Iowa Renewable Energy LLC
Permit Number: 14-TV-014-M001

Permit conditions are established in accord with 567 Iowa Administrative Code rule 22.108

Permit Duration

The term of this permit is: Five Years
Commencing on: December 22, 2014
Ending on: December 21, 2019

Amendments, modifications, and reopenings of the permit shall be obtained in accordance with 567 Iowa Administrative Code rules 22.110 - 22.114. Permits may be suspended, terminated, or revoked as specified in 567 Iowa Administrative Code Rules 22.115.

Emission Limits

Unless specified otherwise in the Source Specific Conditions, the following limitations and supporting regulations apply to all emission points at this plant:

Single HAP: 9.40 ton/yr ⁽¹⁾

Authority for Requirement: DNR Construction Permit 06-A-571-P6, 08-A-476-S2-P, 08-A-477-S2-P, 06-A-581-P1, 06-A-577-P4, 06-A-578-P1, 06-A-583-P1, 06-A-586-P, 06-A-587-P, 06-A-588-P, 06-A-589-P, 06-A-590-P

Total HAP: 24.40 ton/yr ⁽¹⁾

Authority for Requirement: DNR Construction Permit 06-A-571-P6, 08-A-476-S2-P, 08-A-477-S2-P, 06-A-581-P1, 06-A-577-P4, 06-A-578-P1, 06-A-583-P1, 06-A-586-P, 06-A-587-P, 06-A-588-P, 06-A-589-P, 06-A-590-P

⁽¹⁾ The potential to emit is limited below 9.4 ton/yr single HAP and 24.40 ton/hr total HAP by the ethanol production limit, grain receiving limit, fuel usage limits, specific emission unit limits, and operating restrictions contained within the applicable construction permits.

Opacity (visible emissions): 40% opacity

Authority for Requirement: 567 IAC 23.3(2)"d"

Sulfur Dioxide (SO₂): 500 parts per million by volume

Authority for Requirement: 567 IAC 23.3(3)"e"

Particulate Matter:

No person shall cause or allow the emission of particulate matter from any source in excess of the emission standards specified in this chapter, except as provided in 567 – Chapter 24. For sources constructed, modified or reconstructed after July 21, 1999, the emission of particulate matter from any process shall not exceed an emission standard of 0.1 grain per dry standard cubic foot of exhaust gas, except as provided in 567 – 21.2(455B), 23.1(455B), 23.4(455B) and 567 – Chapter 24.

For sources constructed, modified or reconstructed prior to July 21, 1999, the emission of particulate matter from any process shall not exceed the amount determined from Table I, or amount specified in a permit if based on an emission standard of 0.1 grain per standard cubic foot of exhaust gas or established from standards provided in 23.1(455B) and 23.4(455B).

Authority for Requirement: 567 IAC 23.3(2)"a"

Fugitive Dust: Attainment and Unclassified Areas - A person shall take reasonable precautions to prevent particulate matter from becoming airborne in quantities sufficient to cause a nuisance as defined in Iowa Code section 657.1 when the person allows, causes or permits any materials to be handled, transported or stored or a building, its appurtenances or a construction haul road to be used, constructed, altered, repaired or demolished, with the exception of farming operations or dust generated by ordinary travel on unpaved roads. Ordinary travel includes routine traffic and road maintenance activities such as scarifying, compacting, transporting road maintenance surfacing material, and scraping of the unpaved public road surface. (the preceding sentence is State Only) All persons, with the above exceptions, shall take reasonable precautions to prevent the discharge of visible emissions of fugitive dusts beyond the lot line of the property on which the emissions originate. The public highway authority shall be responsible for taking corrective action in those cases where said authority has received complaints of or has actual knowledge of dust conditions which require abatement pursuant to this subrule. Reasonable precautions may include, but not be limited to, the following procedures.

1. Use, where practical, of water or chemicals for control of dusts in the demolition of existing buildings or structures, construction operations, the grading of roads or the clearing of land.
2. Application of suitable materials, such as but not limited to asphalt, oil, water or chemicals on unpaved roads, material stockpiles, race tracks and other surfaces which can give rise to airborne dusts.
3. Installation and use of containment or control equipment, to enclose or otherwise limit the emissions resulting from the handling and transfer of dusty materials, such as but not limited to grain, fertilizer or limestone.
4. Covering, at all times when in motion, open-bodied vehicles transporting materials likely to give rise to airborne dusts.
5. Prompt removal of earth or other material from paved streets or to which earth or other material has been transported by trucking or earth-moving equipment, erosion by water or other means.
6. Reducing the speed of vehicles traveling over on-property surfaces as necessary to minimize the generation of airborne dusts.

Authority for Requirement: 567 IAC 23.3(2)"c"

40 CFR 60 Subpart III Requirements

This facility is subject to Standards of Performance for *Stationary Compression Ignition Internal Combustion Engines*. The affected unit is EP-EMERG.
See Appendix for a link to the Standard.

Authority for Requirements: 40 CFR 60 Subpart III
567 IAC 23.1(2) "yyy"

40 CFR 63 Subpart ZZZZ Requirements

This facility is subject to Standards of Performance for *Stationary Reciprocating Internal Combustion Engines*. The affected unit is EP-EMERG.
See Appendix for a link to the Standard.

Authority for Requirements: 40 CFR 60 Subpart ZZZZ
567 IAC 23.1(4) "cz"

III. Emission Point-Specific Conditions

Facility Name: Southwest Iowa Renewable Energy, LLC

Permit Number: 14-TV-014-M001

Emission Point ID Number: EP-S10

Associated Equipment

Associated Emission Unit ID Numbers: EU-S10

Emissions Control Equipment ID Number: CE 10a, CE 10b

Emissions Control Equipment Description: 2 Regenerative Thermal Oxidizers, 18 MMBtu/hr (each)

Continuous Emissions Monitors ID Numbers: None

Emission Unit vented through this Emission Point: EU-S10

Emission Unit Description: DDGS Dryers 1 through 6 and Distillation

Raw Material/Fuel: DDGS/Natural Gas and/or Process Gases

Rated Capacity: 60 ton/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 40% ⁽¹⁾

Authority for Requirement: DNR Construction Permit 06-A-571-P6
567 IAC 23.3(2) "d"

⁽¹⁾An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM₁₀)

Emission Limit(s): 9.28 lb/hr; 40.65 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-571-P6

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.1 gr/dscf

Authority for Requirement: DNR Construction Permit 06-A-571-P6
567 IAC 23.3 (2)"a"

Pollutant: Sulfur Dioxide (SO₂)

Emission Limit(s): 500 ppmv

Authority for Requirement: DNR Construction Permit 06-A-571-P6
567 IAC 23.3(3)"e"

Pollutant: Nitrogen Oxides (NO_x)
Emission Limit(s): 3.6 lb/hr; 15.8 ton/yr
Authority for Requirement: DNR Construction Permit 06-A-571-P6
NSPS Subpart Db

Pollutant: Carbon Monoxide (CO)
Emission Limit(s): 9.5 lb/hr; 41.6 ton/yr
Authority for Requirement: DNR Construction Permit 06-A-571-P6

Pollutant: Acetaldehyde (HAP)
Emission Limit(s): 1.36 lb/hr; 9.4 ton/yr
Authority for Requirement: DNR Construction Permit 06-A-571-P6

Pollutant: Acrolein (HAP)
Emission Limit(s): 0.434 lb/hr; 9.4 ton/yr
Authority for Requirement: DNR Construction Permit 06-A-571-P6

Pollutant: Formaldehyde (HAP)
Emission Limit(s): 0.123 lb/hr; 9.4 ton/yr
Authority for Requirement: DNR Construction Permit 06-A-571-P6

Pollutant: Methanol (HAP)
Emission Limit(s): 0.429 lb/hr; 9.4 ton/yr
Authority for Requirement: DNR Construction Permit 06-A-571-P6

Pollutant: Total HAP
Emission Limit(s): 2.35 lb/hr; 24.4 ton/yr
Authority for Requirement: DNR Construction Permit 06-A-571-P6

BACT Limits:

Pollutant: Opacity
Emission Limit(s): 0%
Authority for Requirement: DNR Construction Permit 06-A-571-P6

Pollutant: Particulate Matter (PM₁₀)
Emission Limit(s): 9.28 lb/hr; 40.65 ton/yr; 0.037 gr/dscf
Authority for Requirement: DNR Construction Permit 06-A-571-P6

Pollutant: Particulate Matter (PM)
Emission Limit(s): 9.28 lb/hr; 40.65 ton/yr; 0.037 gr/dscf
Authority for Requirement: DNR Construction Permit 06-A-571-P6
567 IAC 23.3 (2) "a"

Pollutant: Sulfur Dioxide (SO₂)
Emission Limit(s): 21.4 lb/hr; 93.7 ton/yr
Authority for Requirement: DNR Construction Permit 06-A-571-P6
567 IAC 23.3(3) "e"

Pollutant: Volatile Organic Compounds (VOC)
Emission Limit(s): 8.39 lb/hr; 36.75 ton/yr; 98% reduction or 10 ppmv
Authority for Requirement: DNR Construction Permit 06-A-571-P6

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Operating Limits

- A. All control equipment shall be maintained according to the manufacturer's specifications.
- B. The thermal oxidizers (C10a & C10b) shall maintain a temperature (3-hour average) during operation of no less than 1600 °F, and shall be operated at all times the dryers or distillation equipment is being used.
- C. The thermal oxidizers shall combust only natural gas and/or process off gases.

Reporting and Recordkeeping

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.

- A. The owner or operator shall maintain a record of all inspections of the control equipment. The owner or operator shall document the results of the inspections and note any repairs that were the result of the inspections.
- B. The owner or operator shall maintain hourly records of the operating temperature of the thermal oxidizers (C10a & C10b) and record all three-hour periods (during actual operation) during which the average temperature of the thermal oxidizer is less than 1600 °F.
- C. The owner or operator shall record the number of hours the dryers are operated. Calculate and record monthly and 12-month rolling totals.

Authority for Requirement: DNR Construction Permit 06-A-571-P6

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 125

Stack Opening, (inches, dia.): 84

Exhaust Flow Rate (scfm): 100,000 - 150,000

Exhaust Temperature (°F): 380

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 06-A-571-P6

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Opacity Monitoring

Visible emissions shall be observed on a weekly basis to ensure there are none when the emission unit on this emission point is at or near full capacity. If visible emissions are observed corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity (>0 %) is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from observation of the violation.

If weather conditions prevent the observer from conducting an observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Maintain a written record of the observation and any action resulting from the observation for a minimum of five years.

Authority for Requirement: 567 IAC 22.108(14)

Stack Testing:

Pollutant – VOC ^{(1) (2)}

Stack Test to be Complete by (Date): Annually

Test Method - 40 CFR 60, Appendix A, Method 18 or 320

Authority for Requirement - DNR Construction Permit 06-A-571-P6

⁽¹⁾ Testing shall determine pounds per hour and either percent reduction or outlet concentration.

Pollutant – Individual HAP ^{(2) (3)}

Stack Test to be Complete by (Date): Annually

Test Method - 40 CFR 60, Appendix A, Method 18

Authority for Requirement - DNR Construction Permit 06-A-571-P6

Pollutant – Total HAP ^{(2) (3)}

Stack Test to be Complete by (Date): Annually

Test Method - 40 CFR 60, Appendix A, Method 18

Authority for Requirement - DNR Construction Permit 06-A-571-P6

⁽²⁾ Annual tests shall be performed during the months of June, July or August.

⁽³⁾ Acrolein, acetaldehyde, formaldehyde and methanol shall be tested for specifically. With the exception of acrolein, acetaldehyde, formaldehyde and methanol, any HAP whose emissions are below the detection limit shall be assumed to be zero.

The owner of this equipment or the owner's authorized agent shall provide written notice to the Director, not less than 30 days before a required stack test or performance evaluation of a continuous emission monitor. Results of the test shall be submitted in writing to the Director in the form of a comprehensive report within 6 weeks of the completion of the testing. 567 IAC 25.1(7)

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: EP-S12A, EP-S12B

Associated Equipment

Associated Emission Unit ID Numbers: EU-S12A, EU-S12B
Emissions Control Equipment ID Number: CE 12A, CE 12B
Emissions Control Equipment Description: Low-NO_x Burners
Continuous Emissions Monitors ID Numbers: ME-12

Emission Unit vented through this Emission Point: EU-S12A, EU-S12B
Emission Unit Description: Boiler #1, Boiler #2
Raw Material/Fuel: Natural Gas
Rated Capacity: 245 MMBtu/hr (each)

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from emission points shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 40% ⁽¹⁾

Authority for Requirement: DNR Construction Permits 08-A-476-P2, 08-A-477-P2
567 IAC 23.3(2) "d"

⁽¹⁾An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM₁₀)

Emission Limit(s): 1.86 lb/hr; 11.29 tons/yr ⁽²⁾

Authority for Requirement: DNR Construction Permits 08-A-476-P2, 08-A-477-P2

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.2 lb/MMBtu

Authority for Requirement: DNR Construction Permits 08-A-476-P2, 08-A-477-P2
567 IAC 23.3(2) "b" (3)

Pollutant: Sulfur Dioxide (SO₂)

Emission Limit(s): 500 ppmv

Authority for Requirement: DNR Construction Permits 08-A-476-P2, 08-A-477-P2
567 IAC 23.3(3) "e"

Pollutant: Nitrogen Oxides (NO_x)

Emission Limit(s): 14.7 lb/hr; 89.13 ton/yr ⁽²⁾; 0.1 lb/MMBtu

Authority for Requirement: DNR Construction Permits 08-A-476-P2, 08-A-477-P2
NSPS Subpart Db

Pollutant: Carbon Monoxide (CO)

Emission Limit(s): 16.17 lb/hr; 98.04ton/yr ⁽²⁾; 0.066 lb/MMBtu

Authority for Requirement: DNR Construction Permits 08-A-476-P2, 08-A-477-P2

⁽²⁾ Limits are for Boiler #1 and #2 combined. These limits are based on the fuel usage limit.

Pollutant: Single HAP

Emission Limit(s): 9.40 ton/yr

Authority for Requirement: DNR Construction Permits 08-A-476-P2, 08-A-477-P2

Pollutant: Total HAP

Emission Limit(s): 24.40 ton/yr

Authority for Requirement: DNR Construction Permits 08-A-476-P2, 08-A-477-P2

BACT Limits:

Pollutant: Opacity

Emission Limit(s): 0%

Authority for Requirement: DNR Construction Permits 08-A-476-P2, 08-A-477-P2
567 IAC 23.3(2) "d"

Pollutant: Particulate Matter (PM₁₀)

Emission Limit(s): 1.86 lb/hr; 0.0076 lb/MMBtu

Authority for Requirement: DNR Construction Permits 08-A-476-P2, 08-A-477-P2

Pollutant: Particulate Matter (PM)

Emission Limit(s): 1.86 lb/hr; 0.0076 lb/MMBtu

Authority for Requirement: DNR Construction Permits 08-A-476-P2, 08-A-477-P2
567 IAC 23.3(2) "b" (3)

Pollutant: Sulfur Dioxide (SO₂)

Emission Limit(s): 0.0006 lb/MMBtu

Authority for Requirement: DNR Construction Permits 08-A-476-P2, 08-A-477-P2

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 0.0055 lb/MMBtu

Authority for Requirement: DNR Construction Permits 08-A-476-P2, 08-A-477-P2

Operational Limits & Requirements

The owner/operator shall comply with the operational limits and requirements listed below for each emission unit.

Operating Limits

- A. This boiler shall be fired by natural gas only.
- B. The total amount of natural gas that Boiler #1 and Boiler #2 may burn shall not exceed 2890×10^6 cubic feet per 12-month rolling period.
- C. The owner or operator shall follow the applicable standards of NSPS Subpart Db, 40 CFR §60.40b through §60.49b.

Reporting and Recordkeeping

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.

- A. Record the amount of natural gas combusted in Boiler #1 and Boiler #2 combined, in cubic feet. Calculate and record monthly and 12-month rolling totals.
- B. The owner or operator shall maintain records of the amounts of each fuel combusted during each day, and calculate the annual capacity factor on a 12-month rolling average basis a new annual capacity factor calculated at the end of each calendar month, as required in 40 CFR §60.49b(d). The annual capacity factor is defined as the ratio between the actual heat input to a steam generating unit during a calendar year, and the potential heat input had it been operated for 8,760 hours during a calendar year at the maximum steady state design heat input capacity.
- C. The owner or operator shall maintain records of the following information for each steam generating unit operating day, as required in 40 CFR §60.49b(g). This information shall also be submitted in a report, as required in 40 CFR §60.49b(i).
 1. Calendar date.
 2. Average hourly nitrogen oxides emission (as NO₂) rates measured or predicted.
 3. 30-day average nitrogen oxides emission rates calculated at the end of each steam generating unit operating day from the measured hourly nitrogen oxide emission rates for the preceding 30 steam generating unit operating days.
 4. Identification of the steam generating unit operating days when the calculated 30-day average nitrogen oxides emission rates are in excess of the emission standard (0.10 lb/MMBTU), with the reason for such excess emissions as well as a description of corrective actions taken.
 5. Identification of the steam generating unit operating days for which pollutant data have not been obtained, including reasons for not obtaining sufficient data and a description of corrective actions taken.
 6. Identification of the times when emission data have been excluded from the calculation of average emission rates and the reason for excluding the data.
 7. Identification of "F" factor used for calculations, method of determination and type of fuel combusted.
 8. Identification of the times when the pollutant concentrations exceed the full span of the continuous monitoring system.
 9. Description of any modifications to the continuous monitoring system that could affect the ability of the CEMS to comply with Performance Specification 2 or 3.
 10. Results of daily CEMS drift tests and quarterly accuracy assessments as required under 40 CFR Appendix F, Procedure 1.

Authority for Requirement: DNR Construction Permits 08-A-476-P2, 08-A-477-P2

NSPS and NESHAP Applicability

This emission point is subject to NSPS Subpart A – *General Provisions* and NSPS Subpart Db – *Standards of Performance for Industrial- Commercial-Institutional Steam Generating Units*.

Authority for Requirement: DNR Construction Permits 08-A-476-P2, 08-A-477-P2

Emission Point Characteristics

Each of the emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 65

Stack Opening, (inches, dia.): 54

Exhaust Flow Rate (scfm): 72,500

Exhaust Temperature (°F): 320

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permits 08-A-476-P2, 08-A-477-P2

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator shall comply with the monitoring requirements listed below for each emission point.

Opacity Monitoring

Visible emissions shall be observed on a weekly basis to ensure there are none when the emission unit on this emission point is at or near full capacity. If visible emissions are observed corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity (>0 %) is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from observation of the violation.

If weather conditions prevent the observer from conducting an observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Maintain a written record of the observation and any action resulting from the observation for a minimum of five years.

Authority for Requirement: 567 IAC 22.108(14)

Continuous Emissions Monitoring:

The owner or operator shall install, calibrate, maintain and operate a continuous monitoring system, and record the output of the system, for measuring nitrogen oxides (NO_x) emissions discharged to the atmosphere. The CEM shall be operated and data collected as required under 40 CFR 60.48b(c), (d), (e) and (f), or use an approved monitoring plan.

Authority for Requirement – DNR Construction Permits 08-A-476-P2, 08-A-477-P2

The owner of this equipment or the owner's authorized agent shall provide written notice to the Director, not less than 30 days before a required stack test or performance evaluation of a continuous emission monitor. Results of the test shall be submitted in writing to the Director in the form of a comprehensive report within 6 weeks of the completion of the testing. 567 IAC 25.1(7)

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: EP-S20

Associated Equipment

Associated Emission Unit ID Numbers: EU-20A, EU-20B, EU-20C, EU-20D, EU-20E, EU-20F
Emissions Control Equipment ID Number: CE 20
Emissions Control Equipment Description: Baghouse
Continuous Emissions Monitors ID Numbers: None

Emission Unit vented through this Emission Point: EU-20A, EU-20B, EU-20C, EU-20D, EU-20E, EU-20F

Emission Unit Description: Grain Unloading; 4 x 500,000 bushel bins (EU-20A through EU-20D), 1 x 44,000 bushel bin (EU-20E), 1 x 21,000 bushel scalper bin (EU-20F)

Raw Material/Fuel: Grain

Rated Capacity: 22,000 bushels/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 40% ⁽¹⁾

Authority for Requirement: DNR Construction Permit 06-A-575-P2
567 IAC 23.3(2) "d"

⁽¹⁾An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM₁₀)

Emission Limit(s): 0.78 lb/hr

Authority for Requirement: DNR Construction Permit 06-A-575-P2

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.1 gr/dscf

Authority for Requirement: DNR Construction Permit 06-A-575-P2
567 IAC 23.3(2) "a"

BACT Limits:

Pollutant: Opacity

Emission Limit(s): 0%

Authority for Requirement: DNR Construction Permit 06-A-575-P2

Pollutant: Particulate Matter (PM₁₀)

Emission Limit(s): 1.54 lb/hr; 6.76 ton/yr; 0.004 gr/dscf

Authority for Requirement: DNR Construction Permit 06-A-575-P2

Pollutant: Particulate Matter (PM)

Emission Limit(s): 1.54 lb/hr; 6.76 ton/yr; 0.004 gr/dscf

Authority for Requirement: DNR Construction Permit 06-A-575-P2

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Operating Limits

Operating limits for this emission unit shall be:

- A. All control equipment shall be maintained according to the manufacturer's specifications.
- B. The amount of grain received at this facility (plant number 78-01-110) shall not exceed 44,642,857 bushels per 12-month rolling period.
- C. The grain unloading shall be done using choke flow and enclosed dump pits whenever possible.

Reporting and Recordkeeping

Unless specified by a federal regulation, all records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the Department. Records shall be legible and maintained in an orderly manner. These records shall show the following:

- A. The owner or operator shall maintain a record of all inspections of the control equipment. The owner or operator shall document the results of the inspections and note any repairs that were the result of the inspections.
- B. Record the amount of grain received at this facility (plant number 78-01-110), in bushels. Calculate and record monthly and 12-month rolling totals.

Authority for Requirement: DNR Construction Permit 06-A-575-P2

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 40

Stack Opening, (inches, dia.): 44

Exhaust Flow Rate (scfm): 45,600

Exhaust Temperature (°F): Ambient

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 06-A-575-P2

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall

submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Opacity Monitoring

Visible emissions shall be observed on a weekly basis to ensure there are none when the emission unit on this emission point is at or near full capacity. If visible emissions are observed corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity (>0 %) is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from observation of the violation.

If weather conditions prevent the observer from conducting an observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Maintain a written record of the observation and any action resulting from the observation for a minimum of five years.

Authority for Requirement: 567 IAC 22.108(14)

Stack Testing:

Pollutant – PM
Test Method – 40 CFR 60, Appendix A, Method 5
40 CFR 51, Appendix M, Method 202
Stack Test to be Completed by: December 21, 2016
Authority for Requirement – 567 IAC 22.108(3)

The owner of this equipment or the owner’s authorized agent shall provide written notice to the Director, not less than 30 days before a required stack test or performance evaluation of a continuous emission monitor. Results of the test shall be submitted in writing to the Director in the form of a comprehensive report within 6 weeks of the completion of the testing. 567 IAC 25.1(7)

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the applicable requirements.

Facility operation and maintenance plans are to be developed by the facility within six (6) months of the issuance date of this permit and the data pertaining to the plan maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: EP-22

Associated Equipment

Associated Emission Unit ID Numbers: EU-22

Emissions Control Equipment ID Number: CE 22

Emissions Control Equipment Description: Vapor Recovery System and Flare (12.4 MMBtu/hr)

Continuous Emissions Monitors ID Numbers: None

Emission Unit vented through this Emission Point: EU-22

Emission Unit Description: Product Loadout

Raw Material/Fuel: Denatured and Undenatured Ethanol/Natural Gas

Rated Capacity: 125 Mgal/yr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 0% ⁽¹⁾

Authority for Requirement: DNR Construction Permit 06-A-581-P1

⁽¹⁾An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: PM

Emission Limit: 0.1 gr/dscf

Authority for Requirement: 567 IAC 23.3(2)"a"

Pollutant: Sulfur Dioxide (SO₂)

Emission Limit: 500 ppmv

Authority for Requirement: 567 IAC 23.3(3)"e"

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 3.48 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-581-P1

Pollutant: Acetaldehyde (HAP)

Emission Limit(s): 9.4 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-581-P1

Pollutant: Acrolein (HAP)

Emission Limit(s): 9.4 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-581-P1

Pollutant: Formaldehyde (HAP)

Emission Limit(s): 9.4 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-581-P1

Pollutant: Methanol (HAP)

Emission Limit(s): 9.4 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-581-P1

Pollutant: Total HAPs

Emission Limit(s): 24.4 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-581-P1

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Operating Limits

- A. All control equipment shall be maintained according to the manufacturer's specifications.
- B. The owner or operator shall follow the applicable standards of NSPS Subpart VV, 40 CFR 60.480 through 60.489.
- C. The amount of ethanol (denatured and undenatured) loaded out at this facility shall not exceed 125,000,000 gallons per 12 month rolling period.
- D. The amount of ethanol (denatured and undenatured) loaded out to trucks shall not exceed 37,500,000 gallons per 12 month rolling period.
- E. The flare shall be designed to meet the minimum requirements of 40 CFR 60.18b through 60.18f.
- F. The auxiliary fuel used in the flare is limited to natural gas or propane.

Reporting and Recordkeeping

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.

- A. Record the amount ethanol (denatured and undenatured) loaded out at this facility in gallons. Calculate and record monthly and 12 month rolling totals.
- B. Record the amount ethanol (denatured and undenatured) loaded out at this facility into trucks in gallons. Calculate and record monthly and 12 month rolling totals.

Authority for Requirement: DNR Construction Permit 06-A-581-P1

NSPS and NESHAP Applicability

This facility is subject to the requirements/conditions of New Source Performance Standards (NSPS) Subpart VV – *Standards of Performance for Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry* as specified in 40 CFR Part 60 §60.480. This facility is also subject to the requirements/conditions of NSPS Subpart A – *General Provisions*.

Authority for Requirement: DNR Construction Permit 06-A-581-P1

NOTE: This facility has chosen to satisfy the requirements of NSPS subpart VV by complying with the provisions of NSPS subpart VVa – *Standards of Performance for Equipment Leaks of*

VOC in the Synthetic Organic Chemicals Manufacturing Industry for which Construction, Reconstruction, or Modification Commenced After January 5, 1981, and on or Before November 7, 2006.

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 30

Stack Opening, (inches, dia.): 28.8

Exhaust Flow Rate (scfm): 4,160

Exhaust Temperature (°F): 1,800

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 06-A-581-P1

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Opacity Monitoring

Visible emissions shall be observed on a weekly basis to ensure there are none when the emission unit on this emission point is at or near full capacity. If visible emissions are observed corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity (>0 %) is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from observation of the violation.

If weather conditions prevent the observer from conducting an observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Maintain a written record of the observation and any action resulting from the observation for a minimum of five years.

Authority for Requirement: 567 IAC 22.108(14)

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: EP-S30A, EP-S30B, EP-S30C, EP-S30D

Associated Equipment

Emission Point	Emission Unit ID Number	Emissions Control Equipment ID Number	Emissions Control Equipment Description	Continuous Emissions Monitors ID Numbers
EP-S30A	EU-30A	CE 30a	Baghouse	NA
EP-S30B	EU-30B	CE 30b		
EP-S30C	EU-30C	CE 30c		
EP-S30D	EU-30D	CE 30d		

Emission Point	Emission Unit Vented through this EP	Emission Unit Description	Raw Material/Fuel	Rated Capacity (bu/hr)
EP-S30A	EU-30A	Hammermill	Grain	5500
EP-S30B	EU-30B			
EP-S30C	EU-30C			
EP-S30D	EU-30D			

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from each emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 40% ⁽¹⁾

Authority for Requirement: DNR Construction Permits 06-A-576-S1-P, 08-A-507-P, 08-A-508-P, 08-A-509-P
567 IAC 23.3(2)"d"

⁽¹⁾ An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM₁₀)

Emission Limit(s): 0.11 lb/hr; 0.49 ton/yr

Authority for Requirement: DNR Construction Permits 06-A-576-S1-P, 08-A-507-P, 08-A-508-P, 08-A-509-P

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.1 gr/dscf

Authority for Requirement: DNR Construction Permits 06-A-576-S1-P, 08-A-507-P,
08-A-508-P, 08-A-509-P
567 IAC 23.4(7)

BACT Limits:

Pollutant: Opacity

Emission Limit(s): 0%

Authority for Requirement: DNR Construction Permits 06-A-576-S1-P, 08-A-507-P,
08-A-508-P, 08-A-509-P

Pollutant: Particulate Matter (PM₁₀)

Emission Limit(s): 0.22 lb/hr; 0.98 ton/yr; 0.004 gr/dscf

Authority for Requirement: DNR Construction Permits 06-A-576-S1-P, 08-A-507-P,
08-A-508-P, 08-A-509-P

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.22 lb/hr; 0.98 ton/yr; 0.004 gr/dscf

Authority for Requirement: DNR Construction Permits 06-A-576-S1-P, 08-A-507-P,
08-A-508-P, 08-A-509-P

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Operating Limits

A. All control equipment shall be maintained according to the manufacturer's specifications.

Reporting and Recordkeeping

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.

A. The owner or operator shall maintain a record of all inspections of the control equipment.
The owner or operator shall document the results of the inspections and note any repairs that were the result of the inspections.

Authority for Requirement: DNR Construction Permits 06-A-576-S1-P, 08-A-507-P,
08-A-508-P, 08-A-509-P

Emission Point Characteristics

Each emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 40

Stack Opening, (inches, dia.): 18

Exhaust Flow Rate (scfm): 6,500

Exhaust Temperature (°F): Ambient

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permits 06-A-576-S1-P, 08-A-507-P,
08-A-508-P, 08-A-509-P

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Opacity Monitoring

Visible emissions shall be observed on a weekly basis to ensure there are none when the emission unit on this emission point is at or near full capacity. If visible emissions are observed corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity (>0 %) is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from observation of the violation.

If weather conditions prevent the observer from conducting an observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Maintain a written record of the observation and any action resulting from the observation for a minimum of five years.

Authority for Requirement: 567 IAC 22.108(14)

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required?

Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the applicable requirements.

Facility operation and maintenance plans are to be developed by the facility within six (6) months of the issuance date of this permit and the data pertaining to the plan maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: EP-S40

Associated Equipment

Associated Emission Unit ID Numbers: EU-40
Emissions Control Equipment ID Number: CE 40
Emissions Control Equipment Description: Scrubber
Continuous Emissions Monitors ID Numbers: None

Emission Unit vented through this Emission Point: EU-40
Emission Unit Description: 7 Fermenters and Beer Well
Raw Material/Fuel: Beer
Rated Capacity: 807,000 gallons (each fermenter)

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 40% ⁽¹⁾

Authority for Requirement: DNR Construction Permit 06-A-577-P4

⁽¹⁾An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.1 gr/dscf

Authority for Requirement: DNR Construction Permit 06-A-577-P4
567 IAC 23.3(2) "a"

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 10.4 lb/hr; 45.6 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-577-P4

Pollutant: Acetaldehyde (HAP)

Emission Limit(s): 0.68 lb/hr; 9.4 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-577-P4

Pollutant: Acrolein (HAP)

Emission Limit(s): 0.17 lb/hr; 9.4 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-577-P4

Pollutant: Formaldehyde (HAP)

Emission Limit(s): 0.05 lb/hr; 9.4 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-577-P4

Pollutant: Methanol (HAP)
Emission Limit(s): 0.27 lb/hr; 9.4 ton/yr
Authority for Requirement: DNR Construction Permit 06-A-577-P4

Pollutant: Total HAP
Emission Limit(s): 1.17 lb/hr; 24.4 ton/yr
Authority for Requirement: DNR Construction Permit 06-A-577-P4

BACT Limits:

Pollutant: Opacity
Emission Limit(s): 0%
Authority for Requirement: DNR Construction Permit 06-A-577-P4

Pollutant: Particulate Matter (PM₁₀)
Emission Limit(s): 1.0 lb/hr; 4.38 ton/yr
Authority for Requirement: DNR Construction Permit 06-A-577-P4

Pollutant: Particulate Matter (PM)
Emission Limit(s): 1.0 lb/hr; 4.38 ton/yr
Authority for Requirement: DNR Construction Permit 06-A-577-P4

Pollutant: Volatile Organic Compounds (VOC)
Emission Limit(s): 12.6 lb/hr; 55.3 ton/yr; 95% reduction or 100 ppmv
Authority for Requirement: DNR Construction Permit 06-A-577-P4

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Operating Limits

- A. All control equipment shall be maintained according to the manufacturer's specifications.
- B. The scrubber (CE 40) shall have a minimum scrubber liquid (water) flow rate which is equal to or greater than the total liquid flow rate at the inlet to the wet scrubber measured during a previous performance test demonstrating compliance with the VOC emission limit.
- C. Any additive added to the scrubber liquid during a compliance test to enhance the efficiency of the scrubber shall be added at a rate greater than or equal to the rate recorded during a previous performance test that demonstrated compliance with all applicable emission limitations.

Reporting and Recordkeeping

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.

- A. The owner or operator shall maintain a record of all inspections of the control equipment. The owner or operator shall document the results of the inspections and note any repairs that were the result of the inspections.
- B. Record the scrubber liquid (water) flow rate on a continuous basis. If the flow rate deviates below the minimum flow rate required, then record the time, date and actions taken to correct the situation and when the flow rate is back above the minimum flow rate required.
- C. Record the rate of additive added (additive feed rate) to the scrubber liquid on a continuous

basis. If the additive feed rate deviates below the rate required (i.e., additive feed rate during a previous performance test that demonstrated compliance), then record the time, date and actions taken to correct the situation and also when the additive feed rate is greater than or equal to the required additive feed rate.

Authority for Requirement: DNR Construction Permit 06-A-577-P4

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 75

Stack Opening, (inches, dia.): 27

Exhaust Flow Rate (acfm): 10,000 - 15,000

Exhaust Temperature (°F): 75

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 06-A-577-P4

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Visible emissions shall be observed on a weekly basis to ensure there are none when the emission unit on this emission point is at or near full capacity. If visible emissions are observed corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity (>0 %) is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from observation of the violation.

If weather conditions prevent the observer from conducting an observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Maintain a written record of the observation and any action resulting from the observation for a minimum of five years.

Authority for Requirement: 567 IAC 22.108(14)

Stack Testing:

Pollutant – VOC ^{(1) (2)}

Stack Test to be Completed by (Date) – Annually

Test Method – 40 CFR 60, Appendix A, Method 18 or 320

Authority for Requirement – DNR Construction Permit 06-A-577-P4

⁽¹⁾ Testing shall determine pounds per hour and either percent reduction or outlet concentration.

Pollutant – Individual HAP ^{(2) (3)}

Stack Test to be Completed by (Date) – Annually

Test Method – 40 CFR 60, Appendix A, Method 18

Authority for Requirement – DNR Construction Permit 06-A-577-P4

Pollutant – Total HAP ^{(2) (3)}

Stack Test to be Completed by (Date) – Annually

Test Method – 40 CFR 60, Appendix A, Method 18

Authority for Requirement – DNR Construction Permit 06-A-577-P4

⁽²⁾ Annual tests shall be performed during the months of June, July or August.

⁽³⁾ Acrolein, acetaldehyde, formaldehyde and methanol shall be tested for specifically. With the exception of acrolein, acetaldehyde, formaldehyde and methanol, any HAP whose emissions are below the detection limit shall be assumed to be zero.

The owner of this equipment or the owner's authorized agent shall provide written notice to the Director, not less than 30 days before a required stack test or performance evaluation of a continuous emission monitor. Results of the test shall be submitted in writing to the Director in the form of a comprehensive report within 6 weeks of the completion of the testing. 567 IAC 25.1(7)

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: EP-S70

Associated Equipment

Associated Emission Unit ID Numbers: EU-70
Emissions Control Equipment ID Number: CE 70
Emissions Control Equipment Description: Baghouse
Continuous Emissions Monitors ID Numbers: None

Emission Unit vented through this Emission Point: EU-70
Emission Unit Description: DDGS Cooler
Raw Material/Fuel: DDGS
Rated Capacity: 50 ton/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 40% ⁽¹⁾

Authority for Requirement: DNR Construction Permit 06-A-578-P1

⁽¹⁾An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.1 gr/dscf;

Authority for Requirement: DNR Construction Permit 06-A-578-P1
567 IAC 23.3(2)"a"

Pollutant: Acetaldehyde (HAP)

Emission Limit(s): 0.097 lb/hr; 9.4 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-578-P1

Pollutant: Acrolein (HAP)

Emission Limit(s): 0.135 lb/hr; 9.4 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-578-P1

Pollutant: Formaldehyde (HAP)

Emission Limit(s): 0.06 lb/hr; 9.4 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-578-P1

Pollutant: Methanol (HAP)

Emission Limit(s): 0.174 lb/hr; 9.4 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-578-P1

Pollutant: Total HAP

Emission Limit(s): 0.5 lb/hr; 24.4 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-578-P1

BACT Limits:

Pollutant: Opacity

Emission Limit(s): 0%

Authority for Requirement: DNR Construction Permit 06-A-578-P1

Pollutant: Particulate Matter (PM₁₀)

Emission Limit(s): 0.64 lb/hr; 2.8 ton/yr; 0.004 gr/dscf

Authority for Requirement: DNR Construction Permit 06-A-578-P1

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.64 lb/hr; 2.80 ton/yr; 0.004 gr/dscf

Authority for Requirement: DNR Construction Permit 06-A-578-P1

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 3.0 lb/hr; 13.1 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-578-P1

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Operating Limits

A. All control equipment shall be maintained according to the manufacturer's specifications.

Reporting and Recordkeeping

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.

A. The owner or operator shall maintain a record of all inspections of the control equipment. The owner or operator shall document the results of the inspections and note any repairs that were the result of the inspections.

Authority for Requirement: DNR Construction Permit 06-A-578-P1

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 48

Stack Opening, (inches, dia.): 48

Exhaust Flow Rate (acfm): 15,000

Exhaust Temperature (°F): 85

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 06-A-578-P1

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Opacity Monitoring

Visible emissions shall be observed on a weekly basis to ensure there are none when the emission unit on this emission point is at or near full capacity. If visible emissions are observed corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity (>0 %) is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from observation of the violation.

If weather conditions prevent the observer from conducting an observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Maintain a written record of the observation and any action resulting from the observation for a minimum of five years.

Authority for Requirement: 567 IAC 22.108(14)

Stack Testing:

Pollutant – Particulate Matter (PM)
Test Method – 40 CFR 60, Appendix A, Method 5
40 CFR 51, Appendix M, Method 202
Stack Test to be Completed by: December 21, 2016
Authority for Requirement: 567 IAC 22.108(3)

The owner of this equipment or the owner’s authorized agent shall provide written notice to the Director, not less than 30 days before a required stack test or performance evaluation of a continuous emission monitor. Results of the test shall be submitted in writing to the Director in the form of a comprehensive report within 6 weeks of the completion of the testing. 567 IAC 25.1(7)

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required?

Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the applicable requirements.

Facility operation and maintenance plans are to be developed by the facility within six (6) months of the issuance date of this permit and the data pertaining to the plan maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: EP-F80

Associated Equipment

Associated Emission Unit ID Numbers: EU-80
Emissions Control Equipment ID Number: CE 80
Emissions Control Equipment Description: Mist Eliminator
Continuous Emissions Monitors ID Numbers: None

Emission Unit vented through this Emission Point: EU-80
Emission Unit Description: Cooling Tower (4 Cells)
Raw Material/Fuel: Cooling Water
Rated Capacity: 3,000,000 gal/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 40% ⁽¹⁾

Authority for Requirement: DNR Construction Permit 06-A-584-S1-P
567 IAC 23.3(2) "d"

⁽¹⁾ An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM₁₀)

Emission Limit(s): 0.63 lb/hr; 2.74 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-584-S1-P

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.1 gr/dscf

Authority for Requirement: DNR Construction Permit 06-A-584-S1-P
567 IAC 23.3(2) "a"

BACT Limits:

Pollutant: Opacity

Emission Limit(s): 0%

Authority for Requirement: DNR Construction Permit 06-A-584-S1-P

Pollutant: Particulate Matter (PM₁₀)

Emission Limit(s): 0.63 lb/hr; 2.74 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-584-S1-P

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.63 lb/hr; 2.74 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-584-S1-P
567 IAC 23.3(2) "a"

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Operating Limits

- A. The mist eliminator on the cooling tower cells shall be rated at 0.001% or better.
- B. The Total Dissolved Solids (TDS) content of the water in the cooling towers shall not exceed 2500 ppm.
- C. Chromium-based water treatment chemicals shall not be used in any cooling tower cells.

Reporting and Recordkeeping

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.

- A. The owner or operator shall maintain a record of all inspections of the control equipment.
The owner or operator shall document the results of the inspections and note any repairs that were the result of the inspections.
- B. The TDS content of the water in the cooling towers shall be tested once per calendar month.
- C. Maintain MSDS sheets for all treatment chemicals used in these cooling tower cells.

Authority for Requirement: DNR Construction Permit 06-A-584-S1-P

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 30

Stack Opening, (inches, dia.): 360

Exhaust Flow Rate (scfm): 2,142,840

Exhaust Temperature (°F): 85

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 06-A-584-S1-P

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Opacity Monitoring

Visible emissions shall be observed on a weekly basis to ensure there are none when the emission unit on this emission point is at or near full capacity. If visible emissions are observed corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no

visible emissions, then a Method 9 observation will be required. If an opacity (>0 %) is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from observation of the violation.

If weather conditions prevent the observer from conducting an observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Maintain a written record of the observation and any action resulting from the observation for a minimum of five years.

Authority for Requirement: 567 IAC 22.108(14)

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: EP-S90

Associated Equipment

Associated Emission Unit ID Numbers: EU-90
Emissions Control Equipment ID Number: CE 90
Emissions Control Equipment Description: Baghouse
Continuous Emissions Monitors ID Numbers: None

Emission Unit vented through this Emission Point: EU-90
Emission Unit Description: DDGS Loadout
Raw Material/Fuel: DDGS
Rated Capacity: 200 ton/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 40% ⁽¹⁾

Authority for Requirement: DNR Construction Permit 06-A-579-S1-P
567 IAC 23.3(2) "d"

⁽¹⁾An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM₁₀)

Emission Limit(s): 0.18 lb/hr; 0.79 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-579-S1-P

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.1 gr/dscf

Authority for Requirement: DNR Construction Permit 06-A-579-S1-P
567 IAC 23.3(2) "a"

BACT Limits:

Pollutant: Opacity

Emission Limit(s): 0%

Authority for Requirement: DNR Construction Permit 06-A-579-S1-P

Pollutant: Particulate Matter (PM₁₀)

Emission Limit(s): 0.29 lb/hr; 1.27 ton/yr; 0.004 gr/dscf

Authority for Requirement: DNR Construction Permit 06-A-579-S1-P

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.29 lb/hr; 1.27 ton/yr; 0.004 gr/dscf

Authority for Requirement: DNR Construction Permit 06-A-579-S1-P

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Operating Limits

A. All control equipment shall be maintained according to the manufacturer's specifications.

Reporting and Recordkeeping

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.

A. The owner or operator shall maintain a record of all inspections of the control equipment. The owner or operator shall document the results of the inspections and note any repairs that were the result of the inspections.

Authority for Requirement: DNR Construction Permit 06-A-579-S1-P

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 40

Stack Opening, (inches, dia.): 24

Exhaust Flow Rate (scfm): 10,600

Exhaust Temperature (°F): Ambient

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 06-A-579-S1-P

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Opacity Monitoring

Visible emissions shall be observed on a weekly basis to ensure there are none when the emission unit on this emission point is at or near full capacity. If visible emissions are observed corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity (>0 %) is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from observation of the violation.

If weather conditions prevent the observer from conducting an observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Maintain a written record of the observation and any action resulting from the observation for a minimum of five years.

Authority for Requirement: 567 IAC 22.108(14)

Stack Testing:

Pollutant – Particulate Matter (PM)

Test Method – 40 CFR 60, Appendix A, Method 5
40 CFR 51, Appendix M, Method 202

Stack Test to be Completed by: December 21, 2016

Authority for Requirement: 567 IAC 22.108(3)

The owner of this equipment or the owner's authorized agent shall provide written notice to the Director, not less than 30 days before a required stack test or performance evaluation of a continuous emission monitor. Results of the test shall be submitted in writing to the Director in the form of a comprehensive report within 6 weeks of the completion of the testing. 567 IAC 25.1(7)

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the applicable requirements.

Facility operation and maintenance plans are to be developed by the facility within six (6) months of the issuance date of this permit and the data pertaining to the plan maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: EP-Emerg

Associated Equipment

Associated Emission Unit ID Numbers: EU-Emerg
Emissions Control Equipment ID Number: None
Emissions Control Equipment Description: None
Continuous Emissions Monitors ID Numbers: None

Emission Unit vented through this Emission Point: EU-Emerg
Emission Unit Description: Emergency Fire Pump Generator
Raw Material/Fuel: Diesel
Rated Capacity: 300 bhp

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 20% ⁽¹⁾

Authority for Requirement: DNR Construction Permit 06-A-582-P

⁽¹⁾An exceedance of the indicator opacity of "20%" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM₁₀)

Emission Limit(s): 0.6 lb/hr; 0.1 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-582-P

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.6 lb/hr; 0.1 ton/yr; 0.1 gr/dscf

Authority for Requirement: DNR Construction Permit 06-A-582-P
567 IAC 23.3(2) "a"

Pollutant: Sulfur Dioxide (SO₂)

Emission Limit(s): 0.9 lb/hr; 0.14 ton/yr; 2.5 lb/MMBtu

Authority for Requirement: DNR Construction Permit 06-A-582-P
567 IAC 23.3(3)

Pollutant: Nitrogen Oxides (NO_x)

Emission Limit(s): 8.0 lb/hr; 1.2 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-582-P

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 0.64 lb/hr; 0.1 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-582-P

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Operating Limits

- A. This unit shall be operated a maximum of 300 hours per 12 month rolling period.
- B. This unit shall be fired by diesel fuel only. The sulfur content of the diesel fuel shall not exceed 0.5% by weight.

Reporting and Recordkeeping

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.

- A. Record the number of hours this unit is operated. Calculate and record monthly and 12 month rolling totals.
- B. Record the sulfur content of any fuel used in this generator.

Authority for Requirement: DNR Construction Permit 06-A-582-P

NSPS and NESHAP Applicability

This emission point is subject to NSPS Subpart A – General Provisions and NSPS Subpart IIII – Standards of Performance for Stationary Compression Ignition Internal Combustion Engines. This engine is also subject to NESHAP Subpart ZZZZ - National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines (RICE).

NESHAP Subpart ZZZZ Requirements:

The emergency engine is subject to 40 CFR 63 Subpart ZZZZ - National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines (RICE). According to 40 CFR 63.6590(a)(2)(iii) this emergency engine, located at an area source, is a new stationary RICE as it was constructed on or after June 12, 2006.

According to 40 CFR 63.6590(c)(1), a new stationary RICE located at an area source of HAP emissions must meet the requirements of Part 63 by meeting the requirements of 40 CFR part 60 subpart IIII for compression ignition engines (or 40 CFR part 60 subpart JJJJ for spark ignition engines). No further requirements apply for this engine under Part 63.

Authority for Requirement: 40 CFR Part 63 Subpart ZZZZ
567 IAC 23.1(4)"cz"

NSPS Subpart IIII Requirements:

Emission Standards:

According to 40 CFR 60.4205(c) and Table 1 to Subpart IIII, you must comply with the following emission standards in grams/kW-hr (grams/HP-hr):

Maximum Engine Power	Model Year(s)	NMHC + NO_x	CO	PM
130 ≤ kW ≤ 560 (175 ≤ HP ≤ 750)	2008 and earlier	10.5 (7.8)	3.5 (2.6)	0.54 (.40)

Fuel Requirements:

You must use diesel fuel that has a maximum sulfur content of 15 ppm (0.0015%) by weight and a minimum cetane index of 40 or a maximum aromatic content of 35 percent by volume. 40 CFR 60.4207 and 40 CFR 80.510(b).

Compliance Requirements:

1. You must operate and maintain the engine to comply with the required emission standards over the entire life of the engine (40 CFR 60.4206) by doing all of the following (40 CFR 60.4211(a)).
 - a) Operating and maintaining the engine and control device according to the manufacturer's emission-related written instructions;
 - b) Changing only those emission-related settings that are permitted by the manufacturer; and
 - c) Meeting the requirements of 40 CFR 89, 94 and/or 1068, as they apply to you.
2. You must demonstrate compliance with the applicable emission standards according to one of the following methods. 40 CFR 60.4211(b).
 - a) Purchasing an engine certified according to 40 CFR 89 or 40 CFR 94, as applicable, for the same model year and maximum engine power. The engine must be installed and configured according to the manufacturer's specifications.
 - b) Keeping records of performance test results for each pollutant for a test conducted on a similar engine. The test must have been conducted using the same methods specified in Subpart IIII and these methods must have been followed correctly.
 - c) Keeping records of engine manufacturer data indicating compliance with the standards.
 - d) Keeping records of control device vendor data indicating compliance with the standards.
 - e) Conducting an initial performance test to demonstrate compliance with the emission standards according to the requirements specified in 40 CFR 60.4212, as applicable.
3. If you do not install, configure, operate, and maintain your engine and control device according to the manufacturer's emission-related written instructions, or you change emission-related settings in a way that is not permitted by the manufacturer, you must keep a maintenance plan and records of conducted maintenance to demonstrate compliance and must, to the extent practicable, maintain and operate the engine in a manner consistent with good air pollution control practice for minimizing emissions. In addition, you must conduct the following performance testing in accordance with 40 CFR 60.4212 to demonstrate compliance with applicable emission standards. You are required to notify the DNR 30 days prior to the test date and are required to submit a stack test report to the DNR within 60 days after the completion of the testing. See 40 CFR 60.4211(g) for additional information.

Maximum Engine Power	Initial Test	Subsequent Test
100 ≤ HP ≤ 500	Within 1 year of engine startup, or non-permitted action ⁽¹⁾	Not required

⁽¹⁾ Non-permitted action means that you do not install, configure, operate, and maintain the engine and control device according to the manufacturer's emission-related written instructions, or you change the emission-related settings in a way that is not permitted by the manufacturer.

Operating and Recordkeeping Requirements

1. If your emergency engine does not meet the standards applicable to non-emergency engines, you must install a non-resettable hour meter prior to startup of the engine (40 CFR 40.4209(a)) and, starting with the model years in the following table, you must keep records of the operation of the engine in emergency and non-emergency service that are recorded through the non-resettable hour meter. The owner must record the time of operation of the engine and the reason the engine was in operation during that time. 40 CFR 40.4214(b).

Engine power	Starting model year
130 ≤ KW (175 ≤ HP)	2011

2. There is no time limit on use for emergency situations. 40 CFR 60.4211(f)(1).
3. The engine may be operated for the purpose of maintenance checks and readiness testing, emergency demand response, and deviation of voltage or frequency for a maximum of 100 hours/year. See 40 CFR 60.4211(f)(2) for more information.
4. The engine may be operated for up to 50 hours per year for non-emergency purposes. This operating time cannot be used for peak shaving or non-emergency demand response or to generate income for the facility (e.g. supplying power to the grid) and should be included in the total of 100 hours allowed for maintenance checks and readiness testing. See 40 CFR 60.4211(f)(3) for more information.

Authority for Requirement: 40 CFR 63 Subpart III
567 IAC 23.1(2) "yyy"

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 8

Stack Opening, (inches, dia.): 3.6

Exhaust Flow Rate (acfm): 514

Exhaust Temperature (°F): 660

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 06-A-582-P

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the

temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: EP-F60

Associated Equipment

Associated Emission Unit ID Numbers: EU-F60

Emissions Control Equipment ID Number: None

Emissions Control Equipment Description: Leak Detection and Repair (LDAR)

Continuous Emissions Monitors ID Numbers: None

Emission Unit vented through this Emission Point: EU-F60

Emission Unit Description: VOC Emissions from Equipment Leaks

Raw Material/Fuel: VOC Leaks

Rated Capacity: NA

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 7.17 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-583-P1

Pollutant: Single HAP

Emission Limit(s): 9.4 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-583-P1

Pollutant: Total HAP

Emission Limit(s): 24.4 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-583-P1

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Operating Limits

- A. The component count shall be documented as to the number and types of components used. Components include but are not limited to valves, pumps, compressor seals, flanges, etc.
- B. The owner or operator shall follow the applicable standards of NSPS Subpart VVa, 40 CFR 60.480a through 40 CFR 60.489a.

Reporting and Recordkeeping

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.

- A. Calculate and record the VOC emissions based on the documented component count. Update annualized VOC emission calculations as the component count varies. Emission factors shall be based on EPA document 453/R-95-017 entitled Protocol for Equipment Leak Emission Estimates.
- B. The owner or operator shall keep records as required in 40 CFR 60.486a, and reports as

required in 40 CFR 60.487a.

Authority for Requirement: DNR Construction Permit 06-A-583-P1

NSPS and NESHAP Applicability

The equipment leaks at this facility are subject to the requirements of the New Source Performance Standard (NSPS) for Standards of Performance for Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry for which Construction, Reconstruction, or Modification Commenced After November 7, 2006 (40 CFR 60 Subpart VVa; 567 IAC 23.1(2)”).

Authority for Requirement: DNR Construction Permit 06-A-583-P1

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: EP-F100

Associated Equipment

Associated Emission Unit ID Numbers: EU-F100
Emissions Control Equipment ID Number: None
Emissions Control Equipment Description: None
Continuous Emissions Monitors ID Numbers: None

Emission Unit vented through this Emission Point: EU-F100
Emission Unit Description: Haul Roads
Raw Material/Fuel: NA
Rated Capacity: NA

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Fugitive Dust

Emission Limit: No person shall allow, cause or permit any materials to be handled, transported or stored; or a building, its appurtenances or a construction haul road to be used, constructed, altered, repaired or demolished, without taking reasonable precautions to prevent a nuisance. All persons shall take reasonable precautions to prevent the discharge of visible emissions of fugitive dusts beyond the lot line of the property on which the emissions originate.

Authority for Requirement: 567 IAC 23.3(2)"c"

Pollutant: Particulate Matter (PM₁₀)

Emission Limit(s): 4.24 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-585-P

Pollutant: Particulate Matter (PM)

Emission Limit(s): 21.7 ton/yr

Authority for Requirement: DNR Construction Permit 06-A-585-P

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Operating Limits

- A. All haul roads at this facility shall be paved.
- B. All haul roads shall be vacuum swept and water flushed daily. Southwest Iowa Renewable Energy LLC may suspend sweeping haul roads if the daily high temperature is below 35 degrees F. The roads need not be swept on days with no traffic.
- C. Clean up spills on the haul roads immediately.
- D. The posted speed limit on haul roads shall be 25 mph or less.

Reporting and Recordkeeping

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.

A. Record any days that the haul roads are not swept due to weather conditions or lack of traffic.

Authority for Requirement: DNR Construction Permit 06-A-585-P

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: EP-T61, EP-T62, EP-T63, EP-T64, and EP-T65

Associated Equipment

Emission Point	Emission Unit Vented through this EP	Emissions Control Equipment ID Number	Emissions Control Equipment Description	Emission Unit Description	Raw Material/Fuel	Rated Capacity (gallons)
EP-T61	EU-T61	CE T61	Internal Floating Roof	Denatured Ethanol Storage Tank	Denatured Ethanol	1,500,000
EP-T62	EU-T62	CE T62				1,500,000
EP-T63	EU-T63	CE T63		200 Proof Ethanol Storage Tank	200 Proof Ethanol	200,000
EP-T64	EU-T64	CE T64		Denaturant Storage Tank	Denaturant	200,000
EP-T65	EU-T65	CE T65		190 Proof Ethanol Storage Tank	190 Proof Ethanol	200,000

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from these emission points shall not exceed the levels specified below.

Pollutant: Acetaldehyde (HAP)

Emission Limit(s): 9.4 ton/yr

Authority for Requirement: DNR Construction Permits 06-A-586-P, 06-A-587-P, 06-A-588-P, 06-A-589-P, 06-A-590-P

Pollutant: Acrolein (HAP)

Emission Limit(s): 9.4 ton/yr

Authority for Requirement: DNR Construction Permits 06-A-586-P, 06-A-587-P, 06-A-588-P, 06-A-589-P, 06-A-590-P

Pollutant: Formaldehyde (HAP)

Emission Limit(s): 9.4 ton/yr

Authority for Requirement: DNR Construction Permits 06-A-586-P, 06-A-587-P, 06-A-588-P, 06-A-589-P, 06-A-590-P

Pollutant: Methanol (HAP)

Emission Limit(s): 9.4 ton/yr

Authority for Requirement: DNR Construction Permits 06-A-586-P, 06-A-587-P, 06-A-588-P, 06-A-589-P, 06-A-590-P

Pollutant: Total HAP

Emission Limit(s): 24.4 ton/yr

Authority for Requirement: DNR Construction Permits 06-A-586-P, 06-A-587-P, 06-A-588-P, 06-A-589-P, 06-A-590-P

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Operating Limits

Emission Point	Emission Unit Vented through this EP	Operating Limit
EP-T61	EU-T61	The tanks shall be used for the storage of denatured ethanol only.
EP-T62	EU-T62	
EP-T63	EU-T63	This tank shall be used for the storage of 200 proof ethanol only.
EP-T64	EU-T64	This tank shall be used for the storage of unleaded gasoline only.
EP-T65	EU-T65	This tank shall be used for the storage of 190 proof ethanol only.

Reporting and Recordkeeping

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.

- A. This facility shall follow the recordkeeping requirements of NSPS subpart VV according to 40 CFR §60.486.
- B. This facility shall follow the reporting requirements of NSPS subpart VV according to 40 CFR §60.487.

Authority for Requirement: DNR Construction Permits 06-A-586-P, 06-A-587-P, 06-A-588-P, 06-A-589-P, 06-A-590-P

NSPS and NESHAP Applicability

These tanks are subject to the following NSPS subparts:

NSPS Subpart A – *General Provisions*

NSPS Subpart Kb – *Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced after July 23, 1984*

NSPS Subpart VV – Standards of Performance for *Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry*.

Authority for Requirement: DNR Construction Permits 06-A-586-P, 06-A-587-P, 06-A-588-P, 06-A-589-P, 06-A-590-P

NOTE: This facility has chosen to satisfy the requirements of NSPS subpart VV by complying with the provisions of NSPS subpart VVa – Standards of Performance for *Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry* for which Construction, Reconstruction, or Modification Commenced After January 5, 1981, and on or Before November 7, 2006.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

IV. General Conditions

This permit is issued under the authority of the Iowa Code subsection 455B.133(8) and in accordance with 567 Iowa Administrative Code chapter 22.

G1. Duty to Comply

1. The permittee must comply with all conditions of the Title V permit. Any permit noncompliance constitutes a violation of the Act and is grounds for enforcement action; for a permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application. *567 IAC 22.108(9)"a"*
2. Any compliance schedule shall be supplemental to, and shall not sanction noncompliance with, the applicable requirements on which it is based. *567 IAC 22.105 (2)"h"(3)*
3. Where an applicable requirement of the Act is more stringent than an applicable requirement of regulations promulgated under Title IV of the Act, both provisions shall be enforceable by the administrator and are incorporated into this permit. *567 IAC 22.108 (1)"b"*
4. Unless specified as either "state enforceable only" or "local program enforceable only", all terms and conditions in the permit, including provisions to limit a source's potential to emit, are enforceable by the administrator and citizens under the Act. *567 IAC 22.108 (14)*
5. It shall not be a defense for a permittee, in an enforcement action, that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. *567 IAC 22.108 (9)"b"*
6. For applicable requirements with which the permittee is in compliance, the permittee shall continue to comply with such requirements. For applicable requirements that will become effective during the permit term, the permittee shall meet such requirements on a timely basis. *567 IAC 22.108(15)"c"*

G2. Permit Expiration

1. Except as provided in rule 567—22.104(455B), permit expiration terminates a source's right to operate unless a timely and complete application for renewal has been submitted in accordance with rule 567—22.105(455B). *567 IAC 22.116(2)*
2. To be considered timely, the owner, operator, or designated representative (where applicable) of each source required to obtain a Title V permit shall submit on forms or electronic format specified by the Department to the Air Quality Bureau, Iowa Department of Natural Resources, Air Quality Bureau, 7900 Hickman Rd, Suite #1, Windsor Heights, Iowa 50324, two copies (three if your facility is located in Linn or Polk county) of a complete permit application, at least 6 months but not more than 18 months prior to the date of permit expiration. An additional copy must also be sent to U.S. EPA Region VII, Attention: Chief of Air Permits, 11201 Renner Blvd., Lenexa, KS 66219. Additional copies to local programs or EPA are not required for application materials submitted through the electronic format specified by the Department. The application must include all emission points, emission units, air pollution control equipment, and monitoring devices at the facility. All emissions generating activities, including fugitive emissions, must be included. The definition of a complete application is as indicated in 567 IAC 22.105(2). *567 IAC 22.105*

G3. Certification Requirement for Title V Related Documents

Any application, report, compliance certification or other document submitted pursuant to this permit shall contain certification by a responsible official of truth, accuracy, and completeness. All certifications shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete. *567 IAC 22.107 (4)*

G4. Annual Compliance Certification

By March 31 of each year, the permittee shall submit compliance certifications for the previous calendar year. The certifications shall include descriptions of means to monitor the compliance status of all emissions sources including emissions limitations, standards, and work practices in accordance with applicable requirements. The certification for a source shall include the identification of each term or condition of the permit that is the basis of the certification; the compliance status; whether compliance was continuous or intermittent; the method(s) used for determining the compliance status of the source, currently and over the reporting period consistent with all applicable department rules. For sources determined not to be in compliance at the time of compliance certification, a compliance schedule shall be submitted which provides for periodic progress reports, dates for achieving activities, milestones, and an explanation of why any dates were missed and preventive or corrective measures. The compliance certification shall be submitted to the administrator, director, and the appropriate DNR Field office. *567 IAC 22.108 (15)"e"*

G5. Semi-Annual Monitoring Report

By March 31 and September 30 of each year, the permittee shall submit a report of any monitoring required under this permit for the 6 month periods of July 1 to December 31 and January 1 to June 30, respectively. All instances of deviations from permit requirements must be clearly identified in these reports, and the report must be signed by a responsible official, consistent with 567 IAC 22.107(4). The semi-annual monitoring report shall be submitted to the director and the appropriate DNR Field office. *567 IAC 22.108 (5)*

G6. Annual Fee

1. The permittee is required under subrule 567 IAC 22.106 to pay an annual fee based on the total tons of actual emissions of each regulated air pollutant. Beginning July 1, 1996, Title V operating permit fees will be paid on July 1 of each year. The fee shall be based on emissions for the previous calendar year.
2. The fee amount shall be calculated based on the first 4,000 tons of each regulated air pollutant emitted each year. The fee to be charged per ton of pollutant will be available from the department by June 1 of each year. The Responsible Official will be advised of any change in the annual fee per ton of pollutant.
3. The following forms shall be submitted annually by March 31 documenting actual emissions for the previous calendar year.
 - a. Form 1.0 "Facility Identification";
 - b. Form 4.0 "Emissions unit-actual operations and emissions" for each emission unit;
 - c. Form 5.0 "Title V annual emissions summary/fee"; and
 - d. Part 3 "Application certification."
4. The fee shall be submitted annually by July 1. The fee shall be submitted with the following forms:
 - a. Form 1.0 "Facility Identification";
 - b. Form 5.0 "Title V annual emissions summary/fee";
 - c. Part 3 "Application certification."
5. If there are any changes to the emission calculation form, the department shall make revised forms available to the public by January 1. If revised forms are not available by January 1, forms from the previous year may be used and the year of emissions documented changed. The department shall calculate the total statewide Title V emissions for the prior calendar year and make this information available to the public no later than April 30 of each year.

6. Phase I acid rain affected units under section 404 of the Act shall not be required to pay a fee for emissions which occur during the years 1993 through 1999 inclusive.
7. The fee for a portable emissions unit or stationary source which operates both in Iowa and out of state shall be calculated only for emissions from the source while operating in Iowa.
8. Failure to pay the appropriate Title V fee represents cause for revocation of the Title V permit as indicated in 567 IAC 22.115(1)"d".

G7. Inspection of Premises, Records, Equipment, Methods and Discharges

Upon presentation of proper credentials and any other documents as may be required by law, the permittee shall allow the director or the director's authorized representative to:

1. Enter upon the permittee's premises where a Title V source is located or emissions-related activity is conducted, or where records must be kept under the conditions of the permit;
2. Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
3. Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
4. Sample or monitor, at reasonable times, substances or parameters for the purpose of ensuring compliance with the permit or other applicable requirements. *567 IAC 22.108 (15)"b"*

G8. Duty to Provide Information

The permittee shall furnish to the director, within a reasonable time, any information that the director may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee also shall furnish to the director copies of records required to be kept by the permit, or for information claimed to be confidential, the permittee shall furnish such records directly to the administrator of EPA along with a claim of confidentiality. *567 IAC 22.108 (9)"e"*

G9. General Maintenance and Repair Duties

The owner or operator of any air emission source or control equipment shall:

1. Maintain and operate the equipment or control equipment at all times in a manner consistent with good practice for minimizing emissions.
2. Remedy any cause of excess emissions in an expeditious manner.
3. Minimize the amount and duration of any excess emission to the maximum extent possible during periods of such emissions. These measures may include but not be limited to the use of clean fuels, production cutbacks, or the use of alternate process units or, in the case of utilities, purchase of electrical power until repairs are completed.
4. Schedule, at a minimum, routine maintenance of equipment or control equipment during periods of process shutdowns to the maximum extent possible. *567 IAC 24.2(1)*

G10. Recordkeeping Requirements for Compliance Monitoring

1. In addition to any source specific recordkeeping requirements contained in this permit, the permittee shall maintain the following compliance monitoring records, where applicable:
 - a. The date, place and time of sampling or measurements
 - b. The date the analyses were performed.
 - c. The company or entity that performed the analyses.
 - d. The analytical techniques or methods used.
 - e. The results of such analyses; and
 - f. The operating conditions as existing at the time of sampling or measurement.
 - g. The records of quality assurance for continuous compliance monitoring systems (including but not limited to quality control activities, audits and calibration drifts.)

2. The permittee shall retain records of all required compliance monitoring data and support information for a period of at least 5 years from the date of compliance monitoring sample, measurement report or application. Support information includes all calibration and maintenance records and all original strip chart recordings for continuous compliance monitoring, and copies of all reports required by the permit.

3. For any source which in its application identified reasonably anticipated alternative operating scenarios, the permittee shall:

- a. Comply with all terms and conditions of this permit specific to each alternative scenario.
- b. Maintain a log at the permitted facility of the scenario under which it is operating.
- c. Consider the permit shield, if provided in this permit, to extend to all terms and conditions under each operating scenario. *567 IAC 22.108(4), 567 IAC 22.108(12)*

G11. Evidence used in establishing that a violation has or is occurring.

Notwithstanding any other provisions of these rules, any credible evidence may be used for the purpose of establishing whether a person has violated or is in violation of any provisions herein.

1. Information from the use of the following methods is presumptively credible evidence of whether a violation has occurred at a source:

- a. A monitoring method approved for the source and incorporated in an operating permit pursuant to 567 Chapter 22;
- b. Compliance test methods specified in 567 Chapter 25; or
- c. Testing or monitoring methods approved for the source in a construction permit issued pursuant to 567 Chapter 22.

2. The following testing, monitoring or information gathering methods are presumptively credible testing, monitoring, or information gathering methods:

- a. Any monitoring or testing methods provided in these rules; or
- b. Other testing, monitoring, or information gathering methods that produce information comparable to that produced by any method in subrule 21.5(1) or this subrule. *567 IAC 21.5(1)-567 IAC 21.5(2)*

G12. Prevention of Accidental Release: Risk Management Plan Notification and Compliance Certification

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Act, the permittee shall notify the department of this requirement. The plan shall be filed with all appropriate authorities by the deadline specified by EPA. A certification that this risk management plan is being properly implemented shall be included in the annual compliance certification of this permit. *567 IAC 22.108(6)*

G13. Hazardous Release

The permittee must report any situation involving the actual, imminent, or probable release of a hazardous substance into the atmosphere which, because of the quantity, strength and toxicity of the substance, creates an immediate or potential danger to the public health, safety or to the environment. A verbal report shall be made to the department at (515) 725-8694 and to the local police department or the office of the sheriff of the affected county as soon as possible but not later than six hours after the discovery or onset of the condition. This verbal report must be followed up with a written report as indicated in 567 IAC 131.2(2). *567 IAC Chapter 131-State Only*

G14. Excess Emissions and Excess Emissions Reporting Requirements

1. Excess Emissions. Excess emission during a period of startup, shutdown, or cleaning of control equipment is not a violation of the emission standard if the startup, shutdown or cleaning is accomplished expeditiously and in a manner consistent with good practice for minimizing emissions. Cleaning of control equipment which does not require the shutdown of the process equipment shall be limited to one six-minute period per one-hour period. An incident of excess emission (other than an incident during startup, shutdown or cleaning of control equipment) is a violation. If the owner or operator of a source maintains that the incident of excess emission was due to a malfunction, the owner or operator must show that the conditions which caused the incident of excess emission were not preventable by reasonable maintenance and control measures. Determination of any subsequent enforcement action will be made following review of this report. If excess emissions are occurring, either the control equipment causing the excess emission shall be repaired in an expeditious manner or the process generating the emissions shall be shutdown within a reasonable period of time. An expeditious manner is the time necessary to determine the cause of the excess emissions and to correct it within a reasonable period of time. A reasonable period of time is eight hours plus the period of time required to shut down the process without damaging the process equipment or control equipment. A variance from this subrule may be available as provided for in Iowa Code section 455B.143. In the case of an electric utility, a reasonable period of time is eight hours plus the period of time until comparable generating capacity is available to meet consumer demand with the affected unit out of service, unless, the director shall, upon investigation, reasonably determine that continued operation constitutes an unjustifiable environmental hazard and issue an order that such operation is not in the public interest and require a process shutdown to commence immediately.

2. Excess Emissions Reporting

a. Initial Reporting of Excess Emissions. An incident of excess emission (other than an incident of excess emission during a period of startup, shutdown, or cleaning) shall be reported to the appropriate field office of the department within eight hours of, or at the start of the first working day following the onset of the incident. The reporting exemption for an incident of excess emission during startup, shutdown or cleaning does not relieve the owner or operator of a source with continuous monitoring equipment of the obligation of submitting reports required in 567-subrule 25.1(6). An initial report of excess emission is not required for a source with operational continuous monitoring equipment (as specified in 567-subrule 25.1(1)) if the incident of excess emission continues for less than 30 minutes and does not exceed the applicable emission standard by more than 10 percent or the applicable visible emission standard by more than 10 percent opacity. The initial report may be made by electronic mail (E-mail), in person, or by telephone and shall include as a minimum the following:

- i. The identity of the equipment or source operation from which the excess emission originated and the associated stack or emission point.
- ii. The estimated quantity of the excess emission.
- iii. The time and expected duration of the excess emission.
- iv. The cause of the excess emission.
- v. The steps being taken to remedy the excess emission.
- vi. The steps being taken to limit the excess emission in the interim period.

b. Written Reporting of Excess Emissions. A written report of an incident of excess emission shall be submitted as a follow-up to all required initial reports to the department

within seven days of the onset of the upset condition, and shall include as a minimum the following:

- i. The identity of the equipment or source operation point from which the excess emission originated and the associated stack or emission point.
- ii. The estimated quantity of the excess emission.
- iii. The time and duration of the excess emission.
- iv. The cause of the excess emission.
- v. The steps that were taken to remedy and to prevent the recurrence of the incident of excess emission.
- vi. The steps that were taken to limit the excess emission.
- vii. If the owner claims that the excess emission was due to malfunction, documentation to support this claim. *567 IAC 24.1(1)-567 IAC 24.1(4)*

3. Emergency Defense for Excess Emissions. For the purposes of this permit, an “emergency” means any situation arising from sudden and reasonably unforeseeable events beyond the control of the source, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the source to exceed a technology-based emission limitation under the permit due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include non-compliance, to the extent caused by improperly designed equipment, lack of preventive maintenance, careless or improper operation or operator error. An emergency constitutes an affirmative defense to an action brought for non-compliance with technology based limitations if it can be demonstrated through properly signed contemporaneous operating logs or other relevant evidence that:

- a. An emergency occurred and that the permittee can identify the cause(s) of the emergency;
- b. The facility at the time was being properly operated;
- c. During the period of the emergency, the permittee took all reasonable steps to minimize levels of emissions that exceeded the emissions standards or other requirements of the permit; and
- d. The permittee submitted notice of the emergency to the director by certified mail within two working days of the time when the emissions limitations were exceeded due to the emergency. This notice fulfills the requirement of paragraph 22.108(5)"b." – See G15. This notice must contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken.

In any enforcement proceeding, the permittee seeking to establish the occurrence of an emergency has the burden of proof. This provision is in addition to any emergency or upset provision contained in any applicable requirement. *567 IAC 22.108(16)*

G15. Permit Deviation Reporting Requirements

A deviation is any failure to meet a term, condition or applicable requirement in the permit. Reporting requirements for deviations that result in a hazardous release or excess emissions have been indicated above (see G13 and G14). Unless more frequent deviation reporting is specified in the permit, any other deviation shall be documented in the semi-annual monitoring report and the annual compliance certification (see G4 and G5). *567 IAC 22.108(5)"b"*

G16. Notification Requirements for Sources That Become Subject to NSPS and NESHAP Regulations

During the term of this permit, the permittee must notify the department of any source that becomes subject to a standard or other requirement under 567-subrule 23.1(2) (standards of

performance of new stationary sources) or section 111 of the Act; or 567-subrule 23.1(3) (emissions standards for hazardous air pollutants), 567-subrule 23.1(4) (emission standards for hazardous air pollutants for source categories) or section 112 of the Act. This notification shall be submitted in writing to the department pursuant to the notification requirements in 40 CFR Section 60.7, 40 CFR Section 61.07, and/or 40 CFR Section 63.9. *567 IAC 23.1(2), 567 IAC 23.1(3), 567 IAC 23.1(4)*

G17. Requirements for Making Changes to Emission Sources That Do Not Require Title V Permit Modification

1. Off Permit Changes to a Source. Pursuant to section 502(b)(10) of the CAAA, the permittee may make changes to this installation/facility without revising this permit if:
 - a. The changes are not major modifications under any provision of any program required by section 110 of the Act, modifications under section 111 of the act, modifications under section 112 of the act, or major modifications as defined in 567 IAC Chapter 22.
 - b. The changes do not exceed the emissions allowable under the permit (whether expressed therein as a rate of emissions or in terms of total emissions);
 - c. The changes are not modifications under any provisions of Title I of the Act and the changes do not exceed the emissions allowable under the permit (whether expressed therein as a rate of emissions or as total emissions);
 - d. The changes are not subject to any requirement under Title IV of the Act (revisions affecting Title IV permitting are addressed in rules 567—22.140(455B) through 567 - 22.144(455B));
 - e. The changes comply with all applicable requirements.
 - f. For each such change, the permitted source provides to the department and the administrator by certified mail, at least 30 days in advance of the proposed change, a written notification, including the following, which must be attached to the permit by the source, the department and the administrator:
 - i. A brief description of the change within the permitted facility,
 - ii. The date on which the change will occur,
 - iii. Any change in emission as a result of that change,
 - iv. The pollutants emitted subject to the emissions trade
 - v. If the emissions trading provisions of the state implementation plan are invoked, then Title V permit requirements with which the source shall comply; a description of how the emissions increases and decreases will comply with the terms and conditions of the Title V permit.
 - vi. A description of the trading of emissions increases and decreases for the purpose of complying with a federally enforceable emissions cap as specified in and in compliance with the Title V permit; and
 - vii. Any permit term or condition no longer applicable as a result of the change.*567 IAC 22.110(1)*
2. Such changes do not include changes that would violate applicable requirements or contravene federally enforceable permit terms and conditions that are monitoring (including test methods), record keeping, reporting, or compliance certification requirements. *567 IAC 22.110(2)*
3. Notwithstanding any other part of this rule, the director may, upon review of a notice, require a stationary source to apply for a Title V permit if the change does not meet the requirements of subrule 22.110(1). *567 IAC 22.110(3)*

4. The permit shield provided in subrule 22.108(18) shall not apply to any change made pursuant to this rule. Compliance with the permit requirements that the source will meet using the emissions trade shall be determined according to requirements of the state implementation plan authorizing the emissions trade. *567 IAC 22.110(4)*
5. No permit revision shall be required, under any approved economic incentives, marketable permits, emissions trading and other similar programs or processes, for changes that are provided for in this permit. *567 IAC 22.108(11)*

G18. Duty to Modify a Title V Permit

1. Administrative Amendment.

- a. An administrative permit amendment is a permit revision that does any of the following:
 - i. Correct typographical errors
 - ii. Identify a change in the name, address, or telephone number of any person identified in the permit, or provides a similar minor administrative change at the source;
 - iii. Require more frequent monitoring or reporting by the permittee; or
 - iv. Allow for a change in ownership or operational control of a source where the director determines that no other change in the permit is necessary, provided that a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new permittee has been submitted to the director.
- b. The permittee may implement the changes addressed in the request for an administrative amendment immediately upon submittal of the request. The request shall be submitted to the director.
- c. Administrative amendments to portions of permits containing provisions pursuant to Title IV of the Act shall be governed by regulations promulgated by the administrator under Title IV of the Act.

2. Minor Title V Permit Modification.

- a. Minor Title V permit modification procedures may be used only for those permit modifications that satisfy all of the following:
 - i. Do not violate any applicable requirement;
 - ii. Do not involve significant changes to existing monitoring, reporting or recordkeeping requirements in the Title V permit;
 - iii. Do not require or change a case by case determination of an emission limitation or other standard, or an increment analysis;
 - iv. Do not seek to establish or change a permit term or condition for which there is no corresponding underlying applicable requirement and that the source has assumed in order to avoid an applicable requirement to which the source would otherwise be subject. Such terms and conditions include any federally enforceable emissions caps which the source would assume to avoid classification as a modification under any provision under Title I of the Act; and an alternative emissions limit approved pursuant to regulations promulgated under section 112(i)(5) of the Act;
 - v. Are not modifications under any provision of Title I of the Act; and
 - vi. Are not required to be processed as significant modification under rule 567 - 22.113(455B).

- b. An application for minor permit revision shall be on the minor Title V modification application form and shall include at least the following:
- i. A description of the change, the emissions resulting from the change, and any new applicable requirements that will apply if the change occurs;
 - ii. The permittee's suggested draft permit;
 - iii. Certification by a responsible official, pursuant to 567 IAC 22.107(4), that the proposed modification meets the criteria for use of minor permit modification procedures and a request that such procedures be used; and
 - iv. Completed forms to enable the department to notify the administrator and the affected states as required by 567 IAC 22.107(7).
- c. The permittee may make the change proposed in its minor permit modification application immediately after it files the application. After the permittee makes this change and until the director takes any of the actions specified in 567 IAC 22.112(4) "a" to "c", the permittee must comply with both the applicable requirements governing the change and the proposed permit terms and conditions. During this time, the permittee need not comply with the existing permit terms and conditions it seeks to modify. However, if the permittee fails to comply with its proposed permit terms and conditions during this time period, the existing permit terms and conditions it seeks to modify may be enforced against the facility.

3. Significant Title V Permit Modification.

Significant Title V modification procedures shall be used for applications requesting Title V permit modifications that do not qualify as minor Title V modifications or as administrative amendments. These include but are not limited to all significant changes in monitoring permit terms, every relaxation of reporting or recordkeeping permit terms, and any change in the method of measuring compliance with existing requirements. Significant Title V modifications shall meet all requirements of 567 IAC Chapter 22, including those for applications, public participation, review by affected states, and review by the administrator, as those requirements that apply to Title V issuance and renewal.

The permittee shall submit an application for a significant permit modification not later than three months after commencing operation of the changed source unless the existing Title V permit would prohibit such construction or change in operation, in which event the operation of the changed source may not commence until the department revises the permit. *567 IAC 22.111-567 IAC 22.113*

G19. Duty to Obtain Construction Permits

Unless exempted in 567 IAC 22.1(2) or to meet the parameters established in 567 IAC 22.1(1)"c", the permittee shall not construct, install, reconstruct or alter any equipment, control equipment or anaerobic lagoon without first obtaining a construction permit, or conditional permit, or permit pursuant to rule 567 IAC 22.8, or permits required pursuant to rules 567 IAC 22.4, 567 IAC 22.5, 567 IAC 31.3, and 567 IAC 33.3 as required in 567 IAC 22.1(1). A permit shall be obtained prior to the initiation of construction, installation or alteration of any portion of the stationary source or anaerobic lagoon. *567 IAC 22.1(1)*

G20. Asbestos

The permittee shall comply with 567 IAC 23.1(3)"a", and 567 IAC 23.2(3)"g" when activities involve asbestos mills, surfacing of roadways, manufacturing operations, fabricating, insulating, waste disposal, spraying applications, demolition and renovation operations (*567 IAC 23.1(3)"a"*); training fires and controlled burning of a demolished building (*567 IAC 23.2*).

G21. Open Burning

The permittee is prohibited from conducting open burning, except as provided in 567 IAC 23.2. *567 IAC 23.2 except 23.2(3)"j"; 567 IAC 23.2(3)"j" - State Only*

G22. Acid Rain (Title IV) Emissions Allowances

The permittee shall not exceed any allowances that it holds under Title IV of the Act or the regulations promulgated there under. Annual emissions of sulfur dioxide in excess of the number of allowances to emit sulfur dioxide held by the owners and operators of the unit or the designated representative of the owners and operators is prohibited. Exceedences of applicable emission rates are prohibited. "Held" in this context refers to both those allowances assigned to the owners and operators by USEPA, and those allowances supplementally acquired by the owners and operators. The use of any allowance prior to the year for which it was allocated is prohibited. Contravention of any other provision of the permit is prohibited. *567 IAC 22.108(7)*

G23. Stratospheric Ozone and Climate Protection (Title VI) Requirements

1. The permittee shall comply with the standards for labeling of products using ozone-depleting substances pursuant to 40 CFR Part 82, Subpart E:
 - a. All containers in which a class I or class II substance is stored or transported, all products containing a class I substance, and all products directly manufactured with a class I substance must bear the required warning statement if it is being introduced into interstate commerce pursuant to § 82.106.
 - b. The placement of the required warning statement must comply with the requirements pursuant to § 82.108.
 - c. The form of the label bearing the required warning statement must comply with the requirements pursuant to § 82.110.
 - d. No person may modify, remove, or interfere with the required warning statement except as described in § 82.112.
2. The permittee shall comply with the standards for recycling and emissions reduction pursuant to 40 CFR Part 82, Subpart F, except as provided for MVACs in Subpart B:
 - a. Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to § 82.156.
 - b. Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to § 82.158.
 - c. Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to § 82.161.
 - d. Persons disposing of small appliances, MVACs, and MVAC-like appliances must comply with reporting and recordkeeping requirements pursuant to § 82.166. ("MVAC-like appliance" as defined at § 82.152)
 - e. Persons owning commercial or industrial process refrigeration equipment must comply with the leak repair requirements pursuant to § 82.156.
 - f. Owners/operators of appliances normally containing 50 or more pounds of refrigerant must keep records of refrigerant purchased and added to such appliances pursuant to § 82.166.
3. If the permittee manufactures, transforms, imports, or exports a class I or class II substance, the permittee is subject to all the requirements as specified in 40 CFR part 82, Subpart A, Production and Consumption Controls.
4. If the permittee performs a service on motor (fleet) vehicles when this service involves ozone-depleting substance refrigerant (or regulated substitute substance) in the motor vehicle air

conditioner (MVAC), the permittee is subject to all the applicable requirements as specified in 40 CFR part 82, Subpart B, Servicing of Motor Vehicle Air Conditioners. The term "motor vehicle" as used in Subpart B does not include a vehicle in which final assembly of the vehicle has not been completed. The term "MVAC" as used in Subpart B does not include the air-tight sealed refrigeration system used as refrigerated cargo, or system used on passenger buses using HCFC-22 refrigerant,

5. The permittee shall be allowed to switch from any ozone-depleting substance to any alternative that is listed in the Significant New Alternatives Program (SNAP) promulgated pursuant to 40 CFR part 82, Subpart G, Significant New Alternatives Policy Program. *40 CFR part 82*

G24. Permit Reopenings

1. This permit may be modified, revoked, reopened, and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition. *567 IAC 22.108(9)"c"*

2. Additional applicable requirements under the Act become applicable to a major part 70 source with a remaining permit term of 3 or more years. Revisions shall be made as expeditiously as practicable, but not later than 18 months after the promulgation of such standards and regulations.

a. Reopening and revision on this ground is not required if the permit has a remaining term of less than three years;

b. Reopening and revision on this ground is not required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions have been extended pursuant to 40 CFR 70.4(b)(10)(i) or (ii) as amended to May 15, 2001.

c. Reopening and revision on this ground is not required if the additional applicable requirements are implemented in a general permit that is applicable to the source and the source receives approval for coverage under that general permit. *567 IAC 22.108(17)"a"*, *567 IAC 22.108(17)"b"*

3. A permit shall be reopened and revised under any of the following circumstances:

a. The department receives notice that the administrator has granted a petition for disapproval of a permit pursuant to 40 CFR 70.8(d) as amended to July 21, 1992, provided that the reopening may be stayed pending judicial review of that determination;

b. The department or the administrator determines that the Title V permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of the Title V permit;

c. Additional applicable requirements under the Act become applicable to a Title V source, provided that the reopening on this ground is not required if the permit has a remaining term of less than three years, the effective date of the requirement is later than the date on which the permit is due to expire, or the additional applicable requirements are implemented in a general permit that is applicable to the source and the source receives approval for coverage under that general permit. Such a reopening shall be complete not later than 18 months after promulgation of the applicable requirement.

d. Additional requirements, including excess emissions requirements, become applicable to a Title IV affected source under the acid rain program. Upon approval by the administrator, excess emissions offset plans shall be deemed to be incorporated into the

permit.

e. The department or the administrator determines that the permit must be revised or revoked to ensure compliance by the source with the applicable requirements. *567 IAC 22.114(1)*

4. Proceedings to reopen and reissue a Title V permit shall follow the procedures applicable to initial permit issuance and shall effect only those parts of the permit for which cause to reopen exists. *567 IAC 22.114(2)*

5. A notice of intent shall be provided to the Title V source at least 30 days in advance of the date the permit is to be reopened, except that the director may provide a shorter time period in the case of an emergency. *567 IAC 22.114(3)*

G25. Permit Shield

1. The director may expressly include in a Title V permit a provision stating that compliance with the conditions of the permit shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that:

a. Such applicable requirements are included and are specifically identified in the permit; or

b. The director, in acting on the permit application or revision, determines in writing that other requirements specifically identified are not applicable to the source, and the permit includes the determination or a concise summary thereof.

2. A Title V permit that does not expressly state that a permit shield exists shall be presumed not to provide such a shield.

3. A permit shield shall not alter or affect the following:

a. The provisions of Section 303 of the Act (emergency orders), including the authority of the administrator under that section;

b. The liability of an owner or operator of a source for any violation of applicable requirements prior to or at the time of permit issuance;

c. The applicable requirements of the acid rain program, consistent with Section 408(a) of the Act;

d. The ability of the department or the administrator to obtain information from the facility pursuant to Section 114 of the Act. *567 IAC 22.108 (18)*

G26. Severability

The provisions of this permit are severable and if any provision or application of any provision is found to be invalid by this department or a court of law, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected by such finding. *567 IAC 22.108 (8)*

G27. Property Rights

The permit does not convey any property rights of any sort, or any exclusive privilege. *567 IAC 22.108 (9)"d"*

G28. Transferability

This permit is not transferable from one source to another. If title to the facility or any part of it is transferred, an administrative amendment to the permit must be sought consistent with the requirements of *567 IAC 22.111(1)*. *567 IAC 22.111 (1)"d"*

G29. Disclaimer

No review has been undertaken on the engineering aspects of the equipment or control equipment other than the potential of that equipment for reducing air contaminant emissions. *567 IAC 22.3(3)"c"*

G30. Notification and Reporting Requirements for Stack Tests or Monitor Certification

The permittee shall notify the department's stack test contact in writing not less than 30 days before a required test or performance evaluation of a continuous emission monitor is performed to determine compliance with applicable requirements of 567 – Chapter 23 or a permit condition. Such notice shall include the time, the place, the name of the person who will conduct the test and other information as required by the department. If the owner or operator does not provide timely notice to the department, the department shall not consider the test results or performance evaluation results to be a valid demonstration of compliance with applicable rules or permit conditions. Upon written request, the department may allow a notification period of less than 30 days. At the department's request, a pretest meeting shall be held not later than 15 days prior to conducting the compliance demonstration. A testing protocol shall be submitted to the department no later than 15 days before the owner or operator conducts the compliance demonstration. A representative of the department shall be permitted to witness the tests. Results of the tests shall be submitted in writing to the department's stack test contact in the form of a comprehensive report within six weeks of the completion of the testing. Compliance tests conducted pursuant to this permit shall be conducted with the source operating in a normal manner at its maximum continuous output as rated by the equipment manufacturer, or the rate specified by the owner as the maximum production rate at which the source shall be operated. In cases where compliance is to be demonstrated at less than the maximum continuous output as rated by the equipment manufacturer, and it is the owner's intent to limit the capacity to that rating, the owner may submit evidence to the department that the source has been physically altered so that capacity cannot be exceeded, or the department may require additional testing, continuous monitoring, reports of operating levels, or any other information deemed necessary by the department to determine whether such source is in compliance.

Stack test notifications, reports and correspondence shall be sent to:

Stack Test Review Coordinator
Iowa DNR, Air Quality Bureau
7900 Hickman Road, Suite #1
Windsor Heights, IA 50324
(515) 725-9545

Within Polk and Linn Counties, stack test notifications, reports and correspondence shall also be directed to the supervisor of the respective county air pollution program.

567 IAC 25.1(7)"a", 567 IAC 25.1(9)

G31. Prevention of Air Pollution Emergency Episodes

The permittee shall comply with the provisions of 567 IAC Chapter 26 in the prevention of excessive build-up of air contaminants during air pollution episodes, thereby preventing the occurrence of an emergency due to the effects of these contaminants on the health of persons.

567 IAC 26.1(1)

G32. Contacts List

The current address and phone number for reports and notifications to the EPA administrator is:

Chief of Air Permits
U.S. EPA Region 7
Air Permits and Compliance Branch
11201 Renner Blvd.
Lenexa, KS 66219
(913) 551-7020

The current address and phone number for reports and notifications to the department or the Director is:

Chief, Air Quality Bureau
Iowa Department of Natural Resources
7900 Hickman Road, Suite #1
Windsor Heights, IA 50324
(515) 725-9500

Reports or notifications to the DNR Field Offices or local programs shall be directed to the supervisor at the appropriate field office or local program. Current addresses and phone numbers are:

Field Office 1

909 West Main – Suite 4
Manchester, IA 52057
(563) 927-2640

Field Office 2

2300-15th St., SW
Mason City, IA 50401
(641) 424-4073

Field Office 3

1900 N. Grand Ave.
Spencer, IA 51301
(712) 262-4177

Field Office 4

1401 Sunnyside Lane
Atlantic, IA 50022
(712) 243-1934

Field Office 5

7900 Hickman Road, Suite #200
Windsor Heights, IA 50324
(515) 725-0268

Field Office 6

1023 West Madison Street
Washington, IA 52353-1623
(319) 653-2135

Polk County Public Works Dept.

Air Quality Division
5885 NE 14th St.
Des Moines, IA 50313
(515) 286-3351

Linn County Public Health

Air Quality Branch
501 13th St., NW
Cedar Rapids, IA 52405
(319) 892-6000

V. Appendix

- A. 40 CFR Part 60 Subpart A- *General Provisions*
<http://www.ecfr.gov/cgi-bin/text-idx?c=ecfr&rgn=div6&view=text&node=40:7.0.1.1.1.1>
- B. 40 CFR Part 60 Subpart Db- Standards of Performance for *Industrial-Commercial-Institutional Steam Generating Units*
<http://www.ecfr.gov/cgi-bin/text-idx?SID=76cffe0ca64bf9144e6b4164f40f78c1&node=pt40.7.60&rgn=div5#sp40.7.60.d.0b>
- C. 40 CFR Part 60 Subpart Kb- Standards of Performance for *Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels)* for Which Construction, Reconstruction or Modification Commenced After July 23, 1984
<http://www.tceq.state.tx.us/permitting/air/rules/federal/60/kb/kbhp.html>
- D. 40 CFR Part 60 Subpart VVa- Standards of Performance for *Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry* for Which Construction, Reconstruction, or Modification Commenced after November 7, 2006
<http://www.ecfr.gov/cgi-bin/retrieveECFR?gp=&SID=bc4c913cc779deb441f61b794bf739ec&r=SUBPART&n=sp40.7.60.vv.0a>
- E. 40 CFR Part 60 Subpart IIII—Standards of Performance for *Stationary Compression Ignition Internal Combustion Engines*
<http://www.ecfr.gov/cgi-bin/text-idx?c=ecfr&rgn=div6&view=test&node=40:7.0.1.1.1.98>
- F. 40 CFR 63 Subpart ZZZZ – National Emission Standard for Hazardous Air Pollutants for *Stationary Reciprocating Internal Combustion Engines*
<http://www.ecfr.gov/cgi-bin/text-idx?c=ecfr&rgn=div6&view=text&node=40:14.0.1.1.1.1>