

Iowa Department of Natural Resources Title V Operating Permit

Name of Permitted Facility: ADM- Des Moines Soybean
Facility Location: 1935 E. Euclid Ave., Des Moines, IA 50313
Air Quality Operating Permit Number: 04-TV-020R2
Expiration Date: June 15, 2031
Permit Renewal Application Deadline: December 15, 2030

EIQ Number: 92-6313
Facility File Number: 77-01-045

Responsible Official

Name: Dan James
Title: Complex Manager
Mailing Address: 1935 E. Euclid Avenue
Des Moines, Iowa 50313
Phone Number: 515-802-9787

Permit Contact Person for the Facility

Name: Amanda Jennings
Title: Area Environmental Manager
Mailing Address: 1935 E. Euclid Avenue
Des Moines, Iowa 50313
Phone Number: 515-380-0811

This permit is issued in accordance with 567 Iowa Administrative Code Chapter 24, and is issued subject to the terms and conditions contained in this permit.

For the Director of the Department of Natural Resources

Corey McCoid

Corey McCoid, Supervisor of Air Operating Permits Section

06/16/2026

Date

Table of Contents

I. Facility Description and Equipment List	5
II. Plant - Wide Conditions	8
III. Emission Point Specific Conditions	13
IV. General Conditions	137
G1. Duty to Comply	
G2. Permit Expiration	
G3. Certification Requirement for Title V Related Documents	
G4. Annual Compliance Certification	
G5. Semi-Annual Monitoring Report	
G6. Annual Fee	
G7. Inspection of Premises, Records, Equipment, Methods and Discharges	
G8. Duty to Provide Information	
G9. General Maintenance and Repair Duties	
G10. Recordkeeping Requirements for Compliance Monitoring	
G11. Evidence used in establishing that a violation has or is occurring.	
G12. Prevention of Accidental Release: Risk Management Plan Notification and Compliance Certification	
G13. Hazardous Release	
G14. Excess Emissions and Excess Emissions Reporting Requirements	
G15. Permit Deviation Reporting Requirements	
G16. Notification Requirements for Sources That Become Subject to NSPS and NESHAP Regulations	
G17. Requirements for Making Changes to Emission Sources That Do Not Require Title V Permit Modification	
G18. Duty to Modify a Title V Permit	
G19. Duty to Obtain Construction Permits	
G20. Asbestos	
G21. Open Burning	
G22. Acid Rain (Title IV) Emissions Allowances	
G23. Stratospheric Ozone and Climate Protection (Title VI) Requirements	
G24. Permit Reopenings	
G25. Permit Shield	
G26. Severability	
G27. Property Rights	
G28. Transferability	
G29. Disclaimer	
G30. Notification and Reporting Requirements for Stack Tests or Monitor Certification	
G31. Prevention of Air Pollution Emergency Episodes	
G32. Contacts List	

V. Appendix 1: Weblinks to applicable NSPS and NESHAP.....152
VI. Appendix 2: EO10 Rules Crosswalk153

Abbreviations

acfm.....	actual cubic feet per minute
AERMOD.....	AMS/EPA Regulatory Model
AQD.....	Polk County Public Works- Air Quality Division
CAS.....	Chemical Abstract Service Registry
CE.....	Control Equipment
CEM.....	Continuous Emission Monitor
CFR.....	Code of Federal Regulation
DNR.....	Iowa Department of Natural Resources
°F.....	degrees Fahrenheit
EIQ.....	Emissions Inventory Questionnaire
EP.....	Emission Point
EU.....	Emission Unit
gr./dscf.....	grains per dry standard cubic foot
IAC.....	Iowa Administrative Code
MACT.....	Maximum Achievable Control Technology
µg/m ³	Micrograms per Cubic Meter
MM BTU/ Hr.....	Million British Thermal Units per Hour
MSDS.....	Material Safety Data Sheet(s)
MVAC.....	Motor Vehicle Air Conditioner
NAICS.....	North American Industry Classification System
NESHAP.....	National Emission Standards for Hazardous Air Pollutants
NSPS.....	New Source Performance Standard
ppmv.....	parts per million by volume
psia.....	pounds per square inch absolute
lb./hr.....	pounds per hour
lb./MMBtu.....	pounds per Million British thermal units
SCC.....	Source Classification Codes
scfm.....	standard cubic feet per minute
sdcfm.....	standard dry cubic feet per minute
SIC.....	Standard Industrial Classification
TPY.....	Tons Per Year
USEPA.....	United States Environmental Protection Agency

Pollutants

PM.....	Particulate Matter
PM ₁₀	Particulate Matter ten microns or less in diameter
PM _{2.5}	Particulate Matter 2.5 microns or less in diameter
SO ₂	Sulfur dioxide
NO _x	Nitrogen Oxides
VOC(s).....	Volatile Organic Compound(s)
CO.....	Carbon Monoxide
HAP(s).....	Hazardous Air Pollutant(s)

I. Facility Description and Equipment List

Facility Name: ADM- Des Moines Soybean

Permit Number: 04-TV-020R2

Facility Description: Soybean Oil Mills (SIC 2075)

Soybean oil, refined, crushing mills (NAICS 311224)

Equipment List

Emission Point Number	Emission Unit Number	Emission Unit Description	Polk County / DNR Construction Permit Number
C06A	C06	Fly Ash Transfer	87-A-021-S1
C06B	C06	Fly Ash Transfer	09-A-413
C07	C07	Fly Ash Silo	87-A-022-S90
C09	C09	Standby Boiler	88-A-203-S4
C09A	C09	Standby Boiler By-Pass	09-A-414-S1
C10	C10	Boiler with Low NOx Burners, 240 MMBtu/hr	3794
C012	C012	Caterpillar Model 3412 Diesel Generator	1115 Modified #2
C013	C013	61.5 MMBtu Nebraska Boiler	2530
GP02	GP02	(2) – 500,000 bushel Bean Storage Tanks	Grandfathered
GP04A	GP04	Conveying to Process	1892 Modified #4
GP05A	GP05	Escher Wyss Conditioning / Dehulling	1407 Modified #4
GP06A	GP06A	Flaking Aspiration	1618 Modified #7
GP07	GP07	Conveying to Extractor	0103 Modified #4
GP09A	GP09	Extractor (Solvent Bubble)	07-A-1078-P2
	GP014	(2)-30,000 gallon Hexane Tanks	
	MP01	Desolventizer Toaster Dryer Cooler (DTDC)	
GP013	GP013	Natural Gas Emergency Lighting Generator	Exempt
GP015A	GP015A	Prep Building Central Vacuum System	0092 Modified
GP016	GP016	Crown Model VSC130 Soybean Heater	2343 Modified
GP019 A/B/C/D	GP019 A/B/C/D	4 Cell Extraction Evapco Cooling Tower	2823 Modified
GP021	GP021	Extraction – Diesel Fire Pump	4027
GP022	GP022	Extraction – Diesel Fire Pump	4028
GP023	GP023	Extraction – Diesel Fire Pump	4029
HR01A	GP011	Conveying to Aspirator / Whole Bean Aspiration	2531 Modified #2
	HR01A	Secondary Aspiration / Hull Gravity Tables	
HR02A	HR02A	Hull Grinding	0100 Modified #7
HR03	HR03	Pellet Cooler	2827 Modified #2
MP01	MP01	Crown Desolventizer Toaster Dryer Cooler (DTDC)	1626 Modified #5
MP02A	MP02A	Meal Grinding	0090 Modified #6
	MP03	Meal Transfer	
	MP04	Flowability Agent Silo	
	MP08B	Concrete Meal Storage Tank #2	
	HR04	Hull Pellet Storage Tank	

Emission Point Number	Emission Unit Number	Emission Unit Description	Polk County / DNR Construction Permit Number
MP06A	MP05	Meal Conveying	2128 Modified #2
	MP06	Meal Loading	
MP07A	MP07	Meal Rail Loadout	0105 Modified #4
MP010	MP010	Meal/ Hull Unloading Pit	1775
R01	R01	Filter Aid Receiving / Storage	0366
R02	R02	Bleaching Clay Receiving / Storage	0367
R03	R03	Slurry / Precoat Tanks	0414 Modified #2
R04	R04	Filter Aid / Bleaching Clay Day Bins	1767
R06	R06	3 Cell Refinery Cooling Tower	2134
R08	R08	Detroit Diesel Allison Diesel Fire Pump at Refinery	3411 Modified
R09	R09	Refinery – Steam Generator	4006
U03	U03	Rail Receiving # 1 and Conveying	0802 Modified
U03F	U03	Rail Receiving #1 Fugitive Emissions	0802 Modified
U05, U05A	U05	Grain Storage – 4 West Bean Tanks	2595
U07	U01	West Truck Truck Dump	2235 Modified
	U02	East Truck Truck Dump	
	U04	Grain Conveyor	
U07F	U01, U02	Truck Dump Fugitive Emissions	2235 Modified
U08	BEN	Haul Roads- Truck Traffic Fugitive Emissions: Soybean Receiving	2828 Modified
	MEL	Haul Roads- Truck Traffic Fugitive Emissions: Meal/ Hull Truck Loadout	
	OIL	Haul Roads- Truck Traffic Fugitive Emissions: Oil Loadout	
	HEX	Haul Roads- Truck Traffic Fugitive Emissions: Hexane Receiving	
	FLO	Haul Roads- Truck Traffic Fugitive Emissions: Flowability Agent Receiving	

Insignificant Equipment List

Insignificant Emission Unit Number	Insignificant Emission Unit Description
IA3	Refinery Bag Unloading System
IA5	(2) 15,000 Gallon No. 2 Fuel Oil Tanks
IA6	3,196 Gallon Dilute Acid Tank
IA7	10,000 Gallon Concentrated Acid Tank
IA8	Yard Waste Hopper
IA10	790 Gallon Primary Boiler Lube Oil Tank
IA11	15,863 Gallon Wastewater Tank
IA12	Vent Off Sewer Line
IA14	CoGen Cooling Tower
IA16	Hot Gas Generator
IA17	(2) 15,000 Gallon Cogen No. 2 Fuel Oil Tanks
IA18	(1) 300 Gallon Cogen Cat No. 2 Fuel Oil Tank

II. Plant-Wide Conditions

Facility Name: ADM- Des Moines Soybean Processing Plant
Permit Number: 04-TV-020-R2

Permit conditions are established in accord with 567 Iowa Administrative Code rule 24.108. When 567 IAC as amended May 15, 2024, and cited in this permit becomes State Implementation Plan (SIP) approved, it will supersede 567 IAC as amended February 8, 2023. Prior to May 15, 2024, all Title V rule citations in this Title V permit were found and cited in 567 IAC Chapter 24. During the period from May 15, 2024, to the date that 567 IAC as amended May 15, 2024, is approved into the SIP, both 567 IAC as amended May 15, 2024 and 567 IAC as amended February 8, 2023 form the legal basis for the applicable requirements included in this permit. A crosswalk showing the citation changes is attached to this permit in Appendix 2.

Permit Duration

The term of this permit is: Five (5) years
Commencing on: June 16, 2026
Ending on: June 15, 2031

Amendments, modifications and reopenings of the permit shall be obtained in accordance with 567 Iowa Administrative Code rules 24.110 - 24.114. Permits may be suspended, terminated, or revoked as specified in 567 Iowa Administrative Code Rules 24.115.

Emission Limits

Unless specified otherwise in the Source Specific Conditions, the following limitations and supporting regulations apply to all emission points at this plant:

Opacity (visible emissions): <40% opacity
Authority for Requirement: 567 IAC 23.3(2)"d"
Polk County Board of Health Rules and Regulations Chapter V, Article IV, Section 5-9

Sulfur Dioxide (SO₂): 500 parts per million by volume
Authority for Requirement: 567 IAC 23.3(3)"e"
Polk County Board of Health Rules and Regulations Chapter V,
Article IX, Section 5-27

Particulate Matter:

(1) General. The emission standards contained in this article shall apply to each source operation unless performance standard for the process is specified in Section 5-16, in which case the performance standard shall apply.

(2) Compliance with other requirements. For the purposes of this chapter, Compliance with other requirements, as set forth in 567 IAC 21.9(455B), is adopted by reference.

(3) Particulate matter. No person shall cause or allow the emission of particulate matter from any source in excess of the emission standards specified in Section 5-14, except as provided in Sections 5-17, 5-17.1, 5-18, 5-59, 5-68.1, 5-69.1, 5-70.1, and 5-71.1 and 567 – Chapter 24.

For sources constructed, modified or reconstructed prior to July 21, 1999, the emission of particulate matter from any process shall not exceed the amount determined from Table I, or amount specified in a permit if based on an emission standard of 0.1 grain per standard cubic foot of exhaust gas or established from standards provided in 23.1(455B) and 23.4(455B).

Authority for Requirement: 567 IAC 23.3(2)"a"

Polk County Board of Health Rules and Regulations Chapter V, Article VI, Section 5-14.

Combustion for indirect heating. Emissions of particulate matter from the combustion of fuel for indirect heating or for power generation shall be limited by the ASME Standard APS-1, Second Edition, November 1968, "Recommended Guide for the Control of Dust Emission—Combustion for Indirect Heat Exchangers." For the purpose of this paragraph, the allowable emissions shall be calculated from equation (15) in that standard, with $C_{max} = 50$ micrograms per cubic meter. The maximum ground level dust concentrations designated are above the background level. For plants with 4,000 million Btu/hour input or more, the "a" factor shall be 1.0. In plants with less than 4,000 million Btu/hour input, appropriate "a" factors, less than 1.0, shall be applied. Pertinent correction factors, as specified in the standard, shall be applied for installations with multiple stacks. However, for fuel-burning units in operation on January 13, 1976, the maximum allowable emissions calculated under APS-1 for the facility's equipment configuration on January 13, 1976, shall not be increased even if the changes in the equipment or stack configuration would otherwise allow a recalculation and a higher maximum allowable emission under APS-1.

Authority for Requirement: 567 IAC 23.3(2)"b"(2)

Polk County Board of Health Rules and Regulations Chapter V, Article VI, Section 5-14(3)

Fugitive Dust:

(1) Attainment and unclassified areas. A person shall take reasonable precautions to prevent particulate matter from becoming airborne in quantities sufficient to cause a nuisance as defined in Iowa Code section 657.1 when the person allows, causes or permits any materials to be handled, transported or stored or a building, its appurtenances or a construction haul road to be used, constructed, altered, repaired or demolished, with the exception of farming operations or dust generated by ordinary travel on unpaved roads. Ordinary travel includes routine traffic and road maintenance activities such as scarifying, compacting, transporting road maintenance surfacing material, and scraping of the unpaved public road surface. All persons, with the above exceptions, shall take reasonable precautions to prevent the discharge of visible emissions of fugitive dusts beyond the lot

line of the property on which the emissions originate. The public highway authority shall be responsible for taking corrective action in those cases where said authority has received complaints of or has actual knowledge of dust conditions that require abatement pursuant to this subrule. Reasonable precautions may include but not be limited to the following procedures:

- a. Use, where practical, of water or chemicals for control of dust in the demolition of existing buildings or structures, construction operations, the grading of roads or the clearing of land;
- b. Application of suitable materials, such as but not limited to asphalt, oil, water or chemicals on unpaved roads, material stockpiles, race tracks and other surfaces which can give rise to airborne dusts.
- c. Installation and use of containment or control equipment, to enclose or otherwise limit the emissions resulting from the handling and transfer of dusty materials, such as but not limited to grain, fertilizer or limestone.
- d. Covering, at all times when in motion, open-bodied trucks transporting materials likely to give rise to airborne dusts;
- e. The prompt removal of earth or other material from paved streets onto which earth or other material has been transported by trucking or earth-moving equipment, erosion by water or other means.

Authority for Requirement: 567 IAC 23.3(2)"c"

Polk County Board of Health Rules and Regulations Chapter V, Article IX, Section 5-23

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

NESHAP:

The facility is subject to subpart GGGG-National Emission Standards for Hazardous Air Pollutants: Solvent Extraction for Vegetable Oil Production, promulgated. The subpart is linked in its entirety in Appendix 1 of this Permit.

Authority for Requirement: 40 CFR Part 63 Subpart GGGG,
567 IAC 23.1(4) "cg"

Polk County Board of Health Rules and Regulations
Chapter V, Article VIII, Section 5-20

The facility operates a diesel fired Caterpillar Limited Use Generator (EU C012) and a natural gas fired Emergency Lighting Generator (EU GP013). This equipment is subject to National Emission Standard for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion [40 CFR Part 63 Subpart ZZZZ]. The subpart is linked in its entirety in Appendix 1 of this Permit.

Authority for Requirement: 40 CFR Part 63 Subpart ZZZZ.

567 IAC 23.1(4) "cz"

Polk County Board of Health Rules and Regulations

The facility operates a 175 MMBtu/hr steam generator combusting natural gas or No. 2 fuel oil (EU C09), a 240 MMBtu/hr Boiler, with Low NOx Burners: (EU C10 / CE C10 / EP C10), a 61.5 MMBtu Nebraska Model NS-E-58 natural gas fired Boiler #4: (EP C013 / EU C013). This equipment is subject to the National Emission Standards for Hazardous Air Pollutants for Major Sources: Industrial, Commercial, and Institutional Boilers and Process Heaters [40 CFR Part 63 Subpart DDDDD]. The subpart will be linked in its entirety in Appendix 1 of the Title V Permit.

Authority for Requirement: 40 CFR Part 63 Subpart DDDDD.

567 IAC 23.1(4) "dd"

Polk County Board of Health Rules and Regulations

Chapter V, Article VIII, Section 5-20

III. Emission Point-Specific Conditions

Facility Name: ADM - Des Moines Soybean Processing Plant
Permit Number: 04-TV-020R2

Emission Point ID Number: C06A - Fly Ash Transfer

Associated Equipment

Associated Emission Unit ID Number: C06
Emissions Control Equipment ID Number: C06A
Emissions Control Equipment Description: Cyclone with fabric filter

Emission Unit vented through this Emission Point: C06
Emission Unit Description: Fly Ash Transfer
Raw Material/Fuel: Fly Ash
Rated Capacity: 2.5 Tons/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from each emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: 0%
Authority for Requirement: DNR Construction Permit 87-A-021-S1

Pollutant: PM
Emission Limit: 0.02 gr/dscf
Authority for Requirement: DNR Construction Permit 87-A-021-S1

Pollutant: PM₁₀
Emission Limit: 0.26 lb/hr
Authority for Requirement: DNR Construction Permit 87-A-021-S1

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. This emission point shall not be operated at the same time as EP C06B.
2. The owner or operator shall record the time and date that emissions are switched between EP C06A and EP C06B.

Authority for Requirement: DNR Construction Permit 87-A-021-S1

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 37.2

Stack Diameter (inches): 7

Stack Exhaust Flow Rate (acfm): 1,540

Stack Temperature (°F): 165

Discharge Style: Obstructed Vertical

Authority for Requirement: DNR Construction Permit 87-A-021-S1

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP C06A shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity >0% is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request. Emission observations will not be required when EU C06 is not operated for an entire week. Date and time of equipment shutdown and startup shall be noted in the equipment log book.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source’s compliance with the applicable requirements.

The data pertaining to the plan must be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility’s implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: C06B - Fly Ash Transfer

Associated Equipment

Associated Emission Unit ID Number: C06
Emissions Control Equipment ID Number: C06B
Emissions Control Equipment Description: Cyclone with fabric filter

Emission Unit vented through this Emission Point: C06
Emission Unit Description: Fly Ash Transfer
Raw Material/Fuel: Fly Ash
Rated Capacity: 2.5 Tons/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from each emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: 0%
Authority for Requirement: DNR Construction Permit 09-A-413

Pollutant: PM
Emission Limit: 0.02 gr/dscf
Authority for Requirement: DNR Construction Permit 09-A-413

Pollutant: PM₁₀
Emission Limit: 0.26 lb/hr
Authority for Requirement: DNR Construction Permit 09-A-413

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. This emission point shall not be operated at the same time as EP C06A.
2. The owner or operator shall record the time and date that emissions are switched between EP C06A and EP C06B.

Authority for Requirement: DNR Construction Permit 09-A-413

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 37.2

Stack Diameter (inches): 7

Stack Exhaust Flow Rate (acfm): 1,540

Stack Temperature (°F): 165

Discharge Style: Obstructed Vertical

Authority for Requirement: DNR Construction Permit 09-A-413

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP C06A shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity >0% is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request. Emission observations will not be required when EU C06 is not operated for an entire week. Date and time of equipment shutdown and startup shall be noted in the equipment log book.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the applicable requirements.

The data pertaining to the plan must be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: C07 - Fly Ash Transfer Silo

Associated Equipment

Associated Emission Unit ID Number: C07
Emissions Control Equipment ID Number: C07
Control Equipment Description: Flex-kleen Baghouse Model 58-BVB-C9-IIG

Emission Unit vented through this Emission Point: C07
Emission Unit Description: Fly Ash Storage
Raw Material/Fuel: Fly Ash
Rated Capacity: 2.52 tons/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: 0%
Authority for Requirement: DNR Construction Permit 87-A-022-S90

Pollutant: PM
Emission Limit: 0.08 lb/hr, 0.35 TPY
Authority for Requirement: DNR Construction Permit 87-A-022-S90

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP C07 shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity >0% is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request. Emission observations will not be required when EU C07 is not operated for an entire week. Date and time of equipment shutdown and startup shall be noted in the equipment log book.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source’s compliance with the applicable requirements.

The data pertaining to the plan must be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility’s implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 24.108(3)

**Emission Point ID Numbers: C09 - Standby Boiler
C09A - Standby Boiler (Bypass)**

Associated Equipment

EP	EU	Emission Unit Description	Raw Material	Rated Capacity	DNR Construction Permit
C09	C09	Standby boiler	Natural gas	175 MM BTU/ hr; 193,000 ft ³ /hr	88-A-203-S4
C09A					09-A-414-S1

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from each emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit: 20%⁽¹⁾

Authority for Requirement: DNR Construction Permits 88-A-203-S4 & 09-A-414-S1
567 IAC 23.3(2) "d"

⁽¹⁾ An exceedance of the indicator opacity of "No Visible Emissions (No VE)" will require the owner or operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the Department may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: PM

Emission Limits: 10.9 lb./hr ; 0.2 lb/MMBtu

Authority for Requirement: DNR Construction Permits 88-A-203-S4 & 09-A-414-S1
567 IAC 23.3(2) "b"(3)

Pollutant: PM₁₀

Emission Limit: 1.3 lb/hr

Authority for Requirement: DNR Construction Permits 88-A-203-S4 & 09-A-414-S1

Pollutant: SO₂

Emission Limits: 0.1 lb/hr, 500 ppm_v

Authority for Requirement: DNR Construction Permits 88-A-203-S4 & 09-A-414-S1
567 IAC 23.3(3) "e"
Polk County Board of Health Rules and Regulations
Chapter V, Article IX, Section 5-27(5)

Pollutant: NO_x
Emission Limit: 32.6 lb/hr
Authority for Requirement: DNR Construction Permits 88-A-203-S4 & 09-A-414-S1

Pollutant: CO
Emission Limit: 4.45 lb/hr
Authority for Requirement: DNR Construction Permits 88-A-203-S4 & 09-A-414-S1

NESHAP

This equipment is subject to the National Emission Standards for Hazardous Air Pollutants for Major Sources: Industrial, Commercial, and Institutional Boilers and Process Heaters [40 CFR Part 63 Subpart DDDDD].

Authority for Requirement: 40 CFR Part 63 Subpart DDDDD

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. This emission unit (EU C09) is limited to firing on natural gas.
2. The owner or operator shall operate and maintain this emission unit (EU C09) in accordance with manufacturer's specifications. The owner or operator shall maintain a log of all inspections and maintenance activities performed on the emission unit (EU C09). This log shall include, but is not limited to:
 - a. The date and time any inspection and/or maintenance was performed on the emission unit (EU C09);
 - b. Any issues identified during the inspection and the date each issue was resolved;
 - c. Any issues addressed during the maintenance activities and the date each issue was resolved;
 - d. Identification of the staff member performing the maintenance or inspection.

Authority for Requirement: DNR Construction Permits 88-A-203-S4 & 09-A-414-S1

Emission Point Characteristics

Each emission point shall conform to the specifications listed below.

Stack Height (feet): 44.8
Stack Diameter (inches): 72
Stack Exhaust Flow Rate (scfm): 50,000
Stack Temperature (°F): 500
Discharge Style: Unobstructed Vertical
Authority for Requirement: DNR Construction Permits 88-A-203-S4 & 09-A-414-S1

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values

stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: C10 - Boiler

Associated Equipment

Emissions Control Equipment ID Number: C10
Emissions Control Equipment Description: Low NOx Burners
Continuous Emissions Monitors ID Numbers: C10

Emission Unit vented through this Emission Point: C10
Emission Unit Description: Boiler
Raw Material/Fuel: Natural gas combustion or #2 Fuel Oil
Rated Capacity: 240 MMBtu/hr; 235,295 scf/hr natural gas or 1,715 gal/hr #2 fuel oil.

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit: <20%⁽¹⁾

Authority for Requirement: Polk County Construction Permit Number 3794
Polk County Board of Health Rules and Regulations
Chapter V, Section 5-9
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-16(14)
567 IAC 23.1(2)"ccc"
40 CFR Part 60 Subpart Db

⁽¹⁾ In accordance with 40 CFR §60.43b(f), no owner or operator of an affected facility that combusts coal, oil, wood, or mixtures of these fuels with any other fuels shall cause to be discharged into the atmosphere any gases that exhibit greater than 20 percent opacity (6-minute average), except for one 6-minute period per hour of not more than 27 percent opacity.

Pollutant: PM - Federal

Emission Limit: 0.030 lb/MMBtu

Authority for Requirement: Polk County Construction Permit Number 3794
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-16(14)
567 IAC 23.1(2)"ccc"
40 CFR Part 60 Subpart Db

Pollutant: PM - State
Emission Limit: 0.6 lb/MMBtu
Authority for Requirement: Polk County Construction Permit Number 3794
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-15(b)
567 IAC 23.3(2) "b"

Pollutant: PM₁₀
Emission Limits: 0.96 lb/hr (natural gas);
5.66 lb/hr (No. 2 fuel oil)
Authority for Requirement: Polk County Construction Permit Number 3794

Pollutant: SO₂
Emission Limits: 500 PPM_v (natural gas) ;
0.5 lb/MMBtu (No. 2 fuel oil)
Authority for Requirement: Polk County Construction Permit Number 3794
Polk County Board of Health Rules and Regulations
Chapter V, Article IX, Section 5-27(5)
Polk County Board of Health Rules and Regulations
Chapter V, Article IX, Section 5-27(2)

Pollutant: NO_x
Emission Limits: 8.64 lb/hr (natural gas);
39.40 TPY (total)
Authority for Requirement: Polk County Construction Permit Number 3794

Pollutant: NO_x
Emission Limits: 0.20 lb/MMbtu
Authority for Requirement: Polk County Construction Permit Number 3794
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-16(14)
567 IAC 23.1(2)"ccc"
40 CFR Part 60 Subpart Db

Pollutant: CO
Emission Limit: 8.88 lb/hr
Authority for Requirement: Polk County Construction Permit Number 3794

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

NSPS

The facility shall comply with all applicable conditions of 40 CFR 60 Subpart Db-*Standards of Performance for Industrial-Commercial-Institutional Steam Generating Units*.

1. The Boiler (EU C10) is limited to firing on natural gas and distillate fuel oil.
 - a. The owner or operator shall be limited to one hundred twenty (120) hours of distillate fuel oil usage for the boiler (EU C10) per twelve (12) month period rolled and totaled monthly.
 - b. The facility shall record the total hours of fuel oil combusted on a monthly basis. Said log shall include the 12-month rolling total, rolled monthly.
 - c. The owner or operator shall combust only fuel oil with a sulfur content of 0.05% or less by weight in the boiler. Fuel supplier certification of sulfur content shall be kept on site for each delivery of fuel oil purchased.

2. In accordance with §60.49b(g), the owner or operator of an affected facility subject to the NO_x standards under §60.44b shall maintain records of the following information for each steam generating unit operating day:
 - a. Calendar date;
 - b. The average hourly NO_x emission rates (in ng/J or lb/MMBTU heat input and expressed as NO₂) measured or predicted;
 - c. The thirty (30) day average NO_x emission rates (ng/J or lb/MMBTU heat input) calculated at the end of each steam generating unit operating day from the measured or predicted hourly nitrogen oxide emission rates for the preceding thirty (30) steam generating unit operating days.
 - d. Identification of the steam generating unit operating days when the calculated thirty (30) day average NO_x emission rates are in excess of the NO_x emission standards under 40 CFR §60.44b, with the reasons for such excess emissions as well as a description of corrective actions taken;
 - e. Identification of the steam generating unit operating days for which pollutant data have not been obtained, including reasons for not obtaining sufficient data and a description of corrective actions taken;
 - f. Identification of the times when emissions data have been excluded from the calculation of average emission rates and the reasons for excluding data;
 - g. Identification of "F" factor used for calculations, method of determination, and the type of fuel combusted;
 - h. Identification of the times when the pollutant concentration exceeded full span of the CEMS;
 - i. Description of any modifications to the CEMS that could affect the ability of the CEMS to comply with Performance Specification 2 or 3; and
 - j. Results of daily CEMS drift tests and quarterly accuracy assessments as

required under 40 CFR Appendix F, Procedure 1.

3. In accordance with §60.49b(r)(1), the owner or operator shall obtain and maintain at the affected facility fuel receipts from the fuel supplier that certify that the gaseous fuel meets the definition of natural gas as defined in §60.41b and the applicable sulfur.

Authority for Requirement: Polk County Construction Permit Number 3794
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-16(14)
567 IAC 23.1(2)"ccc"
40 CFR Part 60 Subpart Db

NESHAP

This equipment is subject to the National Emission Standards for Hazardous Air Pollutants for Major Sources: Industrial, Commercial, and Institutional Boilers and Process Heaters [40 CFR Part 63 Subpart DDDDD].

Authority for Requirement: 40 CFR Part 63 Subpart DDDDD

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 115

Stack Diameter (inches): 60

Stack Exhaust Flow Rate (scfm): 35,000

Stack Temperature (°F): 300

Discharge Style: Unobstructed Vertical

Authority for Requirement: Polk County Construction Permit Number 3794

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Continuous Emissions Monitoring:

Pollutant - NO_x

Operational Specifications –

- In accordance with 40 CFR §60.48b(b), the owner or operator shall install, calibrate, maintain, and operate a continuous emission monitoring system (CEMS) and record the output of the system, for measuring nitrogen oxide (NO_x) emissions.

- The system shall be designed to meet the 40 CFR 60, Appendix B, Performance Specification 2 (PS2) and Performance Specification 6 (PS6) requirements. The specifications of 40 CFR Appendix F (Quality Assurance/Quality Control) shall apply.
- This monitor shall also be used to demonstrate compliance with the non-NSPS emission standards in this permit.

Pollutant - O₂ or CO₂

Operational Specifications –

- In accordance with 40 CFR §60.48b(b), the owner or operator shall install, calibrate, maintain, and operate a CEMS and record the output of the system, for measuring the oxygen (O₂) or carbon dioxide (CO₂) content of the flue gases at each location where NO_x emissions are monitored.
- The system shall be designed to meet the 40 CFR 60, Appendix B, Performance Specification 3 (PS3) and Performance Specification 6 (PS6) requirements. The specifications of 40 CFR Appendix F (Quality Assurance/Quality Control) shall apply.
- This monitor shall also be used to demonstrate compliance with the non-NSPS emission standards in this permit.

Flowmeter

Operational Specifications –

- The owner or operator shall install, certify, operate, and maintain a continuous flow monitoring system meeting the requirements of 40 CFR 60, Appendix B, Performance Specification 6 and 40 CFR 60, Appendix F, Procedure 1. In addition, the owner or operator shall record the output of the system, for measuring the volumetric flow of exhaust gases discharged to the atmosphere.

Date of Most Recent System Calibration and Quality Assurance – 7/10/2024

Reporting & Record keeping –

- A. Appendix F requirements shall be supplemented with a quarterly notice to the Department with the dates of the quarterly cylinder gas audits (CGA) and annual relative accuracy test audit (RATA). Annual RATAs and quarterly CGAs are required to be conducted on all CEMS and flowmeters required by this permit. The results shall be reported in units of the standards.

If requested by the Department, the owner/operator shall coordinate the quarterly cylinder gas audits with the Department to afford the Department the opportunity to observe these audits. The relative accuracy test audits shall be coordinated with the Department.

- B. The CEMS required in Condition A. (above) for NO_x and either O₂ or CO₂ shall be operated and the data recorded during all periods of operation including periods of

startup, shutdown, malfunction or emergency conditions, except for CEMS breakdowns, repairs, calibration checks, and zero and span adjustments.

- C. The following data requirements shall apply to all CEMS for non-NSPS emission standards in this permit:
- (1) The CEMS required by this permit shall be operated and data recorded during all periods of operation of the emission unit except for CEM breakdowns and repairs. Data is recorded during calibration checks, and zero and span adjustments.
 - (2) The 1-hour average NO_x and CO₂ emission rates measured by the CEMS and flow measured by the flowmeter required by this permit shall be used to calculate compliance with the emission standards of this permit. At least 2 data points must be used to calculate each 1-hour average.
 - (3) For each hour of missing emission data (NO_x or CO₂), the owner or operator shall substitute data by:
 - (i) If the quarterly monitor data availability is equal to or greater than 95.0%, the owner or operator shall calculate substitute data by means of the automated data acquisition and handling system for each hour of each missing data period according to the following procedures:
 - (a) For the missing data period less than or equal to 24 hours, substitute the average of the hourly concentrations recorded by a pollutant concentration monitor for the hour before and the hour after the missing data period.
 - (b) For a missing data period greater than 24 hours, substitute the greater of:
 - The 90th percentile hourly concentration recorded by a pollutant concentration monitor during the previous 720 quality-assured monitor operating hours; or
 - The average of the hourly concentrations recorded by a pollutant concentration monitor for the hour before and the hour after the missing data period.
 - (ii) If the quarterly monitor data availability is at least 90.0% but less than 95.0%, the owner or operator shall calculate substitute data by means of the automated data acquisition and handling system for each hour of each missing data period according to the following procedures:
 - (a) For a missing data period of less than or equal to 8 hours, substitute the average of the hourly concentrations recorded by a pollutant concentration monitor for the hour before and the hour after the missing data period.
 - (b) For the missing data period of more than 8 hours, substitute the greater of:
 - The 95th percentile hourly pollutant concentration recorded by a pollutant concentration monitor during the previous 720 quality-assured monitor operating hours; or
 - The average of the hourly concentrations recorded by a pollutant concentration monitor for the hour before and the hour after the missing data period.

(iii) If the quarterly monitor data availability is less than 90.0%, the owner or operator shall obtain actual emission data by an alternate testing or monitoring method approved by the Department.

Authority for Requirement: Polk County Construction Permit Number 3794
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-16(14)
567 IAC 23.1(2)"ccc"
40 CFR Part 60 Subpart Db

EP C10 shall be visually checked for observable emissions once every week by a designated observer whenever #2 Fuel Oil is combusted. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer's signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity $\geq 20\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: C012 – Caterpillar Diesel Generator

Associated Equipment

Emissions Control Equipment ID Number: C012

Emissions Control Equipment Description: Johnson Matthey HAPGuard CO Catalyst

Emission Unit vented through this Emission Point: C012

Emission Unit Description: Caterpillar Model 3412 Diesel Generator

Raw Material/Fuel: #2 Fuel Oil

Rated Capacity: 600 kW (896 HP)

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit: <20 %

Authority for Requirement: Polk County Construction Permit Number 1115 Modified #2
Polk County Board of Health Rules and Regulations Chapter
V, Article IV, Section 5-9

Pollutant: PM

Emission Limits: 0.42 lb/hr, 0.11 TPY, 0.10 gr/dscf

Authority for Requirement: Polk County Construction Permit Number 1115 Modified #2
567 IAC 23.3(2)"a"
Polk County Board of Health Rules and Regulations Chapter
V, Article VI, Section 5-14(3)

Pollutant: PM₁₀

Emission Limits: 0.35 lb/hr, 0.09 TPY

Authority for Requirement: Polk County Construction Permit Number 1115 Modified #2

Pollutant: PM_{2.5}

Emission Limits: 0.35 lb/hr, 0.09 TPY

Authority for Requirement: Polk County Construction Permit Number 1115 Modified #2

Pollutant: SO₂

Emission Limits: 0.009 lb/hr, 0.002 TPY, 0.5 lb/MM BTU

Authority for Requirement: Polk County Construction Permit Number 1115 Modified #2
Polk County Board of Health Rules and Regulations Chapter
V, Article IX, Section 5-27(5)

Pollutant: NOx
Emission Limit: 19.51 lb/hr, 4.88 TPY
Authority for Requirement: Polk County Construction Permit Number 1115 Modified #2

Pollutant: VOC
Emission Limit: 0.50 lb/hr, 0.13 TPY
Authority for Requirement: Polk County Construction Permit Number 1115 Modified #2

Pollutant: CO
Emission Limit: 4.42 lb/hr, 0.22 TPY, 23 ppmvd or less at 15% O2, or reduce CO emissions by 70% or more
Authority for Requirement: Polk County Construction Permit Number 1115 Modified #2
40 CFR §63.6600(d), subpart ZZZZ
567 IAC 23.1(4)"cz"
Polk County Board of Health Rules and Regulations Chapter

V, Article

VIII, Section 5-20

NESHAP

This equipment is subject to the National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines (RICE NESHAP) [40 CFR Part 63 Subpart ZZZZ].

Authority for Requirement: 40 CFR Part 63 Subpart ZZZZ
567 IAC 23.1(4)"cz"
Polk County Board of Health Rules and Regulations Chapter

V, Article

VIII, Section 5-20

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

Hours of operation:

1. Each calendar year, EU C012 shall operate as a limited use generator and follow the requirements of Scenario #1 until it has operated 100 hours. Upon exceeding 100 hours of operation in a calendar year, the unit must operate as a non-emergency unit and operate in accordance of Scenario #2. In any subsequent calendar year, if the generator operates for less than 100 hours the unit would revert back to the limited-use category and the Scenario #1 requirements.
2. Prior to exceeding 100 hours in a calendar year for the first time, the owner/operator shall have completed an initial performance test as required by §63.6610(a).
3. The owner/operator shall comply with the Carbon Monoxide (CO) emission limits of 4.42 lb/hr and 0.22 TPY; until such time that an initial performance test is

required. Once the initial performance test is completed the owner/operator shall comply with the emission limits of Carbon Monoxide (CO) determined by the emission test results.

Operational Limits Scenario #1:

1. This equipment is subject to the National Standards for Hazardous Air Pollutants for Stationary Internal Combustion Engines (RICE NESHAP)[40 CFR Part 63 Subpart ZZZZ]. Authority for Requirement; 40 CFR Part 63 Subpart ZZZZ.
2. Per § 63.6590 (3)(iv) as an existing limited use stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, emission unit C012 does not have to meet the requirements of subpart ZZZZ or subpart A, including initial notification requirements.
3. Emission unit C012 shall be operated in a manner consistent with the definition of a limited use stationary RICE as defined by § 63.6675.

Operational Limits Scenario #2:

NESHAP Requirements:

1. The owner/operator shall comply with all applicable requirements of 40 CFR 63 Subpart ZZZZ – National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines.
2. Per §63.6590 (a)(1)(i); the affected source is an existing stationary RICE with a site rating of more than 500 hp located at a major source of HAP emissions.
3. Per §63.6600(d); the owner/operator of an existing non-emergency stationary CI RICE with a site rating of more than 500 HP located at a major source of HAP emissions, must comply with the emission limitations in Table 2c to this subpart and the operating limitations in Table 2b to this subpart which apply to you.
4. Per §63.6604(a); the owner/operator must use diesel fuel that meets the requirements in 40 CFR 80.510(b) for nonroad diesel fuel.
5. Per §63.6605(a); the owner/operator must be in compliance with the emission limitations, operating limitations, and other requirements in this subpart that apply to you at all times.
6. Per §63.6605(b); At all times you must operate and maintain the affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions.
7. Per §63.6610(a); You must conduct the initial performance test or other initial compliance demonstrations in Table 4 to this subpart that apply to you within 180 days after the compliance date that is specified for your stationary RICE in §63.6595 and according to the provisions in §63.7(a)(2).
8. Per §63.6615; You must conduct subsequent performance tests as specified in Table 3 of this subpart.
9. Each performance test shall be conducted in accordance with the procedures of §63.6620.
10. The owner/operator shall comply with the applicable monitoring, installation, collection, operation, and maintenance requirements of §63.6625.
11. The owner/operator shall demonstrate initial compliance with the emission limitations, operating limitations, and other requirements as required by §63.6630.

12. The owner/operator shall monitor and collect data to demonstrate continuous compliance with the emission limitations, operating limitations, and other requirements as required by §63.6635.
13. The owner/operator shall demonstrate continuous compliance with the emission limitations, operating limitations, and other requirements per the procedures of §63.6640.
14. The owner/operator shall submit the notifications required by §63.6645.
15. The owner/operator shall submit each required report in accordance with §63.6650.
16. The owner/operator shall keep the records required by §63.6655 in accordance with the requirements of §63.6660.
17. Per 40 CFR 63 subpart ZZZZ Table 2C(5): Non-Emergency, non-black start CI stationary CI RICE>500 HP must:
 - a. Limit concentration of CO in the stationary RICE exhaust to 23 ppmvd or less at 15% O₂; or
 - b. Reduce CO emissions by 70% or more.
18. Per 40 CFR 63 subpart ZZZZ Table 2B(2): Existing CI stationary RICE > 500 HP complying with the requirement to limit or reduce the concentration of CO in the stationary RICE exhaust and using an oxidation catalyst shall:
 - a. maintain your catalyst so that the pressure drop across the catalyst does not change by more than 2 inches of water from the pressure drop across the catalyst that was measured during the initial performance test; and
 - b. maintain the temperature of your stationary RICE exhaust so that the catalyst inlet temperature is greater than or equal to 450 °F and less than or equal to 1350 °F.

Work practice standards:

1. Fuel sulfur content shall not exceed 0.05% by weight. Fuel supplier certification shall be obtained and maintained on site for each purchase for a period of five years and shall be made available to representatives of this department upon request.

Reporting & Record keeping:

1. A non-resettable totalizing hour meter shall be installed on the unit
2. Operation shall be limited to five hundred (500) hours per twelve (12) month period rolled and totaled monthly.
3. Monthly readings shall be taken and logged on site. Said log shall include the 12 month rolling total, rolled monthly.
4. All records shall be kept on site for a minimum period of five years and be made available to Polk County Air Quality personnel upon request

Authority for Requirement: Polk County Construction Permit Number 1115 Modified #2
 40 CFR §63.6600(d), subpart ZZZZ
 567 IAC 23.1(4)"cz"
 Polk County Board of Health Rules and Regulations Chapter

V, Article

VIII, Section 5-20

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 21

Stack Diameter (inches): 10

Stack Exhaust Flow Rate (scfm): 5,018

Stack Temperature (°F): 907

Discharge Style: Vertical, unobstructed

Authority for Requirement: Polk County Construction Permit Number 1115 Modified #2

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP C012 shall be visually checked for observable emissions once every month by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity $\geq 20\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request. The logbook shall be notated with a negative declaration of operation at the end of each calendar month during which no operation occurs.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: C013 - Nebraska Model NS-E-58 Boiler #4

Associated Equipment

Emission Unit vented through this Emission Point: C013
Emission Unit Description: Nebraska Model NS-E-58 Boiler #4
Raw Material/Fuel: Natural Gas
Rated Capacity: 61.5 MM BTU

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <20 %
Authority for Requirement: Polk County Construction Permit Number 2530

Pollutant: PM
Emission Limits: 0.46 lb/hr, 2.00 TPY, 0.10 gr/dscf, 0.6 lb/MMbtu
Authority for Requirement: Polk County Construction Permit Number 2530
567 IAC 23.3 (2) "b"
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-15(b)

Pollutant: PM₁₀
Emission Limits: 0.46 lb/hr, 2.00 TPY, 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 2530

Pollutant: SO₂
Emission Limits: 0.04 lb/hr, 0.16 TPY, 500 ppm
Authority for Requirement: Polk County Construction Permit Number 2530
567 IAC 23.3 (3)"e"
Polk County Board of Health Rules and Regulations
Chapter V, Article IX, Section 5-27(5)

Pollutant: NO_x
Emission Limits: 6.00 lb/hr, 26.28 TPY
Authority for Requirement: Polk County Construction Permit Number 2530

Pollutant: VOC
Emission Limits: 0.33 lb/hr, 1.45 TPY

Authority for Requirement: Polk County Construction Permit Number 2530

Pollutant: CO

Emission Limits: 5.04 lb/hr, 22.08 TPY

Authority for Requirement: Polk County Construction Permit Number 2530

NESHAP

This equipment is subject to the National Emission Standards for Hazardous Air Pollutants for Major Sources: Industrial, Commercial, and Institutional Boilers and Process Heaters [40 CFR Part 63 Subpart DDDDD].

Authority for Requirement: 40 CFR Part 63 Subpart DDDDD

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 40

Stack Diameter (inches): 41

Stack Exhaust Flow Rate (scfm): 9,660

Stack Temperature (°F): 420

Discharge Style: Unobstructed Vertical

Authority for Requirement: Polk County Construction Permit Number 2530

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: GP02 -2 - 500,000 bushel bean storage tanks

Associated Equipment

Emission Unit vented through this Emission Point: GP02
Emission Unit Description: 2 - 500,000 bushel bean storage tanks
Raw Material/Fuel: Soybeans
Rated Capacity: 960 Tons/hour

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <40%
Authority for Requirement: Polk County Board of Health Rules and Regulations
Chapter V, Section 5-9

Pollutant: PM
Emission Limit: 0.10 gr/dscf
Authority for Requirement: 567 IAC 23.4(7)
Polk County Board of Health Rules and Regulations
Chapter V, Section 5-16(7)

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: GP04A - Conveying to Process

Associated Equipment

Associated Emission Unit ID Numbers: GP04
Emissions Control Equipment ID Number: GP04A
Emissions Control Equipment Description: MAC Elevator Baghouse

Emission Unit vented through this Emission Point: GP04
Emission Unit Description: Conveying to Process
Raw Material/Fuel: Soybeans
Rated Capacity: 250 Tons/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit: 0%

Authority for Requirement: Polk County Construction Permit Number 1892 Modified #4
40 CFR 60 Subpart DD
567 IAC 23.1(2)"ooo"
Polk County Board of Health Rules and Regulations Chapter
V, Article VI,
Section 5-16(14)

Pollutant: PM - Federal

Emission Limit: 0.01 gr/dscf

Authority for Requirement: Polk County Construction Permit Number 1892 Modified #4
40 CFR 60 Subpart DD
567 IAC 23.1(2)"ooo"
Polk County Board of Health Rules and Regulations Chapter
V, Article VI,
Section 5-16(14)

Pollutant: PM₁₀

Emission Limit: 0.48 lb/hr

Authority for Requirement: Polk County Construction Permit Number 1892 Modified #4

Pollutant: PM_{2.5}

Emission Limit: 0.48 lb/hr

Authority for Requirement: Polk County Construction Permit Number 1892 Modified #4
JMG

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

Process throughput:

1. The facility shall not process more than 1,971,000 tons of soybeans per 12 month period, rolled monthly.

Reporting & Record keeping:

- The owner or operator shall record the following:
 - The amount of soybeans processed per hour (both in bushels and tons) for each hour of operation,
 - The amount of soybeans processed per day (both in bushels and tons) for each day of operation,
 - The total amount of soybeans processed per month (both in bushels and tons) for each month of operation, and
 - The annual amount of soybeans processed (both in bushels and tons) on a rolling 12-month basis for each month of operation.

Control equipment parameters:

1. The owner or operator shall maintain and operate the equipment, including control equipment, at all times in a manner consistent with good practice for minimizing emissions.
2. Control equipment (baghouse) shall be used at all times while the EU GP04 is in operation.
3. The owner or operator shall perform routine maintenance and inspections as per manufacturer's guidance for the product line equipment and control equipment (baghouse).
4. The owner or operator shall maintain records of maintenance activities on the EU GP04 equipment, including control equipment (baghouse).

Authority for Requirement: Polk County Construction Permit Number 1892 Modified #4

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 97.5

Stack Diameter (inches): 34

Stack Exhaust Flow Rate (scfm): 16,005

Stack Temperature (°F): Ambient

Discharge Style: Vertical, unobstructed

Authority for Requirement: Polk County Construction Permit Number 1892 Modified #4

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is

determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP GP04A shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If an opacity >0% is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source’s compliance with the applicable requirements.

The data pertaining to the plan must be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility’s implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: GP05A - Bean Conditioning and Dehulling

Associated Equipment

Associated Emission Unit ID Number: GP05
Emissions Control Equipment ID Number: GP05A
Emissions Control Equipment Description: Pneumafil Model RAF-II 11.5-320-12
Baghouse

Emission Unit vented through this Emission Point: GP05
Emission Unit Description: Escher Wyss Bean Conditioning and Dehulling
Raw Material/Fuel: Soybeans
Rated Capacity: 275 Tons/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <20%
Authority for Requirement: Polk County Construction Permit Number 1407 Modified #4

Pollutant: PM
Emission Limits: 0.27 lb/hr, 0.96 TPY, 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 1407 Modified #4
Polk County Board of Health Rules and Regulations Chapter
V, Article VI, Section 5-14(3).
567 IAC 23.3(2)"a"

Pollutant: PM₁₀
Emission Limits: 0.27 lb/hr, 0.96 TPY
Authority for Requirement: Polk County Construction Permit Number 1407 Modified #4

Pollutant: PM_{2.5}
Emission Limits: 0.27 lb/hr, 0.96 TPY
Authority for Requirement: Polk County Construction Permit Number 1407 Modified #4

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

Process throughput:

1. The facility shall not process more than 1,971,000 tons of soybeans per 12 month period, rolled monthly.

Reporting & Record keeping:

1. The facility shall record and maintain daily records of the tons of soybeans processed. Said records shall be maintained on site for a minimum period of 10 years and shall be made available to representatives of this agency upon request.

Authority for Requirement: Polk County Construction Permit Number 1407 Modified #4

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 80

Stack Diameter (inches): 40

Stack Exhaust Flow Rate (acfm): 37,000

Stack Temperature (°F): 130

Discharge Style: Vertical, unobstructed

Authority for Requirement: Polk County Construction Permit Number 1407 Modified #4

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP GP05A shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer's signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity $\geq 20\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts

shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: GP06A - Flaking Aspiration

Associated Equipment

Associated Emission Unit ID Number: GP06A
Emissions Control Equipment ID Number: GP06B
Emissions Control Equipment Description: Baghouse

Emission Unit vented through this Emission Point: GP06A
Emission Unit Description: Flaking Aspiration
Raw Material/Fuel: Soybeans
Rated Capacity: 210 Tons/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit: <20%⁽¹⁾

Authority for Requirement: Polk County Construction Permit Number 1618
Modified #7

⁽¹⁾ An exceedance of the indicator opacity of no visible emissions will require the owner or operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the Local Program may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: PM

Emission Limit: 0.10 gr/dscf

Authority for Requirement: Polk County Construction Permit Number 1618
Modified #7
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-14(3)

Pollutant: PM₁₀

Emission Limit: 0.675 lb/hr

Authority for Requirement: Polk County Construction Permit Number 1618
Modified #7

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. The facility shall not process more than 1,971,000 tons of soybeans per 12-month period, rolled monthly.
2. The owner or operator shall maintain and operate the equipment, including control equipment, at all times in a manner consistent with good practice for minimizing emissions.
3. Control equipment (baghouse) shall be used at all times while the Flaking Aspiration is in operation.
4. The owner or operator shall perform routine maintenance and inspections as per manufacturer's guidance for the product line equipment and control equipment (baghouse).
5. The facility shall record and maintain daily records of soybeans processed (in tons). Said records shall be maintained on site for a minimum of ten (10) years and shall be made available to PCAQD representatives upon request.
6. The owner or operator shall maintain records of maintenance activities on the Flaking Aspiration equipment, including control equipment (baghouse).

Authority for Requirement: Polk County Construction Permit Number 1618 Modified #7

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 97

Stack Diameter (inches): 33

Stack Exhaust Flow Rate (scfm): 27,500

Stack Temperature (°F): 160

Discharge Style: Vertical, unobstructed

Authority for Requirement: Polk County Air Quality Construction Permit
Number 1618 Modified #7

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP GP06A shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity $\geq 20\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: GP07 - Conveying to Extractor

Associated Equipment

Emission Unit vented through this Emission Point: GP07
Emission Unit Description: Conveying to Extractor
Raw Material/Fuel: Flakes
Rated Capacity: 250 Tons/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <20%
Authority for Requirement: Polk County Construction Permit Number 0103 Modified #4

Pollutant: PM
Emission Limit: 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 0103 Modified #4
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-14(3)

Pollutant: PM₁₀
Emission Limit: 0.343 lb/hr
Authority for Requirement: Polk County Construction Permit Number 0103 Modified #4

Pollutant: PM_{2.5}
Emission Limit: 0.343 lb/hr
Authority for Requirement: Polk County Construction Permit Number 0103 Modified #4

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. The facility shall not process more than 1,971,000 tons of soybeans per 12-month period, rolled monthly. The owner or operator shall record the following
 - a. The amount of soybeans processed per hour (both in bushels and tons) for each hour of operation,
 - b. The amount of soybeans processed per day (both in bushels and tons) for each day of operation,
 - c. The total amount of soybeans processed per month (both in bushels and tons) for each month of operation, and
 - d. The annual amount of soybeans processed (both in bushels and tons) on a rolling 12-month basis for each month of operation.

Authority for Requirement: Polk County Construction Permit Number 0103 Modified #4

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 95

Stack Diameter (inches): 8.0

Stack Exhaust Flow Rate (scfm): 960

Stack Temperature (°F): 100

Discharge Style: Vertical, unobstructed

Authority for Requirement: Polk County Air Quality Construction Permit
Number 0103 Modified #4

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP GP07 shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity $\geq 20\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: GP09A – Solvent Bubble [includes GP09 Extractor, MP01 DTDC-Desolventizer/ Toaster, and GP014 Hexane Tanks (2)]

Associated Equipment

Associated Emission Unit ID Numbers: GP09, GP014, MP01
 Emissions Control Equipment ID Number: CE GP09A
 Emissions Control Equipment Description: Mineral Oil Absorption System

EU	Emission Unit Description	Raw Material	Rated Capacity
GP09	Extractor	Hexane/Meal	230 Tons/hr
GP014	Hexane Tanks	Hexane	2 Tanks - 30,000 gallons each
MP01	Desolventizer/Toaster Dryer Cooler (DTDC)	Meal	215 Tons/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: VOC

Emission Limits: 788.0 Tons/yr¹, 0.140 gallons/ton²

Authority for Requirement: DNR Construction Permit 07-A-1078-P2

¹ 12-month rolling total, including startup, shutdown, or malfunction

² gallons of VOC lost per ton of soybeans processed. 12-month rolling total, does not include startup, shutdown, or malfunction

Pollutant: Total HAP

Emission Limits: Compliance Ratio ≤ 1.00

Authority for Requirement: DNR Construction Permit 07-A-1078-P2

40 CFR Part 63 Subpart GGGG

567 IAC 23.1(4)"cg"

NESHAP

This unit is subject to 40 CFR Part 63 Subpart GGGG - National Emission Standards for Solvent Extraction for Vegetable Oil Production and Subpart A – General Provisions.

Authority for Requirement: 40 CFR Part 63 Subpart GGGG

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. This facility (plant number 77-01-045) shall not process more than 1,971,000 tons of soybeans per 12-month rolling period. The owner or operator shall record the following:
 - a. The amount of soybeans processed per day (both in bushels and tons) for each day of operation,
 - b. The total amount of soybeans processed per month (both in bushels and tons) for each month of operation, and
 - c. The annual amount of soybeans processed (both in bushels and tons) on a rolling 12-month basis for each month of operation.
2. In order to demonstrate compliance with the VOC BACT emission limits, the owner or operator shall maintain the following records:
 - a. The solvent loss per month (both in gallons and tons) for the facility (Plant Number 77-01-045) for each month of operation,
 - b. The calculated monthly ratio of solvent loss to soybeans processed (gal/ton) for each month of operation,
 - c. The annual solvent loss (both in gallons and tons) for the facility (Plant Number 77-01-045) on a rolling 12-month basis for each month of operation, and
 - d. The calculated annual ratio of solvent loss to soybeans processed (gal/ton) on a rolling 12-month basis for each month of operation.

NOTE: The rolling 12-month total of tons of solvent loss is required to include SSM, but the ratio of solvent loss to soybeans processed is not required to include SSM.

3. The owner or operator shall conduct an inspection of the emission units (EUs GP09 and MP01) and the associated control equipment (CE GP09A) per the manufacturer's recommendations with a minimum inspection frequency of once per year. The owner or operator shall record:
 - a. The date of each inspection,
 - b. Any issues discovered during the inspection,
 - c. Any maintenance issues discovered outside of any inspections, and
 - d. Any actions taken to resolve issues discovered during any inspection or for maintenance issues.
4. In accordance with 40 CFR §63.2851, the owner or operator shall develop and implement a written plan for demonstrating compliance that provides the detailed procedures to be followed to monitor and record data necessary for demonstrating compliance with NESHAP Subpart GGGG. The plan for demonstrating compliance shall include the following:
 - a. The name and address of the owner or operator.
 - b. The physical address of the vegetable oil production process.
 - c. A detailed description of all methods of measurement the owner or operator will use to determine the solvent losses, HAP content of solvent, and the tons of each type of oilseed processed.
 - d. When each measurement will be made.

- e. Examples of each calculation the owner or operator will use to determine the compliance status of the facility (plant number 77-01-045). The owner or operator shall include examples of how data measured with one parameter will be converted to other terms for use in the compliance determination.
 - f. Example logs of how the data will be recorded.
 - g. A plan to ensure that the data continue to meet compliance demonstration needs.
5. The owner or operator shall record the ratio of solvent loss to soybeans processed to demonstrate compliance with the NESHAP Subpart GGGG requirement (See Total HAP limit in Condition 1.B.) on a rolling 12-month basis. The ratio of solvent loss to soybeans processed for compliance with NESHAP Subpart GGGG shall be determined in accordance with 40 CFR §63.2840 and 40 CFR §63.2850 – 40 CFR §63.2855.
 6. In accordance with 40 CFR §63.2862(c) and in accordance with the plan for demonstrating compliance required by 40 CFR §63.2851, the owner or operator shall record the following:
 - a. For the solvent inventory, record the following information:
 - i. Dates that define each operating status period during a calendar month.
 - ii. The operating status of the facility (plant number 77-01-045) such as normal operation, nonoperation, initial startup period, malfunction period, or exempt operation for each recorded time interval.
 - iii. Record the gallons of extraction solvent in the inventory on the beginning and ending dates of each normal operating period.
 - iv. The gallons of all extraction solvent received, purchased, and recovered during each calendar month.
 - v. All extraction solvent inventory adjustments, additions or subtractions. The owner or operator must document the reason for the adjustment and justify the quantity of the adjustment.
 - vi. The total solvent loss for each calendar month, regardless of the source operating status.
 - vii. The actual solvent loss in gallons for each operating month.
 - b. For the weighted average volume fraction of HAP in the extraction solvent, the owner or operator must record the following items:
 - i. The gallons of extraction solvent received in each delivery.
 - ii. The volume fraction of each HAP exceeding one percent (1%) by volume in each delivery of extraction solvent.
 - iii. The weighted average volume fraction of HAP in extraction solvent received since the end of the last operating month as determined in accordance with 40 CFR §63.2854(b)(2).
 - c. For each type of listed oilseed processed, record the following items:
 - i. The dates that define each operating status period. These dates must be the same as the dates entered for the extraction solvent inventory.
 - ii. The operating status of the facility (plant number 77-01-045) such as normal operation, nonoperation, initial startup period, malfunction period, or exempt operation for each recorded time interval. On the log for each type of listed oilseed that is not being processed during a normal operating period, the owner or operator shall record which type

- of listed oilseed is being processed in addition to the source operating status.
 - iii. The oilseed inventory for the type of listed oilseed being processed on the beginning and ending dates of each normal operating period.
 - iv. The tons of each type of listed oilseed received at the facility (plant number 77-01-045) each normal operating period.
 - v. All listed oilseed inventory adjustments, additions or subtractions for normal operating periods. The owner or operator shall document the reason for the adjustment and justify the quantity of the adjustment.
 - vi. The tons of each type of listed oilseed processed during each operating month.
7. In accordance with 40 CFR §63.2862(d), after the facility (Plant Number 77-01-045) has processed a listed oilseed for 12 operating months, the owner or operator shall record the following items by the end of the calendar month following each operating month:
- a. The twelve (12) operating months rolling sum of the actual solvent loss in gallons as described in 40 CFR §63.2853(c).
 - b. The weighted average volume fraction of HAP in extraction solvent received for the previous twelve (12) operating months as described in 40 CFR §63.2854(b)(3).
 - c. The twelve (12) operating months rolling sum (in tons) of each type of listed oilseed processed at the facility (plant number 77-01-045) as described in 40 CFR §63.2855(c).
 - d. A determination of the compliance ratio. The owner or operator shall use the values from 40 CFR §63.2853, 40 CFR §63.2854, 40 CFR §63.2855, and Table 1 of 40 CFR §63.2840 along with Equation 2 of 40 CFR §63.2840 to calculate the compliance ratio.
 - e. A statement of whether the source is in compliance with all of the requirements of NESHAP Subpart GGGG. This includes a determination of whether the facility (plant number 77-01-045) has met all of the applicable requirements in 40 CFR §63.2850.
8. All notifications for NESHAP Subpart GGGG at the facility (77-01-045) shall be submitted as required per 40 CFR §63.2860.
9. All reports for NESHAP Subpart GGGG at the facility (77-01-045) shall be submitted as required per 40 CFR §63.2861.

Authority for Requirement: State of Iowa Construction Permit Number 07-A-1078-P2
 40 CFR Part 63 Subpart GGGG
 567 IAC 23.1(4)"cg"

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 21

Stack Diameter (inches): 12

Stack Exhaust Flow Rate (scfm): 200

Stack Temperature (°F): 100

Discharge Style: Horizontal

Authority for Requirement: State of Iowa Construction Permit Number 07-A-1078-P2

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Compliance Assurance Monitoring Plan:
Solvent Bubble with Mineral Oil Absorption System

Emission Unit Information

Solvent Bubble

Emission Units: Extractor 230 tons/hr (EU GP09), Hexane Tanks (EU GP014),
DTDC – Desolventizer/Toaster/Dryer/Cooler 215 tons/hr (EU MP01)
Emission Control Technique: Mineral Oil Absorption System
Control Device Identification Number: CE GP09A
Emission Point Identification Number: EP GP09A

Applicable Requirement for EP GP09A

Pollutant: VOC

Emission Limits: 788.0 Tons/yr¹, 0.140 gallons/ton²

¹: 12-month rolling total, including startup, shutdown, or malfunction

²: gallons of VOC lost per ton of soybeans processed. 12-month rolling total, does not include startup, shutdown, or malfunction

Authority for Requirement: State of Iowa Construction Permit Number 07-A-1078-P2

Monitoring Approach

Indicators

Indicator #1: Calculated 12-month rolling total solvent losses and solvent loss ratios

Calculations of solvent loss and grain processed, with monthly accounting adjustments, are described as a portion of the NESHAP Subpart GGGG Compliance Plan for the HAP n-Hexane, and are used monthly to directly verify compliance with the 12-month rolling VOC limits.

Indicator #2: Mineral Oil Absorption System Temperature and Flow Rate

The absorption system's mineral oil flow rate and temperature were selected as the performance indicators as they are indicative of operation of the scrubber in a manner necessary to maximize collection and reuse of hexane and minimize emissions. An excursion of these indicators out of the optimal operating range indicates a possibility of reduced performance of the scrubber.

Indicator Range

Indicator #1: Calculated 12-month rolling total solvent losses and solvent loss ratios

Calculated monthly for compliance with the BACT limits of 788.0 tons VOC/year and 0.140 gallons solvent/ton of grain processed. Calculations greater than the limits is an exceedance

Indicator #2: Mineral Oil Absorption System Temperature and Flow Rate

Monitoring the mineral oil flow rate and temperature will serve to alert the facility in circumstances when the mineral oil absorption system experiences short-term excursions. Any recorded flow rate or temperature outside of the indicator range during normal operations will signify an excursion. Normal operations do not include periods of startup or shutdown of the mineral oil system. The indicator levels for the absorption system are a mineral oil flow rate not less than 10 gallons per minute into the absorber and a mineral oil temperature not less than 180 degrees F into the stripper.

Measurement Approach

Indicator #1: Calculated 12-month rolling total solvent losses and solvent loss ratios

Solvent inventory is determined daily during normal operation of the process. Records of solvent deliveries are maintained. The amount of grain processed is estimated daily and adjusted monthly according to established accounting practices. Calculations demonstrating compliance with the VOC limits are done monthly.

Indicator #2: Mineral Oil Absorption System Temperature and Flow Rate

Oil flow entering the absorber shall be measured for flow rate and temperature shall be measured in the oil entering the stripper. The mineral oil flow rate and temperature sensors provide real-time readings which are recorded a minimum of once per day when the facility's emission unit is in operation.

Performance Criteria

The mineral oil absorption system is designed to operate at maximum control efficiency at specific mineral oil flow rate and temperature ranges. If the flow rate or temperature has drifted out of the optimal efficiency range, this is an indication of the potential for increased hexane emissions. Facility hexane losses are representative of the scrubber's operation.

Response to Excursion

Indicator #1: Calculated 12-month rolling total solvent losses and solvent loss ratios

12-month rolling total hexane emissions are used as long-term performance indicator and evaluation and corrective action regarding operating practices and conditions are an ongoing process. Calculated results greater than the permitted limits is an exceedance.

Indicator #2: Mineral Oil Scrubber Temperature and Flow Rate

When an excursion occurs, corrective action will be initiated within 8 hours, beginning with an evaluation of the occurrence to determine the action required. After any necessary corrective action has been taken, a follow-up check will be performed to insure that the indicator is within the indicator range.

Emission Point ID Number: GP013 – Emergency Lighting Generator

Associated Equipment

Emission Unit vented through this Emission Point: GP013
Emission Unit Description: Emergency Lighting Generator
Raw Material/Fuel: Natural Gas
Rated Capacity: 0.32 MMBTU/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit: <40%

Authority for Requirement: Polk County Board of Health Rules and Regulations
Chapter V, Section 5-9

Pollutant: PM

Emission Limit: 0.1 gr/dscf

Authority for Requirement: 567 IAC 23.3(2) "a"
Polk County Board of Health Rules and Regulations Chapter
V, Article VI, Section 5-14(3)

Pollutant: SO₂

Emission Limit: 500 parts per million by volume

Authority for Requirement: 567 IAC 23.3(3)"e"
Polk County Board of Health Rules and Regulations: Chapter
V,
Article IX, Section 5-27

NESHAP

The emergency generator is subject to 40 CFR 63 Subpart ZZZZ - National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines (RICE). According to 40 CFR 63.6590(a)(1)(ii) this spark ignition emergency generator, located at a HAP major source, is an existing stationary RICE as it was constructed prior to June 12, 2006.

Compliance Date

Per 63.6595(a)(1) you must comply with the provisions of subpart ZZZZ that are applicable by October 19, 2013.

Operation and Maintenance Requirements 40 CFR 63.6602, 63.6625, 63.6640 and Tables 2c and 6 to Subpart ZZZZ

1. Change oil and filter every 500 hours of operation or 1 year + 30 days, whichever comes first. (See 63.6625(j) for the oil analysis option to extend time frame of requirements.)
2. Inspect spark plugs every 1,000 hours of operation or 1 year + 30 days , whichever comes first, and replace as necessary.
3. Inspect all hoses and belts every 500 hours of operation or 1 year + 30 days , whichever comes first, and replace as necessary.
4. Operate and maintain the stationary RICE and after-treatment control device (if any) according to the manufacturer's emission related written instructions or develop your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions.
5. Install a non-resettable hour meter if one is not already installed.
6. Minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes.

Operating Limits 40 CFR 63.6640(f)

1. Any operation other than emergency operation, maintenance and testing, emergency demand response and operation in non-emergency situations (*up to*) 50 hours per year is prohibited.
2. There is no time limit on the use of emergency stationary RICE in emergency situations.
3. You may operate your emergency stationary RICE up to 100 combined hours per calendar year for maintenance checks and readiness testing, emergency demand response and periods where there is a deviation of voltage or frequency of 5 percent or greater below standard voltage or frequency. See 40 CFR 63.6640(f)(2) for additional information and restrictions.
4. You may operate your emergency stationary RICE up to 50 hours per calendar year for non-emergency situations, but those 50 hours are counted toward the 100 hours of maintenance and testing and emergency demand response. The 50 hours per year for non-emergency situations cannot be used for peak shaving or non-emergency demand response, or to generate income for a facility to supply power to an electric grid or otherwise supply power as part of a financial arrangement with another entity.

Recordkeeping Requirements 40 CFR 63.6655

1. Keep records of the maintenance conducted on the stationary RICE.
2. Keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. Document how many hours are spend for emergency operation, including what classified the operation as emergency and how many hours are spent for non-emergency operation. See 40 CFR 63.6655(f) for additional information.

Notification and Reporting Requirements 40 CFR 63.6645, 63.6650 and Table 2c to Subpart ZZZZ

1. An initial notification is not required per 40 CFR 63.6645(a)(5).
2. A report may be required for failure to perform the work practice requirements on the schedule required in Table 2c. (See Footnote 1 of Table 2c for more information.)
3. If you own or operate an emergency stationary RICE with a site rating of more than 100 bhp that operates or is contractually obligated to be available for more than 15 hours per calendar year for the purposes specified in 40 CFR 63.6640(f)(2)(ii) and (iii), you must submit an annual report. See 40 CFR 63.6650(h) for additional information.

Authority for Requirement: 40 CFR Part 63 Subpart ZZZZ
567 IAC 23.1(4)"cz"
Polk County Board of Health Rules and Regulations: Chapter
V,
Article VIII, Section 5-20

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

**Emission Point ID Number: GP015A Prep Building Central Vacuum
Cleaning System**

Associated Equipment

Associated Emission Unit ID Numbers: GP015A
Emissions Control Equipment ID Number: GP015A
Emissions Control Equipment Description: Smoot Prep Vacuum

Emission Unit vented through this Emission Point: GP015A
Emission Unit Description: Prep Building Central Vacuum System
Raw Material/Fuel: Soybean dust
Rated Capacity: 2,500 lb/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <40%
Authority for Requirement: Polk County Board of Health Rules and Regulations
Chapter V, Section 5-9

Pollutant: PM
Emission Limit: 0.043 lb/hr, 0.19 TPY, 0.01 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 0092 Modified

Pollutant: PM₁₀
Emission Limit: 0.043 lb/hr, 0.19 TPY, 0.01 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 0092 Modified

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 120

Stack Diameter (inches): 5

Stack Exhaust Flow Rate (acfm): 500

Stack Temperature (°F): Ambient

Discharge Style: Horizontal

Authority for Requirement: Polk County Construction Permit Number 0092 Modified

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: GP016 Soybean Heater

Associated Equipment

Associated Emission Unit ID Numbers: GP016
Emissions Control Equipment ID Number: GP016A
Emissions Control Equipment Description: Pneumafil Model RAF-II 11.5x320x12
Baghouse

Emission Unit vented through this Emission Point: GP016
Emission Unit Description: Crown Model VSC130 Soybean Heater
Raw Material/Fuel: Soybeans
Rated Capacity: 275 Tons/hour

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <20%
Authority for Requirement: Polk County Construction Permit Number 2343 Modified

Pollutant: PM
Emission Limits: 0.25 lb/hr, 1.10 TPY, and 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 2343 Modified
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-14(3)

Pollutant: PM₁₀
Emission Limits: 0.25 lb/hr, 1.10 TPY
Authority for Requirement: Polk County Construction Permit Number 2343 Modified

Pollutant: PM_{2.5}
Emission Limits: 0.25 lb/hr, 1.10 TPY
Authority for Requirement: Polk County Construction Permit Number 2343 Modified

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. The facility shall not process more than 1,971,000 tons of soybeans per 12-month period, rolled monthly.
2. The facility shall record and maintain daily records of the tons of soybeans processed. Said records shall be maintained on site for a minimum period of 10 years and shall be made available to representatives of this agency upon request.

Authority for Requirement: Polk County Construction Permit Number 2343 Modified

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 72.3

Stack Diameter (inches): 30

Stack Exhaust Flow Rate (acfm): 28,000

Stack Temperature (°F): 165

Discharge Style: Vertical, Unobstructed

Authority for Requirement: Polk County Construction Permit Number 2343 Modified

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP GP016 shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer's signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity >20% is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will

be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the applicable requirements.

The data pertaining to the plan must be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Numbers: GP019A, GP019B, GP019C, & GP019D

Associated Equipment

Associated Emission Unit ID Numbers: GP019A, GP019B, GP019C, GP019D
Emissions Control Equipment ID Numbers: GP019A, GP019B, GP019C, GP019D
Emissions Control Equipment Description: Evapco Mist Eliminator 0.0005%

Emission Units vented through this Emission Point: GP019A, GP019B, GP019C, GP019D
Emission Unit Description: 4 Cell Extraction Evapco Cooling Tower
Raw Material/Fuel: Water
Rated Capacity: 15,000 gallons/ minute

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from each emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <20%
Authority for Requirement: Polk County Construction Permit Number 2823 Modified

Pollutant: PM
Emission Limits: 0.056 lb/hr, and 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 2823 Modified
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-14(3)

Pollutant: PM₁₀
Emission Limit: 0.056 lb/hr
Authority for Requirement: Polk County Construction Permit Number 2823 Modified

Pollutant: PM_{2.5}
Emission Limit: 0.056 lb/hr
Authority for Requirement: Polk County Construction Permit Number 2823 Modified

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. Chromium based, VOC containing, and HAP containing water treatment chemicals (i.e. biocides, fungicides, scale inhibitors, etc.) shall not be used in this emission unit.
 2. A copy of the Safety Data Sheets (SDS) for each water treatment chemical used in this emission unit shall be kept on site.
 3. The total dissolved solids (TDS) of the water used shall not exceed 1,500 ppm.
 4. The drift eliminator (CE GP019A/B/C/D) shall be designed to meet a control efficiency of 0.0005% (gallons of drift per gallon of cooling water flow) or better.
 5. A minimum of one TDS Water Sampling analysis shall be conducted each month. If more than one analysis is conducted, the average of the analyses shall be used to demonstrate compliance.
 6. Record the analysis of the TDS of the water used on a monthly basis.
- Authority for Requirement: Polk County Construction Permit Number 2823 Modified

Emission Point Characteristics

Each emission point shall conform to the specifications listed below.

Stack Height (feet): 24.5

Stack Diameter (inches): 160

Stack Exhaust Flow Rate (scfm): 204,500 (per cell)

Stack Temperature (°F): 78

Discharge Style: Vertical, Unobstructed

Authority for Requirement: Polk County Construction Permit Number 2823 Modified

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP GP019A/B/C/D shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer's signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity >20% is observed, this would be a violation and corrective action

will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Numbers: GP021, GP022, & GP023

Associated Equipment

EP	EU	Emission Unit Description	Raw Material	Rated Capacity	Polk County Permit Number
GP021	GP021	Extraction – Diesel Fire Pump	#2 Fuel Oil	455 hp	4027
GP022	GP022	Extraction – Diesel Fire Pump	#2 Fuel Oil	455 hp	4028
GP023	GP023	Extraction – Diesel Fire Pump	#2 Fuel Oil	455 hp	4029

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from each emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit: <40 %

Authority for Requirement: Polk County Construction Permit Numbers 4027, 4028, 4029
Chapter V, Article IV, Section 5-9

Pollutant: PM

Emission Limit: 0.10 gr/dscf

Authority for Requirement: Polk County Construction Permit Numbers 4027, 4028, 4029
567 IAC 23.3 (2) "a"
Chapter V, Article VI, Section 5-14(3) "a" (1)

Pollutant: PM₁₀

Emission Limit: 0.16 lb/hr

Authority for Requirement: Polk County Construction Permit Numbers 4027, 4028, 4029

Pollutant: PM_{2.5}

Emission Limit: 0.16 lb/hr

Authority for Requirement: Polk County Construction Permit Numbers 4027, 4028, 4029

Pollutant: SO₂

Emission Limit: 0.5% by weight

Authority for Requirement: Polk County Construction Permit Numbers 4027, 4028, 4029
Chapter V, Article IX, Section 5-27(2) "a"

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

NESHAP:

These emergency engines are subject to 40 CFR 63 Subpart ZZZZ - National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines (RICE). According to 40 CFR 63.6590(a)(2)(ii) these compression ignition emergency engines, located at a major source, are new stationary RICE as they were constructed on or after June 12, 2006.

According to 40 CFR 63.6590(c)(6), these emergency engines must meet the requirements of subpart ZZZZ by meeting the requirements of 40 CFR 60 Subpart IIII for compression ignition engines. No further requirements apply for this emergency engine under subpart ZZZZ.

Authority for Requirement: 40 CFR Part 63 Subpart ZZZZ
567 IAC 23.1(4)"cz"

New Source Performance Standards (NSPS):

These engines are subject to the following requirements of 40 CFR 60 Subpart IIII – Standards of Performance for Stationary Internal Combustion Engines:

- (1) In accordance with 40 CFR §60.4211(c), the engine must be certified by its manufacturer to comply with the emissions standards for emergency engines from 40 CFR §60.4205(c) and 40 CFR §60.4202(d). The emission standards that the engine must be certified by the manufacturer to meet are:

NSPS Certification Standards

Pollutant	Emission Standard	Basis/Reference
Particulate Matter (PM)	0.15 grams/HP-hr	NSPS Subpart IIII, Table 4
NMHC + NO _x	3.0 grams/HP-hr	NSPS Subpart IIII, Table 4
Carbon Monoxide (CO)	2.6 grams/HP-hr	NSPS Subpart IIII, Table 4

- (2) In accordance with 40 CFR §60.4211(c), the owner or operator must comply with the required NSPS emissions standards by purchasing an engine certified by its manufacturer to meet the applicable emission standards for the same model year and engine power. The engine must be installed and configured to the manufacturer's specifications. Provided these requirements are satisfied, no further demonstration of compliance with the emission standards from 40 CFR §60.4205(c) and 40 CFR §60.4202(d) is required. However, if the engine is not installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions, a compliance demonstration is required in accordance with 40 CFR §60.4211(g).

NOTE: The absence of the inclusion of any NSPS requirements as part of this permit does not relieve the owner or operator from any obligation to comply with all applicable NSPS conditions.

- (3) Each engine is limited to operating a maximum of 400 hours in any rolling 12-month period.
- (4) Each engine:
 - (1) Is limited to operate as an emergency stationary internal combustion engine as defined in 40 CFR §60.4219 and in accordance with 40 CFR §60.4211(f). There is no time limit on the use of the engine in emergency situations provided that the annual hourly limit established in Condition 3 (above). is not exceeded. In accordance with 40 CFR §60.4211(f)(2), the engine is limited to operate a maximum of 100 hours per calendar year for maintenance checks and readiness testing.
 - (2) Is also allowed to operate up to 50 hours per calendar year in non-emergency situations in accordance with 40 CFR §60.4211(f)(3), but the 50 hours are counted toward the 100 hours provided for maintenance and testing. The 50 hours per calendar year for non-emergency operation cannot be used for peak shaving or non-emergency demand response or to generate income for the facility to supply power to the electric grid or otherwise supply non-emergency power as part of a financial arrangement with another entity.
- (5) In accordance with 40 CFR §60.4209(a), each engine shall be equipped with a non-resettable hour meter.
- (6) The owner or operator shall maintain the following monthly records:
 - (1) the number of hours that each engine operated for maintenance checks and readiness testing;
 - (2) the number of hours that each engine operated for allowed non-emergency service and the reason for the non-emergency operation;
 - (3) the number of hours that each engine operated for emergency service and the reason for the emergency operation [See 40 CFR §60.4214(b)];
 - (4) the total number of hours that each engine operated; and
 - (5) the rolling 12-month total amount of the number of hours that the engine operated.
- (7) The owner or operator shall maintain the following annual records:
 - a. the number of hours that each engine operated for maintenance checks and readiness testing;
 - b. the number of hours that each engine operated for allowed non-emergency operations; and
 - c. the total number of hours that each engine operated for maintenance checks, readiness testing, and allowed non-emergency operations.
- (8) In accordance with §60.4207(b), the diesel fuel burned in these engines shall meet the following specifications from 40 CFR 1090.305 for ultra-low sulfur diesel (ULSD):

Diesel Fuel Specifications

Parameter	Limit
Sulfur (S) content	15 ppm (0.0015%) by weight
Minimum cetane index or	40
Maximum aromatic content	35% (by volume)

- (1) The owner or operator shall comply with the requirements listed above by one of the following methods:
 - a. have the fuel supplier certify that the fuel delivered meets the of non-road diesel fuel ULSD as defined in 40 CFR 1090.80; or
 - b. obtain a fuel analysis from the supplier showing the sulfur content and cetane index or aromatic content of the fuel delivered; or
 - c. perform an analysis of the fuel to determine the sulfur content and cetane index or aromatic content of the fuel received.
- (9) The engine must be installed and configured according to the manufacturer's emission-related specifications, except as permitted in 40 CFR §60.4211(g).
- (10) In accordance with 40 CFR §60.4211(a), the engine shall be operated and maintained in accordance with the manufacturer's emission-related written instructions. Except as permitted in 40 CFR §60.4211(g), the owner or operator may only change emission-related engine settings that are permitted by the manufacturer.
- (11) The fire pump shall be operated in a manner consistent with the definition of an emergency stationary internal combustion fire pump engine per §60.4219.
- (12) The owner or operator shall complete all applicable monitoring, compliance, notification, reporting, and recordkeeping requirements as required by NSPS Subpart IIII not specifically listed in this permit:
 - (1) The owner or operator of the engine shall follow the monitoring requirements of 40 CFR §60.4209.
 - (2) The owner or operator of the engine shall follow the compliance requirements of 40 CFR §60.4211.
 - (3) The owner or operator of the engine shall follow the notification, reporting, and recordkeeping requirements of 40 CFR §60.4214(b).
- (13) Any required compliance testing shall be performed according to the methods and procedures of §60.4212.

Authority for Requirement: Polk County Construction Permit Numbers 4027, 4028, 4029
40 CFR §63.6600(d), subpart ZZZZ
567 IAC 23.1(4)"cz"
Chapter V, Article VIII, Section 5-20

Emission Point Characteristics

Each emission point shall conform to the specifications listed below.

Stack Height (feet): 20
Stack Diameter (inches): 8
Stack Exhaust Flow Rate (scfm): 1,065
Stack Temperature (°F): 952

Discharge Style: Vertical, unobstructed

Authority for Requirement: Polk County Construction Permit Numbers 4027, 4028, 4029

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: HR01A – Conveying to Aspirator/Whole Bean Aspiration; Secondary Aspiration/ Hull Gravity Tables

Associated Equipment

Associated Emission Unit ID Numbers: GP011, HR01A
 Emissions Control Equipment ID Number: HR01A
 Emissions Control Equipment Description: Pneumafil Model 13.5x460x10 Baghouse

EP	EU	Emission Unit Description	Raw Material	Rated Capacity
HR01A	GP011	Conveying to Aspirator/Whole Bean Aspiration	Soybeans	250 Tons/hr
HR01A	HR01A	Secondary Aspiration, Hull Gravity Tables	Soybeans	250 Tons/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit: <20%

Authority for Requirement: Polk County Construction Permit Number 2531 Modified #2

Pollutant: PM

Emission Limit: 0.10 gr/dscf

Authority for Requirement: Polk County Construction Permit Number 2531 Modified #2
 Polk County Board of Health Rules and Regulations
 Chapter V, Article VI, Section 5-14(3)

Pollutant: PM₁₀

Emission Limit: 0.75 lb/hr

Authority for Requirement: Polk County Construction Permit Number 2531 Modified #2

Pollutant: PM_{2.5}

Emission Limit: 0.75 lb/hr

Authority for Requirement: Polk County Construction Permit Number 2531 Modified #2

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. The facility shall not process more than 1,971,000 tons of soybeans per 12-month period, rolled monthly.
2. The owner or operator shall record the following:
 - a. The amount of soybeans processed per hour (both in bushels and tons) for each hour of operation,
 - b. The amount of soybeans processed per day (both in bushels and tons) for each day of operation,
 - c. The total amount of soybeans processed per month (both in bushels and tons) for each month of operation, and
 - d. The annual amount of soybeans processed (both in bushels and tons) on a rolling 12-month basis for each month of operation.
3. The owner or operator shall maintain and operate the equipment, including control equipment, at all times in a manner consistent with good practice for minimizing emissions.
4. Control equipment (baghouse) shall be used at all times while the EU HR01A and EU GP011 are in operation.
5. The owner or operator shall perform routine maintenance and inspections as per manufacturer's guidance for the product line equipment and control equipment (baghouse).
6. The owner or operator shall maintain records of maintenance activities on the EU HR01A and EU GP011 equipment, including control equipment (baghouse).

Authority for Requirement: Polk County Construction Permit Number 2531 Modified #2

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 110

Stack Diameter (inches): 48

Stack Exhaust Flow Rate (scfm): 31,955

Stack Temperature (°F): 80

Discharge Style: Vertical, unobstructed

Authority for Requirement: Polk County Construction Permit Number 2531 Modified #2

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP HR01A shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity $\geq 20\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: HR02A – Hull Grinding

Associated Equipment

Emissions Control Equipment ID Number: HR02A
Emissions Control Equipment Description: Donaldson Model 124RFW8 Baghouse

Emission Unit vented through this Emission Point: HR02A
Emission Unit Description: Hull Grinding
Raw Material/Fuel: Hulls
Rated Capacity: 19.25 Tons/hour

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <20%
Authority for Requirement: Polk County Construction Permit Number 0100 Modified #7

Pollutant: PM
Emission Limits: 0.29 lb/hr, 0.59 TPY, and 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 0100 Modified #7
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-14(3)

Pollutant: PM₁₀
Emission Limits: 0.29 lb/hr, 0.59 TPY
Authority for Requirement: Polk County Construction Permit Number 0100 Modified #7

Pollutant: PM_{2.5}
Emission Limits: 0.29 lb/hr, 0.59 TPY
Authority for Requirement: Polk County Construction Permit Number 0100 Modified #7

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. The facility shall not process more than 1,971,000 tons of soybeans per 12 month period, rolled monthly.
2. The facility shall record and maintain daily records of the tons of soybeans processed. Said records shall be maintained on site for a minimum period of 10 years and shall be made available to representatives of this agency upon request.

Authority for Requirement: Polk County Construction Permit Number 0100 Modified #7

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 90

Stack Diameter (inches): 30

Stack Exhaust Flow Rate (scfm): 12,300

Stack Temperature: Ambient

Discharge Style: Vertical, Unobstructed

Authority for Requirement: Polk County Construction Permit Number 0100 Modified #7

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP HR02A shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer's signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity $\geq 20\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will

be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: HR03 – Pellet Cooler

Associated Equipment

Associated Emission Unit ID Numbers: HR03
Emissions Control Equipment ID Number: HR03
Emissions Control Equipment Description: Carter Day Cyclone Model Number HV74

Emission Unit vented through this Emission Point: HR03
Emission Unit Description: Pellet Cooler
Raw Material/Fuel: Hulls
Rated Capacity: 14.5 Tons/ hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <20%
Authority for Requirement: Polk County Construction Permit Number 2827 Modified #2

Pollutant: PM
Emission Limit: 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 2827 Modified #2
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-14(3)

Pollutant: PM₁₀
Emission Limit: 0.65 lb/hr
Authority for Requirement: Polk County Construction Permit Number 2827 Modified #2

Pollutant: PM_{2.5}
Emission Limit: 0.65 lb/hr
Authority for Requirement: Polk County Construction Permit Number 2827 Modified #2

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. Maximum capacity of EU HR03A (Pellet Cooler) shall not exceed 14.5 tons per hour.
2. The facility (plant number 77-01-045) shall not process more than 1,971,000 tons of soybeans per 12-month period, rolled monthly. The owner or operator shall record the following:
 - a. The amount of soybeans processed per hour (both in bushels and tons) for each hour of operation,
 - b. The amount of soybeans processed per day (both in bushels and tons) for each day of operation,
 - c. The total amount of soybeans processed per month (both in bushels and tons) for each month of operation, and
 - d. The annual amount of soybeans processed (both in bushels and tons) on a rolling 12-month basis for each month of operation.
3. The frequency (Hz) across both pellet mills shall not exceed 90 Hz.
4. The owner/operator shall collect and record the Hz of the pellet mill feeders with a Continuous Parameter Monitoring System (CPMS).
5. The CPMS data will be reduced and recorded as hourly averages. These records shall be maintained for a minimum period of 10 years.

Authority for Requirement: Polk County Construction Permit Number 2827 Modified #2

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 120

Stack Diameter (inches): 24

Stack Exhaust Flow Rate (scfm): 11,170

Stack Temperature (°F): 90

Discharge Style: Vertical, Unobstructed

Authority for Requirement: Polk County Construction Permit Number 2827 Modified #2

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP HR03 shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity $\geq 20\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: MP01 – Crown Desolventizer Toaster Dryer Cooler (DTDC)

Associated Equipment

EU ID	DTDC	Components	Maximum Rated Capacity	Control Equipment Description and ID
MP01	Vessel 1- Desolventizer/ Toaster	(3) Pre-desolventizing trays	215 ton/hr	NA
		(4) Desolventizing decks		NA
		(1) Sparge tray		NA
		(1) Vapor recovery tray		NA
	Vessel 2- Dryer/Cooler (6-trays with cyclones operating in parallel)	Tray A		Cyclone (CE MP01 A)
		Tray B		Cyclone (CE MP01 B)
		Tray C		Cyclone (CE MP01 C)
		Tray D		Cyclone (CE MP01 D)
		Tray E		Cyclone (CE MP01 E)
		Tray F		Cyclone (CE MP01 F)

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from each emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit: <20%⁽¹⁾

Authority for Requirement: Polk County Construction Permit Number 1626 Modified #5

⁽¹⁾An exceedance of the indicator opacity of no visible emissions will require the owner or operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the Local Program may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: PM

Emission Limit: 0.1 gr/dscf

Authority for Requirement: Polk County Construction Permit Number 1626 Modified #5
Polk County Board of Health Rules and Regulations

Pollutant: PM₁₀

Emission Limit: 3.37 lb/hr

Authority for Requirement: Polk County Construction Permit Number 1626 Modified #5

Pollutant: PM_{2.5}

Emission Limit: 3.37 lb/hr

Authority for Requirement: Polk County Construction Permit Number 1626 Modified #5

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. The facility shall not process more than 1,971,000 tons of soybeans per 12 month period, rolled monthly. The owner or operator shall record the following:
 - a. The amount of soybeans processed per hour (both in bushels and tons) for each hour of operation,
 - b. The amount of soybeans processed per day (both in bushels and tons) for each day of operation,
 - c. The total amount of soybeans processed per month (both in bushels and tons) for each month of operation, and
 - d. The annual amount of soybeans processed (both in bushels and tons) on a rolling 12-month basis for each month of operation.
2. The owner or operator shall maintain and operate the equipment, including control equipment, at all times in a manner consistent with good practice for minimizing emissions.
3. Control equipment (cyclones) shall be used at all times while the DTDC equipment is in operation.
4. The owner or operator shall perform routine maintenance and inspections as per manufacturer's guidance for the DTDC equipment and control equipment (cyclones).
5. The owner or operator shall maintain records of maintenance activities on the DTDC equipment, including control equipment (cyclones).

For the purposes of Prevention of Significant Deterioration (PSD) determination:

6. In accordance with 567 IAC 33.3(18) "f"(1), prior to beginning actual construction of the DTDC Upgrade Project, the owner or operator shall document:
 - (1) A description of the DTDC Upgrade Project,
 - (2) Identification of the emission unit(s) whose emissions of a regulated NSR pollutant could be affected by the DTDC Upgrade Project, and
 - (3) A description of the applicability test used to determine that the DTDC Upgrade Project is not a major modification for any regulated NSR pollutant, including the baseline actual emissions (BAE), the projected actual emissions (PAE), the amount of emissions excluded under paragraph "3" of the definition of "projected actual emissions" in subrule 33.3(1), an explanation describing why such amount was

excluded, and any netting analysis if applicable.

7. In accordance with 567 IAC 33.3(18) "f"(4), the owner or operator shall:
 - (1) Monitor the emission of any regulated NSR pollutant that could increase as a result of the DTDC Upgrade Project that is emitted by any emissions unit identified in Condition F.(2).
 - (2) Calculate and record the annual emissions, in tons per year on a calendar-year basis, for a period of 10 years following resumption of regular operations and maintain a record of regular operations after the change.
8. In accordance with 567 IAC 33.3(18) "f"(5), the owner or operator shall retain a written record containing the information required in Condition G. of this permit for a period of 10 years after the date of permit issuance.
9. In accordance with 567 IAC 33.3(18) "g", the owner or operator shall make the information required to be documented and maintained pursuant to 567 IAC 33.3(18) "f" available for review upon request for inspection by this agency or the general public pursuant to the requirements for Title V operating permits contained in 567 IAC 24.107(6).

Authority for Requirement: Polk County Construction Permit Number 1626 Modified #5

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 120

Stack Diameter (inches): 60

Stack Exhaust Flow Rate (scfm): 96,000

Stack Temperature (°F): 140

Discharge Style: Vertical, Unobstructed

Authority for Requirement: Polk County Construction Permit Number 1626 Modified #5

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP MP01 shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer's signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an

opacity $\geq 20\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: MP02A – Meal Grinding / Meal Transfer / Flowability Agent Silo / Concrete Meal Storage Tank #2 / Hull Pellet Storage Tank

Associated Equipment

EU	Emission Unit Description	Raw Material	Rated Capacity	Control Equipment Description and ID
MP02A	Meal Grinding	Bean Meal	215 Tons/hr	CE MP02A: Baghouse
MP03	Meal Transfer	Bean Meal	215 Tons/hr	
MP04	Flowability Agent Silo	Flowability Agent	215 Tons/hr	
MP08B	Concrete Meal Storage Tank #2	Bean Meal	215 Tons/hr	
HR04	Hull Pellet Storage Tank	Hulls	19.25 Tons/hr	

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit: <20%

Authority for Requirement: Polk County Construction Permit Number 0090 Modified #6

Pollutant: PM

Emission Limit: 0.10 gr/dscf

Authority for Requirement: Polk County Construction Permit Number 0090 Modified #6
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-14(3)

Pollutant: PM₁₀

Emission Limit: 0.67 lb/hr

Authority for Requirement: Polk County Construction Permit Number 0090 Modified #6

Pollutant: PM_{2.5}

Emission Limit: 0.67 lb/hr

Authority for Requirement: Polk County Construction Permit Number 0090 Modified #6

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

- The facility (plant number 77-01-045) shall not process more than 1,971,000 tons of soybeans per 12-month period, rolled monthly
- The owner or operator shall maintain and operate the equipment, including control equipment, at all times in a manner consistent with good practice for minimizing emissions.
- Control equipment (baghouse) shall be used at all times while the Meal System (EU: MP02A, MP03, MP04, MP08B, and HR04) is in operation.
- The owner or operator shall perform routine maintenance and inspections as per manufacturer's guidance for the product line equipment and control equipment (baghouse).
- The owner or operator shall maintain records of maintenance activities on the Meal System (EU: MP02A, MP03, MP04, MP08B, and HR04) equipment, including control equipment (baghouse).
- The owner or operator shall record the following:
 - a. The amount of soybeans processed per hour (both in bushels and tons) for each hour of operation,
 - b. The amount of soybeans processed per day (both in bushels and tons) for each day of operation,
 - c. The total amount of soybeans processed per month (both in bushels and tons) for each month of operation, and
 - d. The annual amount of soybeans processed (both in bushels and tons) on a rolling 12-month basis for each month of operation.

Authority for Requirement: Polk County Construction Permit Number 0090 Modified #6

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 120

Stack Diameter (inches): 34

Stack Exhaust Flow Rate (scfm): 23,840

Stack Temperature (°F): 81

Discharge Style: Vertical, Unobstructed

Authority for Requirement: Polk County Construction Permit Number 0090 Modified #6

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP MP02A shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity $\geq 20\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source’s compliance with the applicable requirements.

The data pertaining to the plan must be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility’s implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: MP06A – Meal Conveying & Meal Loading

Associated Equipment

EU	Emission Unit Description	Raw Material	Rated Capacity	Control Equipment Description and ID
MP05	Meal Conveying	Bean Meal	350 Tons/hr	CE MO06A: Baghouse
MP06	Meal Loading	Bean Meal	350 Tons/hr	

Applicable Requirements**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit: <20%

Authority for Requirement: Polk County Construction Permit Number 2128 Modified #2

Pollutant: PM

Emission Limits: 0.75 lb/hr, 3.29 TPY, and 0.10 gr/dscf

Authority for Requirement: Polk County Construction Permit Number 2128 Modified #2
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-14(3)

Pollutant: PM₁₀

Emission Limits: 0.75 lb/hr, 3.29 TPY

Authority for Requirement: Polk County Construction Permit Number 2128 Modified #2

Pollutant: PM_{2.5}

Emission Limits: 0.75 lb/hr, 3.29 TPY

Authority for Requirement: Polk County Construction Permit Number 2128 Modified #2

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. The facility shall not process more than 1,971,000 tons of soybeans per 12 month period, rolled monthly.
2. The facility shall record and maintain daily records of the tons of soybeans processed. Said records shall be maintained on site for a minimum period of 10 years and shall be made available to representatives of this agency upon request.

Authority for Requirement: Polk County Construction Permit Number 2128 Modified #2

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 30

Stack Diameter (inches): 46

Exhaust Flow Rate (acfm): 40,150

Exhaust Temperature (°F): Ambient

Discharge Style: Vertical, Unobstructed

Authority for Requirement: Polk County Construction Permit Number 2128 Modified #2

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP MP06A shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity $\geq 20\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source’s compliance with the applicable requirements.

The data pertaining to the plan must be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility’s implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: MP07A – Meal Rail Loadout

Associated Equipment

Emissions Control Equipment ID Number: MP07A
Emissions Control Equipment Description: MAC Model 144MPH416 Baghouse

Emission Unit vented through this Emission Point: MP07
Emission Unit Description: Meal Rail Loadout
Raw Material/Fuel: Meal
Rated Capacity: 250 Tons/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <20%
Authority for Requirement: Polk County Construction Permit Number 0105 Modified #4

Pollutant: PM
Emission Limit : 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 0105 Modified #4
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-14(3)

Pollutant: PM₁₀
Emission Limit: 0.75 lb/hr
Authority for Requirement: Polk County Construction Permit Number 0105 Modified #4

Pollutant: PM_{2.5}
Emission Limit: 0.75 lb/hr
Authority for Requirement: Polk County Construction Permit Number 0105 Modified #4

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. The facility shall not process more than 1,971,000 tons of soybeans per 12 month period, rolled monthly.
2. The owner or operator shall maintain and operate the equipment, including control equipment, at all times in a manner consistent with good practice for minimizing emissions.
3. Control equipment (baghouse) shall be used at all times while the EU MP07 is in operation.
4. The owner or operator shall perform routine maintenance and inspections as per manufacturer's guidance for the product line equipment and control equipment (baghouse).
5. The owner or operator shall maintain records of maintenance activities on the EU MP07 equipment, including control equipment (baghouse).
6. The owner or operator shall record the following:
 - a. The amount of soybeans processed per hour (both in bushels and tons) for each hour of operation,
 - b. The amount of soybeans processed per day (both in bushels and tons) for each day of operation,
 - c. The total amount of soybeans processed per month (both in bushels and tons) for each month of operation, and
 - d. The annual amount of soybeans processed (both in bushels and tons) on a rolling 12-month basis for each month of operation.

Authority for Requirement: Polk County Construction Permit Number 0105 Modified #4

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 90

Stack Diameter (inches): 34

Exhaust Flow Rate (scfm): 17,667

Exhaust Temperature (°F): Ambient

Discharge Style: Vertical, unobstructed

Authority for Requirement: Polk County Construction Permit Number 0105 Modified #4

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP MP07A shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity $\geq 20\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source’s compliance with the applicable requirements.

The data pertaining to the plan must be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility’s implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: MP010 – Meal/Hull Unloading Pit

Associated Equipment

Emission Unit vented through this Emission Point: MP010
Emission Unit Description: Meal/Hull Unloading Pit
Raw Material/Fuel: Soybean meal and hulls
Rated Capacity: 260 tons/hour

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: 5%
Authority for Requirement: Polk County Construction Permit Number 1775

Pollutant: PM
Emission Limit: 28.22 lb/hr, 1.62 TPY, and 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 1775
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-14(3)

Pollutant: PM₁₀
Emission Limit: 10.15 lb/hr, 0.59 TPY
Authority for Requirement: Polk County Construction Permit Number 1775

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. The facility is limited to receiving 21,000 tons of meal and 2,000 tons of hulls/hull pellets per 12 month period rolled monthly in EU MP010.
2. The facility shall maintain a log of the amount of meal, hulls and hull pellets received in EU MP010. The amounts shall be totaled monthly and a rolling 12 month total shall be recorded.
3. Said log shall be made available to representatives of Polk County AQD upon request.

Authority for Requirement: Polk County Construction Permit Number 1775

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP MP10 shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity > 5% is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: R01 – Filter Aid Receiving/Storage

Associated Equipment

Associated Emission Unit ID Number : R01
Emissions Control Equipment ID Number: R01
Emissions Control Equipment Description: Flex-Kleen Model 84-BV-9 Baghouse

Emission Unit vented through this Emission Point: R01
Emission Unit Description: Filter Aid Receiving/Storage
Raw Material/Fuel: Filter Aid
Rated Capacity: 6 Tons/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <40%
Authority for Requirement: Polk County Board of Health Rules and Regulations
Chapter V, Section 5-9

Pollutant: PM
Emission Limit: 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 0366
Polk County Board of Health Rules and Regulations
Chapter V, Section 5-14(3)

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP R01 shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity $\geq 40\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source’s compliance with the applicable requirements.

The data pertaining to the plan must be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility’s implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: R02 – Bleaching Clay Receiving/Storage

Associated Equipment

Associated Emission Unit ID Numbers: R02
Emissions Control Equipment ID Number: R02
Emissions Control Equipment Description: Flex-Kleen Model # 84-BV-9 Baghouse

Emission Unit vented through this Emission Point: R02
Emission Unit Description: Bleaching Clay Receiving/Storage
Raw Material/Fuel: Bleaching Clay
Rated Capacity: 7.5 Tons/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <40%
Authority for Requirement: Polk County Board of Health Rules and Regulations
Chapter V, Section 5-9

Pollutant: PM
Emission Limit: 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 0367
Polk County Board of Health Rules and Regulations
Chapter V, Section 5-14(3)

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP R02 shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity $\geq 40\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source’s compliance with the applicable requirements.

The data pertaining to the plan must be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility’s implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: R03 – Slurry/Precoat Tanks

Associated Equipment

Associated Emission Unit ID Number: R03
Emissions Control Equipment ID Number: R03
Emissions Control Equipment Description: Ducon Model # 3 Scrubber

Emission Unit vented through this Emission Point: R03
Emission Unit Description: Slurry/Precoat Tanks
Raw Material/Fuel: Filter Aid/Bleaching Clay/Vegetable Oil
Rated Capacity: 1.6 Ton/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <20%
Authority for Requirement: Polk County Construction Permit Number 0414 Modified #2

Pollutant: PM
Emission Limits: 0.90 lb/hr, 3.94 Tons/yr, 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 0414 Modified #2
Polk County Board of Health Rules and Regulations
Chapter V, Section 5-14(3)

Pollutant: PM₁₀
Emission Limits: 0.90 lb/hr, 3.94 Tons/yr, 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 0414 Modified #2

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. The facility shall not process more than 1,971,000 tons of soybeans per 12 month period, rolled monthly.
2. The facility shall record and maintain daily records of the tons of soybeans processed. Said records shall be maintained on site for a minimum period of 10 years and shall be made available to representatives of this agency upon request.

Authority for Requirement: Polk County Construction Permit Number 0414 Modified #2

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 29.5

Stack Diameter (inches): 12

Exhaust Flow Rate (acfm): 1,600

Exhaust Temperature (°F): 150

Discharge Style: Vertical Unobstructed

Authority for Requirement: Polk County Construction Permit Number 0414 Modified #2

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP R03 shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity $\geq 20\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source’s compliance with the applicable requirements.

The data pertaining to the plan must be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility’s implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: R04 – Filter Aid/ Bleaching Clay Day Bins

Associated Equipment

Associated Emission Unit ID Number: R04
Emissions Control Equipment ID Number: R04A, R04B
Emissions Control Equipment Description: 2-Torrit Day Model Number 84-OB Bag-
filters (R04A, R04B)

Emission Unit vented through this Emission Point: R04
Emission Unit Description: Day Bins
Raw Material/Fuel: Filter Aid/ Bleaching Clay
Rated Capacity: 1.6 ton/ hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <40%
Authority for Requirement: Polk County Board of Health Rules and Regulations
Chapter V, Section 5-9

Pollutant: PM
Emission Limit: 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permits Numbered 0368, 0369
Polk County Board of Health Rules and Regulations
Chapter V, Section 5-14 (3)

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP R04 shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity $\geq 40\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source’s compliance with the applicable requirements.

The data pertaining to the plan must be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility’s implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: R06 – Refinery Cooling Tower

Associated Equipment

Emission Unit vented through this Emission Point: R06
Emission Unit Description: 3 cell Refinery Cooling Tower
Raw Material/Fuel: Water
Rated Capacity: 6,000 gallon/ minute

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <40%
Authority for Requirement: Polk County Board of Health Rules and Regulations
Chapter V, Section 5-9

Pollutant: PM
Emission Limits: 0.45 lb/hr, 1.97 Tons/yr, 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 2134
Polk County Board of Health Rules and Regulations
Chapter V, Section 5-14

Pollutant: PM₁₀
Emission Limits: 0.225 lb/hr, 0.99 TPY, 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 2134

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. The owner or operator shall not use any chromium based water treatment chemicals in the cooling tower.
2. The owner or operator shall not use any water treatment chemicals in the cooling tower containing VOC or HAP compounds.
3. Technical Data Sheets of all additives to the cooling tower shall be maintained on-site.
4. The Total Dissolved Solids (TDS) level shall not exceed 3,000 mg/l.

5. The owner or operator shall install a continuous conductivity monitor. The conductivity monitor shall initiate blowdown when the conductivity reaches a level equivalent to a TDS concentration of no greater than 3,000 mg/l
6. All records required above shall be maintained on-site for a period of five (5) years and shall be made available to representatives of Polk County AQD upon request.

Authority for Requirement: Polk County Construction Permit Number 2134

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

**Emission Point ID Number: R08 – Detroit Diesel Allison Diesel
Fire Pump at Refinery**

Associated Equipment

Emission Unit vented through this Emission Point: R08
Emission Unit Description: Detroit Diesel Allison Diesel Fire Pump at Refinery
Raw Material/Fuel: Diesel
Rated Capacity: 357 hp (18.2 gallons/hour)

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <20%
Authority for Requirement: Polk County Construction Permit Number 3411 Modified

Pollutant: PM
Emission Limit: 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 3411 Modified
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-14(3)

Pollutant: PM₁₀
Emission Limit: 0.79 lb/hr
Authority for Requirement: Polk County Construction Permit Number 3411 Modified

Pollutant: PM_{2.5}
Emission Limit: 0.79 lb/hr
Authority for Requirement: Polk County Construction Permit Number 3411 Modified

Pollutant: SO₂
Emission Limit: 0.5 lb/MMBtu
Authority for Requirement: Polk County Construction Permit Number 3411 Modified
Polk County Board of Health Rules and Regulations
Chapter V, Article IX, Section 5-27

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

NESHAP Requirements:

Operation and Maintenance Requirements 40 CFR 63.6603, 63.6625, 63.6640 and Tables 2c and 6 to Subpart ZZZZ

1. Change oil and filter every 500 hours of operation or 1 year + 30 days, whichever comes first. (See 63.6625(i) for the oil analysis option to extend time frame of requirements.)
2. Inspect air cleaner every 1000 hours of operation or 1 year + 30 days , whichever comes first, and replace as necessary.
3. Inspect all hoses and belts every 500 hours of operation or 1 year + 30 days , whichever comes first, and replace as necessary.
4. Operate and maintain the stationary RICE and after-treatment control device (if any) according to the manufacturer's emission related written instructions or develop your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions.
5. Install a non-resettable hour meter if one is not already installed.
6. Minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes.

Operating Limits 40 CFR 63.6640(f)

1. Any operation other than emergency operation, maintenance and testing, and operation in non-emergency situations (up to) 50 hours per year is prohibited.
2. There is no time limit on the use of emergency stationary RICE in emergency situations.
3. You may operate your emergency stationary RICE up to 100 combined hours per calendar year for maintenance checks and readiness testing. See 40 CFR 63.6640(f)(2) for additional information and restrictions.
4. You may operate your emergency stationary RICE up to 50 hours per calendar year for non-emergency situations, but those 50 hours are counted toward the 100 hours of maintenance and testing. Except as provided in 40 CFR 63.6640(f)(4)(i) and (ii), the 50 hours per year for non-emergency situations cannot be used for peak shaving, or to generate income for a facility to supply power to an electric grid or otherwise supply power as part of a financial arrangement with another entity.

Recordkeeping Requirements 40 CFR 63.6655

1. Keep records of the maintenance conducted on the stationary RICE.
2. Keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. Document how many hours are spent for emergency operation, including what classified the operation as emergency and how many hours are spent for non-emergency operation. See 40 CFR 63.6655(f) for additional information.

Notification and Reporting Requirements 40 CFR 63.6645, 63.6650 and Table 2c to Subpart ZZZZ

1. An initial notification is not required per 40 CFR 63.6645(a)(5).
2. A report may be required for failure to perform the work practice requirements on the schedule required in Table 2c. (See Footnote 2 of Table 2c for more information).

Operational Limits:

1. Operation shall be limited to five-hundred (500) hours per twelve (12) month period rolled and totaled monthly.
2. A non-resettable totalizing hour meter shall be installed on the unit.
3. The owner or operator shall maintain the following monthly records:
 - a. the number of hours that the engine is operated for maintenance checks and readiness testing.
 - b. the number of hours that the engine is operated for allowed non-emergency operations.
 - c. the total number of hours that the engine is operated.
 - d. each of the above records shall include the rolling 12-month total of hours for each category of operation (i.e. maintenance and readiness testing, non-emergency use, total hours of operation).
4. The owner or operator shall maintain the following annual records:
 - a. the number of hours that the engine operated for maintenance checks and readiness testing;
 - b. the number of hours that the engine operated for allowed non-emergency operations; and
 - c. the total number of hours that the engine operated for maintenance checks, readiness testing, and allowed non-emergency operations.
5. Sulfur content of fuel shall not exceed 0.05%. Fuel supplier certification of sulfur content shall be kept on site for each delivery of fuel oil purchased.

Authority for Requirement: Polk County Construction Permit Number 3411 Modified
40 CFR Part 63 Subpart ZZZZ
567 IAC 23.1(4)"cz"
Polk County Board of Health Rules and Regulations
Chapter V, Article VIII, Section 5-20

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 20

Stack Diameter (inches): 6

Stack Exhaust Flow Rate (scfm): 540

Stack Temperature (°F): 820

Discharge Style: Vertical, unobstructed

Authority for Requirement: Polk County Construction Permit Number 3411 Modified

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: R09 – Refinery - Steam Generator

Associated Equipment

Emission Unit vented through this Emission Point: R09
Emission Unit Description: Refinery - Steam Generator
Raw Material/Fuel: Natural Gas
Rated Capacity: 13.853 MM BTU/ hr; 13,581 ft³/ hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <20%
Authority for Requirement: Polk County Construction Permit Number 4006

Pollutant: PM
Emission Limit: 0.6 lb/MMBtu
Authority for Requirement: Polk County Construction Permit Number 4006
Polk County Board of Health Rules and Regulations
Chapter V, Article VI, Section 5-14(3)b

Pollutant: PM₁₀
Emission Limit: 0.06 lb/hr
Authority for Requirement: Polk County Construction Permit Number 4006

Pollutant: PM_{2.5}
Emission Limit: 0.06 lb/hr
Authority for Requirement: Polk County Construction Permit Number 4006

Pollutant: SO₂
Emission Limit: 500ppmv
Authority for Requirement: Polk County Construction Permit Number 4006
Polk County Board of Health Rules and Regulations
Chapter V, Article IX, Section 5-27

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

New Source Performance Standards (NSPS):

The following subparts apply to the listed emission unit in this permit:

Subpart	Title	Type	State Reference (567 IAC)	Federal Reference (40 CFR)
A	General Provisions	NA	23.1(2)	§60.1 – §60.19
Dc	Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units	Natural Gas	23.1(2)"III"	§60.40c – §60.48c

Authority for Requirement: Polk County Construction Permit Number 4006
40 CFR Part 60 Subpart Dc

National Emission Standards for Hazardous Air Pollutants (NESHAP):

This emission unit (EU R09) is subject to the following federal regulation: National Emission Standards for Hazardous Air Pollutants for Industrial, Commercial, and Institutional Boilers and Process Heaters (40 CFR §63.7480 – §63.7575, Subpart DDDDD).

Authority for Requirement: Polk County Construction Permit Number 4006
40 CFR Part 63 Subpart DDDDD

1. (EU R09) is limited to firing on natural gas.
2. The owner or operator shall operate and maintain this emission unit (EU R09) in accordance with manufacturer’s specifications. The owner or operator shall maintain a log of all inspections and maintenance activities performed on the emission unit (EU R09). This log shall include, but is not limited to:
 - a. The date and time any inspection and/or maintenance was performed on the emission unit (EU R09);
 - b. Any issues identified during the inspection and the date each issue was resolved;
 - c. Any issues addressed during the maintenance activities and the date each issue was resolved;
 - d. Identification of the staff member performing the maintenance or inspection.

Authority for Requirement: Polk County Construction Permit Number 4006

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 45.0

Stack Diameter (inches): 48

Stack Exhaust Flow Rate (scfm): 3,705

Stack Temperature (°F): 653

Discharge Style: Vertical Unobstructed

Authority for Requirement: Polk County Construction Permit Number 4006

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

**Emission Point ID Number: U03 Rail Receiving #1/ Conveying and
U03F Rail Receiving #1 Fugitive Emissions**

Associated Equipment

Associated Emission Unit ID Numbers: U03
Emissions Control Equipment ID Number: U03
Emissions Control Equipment Description: Donaldson Model 232-RFW-12 Baghouse

Emission Unit vented through this Emission Point: U03
Emission Unit Description: Rail Receiving #1/ Conveying and
Rail Receiving #1 Fugitive Emissions
Raw Material/Fuel: Soybeans
Rated Capacity: 960 tons/hour

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from Emission Point U03 shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limits: None allowed
Authority for Requirement: Polk County Construction Permit Number 0802 Modified
40 CFR60 Subpart DD
567 IAC 23.1(2)"ooo"
Polk County Board of Health Rules and Regulations Chapter
V, Article VI, Section 5-16 (14)

Pollutant: PM
Emission Limits: 2.57 lb/hr, 11.26 Tons/yr, 0.01 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 0802 Modified
40 CFR60 Subpart DD
567 IAC 23.1(2)"ooo"
Polk County Board of Health Rules and Regulations Chapter
V, Article VI, Section 5-16 (14)

Pollutant: PM/ PM₁₀
Emission Limits: 2.57 lb/hr, 11.26 Tons/yr, 0.01 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 0802 Modified

The emissions from Emission Point U03F shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit: 5%

Authority for Requirement: Polk County Construction Permit Number 0802 Modified
40 CFR60 Subpart DD
567 IAC 23.1(2)"ooo"
Polk County Board of Health Rules and Regulations Chapter
V, Article VI, Section 5-16 (14)

Pollutant: PM

Emission Limits: 1.54 lb/hr, 6.73 Tons/yr, 0.10 gr/dscf

Authority for Requirement: Polk County Construction Permit Number 0802 Modified
Polk County Board of Health Rules and Regulations Chapter
V, Article VI, Section 5-14 (3)

Pollutant: PM₁₀

Emission Limits: 0.37 lb/hr, 1.64 Tons/yr

Authority for Requirement: Polk County Construction Permit Number 0802 Modified
40 CFR60 Subpart DD
567 IAC 23.1(2)"ooo"
Polk County Board of Health Rules and Regulations Chapter
V, Article VI, Section 5-16 (14)

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height (feet): 28 minimum above grade

Stack Diameter (inches): 42

Stack Exhaust Flow Rate (acfm): 30,000

Stack Temperature (°F): Ambient

Discharge Style: Vertical with Obstructing Rain Cap

Authority for Requirement: Polk County Construction Permit Number 0802 Modified

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP U03F shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If fugitive emissions greater than five percent (5%) opacity are observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Stack Testing:

Pollutant - PM

Stack Test to be Completed by (date) – June 14, 2028

Test Method - 40 CFR Part 51, Appendix M, Method 202
in conjunction with a Method 201A

Authority for Requirement: 567 IAC 24.108(3)

The owner of this equipment or the owner’s authorized agent shall provide written notice to the Director, not less than 30 days before a required stack test or performance evaluation of a continuous emission monitor. Results of the test shall be submitted in writing to the Director in the form of a comprehensive report within 6 weeks of the completion of the testing. 567 IAC 25.1(7)

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Compliance Assurance Monitoring Plan:
Rail Receiving Number 1/ Conveying with Baghouse

Emission Unit Information

Grain Rail Receiving/Conveying

Emission Unit: Rail Receiving #1/ Conveying (U03)
Emission Control Technique: Baghouse
Control Device Identification Number: CE U03
Emission Point Identification Number: EP U03

Emissions generated by the grain rail receiving pit and conveying system are controlled by baghouse CE U03. Emission Point EP U03 is the exhaust for baghouse CE U03.

Applicable Requirement for U03

Pollutant: PM/PM₁₀
Emission Limits: 2.57 lb/hr, 11.26 Tons/yr, 0.01 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 0802 Modified
40 CFR60 Subpart DD
567 IAC 23.1(2)"ooo"
Polk County Chapter V, Article VI, Section 5-16 (14)

Monitoring Approach

Indicators

Indicator #1: Opacity (Visible Emission)

Visible Emissions (opacity) was selected as a performance indicator because it is indicative of good operation and maintenance of the baghouse. When the baghouse is operating optimally, there will be little to no visible emissions from the exhaust. In general, an increase in visible emissions indicates reduced performance of the baghouse.

Indicator #2: Pressure Drop

Pressure range across the filter bags in an indicator of baghouse performance. A pressure change outside the indicator range indicates a decrease in baghouse performance and potentially indicates an increase in particulate emissions. A pressure gauge is installed to measure the differential pressure between the baghouse inlet and outlet, allowing representative data to be obtained.

Indicator Range

Indicator #1: Opacity (Visible Emission)

The indicator range is visible emissions or no visible emissions.

Indicator #2: Pressure Drop

Control Equipment ID#	Emission Unit Description	Acceptable Indicator Range
CE U03	Rail Receiving #1/Conveying Baghouse	1-6" wg

Measurement Approach

Indicator #1: Opacity (Visible Emissions)

Visible emission observations will be performed weekly on the baghouse. If visible emissions are observed corrective action will be taken as soon as possible, but no later than eight hours from observation of visible emissions. Records of the weekly visible emission checks will be maintained for five years.

Indicator #2: Pressure Drop

Each day the baghouse is in operation, the pressure level across the filter bags will be manually recorded from the baghouse pressure gauge to ensure the level is within the appropriate operating range. Records of pressure readings will be maintained for five years.

Performance Criteria

To ensure the data collected is representative, visible emission observations and pressure drop readings will be taken when the equipment is operating. The person performing the observations and readings will be qualified to perform such duties and the individual performing the Method 9 readings, when required, will have a valid certification. The equipment will not be operating while corrective action is being performed.

Response to Excursion

Indicator #1: Opacity (Visible Emissions)

If visible emissions are observed during a weekly visible emissions check, corrective action will be taken as soon as possible, but no later than eight hours from observation of visible emissions. A deviation shall be reported in the semiannual compliance report.

Indicator #2: Pressure Drop

If an observed pressure drop across the filter bags is outside the appropriate operating range for more than five minutes, corrective action will be taken within 8 hours. A deviation shall be reported in the semiannual compliance report.

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: U05, U05A - Grain Storage - 4 West Bean Tanks

Associated Equipment

Emission Unit vented through this Emission Point: U05
Emission Unit Description: Grain storage – 4 West Bean Tanks
Raw Material/Fuel: Soybeans
Rated Capacity: 500 tons/hour

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from each emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit: <20%
Authority for Requirement: Polk County Construction Permit Number 2595

Pollutant: PM
Emission Limit: 0.59 lbs/hr, 2.58 TPY, 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 2595
567 IAC 23.4(7)
Polk County Board of Health Rules and Regulations
Chapter V, Section 5-16(1)

Pollutant: PM₁₀
Emission Limit: 0.59 lbs/hr, 2.58 TPY, 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 2595

Pollutant: PM_{2.5}
Emission Limit: 0.59 lbs/hr, 2.58 TPY, 0.10 gr/dscf
Authority for Requirement: Polk County Construction Permit Number 2595

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. The facility shall record and maintain daily records of the number of tons of soybeans processed.

Authority for Requirement: Polk County Construction Permit Number 2595

Emission Point Characteristics

The emission points shall conform to the specifications listed below.

Emission Point Characteristic	U05A: 24 round vents
Shape	Circular
Size/Diameter	24 inches
Height Above Ground	70.8 feet
Discharge Style	Vertical Obstructed
Rated Flow Rate (scfm)	N/A
Exhaust Temperature	Ambient

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Authority for Requirement: Polk County Construction Permit Number 2595

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP U05, U05A shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer’s signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity $\geq 20\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

**Emission Point ID Numbers: U07, U07F – West Side Truck Dump,
East Side Truck Dump, Grain Conveyor,
and Truck Dump Fugitive Emissions**

Associated Equipment

Associated Emission Unit ID Numbers: U01, U02, U04

Emissions Control Equipment ID Number: U07

Emissions Control Equipment Description: Donaldson Model 376 RFW-10 Baghouse

Emission Units vented through this Emission Point: U01, U02, U04

Emission Unit Descriptions: West Side Truck Dump, East Side Truck Dump,
Grain Conveyor, and Truck Dump Fugitive Emissions

Raw Material/Fuel: Soybeans

Rated Capacity: 600 Tons/hour per truck dump

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from Emission Point U07 shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit: <20%

Authority for Requirement: Polk County Construction Permit Number 2235 Modified

Pollutant: PM

Emission Limit: 1.132 lb/hr, 0.55 Tons/yr, 0.10 gr/dscf

Authority for Requirement: Polk County Construction Permit Number 2235 Modified
567 IAC 23.4(7)
Polk County Board of Health Rules and Regulations
Chapter VI, Section 5-14(3)

Pollutant: PM₁₀

Emission Limit: 1.132 lb/hr, 0.55 Tons/yr

Authority for Requirement: Polk County Construction Permit Number 2235 Modified

Pollutant: PM_{2.5}

Emission Limit: 1.132 lb/hr, 0.55 Tons/yr

Authority for Requirement: Polk County Construction Permit Number 2235 Modified

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from Emission Point U07F (Fugitive) shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit: <20%

Authority for Requirement: Polk County Construction Permit Number 2235 Modified

Pollutant: PM

Emission Limits: 2.10 lb/hr, 1.84 Tons/yr

Authority for Requirement: Polk County Construction Permit Number 2235 Modified

Pollutant: PM₁₀

Emission Limits: 0.468 lb/hr, 0.41 Tons/yr

Authority for Requirement: Polk County Construction Permit Number 2235 Modified

Pollutant: PM_{2.5}

Emission Limits: 0.078 lb/hr, 0.07 Tons/yr

Authority for Requirement: Polk County Construction Permit Number 2235 Modified

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. The facility shall not process more than 1,971,000 tons of soybeans per 12 month period, rolled monthly.
2. The facility shall record and maintain daily records of the tons of soybeans processed. Said records shall be maintained on site for a minimum period of 10 years and shall be made available to representatives of this agency upon request.

Authority for Requirement: Polk County Construction Permit Number 2235 Modified

Emission Point Characteristics

Emission Point U07 shall conform to the specifications listed below.

Stack Height (feet): 50

Stack Diameter (inches): 44

Stack Exhaust Flow Rate (acfm): 30,000

Stack Temperature (°F): Ambient

Discharge Style: Vertical, Unobstructed

Authority for Requirement: Polk County Construction Permit Number 2235 Modified

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Emission Point U07F shall conform to the specifications listed below.

EP U07F is Truck Dump fugitive emissions.
Authority for Requirement: Polk County Construction Permit Number 2235 Modified

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

EP U07 and EP U07F shall be visually checked for observable emissions once every week by a designated observer. The observation shall be taken while the equipment is operating at or near full capacity. The observation shall be noted in a log book, which shall state the date, time, observer's signature, and whether any emissions were observed. If visible emissions are observed, corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity $\geq 20\%$ is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits. The log book will be maintained on site for 5 years and be made available to representatives of Polk County AQD upon request.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

Emission Point ID Number: U08 – Haul Roads- Truck Traffic Fugitive Emissions

Associated Equipment

EU ID	EU Description	Maximum Rated Capacity	Control Equipment Description and ID
BEN	Soybean Receiving	57,670 VMT	Weekly sweeping /vacuuming requirements
MEL	Meal/ Hull Truck Loadout	19,163 VMT	
OIL	Oil Loadout	7,083 VMT	
HEX	Hexane Receiving	6.23 VMT	Maximum speed limit of 5 MPH
FLO	Flowability Agent Receiving	167.90 VMT	

Raw Material/Fuel: Fugitive Dust
 Rated Capacity: Not Applicable

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
 Emission Limit: <20%
 Authority for Requirement: Polk County Construction Permit Number 2828 Modified

Pollutant: PM
 Emission Limit: 1.0 g/m2 silt
 Authority for Requirement: Polk County Construction Permit Number 2828 Modified
 Iowa Department of Natural Resources (DNR) Administrative Consent Order No. 2023-AQ-15 (May 24, 2023).

Pollutant: PM₁₀
 Emission Limit: 1.0 g/m2 silt
 Authority for Requirement: Polk County Construction Permit Number 2828 Modified
 Iowa Department of Natural Resources (DNR) Administrative Consent Order No. 2023-AQ-15 (May 24, 2023).

Pollutant: PM_{2.5}

Emission Limit: 1.0 g/m² silt

Authority for Requirement: Polk County Construction Permit Number 2828 Modified
Iowa Department of Natural Resources (DNR) Administrative
Consent Order No. 2023-AQ-15 (May 24, 2023).

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. The facility shall be limited to a total maximum annual truck traffic for each of the Haul Roads processes:
 - a. Soybean Receiving (BNE) shall be limited to 57,670 vehicle miles traveled (VMT).
 - b. Meal/Hull Truck Loadout (MEL) shall be limited to 19,163 VMT.
 - c. Oil Loadout (OIL) shall be limited to 7,083 VMT.
 - d. Hexane Receiving (HEX) shall be limited to 6.23 VMT.
 - e. Flowability Agent Receiving (FLO) shall be limited to 167.90 VMT.
2. The facility shall record on a monthly basis the VMT for each Haul Roads process (BNE, MEL, OIL, HEX and FLO) per 12-month period, rolled monthly.
3. The road surface silt loading concentration shall not exceed 1.0 g/m².
4. Truck Traffic on the haul roads shall not exceed 5 mph. The speed limit shall be posted.
5. Truck loads shall be covered leaving the property when covers are available.
6. Any spills on the road shall be cleaned up as soon as practical.
7. The facility shall sweep/vacuum the haul roads a minimum of once per week.
8. The sweeping/vacuuming need not occur when:
 - a. Salt or sand is applied to the road for worker safety.
 - b. When the roads are wet from precipitation.
9. Salt or sand is applied to the road for worker safety.
10. The facility shall maintain a record of the sweeping/vacuuming activities and shall include a record of any deviation from the listed requirements due to suspended use of the haul roads or weather conditions.

Authority for Requirement: Polk County Construction Permit Number 2828 Modified

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Silt Testing:

Silt Testing to be Completed – Quarterly¹

Test Method - Silt load testing shall be conducted according to the procedures outlined in AP-42, Appendix C.1 (Procedures for Sampling Surface/Bulk Dust Loading) and C.2 (Procedures for Laboratory Analysis of Surface/Bulk Dust Loading Samples).

Authority for Requirement: Polk County Construction Permit Number 2828 Modified

¹ The facility may petition the PCAQD to request a reduced testing schedule after demonstrating

compliance with the silt loading standard of 1.0 g/m² for eight consecutive quarters.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 24.108(3)

IV. General Conditions

This permit is issued under the authority of the Iowa Code subsection 455B.133(8) and in accordance with 567 Iowa Administrative Code (IAC). When 567 IAC as amended May 15, 2024, and cited in this permit becomes State Implementation Plan (SIP) approved, it will supersede 567 IAC as amended February 8, 2023. Prior to May 15, 2024, all Title V rule citations in this Title V permit were found and cited in 567 IAC Chapter 22. During the period from May 15, 2024, to the date that 567 IAC as amended May 15, 2024, is approved into the SIP, both 567 IAC as amended May 15, 2024, and 567 IAC as amended February 8, 2023 form the legal basis for the applicable requirements included in this permit. A crosswalk showing the citation changes is attached to this permit in Appendix 2.

G1. Duty to Comply

1. The permittee must comply with all conditions of the Title V permit. Any permit noncompliance constitutes a violation of the Act and is grounds for enforcement action; for a permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application. *567 IAC 24.108(9)"a"*
2. Any compliance schedule shall be supplemental to, and shall not sanction noncompliance with, the applicable requirements on which it is based. *567 IAC 24.105(2)"h"(3)*
3. Where an applicable requirement of the Act is more stringent than an applicable requirement of regulations promulgated under Title IV of the Act, both provisions shall be enforceable by the administrator and are incorporated into this permit. *567 IAC 24.108(1)"b"*
4. Unless specified as either "state enforceable only" or "local program enforceable only", all terms and conditions in the permit, including provisions to limit a source's potential to emit, are enforceable by the administrator and citizens under the Act. *567 IAC 24.108(14)*
5. It shall not be a defense for a permittee, in an enforcement action, that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. *567 IAC 24.108(9)"b"*
6. For applicable requirements with which the permittee is in compliance, the permittee shall continue to comply with such requirements. For applicable requirements that will become effective during the permit term, the permittee shall meet such requirements on a timely basis. *567 IAC 24.108(15)"c"*

G2. Permit Expiration

1. Except as provided in rule 567—24.104(455B), permit expiration terminates a source's right to operate unless a timely and complete application for renewal has been submitted in accordance with rule 567—24.105(455B). *567 IAC 24.116(2)*
2. To be considered timely, the owner, operator, or designated representative (where applicable) of each source required to obtain a Title V permit shall submit on forms or electronic format specified by the Department. Additional copies to local programs or EPA are not required for application materials submitted through the electronic format specified by the Department. The application must include all emission points, emission units, air pollution control equipment, and monitoring devices at the facility. All emissions generating activities, including fugitive emissions, must be included. The definition of a complete application is as indicated in 567 IAC 24.105(2). *567 IAC 24.105*

G3. Certification Requirement for Title V Related Documents

Any application, report, compliance certification or other document submitted pursuant to this permit shall contain certification by a responsible official of truth, accuracy, and completeness. All certifications shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete. *567 IAC 24.107(4)*

G4. Annual Compliance Certification

By March 31 of each year, the permittee shall submit compliance certifications for the previous calendar year. The certifications shall include descriptions of means to monitor the compliance status of all emissions sources including emissions limitations, standards, and work practices in accordance with applicable requirements. The certification for a source shall include the identification of each term or condition of the permit that is the basis of the certification; the compliance status; whether compliance was continuous or intermittent; the method(s) used for determining the compliance status of the source, currently and over the reporting period consistent with all applicable department rules. For sources determined not to be in compliance at the time of compliance certification, a compliance schedule shall be submitted which provides for periodic progress reports, dates for achieving activities, milestones, and an explanation of why any dates were missed and preventive or corrective measures. The compliance certification shall be submitted to the administrator, director, and Polk County Air Quality Division. *567 IAC 24.108(15)"e"*

G5. Semi-Annual Monitoring Report

By March 31 and September 30 of each year, the permittee shall submit a report of any monitoring required under this permit for the 6 month periods of July 1 to December 31 and January 1 to June 30, respectively. All instances of deviations from permit requirements must be clearly identified in these reports, and the report must be signed by a responsible official, consistent with *567 IAC 24.107(4)*. The semi-annual monitoring report shall be submitted to the director and the appropriate Polk County Air Quality Division. *567 IAC 24.108 (5)*

G6. Annual Fee

1. The permittee is required under subrule *567 IAC 24.106* to pay an annual fee based on the total tons of actual emissions of each regulated air pollutant. Beginning July 1, 1996, Title V operating permit fees will be paid on July 1 of each year. The fee shall be based on emissions for the previous calendar year.
2. The fee amount shall be calculated based on the first 4,000 tons of each regulated air pollutant emitted each year. The fee to be charged per ton of pollutant will be available from the department by June 1 of each year. The Responsible Official will be advised of any change in the annual fee per ton of pollutant.
3. The emissions inventory shall be submitted annually by March 31 with forms specified by the department documenting actual emissions for the previous calendar year.
4. The fee shall be submitted annually by July 1 with forms specified by the department.
5. If there are any changes to the emission calculation form, the department shall make revised forms available to the public by January 1. If revised forms are not available by January 1, forms from the previous year may be used and the year of emissions documented changed. The department shall calculate the total statewide Title V

emissions for the prior calendar year and make this information available to the public no later than April 30 of each year.

6. Phase I acid rain affected units under section 404 of the Act shall not be required to pay a fee for emissions which occur during the years 1993 through 1999 inclusive.
7. The fee for a portable emissions unit or stationary source which operates both in Iowa and out of state shall be calculated only for emissions from the source while operating in Iowa.
8. Failure to pay the appropriate Title V fee represents cause for revocation of the Title V permit as indicated in 567 IAC 24.115(1)"d".

G7. Inspection of Premises, Records, Equipment, Methods and Discharges

Upon presentation of proper credentials and any other documents as may be required by law, the permittee shall allow the director or the director's authorized representative to:

1. Enter upon the permittee's premises where a Title V source is located or emissions-related activity is conducted, or where records must be kept under the conditions of the permit;
2. Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
3. Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
4. Sample or monitor, at reasonable times, substances or parameters for the purpose of ensuring compliance with the permit or other applicable requirements. *567 IAC 24.108 (15)"b" and Chapter V, Article II, 5-3 and 5-4*

G8. Duty to Provide Information

The permittee shall furnish to the director, within a reasonable time, any information that the director may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee also shall furnish to the director copies of records required to be kept by the permit, or for information claimed to be confidential, the permittee shall furnish such records directly to the administrator of EPA along with a claim of confidentiality. *567 IAC 24.108 (9)"e" and Chapter V, Article X, 5-46 and 5-47*

G9. General Maintenance and Repair Duties

The owner or operator of any air emission source or control equipment shall:

1. Maintain and operate the equipment or control equipment at all times in a manner consistent with good practice for minimizing emissions.
2. Remedy any cause of excess emissions in an expeditious manner.
3. Minimize the amount and duration of any excess emission to the maximum extent possible during periods of such emissions. These measures may include but not be limited to the use of clean fuels, production cutbacks, or the use of alternate process units or, in the case of utilities, purchase of electrical power until repairs are completed.
4. Schedule, at a minimum, routine maintenance of equipment or control equipment during periods of process shutdowns to the maximum extent possible. *567 IAC 21.8(1) and Chapter V, Article VI, Section 5-17.1*

G10. Recordkeeping Requirements for Compliance Monitoring

1. In addition to any source specific recordkeeping requirements contained in this permit, the permittee shall maintain the following compliance monitoring records, where applicable:
 - a. The date, place and time of sampling or measurements
 - b. The date the analyses were performed.
 - c. The company or entity that performed the analyses.
 - d. The analytical techniques or methods used.
 - e. The results of such analyses; and
 - f. The operating conditions as existing at the time of sampling or measurement.
 - g. The records of quality assurance for continuous compliance monitoring systems (including but not limited to quality control activities, audits and calibration drifts.)
2. The permittee shall retain records of all required compliance monitoring data and support information for a period of at least 5 years from the date of compliance monitoring sample, measurement report or application. Support information includes all calibration and maintenance records and all original strip chart recordings for continuous compliance monitoring, and copies of all reports required by the permit.
3. For any source which in its application identified reasonably anticipated alternative operating scenarios, the permittee shall:
 - a. Comply with all terms and conditions of this permit specific to each alternative scenario.
 - b. Maintain a log at the permitted facility of the scenario under which it is operating.
 - c. Consider the permit shield, if provided in this permit, to extend to all terms and conditions under each operating scenario. *567 IAC 24.108(4), 567 IAC 24.108(12)*

G11. Evidence used in establishing that a violation has or is occurring.

Notwithstanding any other provisions of these rules, any credible evidence may be used for the purpose of establishing whether a person has violated or is in violation of any provisions herein.

1. Information from the use of the following methods is presumptively credible evidence of whether a violation has occurred at a source:
 - a. A monitoring method approved for the source and incorporated in an operating permit pursuant to 567 Chapter 24;
 - b. Compliance test methods specified in 567 Chapter 21; or
 - c. Testing or monitoring methods approved for the source in a construction permit issued pursuant to 567 Chapter 22.
2. The following testing, monitoring or information gathering methods are presumptively credible testing, monitoring, or information gathering methods:
 - a. Any monitoring or testing methods provided in these rules; or
 - b. Other testing, monitoring, or information gathering methods that produce information comparable to that produced by any method in subrule 21.5(1) or this subrule. *567 IAC 21.5(1)-567 IAC 21.5(2)*

G12. Prevention of Accidental Release: Risk Management Plan Notification and Compliance Certification

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Act, the permittee shall notify the department of this requirement. The plan shall be filed with all appropriate authorities by the deadline specified by EPA. A certification that this risk management plan is being properly implemented shall be included in the annual compliance certification of this permit. *567 IAC 24.108(6)*

G13. Hazardous Release

The permittee must report any situation involving the actual, imminent, or probable release of a hazardous substance into the atmosphere which, because of the quantity, strength and toxicity of the substance, creates an immediate or potential danger to the public health, safety or to the environment. A verbal report shall be made to the department at (515) 725-8694 and to the local police department or the office of the sheriff of the affected county as soon as possible but not later than six hours after the discovery or onset of the condition. This verbal report must be followed up with a written report as indicated in 567 IAC 131.2(2). *567 IAC Chapter 131-State Only*

G14. Excess Emissions and Excess Emissions Reporting Requirements

1. Excess Emissions. Excess emission during a period of startup, shutdown, or cleaning of control equipment is not a violation of the emission standard if the startup, shutdown or cleaning is accomplished expeditiously and in a manner consistent with good practice for minimizing emissions. Cleaning of control equipment which does not require the shutdown of the process equipment shall be limited to one six-minute period per one-hour period. An incident of excess emission (other than an incident during startup, shutdown or cleaning of control equipment) is a violation. If the owner or operator of a source maintains that the incident of excess emission was due to a malfunction, the owner or operator must show that the conditions which caused the incident of excess emission were not preventable by reasonable maintenance and control measures. Determination of any subsequent enforcement action will be made following review of this report. If excess emissions are occurring, either the control equipment causing the excess emission shall be repaired in an expeditious manner or the process generating the emissions shall be shutdown within a reasonable period of time. An expeditious manner is the time necessary to determine the cause of the excess emissions and to correct it within a reasonable period of time. A reasonable period of time is eight hours plus the period of time required to shut down the process without damaging the process equipment or control equipment. A variance from this subrule may be available as provided for in Iowa Code section 455B.143. In the case of an electric utility, a reasonable period of time is eight hours plus the period of time until comparable generating capacity is available to meet consumer demand with the affected unit out of service, unless, the director shall, upon investigation, reasonably determine that continued operation constitutes an unjustifiable environmental hazard and issue an order that such operation is not in the public interest and require a process shutdown to commence immediately.

2. Excess Emissions Reporting

a. Initial Reporting of Excess Emissions. An incident of excess emission (other than an incident of excess emission during a period of startup, shutdown, or cleaning) shall be reported to the appropriate field office of the department within eight hours of, or at the start of the first working day following the onset of the incident. The

reporting exemption for an incident of excess emission during startup, shutdown or cleaning does not relieve the owner or operator of a source with continuous monitoring equipment of the obligation of submitting reports required in 567-subrule 21.10(6). An initial report of excess emission is not required for a source with operational continuous monitoring equipment (as specified in 567-subrule 21.10(1)) if the incident of excess emission continues for less than 30 minutes and does not exceed the applicable emission standard by more than 10 percent or the applicable visible emission standard by more than 10 percent opacity. The initial report may be made by electronic mail (E-mail), in person, or by telephone and shall include as a minimum the following:

- i. The identity of the equipment or source operation from which the excess emission originated and the associated stack or emission point.
- ii. The estimated quantity of the excess emission.
- iii. The time and expected duration of the excess emission.
- iv. The cause of the excess emission.
- v. The steps being taken to remedy the excess emission.
- vi. The steps being taken to limit the excess emission in the interim period.

b. Written Reporting of Excess Emissions. A written report of an incident of excess emission shall be submitted as a follow-up to all required initial reports to the department within seven days of the onset of the upset condition, and shall include as a minimum the following:

- i. The identity of the equipment or source operation point from which the excess emission originated and the associated stack or emission point.
- ii. The estimated quantity of the excess emission.
- iii. The time and duration of the excess emission.
- iv. The cause of the excess emission.
- v. The steps that were taken to remedy and to prevent the recurrence of the incident of excess emission.
- vi. The steps that were taken to limit the excess emission.
- vii. If the owner claims that the excess emission was due to malfunction, documentation to support this claim. *567 IAC 21.7(1)-567 IAC 21.7(4)*

3. Emergency Defense for Excess Emissions. For the purposes of this permit, an “emergency” means any situation arising from sudden and reasonably unforeseeable events beyond the control of the source, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the source to exceed a technology-based emission limitation under the permit due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include non-compliance, to the extent caused by improperly designed equipment, lack of preventive maintenance, careless or improper operation or operator error. An emergency constitutes an affirmative defense to an action brought for non-compliance with technology based limitations if it can be demonstrated through properly signed contemporaneous operating logs or other relevant evidence that:

- a. An emergency occurred and that the permittee can identify the cause(s) of the emergency;
- b. The facility at the time was being properly operated;
- c. During the period of the emergency, the permittee took all reasonable steps to minimize levels of emissions that exceeded the emissions standards or other requirements of the permit; and

d. The permittee submitted notice of the emergency to the director by certified mail within two working days of the time when the emissions limitations were exceeded due to the emergency. This notice fulfills the requirement of paragraph 22.108(5)"b." – See G15. This notice must contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken.

In any enforcement proceeding, the permittee seeking to establish the occurrence of an emergency has the burden of proof. This provision is in addition to any emergency or upset provision contained in any applicable requirement. *567 IAC 24.108(16)*

G15. Permit Deviation Reporting Requirements

A deviation is any failure to meet a term, condition or applicable requirement in the permit. Reporting requirements for deviations that result in a hazardous release or excess emissions have been indicated above (see G13 and G14). Unless more frequent deviation reporting is specified in the permit, any other deviation shall be documented in the semi-annual monitoring report and the annual compliance certification (see G4 and G5). *567 IAC 24.108(5)"b"*

G16. Notification Requirements for Sources That Become Subject to NSPS and NESHAP Regulations

During the term of this permit, the permittee must notify the department of any source that becomes subject to a standard or other requirement under 567-subrule 23.1(2) (standards of performance of new stationary sources) or section 111 of the Act; or 567-subrule 23.1(3) (emissions standards for hazardous air pollutants), 567-subrule 23.1(4) (emission standards for hazardous air pollutants for source categories) or section 112 of the Act. This notification shall be submitted in writing to the department pursuant to the notification requirements in 40 CFR Section 60.7, 40 CFR Section 61.07, and/or 40 CFR Section 63.9. *567 IAC 23.1(2), 567 IAC 23.1(3), 567 IAC 23.1(4)*. This notification must be made to Polk County Air Quality Division, in lieu of the Department, upon adoption of the NSPS or NESHAP into Chapter V.

G17. Requirements for Making Changes to Emission Sources That Do Not Require Title V Permit Modification

1. Off Permit Changes to a Source. Pursuant to section 502(b)(10) of the CAAA, the permittee may make changes to this installation/facility without revising this permit if:
 - a. The changes are not major modifications under any provision of any program required by section 110 of the Act, modifications under section 111 of the act, modifications under section 112 of the act, or major modifications as defined in 567 IAC Chapter 24.
 - b. The changes do not exceed the emissions allowable under the permit (whether expressed therein as a rate of emissions or in terms of total emissions);
 - c. The changes are not modifications under any provisions of Title I of the Act and the changes do not exceed the emissions allowable under the permit (whether expressed therein as a rate of emissions or as total emissions);
 - d. The changes are not subject to any requirement under Title IV of the Act (revisions affecting Title IV permitting are addressed in rules 567—24.140(455B) through 567 - 24.144(455B));
 - e. The changes comply with all applicable requirements.

- f. For each such change, the permitted source provides to the department and the administrator by certified mail, at least 30 days in advance of the proposed change, a written notification, including the following, which must be attached to the permit by the source, the department and the administrator:
 - i. A brief description of the change within the permitted facility,
 - ii. The date on which the change will occur,
 - iii. Any change in emission as a result of that change,
 - iv. The pollutants emitted subject to the emissions trade
 - v. If the emissions trading provisions of the state implementation plan are invoked, then Title V permit requirements with which the source shall comply; a description of how the emissions increases and decreases will comply with the terms and conditions of the Title V permit.
 - vi. A description of the trading of emissions increases and decreases for the purpose of complying with a federally enforceable emissions cap as specified in and in compliance with the Title V permit; and
 - vii. Any permit term or condition no longer applicable as a result of the change. *567 IAC 24.110(1)*
2. Such changes do not include changes that would violate applicable requirements or contravene federally enforceable permit terms and conditions that are monitoring (including test methods), record keeping, reporting, or compliance certification requirements. *567 IAC 24.110(2)*
3. Notwithstanding any other part of this rule, the director may, upon review of a notice, require a stationary source to apply for a Title V permit if the change does not meet the requirements of subrule 24.110(1). *567 IAC 24.110(3)*
4. The permit shield provided in subrule 24.108(18) shall not apply to any change made pursuant to this rule. Compliance with the permit requirements that the source will meet using the emissions trade shall be determined according to requirements of the state implementation plan authorizing the emissions trade. *567 IAC 24.110(4)*
5. No permit revision shall be required, under any approved economic incentives, marketable permits, emissions trading and other similar programs or processes, for changes that are provided for in this permit. *567 IAC 24.108(11)*

G18. Duty to Modify a Title V Permit

1. Administrative Amendment.
 - a. An administrative permit amendment is a permit revision that does any of the following:
 - i. Correct typographical errors
 - ii. Identify a change in the name, address, or telephone number of any person identified in the permit, or provides a similar minor administrative change at the source;
 - iii. Require more frequent monitoring or reporting by the permittee; or
 - iv. Allow for a change in ownership or operational control of a source where the director determines that no other change in the permit is necessary, provided that a written agreement containing a specific date for transfer of permit responsibility, coverage and liability

between the current and new permittee has been submitted to the director.

- b. The permittee may implement the changes addressed in the request for an administrative amendment immediately upon submittal of the request. The request shall be submitted to the director.
- c. Administrative amendments to portions of permits containing provisions pursuant to Title IV of the Act shall be governed by regulations promulgated by the administrator under Title IV of the Act.

2. Minor Title V Permit Modification.

- a. Minor Title V permit modification procedures may be used only for those permit modifications that satisfy all of the following:
 - i. Do not violate any applicable requirement;
 - ii. Do not involve significant changes to existing monitoring, reporting or recordkeeping requirements in the Title V permit;
 - iii. Do not require or change a case by case determination of an emission limitation or other standard, or an increment analysis;
 - iv. Do not seek to establish or change a permit term or condition for which there is no corresponding underlying applicable requirement and that the source has assumed in order to avoid an applicable requirement to which the source would otherwise be subject. Such terms and conditions include any federally enforceable emissions caps which the source would assume to avoid classification as a modification under any provision under Title I of the Act; and an alternative emissions limit approved pursuant to regulations promulgated under section 112(i)(5) of the Act;
 - v. Are not modifications under any provision of Title I of the Act; and
 - vi. Are not required to be processed as significant modification under rule 567 - 24.113(455B).
- b. An application for minor permit revision shall be on the minor Title V modification application form and shall include at least the following:
 - i. A description of the change, the emissions resulting from the change, and any new applicable requirements that will apply if the change occurs;
 - ii. The permittee's suggested draft permit;
 - iii. Certification by a responsible official, pursuant to 567 IAC 24.107(4), that the proposed modification meets the criteria for use of minor permit modification procedures and a request that such procedures be used; and
 - iv. Completed forms to enable the department to notify the administrator and the affected states as required by 567 IAC 24.107(7).
- c. The permittee may make the change proposed in its minor permit modification application immediately after it files the application. After the permittee makes this change and until the director takes any of the actions specified in 567 IAC 24.112(4) "a" to "c", the permittee must comply with both the applicable requirements governing the change and the proposed permit terms and conditions. During this time, the permittee need not comply with the existing permit terms and conditions it seeks to modify.

However, if the permittee fails to comply with its proposed permit terms and conditions during this time period, the existing permit terms and conditions it seeks to modify may be enforced against the facility.

3. Significant Title V Permit Modification.

Significant Title V modification procedures shall be used for applications requesting Title V permit modifications that do not qualify as minor Title V modifications or as administrative amendments. These include but are not limited to all significant changes in monitoring permit terms, every relaxation of reporting or recordkeeping permit terms, and any change in the method of measuring compliance with existing requirements. Significant Title V modifications shall meet all requirements of 567 IAC Chapter 24, including those for applications, public participation, review by affected states, and review by the administrator, as those requirements that apply to Title V issuance and renewal.

The permittee shall submit an application for a significant permit modification not later than three months after commencing operation of the changed source unless the existing Title V permit would prohibit such construction or change in operation, in which event the operation of the changed source may not commence until the department revises the permit. *567 IAC 24.111-567 IAC 24.113*

G19. Duty to Obtain Construction Permits

Unless exempted in 567 IAC 22.1(2) or to meet the parameters established in 567 IAC 22.1(1)"c", the permittee shall not construct, install, reconstruct or alter any equipment, control equipment or anaerobic lagoon without first obtaining a construction permit, or conditional permit, or permit pursuant to rule 567 IAC 22.8, or permits required pursuant to rules 567 IAC 22.4, 567 IAC 22.5, 567 IAC 31.3, and 567 IAC 33.3 as required in 567 IAC 22.1(1). A permit shall be obtained prior to the initiation of construction, installation or alteration of any portion of the stationary source or anaerobic lagoon. *567 IAC 22.1(1) and Chapter V, Article X, 5-28*

G20. Asbestos

The permittee shall comply with 567 IAC 23.1(3)"a", and 567 IAC 23.2(3)"g" when activities involve asbestos mills, surfacing of roadways, manufacturing operations, fabricating, insulating, waste disposal, spraying applications, demolition and renovation operations (*567 IAC 23.1(3)"a"*); training fires and controlled burning of a demolished building (*567 IAC 23.2*).

G21. Open Burning

The permittee is prohibited from conducting open burning, except as provided in *567 IAC 23.2. 567 IAC 23.2 except 23.2(3)"j"; 567 IAC 23.2(3)"j" - State Only*

G22. Acid Rain (Title IV) Emissions Allowances

The permittee shall not exceed any allowances that it holds under Title IV of the Act or the regulations promulgated there under. Annual emissions of sulfur dioxide in excess of the number of allowances to emit sulfur dioxide held by the owners and operators of the unit or the designated representative of the owners and operators is prohibited. Exceedences of applicable emission rates are prohibited. "Held" in this context refers to both those allowances assigned to the owners and operators by USEPA, and those allowances supplementally acquired by the owners and operators. The use of any allowance prior to

the year for which it was allocated is prohibited. Contravention of any other provision of the permit is prohibited. 567 IAC 24.108(7)

G23. Stratospheric Ozone and Climate Protection (Title VI) Requirements

1. The permittee shall comply with the standards for labeling of products using ozone-depleting substances pursuant to 40 CFR Part 82, Subpart E:
 - a. All containers in which a class I or class II substance is stored or transported, all products containing a class I substance, and all products directly manufactured with a class I substance must bear the required warning statement if it is being introduced into interstate commerce pursuant to § 82.106.
 - b. The placement of the required warning statement must comply with the requirements pursuant to § 82.108.
 - c. The form of the label bearing the required warning statement must comply with the requirements pursuant to § 82.110.
 - d. No person may modify, remove, or interfere with the required warning statement except as described in § 82.112.
2. The permittee shall comply with the standards for recycling and emissions reduction pursuant to 40 CFR Part 82, Subpart F, except as provided for MVACs in Subpart B:
 - a. Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to § 82.156.
 - b. Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to § 82.158.
 - c. Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to § 82.161.
 - d. Persons disposing of small appliances, MVACs, and MVAC-like appliances must comply with reporting and recordkeeping requirements pursuant to § 82.166. ("MVAC-like appliance" as defined at § 82.152)
 - e. Persons owning commercial or industrial process refrigeration equipment must comply with the leak repair requirements pursuant to § 82.156.
 - f. Owners/operators of appliances normally containing 50 or more pounds of refrigerant must keep records of refrigerant purchased and added to such appliances pursuant to § 82.166.
3. If the permittee manufactures, transforms, imports, or exports a class I or class II substance, the permittee is subject to all the requirements as specified in 40 CFR part 82, Subpart A, Production and Consumption Controls.
4. If the permittee performs a service on motor (fleet) vehicles when this service involves ozone-depleting substance refrigerant (or regulated substitute substance) in the motor vehicle air conditioner (MVAC), the permittee is subject to all the applicable requirements as specified in 40 CFR part 82, Subpart B, Servicing of Motor Vehicle Air Conditioners. The term "motor vehicle" as used in Subpart B does not include a vehicle in which final assembly of the vehicle has not been completed. The term "MVAC" as used in Subpart B does not include the air-tight sealed refrigeration system used as refrigerated cargo, or system used on passenger buses using HCFC-22 refrigerant,
5. The permittee shall be allowed to switch from any ozone-depleting or greenhouse gas generating substances to any alternative that is listed in the Significant New Alternatives

Program (SNAP) promulgated pursuant to 40 CFR part 82, Subpart G, Significant New Alternatives Policy Program. *40 CFR part 82*

G24. Permit Reopenings

1. This permit may be modified, revoked, reopened, and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition. *567 IAC 24.108(9)"c"*
2. Additional applicable requirements under the Act become applicable to a major part 70 source with a remaining permit term of 3 or more years. Revisions shall be made as expeditiously as practicable, but not later than 18 months after the promulgation of such standards and regulations.
 - a. Reopening and revision on this ground is not required if the permit has a remaining term of less than three years;
 - b. Reopening and revision on this ground is not required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions have been extended pursuant to 40 CFR 70.4(b)(10)(i) or (ii) as amended to May 15, 2001.
 - c. Reopening and revision on this ground is not required if the additional applicable requirements are implemented in a general permit that is applicable to the source and the source receives approval for coverage under that general permit. *567 IAC 24.108(17)"a", 567 IAC 24.108(17)"b"*
3. A permit shall be reopened and revised under any of the following circumstances:
 - a. The department receives notice that the administrator has granted a petition for disapproval of a permit pursuant to 40 CFR 70.8(d) as amended to July 21, 1992, provided that the reopening may be stayed pending judicial review of that determination;
 - b. The department or the administrator determines that the Title V permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of the Title V permit;
 - c. Additional applicable requirements under the Act become applicable to a Title V source, provided that the reopening on this ground is not required if the permit has a remaining term of less than three years, the effective date of the requirement is later than the date on which the permit is due to expire, or the additional applicable requirements are implemented in a general permit that is applicable to the source and the source receives approval for coverage under that general permit. Such a reopening shall be complete not later than 18 months after promulgation of the applicable requirement.
 - d. Additional requirements, including excess emissions requirements, become applicable to a Title IV affected source under the acid rain program. Upon approval by the administrator, excess emissions offset plans shall be deemed to be incorporated into the permit.
 - e. The department or the administrator determines that the permit must be revised or revoked to ensure compliance by the source with the applicable requirements. *567 IAC 24.114(1)*

4. Proceedings to reopen and reissue a Title V permit shall follow the procedures applicable to initial permit issuance and shall effect only those parts of the permit for which cause to reopen exists. *567 IAC 24.114(2)*
5. A notice of intent shall be provided to the Title V source at least 30 days in advance of the date the permit is to be reopened, except that the director may provide a shorter time period in the case of an emergency. *567 IAC 24.114(3)*

G25. Permit Shield

1. The director may expressly include in a Title V permit a provision stating that compliance with the conditions of the permit shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that:
 - a. Such applicable requirements are included and are specifically identified in the permit; or
 - b. The director, in acting on the permit application or revision, determines in writing that other requirements specifically identified are not applicable to the source, and the permit includes the determination or a concise summary thereof.
2. A Title V permit that does not expressly state that a permit shield exists shall be presumed not to provide such a shield.
3. A permit shield shall not alter or affect the following:
 - a. The provisions of Section 303 of the Act (emergency orders), including the authority of the administrator under that section;
 - b. The liability of an owner or operator of a source for any violation of applicable requirements prior to or at the time of permit issuance;
 - c. The applicable requirements of the acid rain program, consistent with Section 408(a) of the Act;
 - d. The ability of the department or the administrator to obtain information from the facility pursuant to Section 114 of the Act. *567 IAC 24.108 (18)*

G26. Severability

The provisions of this permit are severable and if any provision or application of any provision is found to be invalid by this department or a court of law, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected by such finding. *567 IAC 24.108 (8) and Chapter V, Article XVII, 5-77*

G27. Property Rights

The permit does not convey any property rights of any sort, or any exclusive privilege. *567 IAC 24.108 (9)"d"*

G28. Transferability

This permit is not transferable from one source to another. If title to the facility or any part of it is transferred, an administrative amendment to the permit must be sought consistent with the requirements of *567 IAC 24.111(1)*. *567 IAC 24.111 (1)"d"*

G29. Disclaimer

No review has been undertaken on the engineering aspects of the equipment or control equipment other than the potential of that equipment for reducing air contaminant emissions. *567 IAC 24.3(3)"c"*

G30. Notification and Reporting Requirements for Stack Tests or Monitor Certification

The permittee shall notify the department's stack test contact in writing not less than 30 days before a required test or performance evaluation of a continuous emission monitor is performed to determine compliance with applicable requirements of 567 – Chapter 23 or a permit condition. Such notice shall include the time, the place, the name of the person who will conduct the test and other information as required by the department. If the owner or operator does not provide timely notice to the department, the department shall not consider the test results or performance evaluation results to be a valid demonstration of compliance with applicable rules or permit conditions. Upon written request, the department may allow a notification period of less than 30 days. At the department's request, a pretest meeting shall be held not later than 15 days prior to conducting the compliance demonstration. A testing protocol shall be submitted to the department no later than 15 days before the owner or operator conducts the compliance demonstration. A representative of the department shall be permitted to witness the tests. Results of the tests shall be submitted in writing to the department's stack test contact in the form of a comprehensive report within six weeks (42 days) of the completion of the testing. Compliance tests conducted pursuant to this permit shall be conducted with the source operating in a normal manner at its maximum continuous output as rated by the equipment manufacturer, or the rate specified by the owner as the maximum production rate at which the source shall be operated. In cases where compliance is to be demonstrated at less than the maximum continuous output as rated by the equipment manufacturer, and it is the owner's intent to limit the capacity to that rating, the owner may submit evidence to the department that the source has been physically altered so that capacity cannot be exceeded, or the department may require additional testing, continuous monitoring, reports of operating levels, or any other information deemed necessary by the department to determine whether such source is in compliance.

Stack test notifications, reports and correspondence shall be sent to:

Stack Test Review Coordinator
Iowa DNR, Air Quality Bureau
6200 Park Ave
Suite 200
Des Moines, IA 50321
(515) 343-6589

Within Polk County, stack test notifications, reports and correspondence shall also be directed to the supervisor of the respective county air pollution program.

567 IAC 21.10(7)"a", 567 IAC 21.10(9) and Chapter V, Article VII, 5-18 and 5-19

G31. Prevention of Air Pollution Emergency Episodes

The permittee shall comply with the provisions of 567 IAC Chapter 26 in the prevention of excessive build-up of air contaminants during air pollution episodes, thereby preventing the occurrence of an emergency due to the effects of these contaminants on the health of persons. *567 IAC 26.1(1)*

G32. Contacts List

The current address and phone number for reports and notifications to the EPA administrator is:

Iowa Compliance Officer
Air Branch
Enforcement and Compliance Assurance Division
U.S. EPA Region 7
11201 Renner Blvd.
Lenexa, KS 66219
(913) 551-7020

The current address and phone number for reports and notifications to the department or the Director is:

Chief, Air Quality Bureau
Iowa Department of Natural Resources
6200 Park Ave
Suite 200
Des Moines, IA 50321
(515) 313-8325

Reports or notifications to the local program shall be directed to the supervisor at the appropriate local program. Current address and phone number is:

Polk County Public Works Department
Air Quality Division
5885 NE 14th St.
Des Moines, IA 50313
(515) 286-3351

V. Appendix 1: Weblinks to applicable NSPS and NESHAP

(Click on blue link + Ctrl will take you to the website for the regulation.)

- 40 CFR Part 60 Subpart DD: Standards of Performance for Grain Elevators. NSPS Subpart DD
<https://www.ecfr.gov/cgi-bin/text-idx?node=sp40.7.60.dd>
 - 40 CFR 60 subpart Db: Standards of Performance for Industrial-Commercial-Institutional Steam Generating Units
https://www.ecfr.gov/cgi-bin/text-idx?SID=7661f5d9f7827b7d7eb71a27ff33f51f&mc=true&node=sp40.7.60.d_0b&rgn=div6
 - 40 CFR 60 subpart Dc: Standards of Performance for Small Industrial-Commercial-Institutional Boilers and Process Heaters
<https://www.epa.gov/stationary-sources-air-pollution/industrial-commercial-institutional-steam-generating-units-new>
 - 40 CFR 60 NSPS Subpart IIII Standards of Performance for Stationary Compression Ignition Internal Combustion Engines.
<https://www.epa.gov/stationary-engines/new-source-performance-standards-stationary-compression-ignition-internal-0>
 - 40 CFR Part 63 Subpart GGGG: National Emission Standards for Hazardous Air Pollutants: Solvent Extraction for Vegetable Oil Production
<https://www.epa.gov/stationary-sources-air-pollution/solvent-extraction-vegetable-oil-production-national-emission>
 - 40 CFR Part 63 Subpart ZZZZ: National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines
<https://www.ecfr.gov/current/title-40/chapter-I/subchapter-C/part-63/subpart-ZZZZ>
- 40 CFR Part 63 Subpart DDDDD: National Emission Standards for Hazardous Air Pollutants for Major Sources: Industrial, Commercial, and Institutional Boilers and Process Heaters
<https://www.ecfr.gov/current/title-40/chapter-I/subchapter-C/part-63/subpart-DDDDD>

VI . Appendix 2: EO10 Crosswalk

Previous Chapter Number (Prior to 5/15/2024)	Current Chapter Number	Previous Title and Description (Prior to 5/15/2024)	Current Title and Description	Actions Taken
20	20 (Reserved)	Scope of Title - Definitions	N/A	Definitions moved to Ch. 21, 22 and 23. Rescinded Ch. 20. (Reserved)
21	21	Compliance	Compliance, Excess Emissions, and Measurement of Emissions	Kept and combined with rules from Chapters 24, 25, 26, and 29.
22	22	Controlling Pollution-Permits	Controlling Air Pollution - Construction Permitting	Kept construction permit rules and combined with Ch. 20 (definitions) and Ch. 28 (NAAQS). Moved operating permit rules to Chapter 24.
22.100 - 22.300(12)	(New) 24	N/A	Operating Permits	Moved operating permit rules from Ch. 22 to Ch. 24.
23	23	Emission Standards	Air Emission Standards	Kept
24	(New) 21	Excess Emissions	Compliance, Excess Emissions, and Measurement of Emissions	Moved rules and combined with Ch. 21. Moved TV rules here (to Ch. 24).
25	(New) 21	Emissions Measurement	Compliance, Excess Emissions, and Measurement of Emissions	Moved rules and combined with Ch. 21. Rescinded Ch. 25. (Reserved)
26	(New) 21	Emergency Air Pollution Episodes	Compliance, Excess Emissions, and Measurement of Emissions	Moved rules and combined with Ch. 21. Rescinded Ch. 26. (Reserved)
27	27	Local Program Acceptance	Local Program Acceptance	Kept
28	22	NAAQS	N/A	Moved rules and combined with Ch. 22. Rescinded Ch. 28. (Reserved)
29	(New) 21	Opacity Qualifications	Compliance, Excess Emissions, and Measurement of Emissions	Moved rules and combined with Ch. 21. Rescinded Ch. 29. (Reserved)
30	30	Fees	Fee	Kept
31	31	Nonattainment Areas	Nonattainment New Source Review	Kept
32	N/A	AFO Field Study	N/A	Rescinded Ch. 32. (Reserved)
33	33	Special regulations and construction permit requirements for major stationary sources—Prevention of significant deterioration (PSD) of air quality	Construction permit requirements for major stationary sources—Prevention of significant deterioration (PSD)	Kept
34	N/A	Emissions Trading-CAIR-CAMR	N/A	Rescinded Ch. 34. (Reserved)
35	N/A	Grant Assistance Programs	N/A	Rescinded Ch. 35. (Reserved)

Previous Chapter Number (Prior to 5/15/2024)	Current Chapter Number	Previous Title and Description (Prior to 5/15/2024)	Current Title and Description	Actions Taken
20	20 (Reserved)	Scope of Title - Definitions	N/A	Definitions moved to Ch. 21, 22 and 23. Rescinded Ch. 20. (Reserved)
20.1	N/A	Scope of title	N/A	
20.2	Ch. 21, 22, 23	Definitions	Definitions	See beginning of Ch. 21, 22, and 23
20.3	N/A	Air quality forms generally	N/A	

21	21	Compliance	Compliance, Excess Emissions, and Measurement of Emissions	Kept and combined with rules from Chapters 24, 25, 26, and 29.
21.1	21.1	Compliance Schedule	Definitions and compliance requirements	Added definitions from Ch. 21, some language updated
21.2	21.2	Variances	Variances	Some language updated
21.3	21.3	Emission reduction program	Reserved	Reserved
21.4	21.4	Circumvention of rules	Circumvention of rules	Minor language updated
21.5	21.5	Evidence used in establishing that a violation has or is occurring	Evidence used in establishing that a violation has occurred or is occurring	21.5(2) Reserved, some language updated
21.6	21.6	Temporary electricity generation for disaster situations	Temporary electricity generation for disaster situations	Minor language updated
24.1	21.7	Excess emission reporting	Excess emission reporting	Moved from Ch. 24, some language updated
24.2	21.8	Maintenance and repair requirements	Maintenance and repair requirements	Moved from Ch. 24, some language updated
N/A	21.9	N/A	Compliance with other requirements	New language
25.1	21.10	Testing and sampling of new and existing equipment	Testing and sampling of new and existing equipment	Moved from Ch. 25, some language updated
25.2	21.11	Continuous emission monitoring under the acid rain program	Continuous emission monitoring under the acid rain program	Moved from Ch. 25, some language updated
25.3	N/A	Mercury emissions testing and monitoring	N/A	Rescinded. Except 25.3(5)
25.3(5)	21.12	Affected sources subject to Section 112(g)	Affected sources subject to Section 112(g)	Moved from Ch. 25, some language updated
29.1	21.13	Methodology and qualified observer	Methodology and qualified observer	Moved from Ch. 29, some language updated
26.1	21.14	Prevention of air pollution emergency episodes - General	Prevention of air pollution emergency episodes	Moved from Ch. 26, some language updated
26.2	21.15	Episode criteria	Episode criteria	Moved from Ch. 26, some language updated
26.3	21.16	Preplanned abatement strategies	Preplanned abatement strategies	Moved from Ch. 26, some language updated
26.4	21.17	Actions taken during episodes	Actions taken during episodes	Moved from Ch. 26, some language updated
Ch 26 Table III	Table I	Abatement strategies emission reduction actions alert level	Abatement strategies emission reduction actions alert level	Moved from Ch. 26, reference federal appendix table
Ch 26 Table IV	Table II	Abatement strategies emission reduction actions warning level	Abatement strategies emission reduction actions warning level	Moved from Ch. 26, reference federal appendix table
Ch 26 Table V	Table III	Abatement strategies emission reduction actions emergency level	Abatement strategies emission reduction actions emergency level	Moved from Ch. 26, reference federal appendix table

22	22	Controlling Pollution-Permits	Controlling Air Pollution - Construction Permitting	Kept construction permit rules and combined with Ch. 20 (definitions) and Ch. 28 (NAAQS). Moved operating permit rules to Chapter 24.
22.1	22.1	Permits required for new or existing stationary sources	Definitions and permit requirements for new or existing stationary sources	Added definitions from Ch. 20, some language updated
22.2	22.2	Processing permit applications	Processing permit applications	
22.3	22.3	Issuing permits	Issuing permits	
22.4	22.4	Special requirements for major stationary sources located in areas designated attainment or unclassified (PSD)	Major stationary sources located in areas designated attainment or unclassified (PSD)	
22.5	22.5	Special requirements for nonattainment areas	Major stationary sources located in areas designated Nonattainment	
22.6	22.6	Nonattainment area designations	Reserved	

Previous Chapter Number (Prior to 5/15/2024)	Current Chapter Number	Previous Title and Description (Prior to 5/15/2024)	Current Title and Description	Actions Taken
22.7	22.7	Alternative emission control program	Alternative emission control program	
22.8	22.8	Permit by rule	Permit by rule	
22.9	22.9	Special requirements for visibility protection	Special requirements for visibility protection	A lot of language updated or removed
22.10	22.10	Permitting requirements for country grain elevators, country grain terminal elevators, grain terminal elevators and feed mill equipment	Permitting requirements for country grain elevators, country grain terminal elevators, grain terminal elevators and feed mill equipment	
28.1	22.11	Ambient air quality standards - Statewide standards	Ambient air quality standards	Moved from Ch. 28, minor language updated
22.12 to 22.99	N/A	Reserved	N/A	Removed

22.100 - 22.300(12)	(New) 24	N/A	Operating Permits	Moved operating permit rules from Ch. 22 to Ch. 24.
22.100	24.100	Definitions for Title V operating permits	Definitions for Title V operating permits	Moved from Ch. 22, some language updated, many 40 CFR 70 definitions adopted by reference
22.101	24.101	Applicability of Title V operating permit requirements	Applicability of Title V operating permit requirements	Moved from Ch. 22, some language updated to correct punctuation and remove old dates
22.102	24.102	Source category exemptions	Source category exemptions	Moved from Ch. 22, some language updated to correct punctuation
22.103	24.103	Insignificant activities	Insignificant activities	Moved from Ch. 22, some language updated to correct typos and remove old dates
22.104	24.104	Requirement to have a Title V permit	Requirement to have a Title V permit	Moved from Ch. 22, some language updated no changes to rule text
22.105	24.105	Title V permit applications	Title V permit applications	Moved from Ch. 22, updated language to address electronic submissions and remove past application due dates
22.106	24.106	Annual Title V emissions inventory	Annual Title V emissions inventory	Moved from Ch. 22, no changes to rule text
22.107	24.107	Title V permit processing procedures	Title V permit processing procedures	Moved from Ch. 22, some language updated to update locations of public records and remove old CFR amendment dates
22.108	24.108	Permit content	Permit content	Moved from Ch. 22, some language updated to correct punctuation, remove old dates, and adopt 40 CFR 70 rules by reference
22.109	24.109	General permits	General permits	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.110	24.110	Changes allowed without a Title V permit revision (off-permit revisions)	Changes allowed without a Title V permit revision (off-permit revisions)	Moved from Ch. 22, some language updated to remove redundant language
22.111	24.111	Administrative amendments to Title V permits	Administrative amendments to Title V permits	Moved from Ch. 22, no changes to rule text
22.112	24.112	Minor Title V permit modifications	Minor Title V permit modifications	Moved from Ch. 22, no changes to rule text
22.113	24.113	Significant Title V permit modifications	Significant Title V permit modifications	Moved from Ch. 22, no changes to rule text
22.114	24.114	Title V permit reopenings	Title V permit re-openings	Moved from Ch. 22 to Ch. 24, some language updated to adopt 40 CFR 70 rules by reference
22.115	24.115	Suspension, termination, and revocation of Title V permits	Suspension, termination, and revocation of Title V permits	Moved from Ch. 22, no changes to rule text
22.116	24.116	Title V permit renewals	Title V permit renewals	Moved from Ch. 22, no changes to rule text
22.117-22.119	24.117-24.119	Reserved	Reserved	Moved from Ch. 22, no changes to rule text
22.120	24.120	Acid rain program—definitions	Acid rain program—definitions	Moved from Ch. 22, some language updated to remove old CFR amendment dates and address electronic submissions
22.121	24.121	Measurements, abbreviations, and acronyms	Reserved	Moved from Ch. 22, no changes to rule text
22.122	24.122	Applicability	Applicability	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.123	24.123	Acid rain exemptions	Acid rain exemptions	Moved from Ch. 22, some language updated to correct punctuation
22.124	24.124	Retired units exemption	Reserved	Moved from Ch. 22, no changes to rule text
22.125	24.125	Standard requirements	Standard requirements	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.126	24.126	Designated representative—submissions	Designated representative—submissions	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.127	24.127	Designated representative—objections	Designated representative—objections	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.128	24.128	Acid rain applications—requirement to apply	Acid rain applications—requirement to apply	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference

22.129	24.129	Information requirements for acid rain permit applications	Information requirements for acid rain permit applications	Moved from Ch. 22, no changes to rule text
Previous Chapter Number (Prior to 5/15/2024)	Current Chapter Number	Previous Title and Description (Prior to 5/15/2024)	Current Title and Description	Actions Taken
22.130	24.130	Acid rain permit application shield and binding effect of permit application	Acid rain permit application shield and binding effect of permit application	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.131	24.131	Acid rain compliance plan and compliance options—general	Acid rain compliance plan and compliance options—general	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.132	24.132	Repowering extensions	Reserved	Moved from Ch. 22, no changes to rule text
22.133	24.133	Acid rain permit contents—general	Acid rain permit contents—general	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.134	24.134	Acid rain permit shield	Acid rain permit shield	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.135	24.135	Acid rain permit issuance procedures—general	Acid rain permit issuance procedures—general	Moved from Ch. 22, no changes to rule text
22.136	24.136	Acid rain permit issuance procedures—completeness	Acid rain permit issuance procedures—completeness	Moved from Ch. 22, no changes to rule text
22.137	24.137	Acid rain permit issuance procedures—statement of basis	Acid rain permit issuance procedures—statement of basis	Moved from Ch. 22, no changes to rule text
22.138	24.138	Issuance of acid rain permits	Issuance of acid rain permits	Moved from Ch. 22, some language updated to remove old dates and deadlines
22.139	24.139	Acid rain permit appeal procedures	Acid rain permit appeal procedures	Moved from Ch. 22, no changes to rule text
22.140	24.140	Permit revisions—general	Permit revisions—general	Moved from Ch. 22, some language updated to remove old dates
22.141	24.141	Permit modifications	Permit modifications	Moved from Ch. 22, no changes to rule text
22.142	24.142	Fast-track modifications	Fast-track modifications	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.143	24.143	Administrative permit amendment	Administrative permit amendment	Moved from Ch. 22, some language updated to remove fax option
22.144	24.144	Automatic permit amendment	Automatic permit amendment	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.145	24.145	Permit reopenings	Permit re-openings	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.146	24.146	Compliance certification—annual report	Compliance certification—annual report	Moved from Ch. 22, no changes to rule text
22.147	24.147	Compliance certification—units with repowering extension plans	Reserved	Moved from Ch. 22, no changes to rule text
22.148	24.148	Sulfur dioxide opt-ins	Sulfur dioxide opt-ins	Moved from Ch. 22, some language updated to update the 40 CFR Part 74 amendment date
22.149 - 22.199	24.149 - 24.299	Reserved	Reserved	Moved from Ch. 22, no changes to rule text
22.200	24.200 - 24.299	Definitions for voluntary operating permits	Reserved	Moved from Ch. 22, no changes to rule text
22.201	24.200 - 24.299	Eligibility for voluntary operating permits	Reserved	Moved from Ch. 22, no changes to rule text
22.203	24.200 - 24.299	Voluntary operating permit applications	Reserved	Moved from Ch. 22, no changes to rule text
22.204	24.200 - 24.299	Voluntary operating permit fees	Reserved	Moved from Ch. 22, no changes to rule text
22.205	24.200 - 24.299	Voluntary operating permit processing procedures	Reserved	Moved from Ch. 22, no changes to rule text
22.206	24.200 - 24.299	Permit content	Reserved	Moved from Ch. 22, no changes to rule text
22.207	24.200 - 24.299	Relation to construction permits	Reserved	Moved from Ch. 22, no changes to rule text
22.208	24.200 - 24.299	Suspension, termination, and revocation of voluntary operating permits	Reserved	Moved from Ch. 22, no changes to rule text
22.209	24.200 - 24.299	Change of ownership for facilities with voluntary operating permits	Reserved	Moved from Ch. 22, no changes to rule text
22.210 - 22.299	24.200 - 24.299	Reserved	Reserved	Moved from Ch. 22, no changes to rule text
22.300	24.300	Operating permit by rule for small sources	Operating permit by rule for small sources	Moved from Ch. 22, no changes to rule text

23	23	Emission Standards	Air Emission Standards	Kept
23.1	23.1	Emission standards	Emission standards	Kept, language updated, tables used
23.2	23.2	Open burning	Open burning	Kept, some language updated
23.3	23.3	Specific contaminants	Specific contaminants	Kept, some language updated
23.4	23.4	Specific processes	Specific processes	Kept, some language updated
23.5	23.5	Anaerobic lagoons	Anaerobic lagoons	Kept, some language updated
23.6	23.6	Alternative emission limits (the “bubble concept”)	Reserved	Removed

Previous Chapter Number (Prior to 5/15/2024)	Current Chapter Number	Previous Title and Description (Prior to 5/15/2024)	Current Title and Description	Actions Taken
24	(New) 21	Excess Emissions	Compliance, Excess Emissions, and Measurement of Emissions	Moved rules and combined with Ch. 21. Moved operating permit rules here (to Ch. 24).
24.1	21.7	Excess emission reporting	Excess emission reporting	Moved from Ch. 24, some language updated
24.2	21.8	Maintenance and repair requirements	Maintenance and repair requirements	Moved from Ch. 24, some language updated
25	(New) 21	Emissions Measurement	Compliance, Excess Emissions, and Measurement of Emissions	Moved rules and combined with Ch. 21. Rescinded Ch. 25. (Reserved)
25.1	21.10	Testing and sampling of new and existing equipment	Testing and sampling of new and existing equipment	Moved from Ch. 25, some language updated
25.2	21.11	Continuous emission monitoring under the acid rain program	Continuous emission monitoring under the acid rain program	Moved from Ch. 25, some language updated
25.3		Mercury emissions testing and monitoring	N/A	Rescinded. Except 25.3(5)
25.3(5)	21.12	Affected sources subject to Section 112(g)	Affected sources subject to Section 112(g)	Moved from Ch. 25, some language updated
26	(New) 21	Emergency Air Pollution Episodes	Compliance, Excess Emissions, and Measurement of Emissions	Moved rules and combined with Ch. 21. Rescinded Ch. 26. (Reserved)
26.1	21.14	Prevention of air pollution emergency episodes - General	Prevention of air pollution emergency episodes	Moved from Ch. 26, some language updated
26.2	21.15	Episode criteria	Episode criteria	Moved from Ch. 26, some language updated
26.3	21.16	Preplanned abatement strategies	Preplanned abatement strategies	Moved from Ch. 26, some language updated
26.4	21.17	Actions taken during episodes	Actions taken during episodes	Moved from Ch. 26, some language updated
Ch 26 Table III	Table I	Abatement strategies emission reduction actions alert level	Abatement strategies emission reduction actions alert level	Moved from Ch. 26, reference federal appendix table
Ch 26 Table IV	Table II	Abatement strategies emission reduction actions warning level	Abatement strategies emission reduction actions warning level	Moved from Ch. 26, reference federal appendix table
Ch 26 Table V	Table III	Abatement strategies emission reduction actions emergency level	Abatement strategies emission reduction actions emergency level	Moved from Ch. 26, reference federal appendix table
27	27	Local Program Acceptance	Local Program Acceptance	Kept
27.1	27.1	General	General	Kept, some language updated
27.2	27.2	Certificate of acceptance	Certificate of acceptance	Kept, some language updated
27.3	27.3	Ordinance or regulations	Ordinance or regulations	Kept, some language updated
27.4	27.4	Administrative organization	Administrative organization	Kept, some language updated
27.5	27.5	Program activities	Program activities	Kept, some language updated
28	22	NAAQS	N/A	Moved rules and combined with Ch. 22. Rescinded Ch. 28. (Reserved)
28.1	22.11	Ambient air quality standards - Statewide standards	Ambient air quality standards	Moved from Ch. 28, minor language updated Rescinded Ch. 28. (Reserved)
29	(New) 21	Opacity Qualifications	Compliance, Excess Emissions, and Measurement of Emissions	Moved rules and combined with Ch. 21. Rescinded Ch. 29. (Reserved)
29.1	21.13	Methodology and qualified observer	Methodology and qualified observer	Moved from Ch. 29, some language updated

Previous Chapter Number (Prior to 5/15/2024)	Current Chapter Number	Previous Title and Description (Prior to 5/15/2024)	Current Title and Description	Actions Taken
30	30	Fees	Fee	Kept
30.1	30.1	Purpose	Purpose	Kept, language updated
30.2	30.2	Fees associated with new source review applications	Fees associated with new source review applications	Kept, some language updated
30.3	30.3	Fees associated with asbestos demolition or renovation notification	Fees associated with asbestos demolition or renovation notification	Kept, some language updated
30.4	30.4	Fees associated with Title V operating permits	Fees associated with Title V operating permits	Kept, some language updated
30.5	30.5	Fee advisory groups	Fee advisory groups	Kept, language updated
30.6	30.6	Process to establish or adjust fees and notification of fee rates	Process to establish or adjust fees and notification of fee rates	Kept, some language updated
30.7	30.7	Fee revenue	Reserved	Language removed

31	31	Nonattainment Areas	Nonattainment New Source Review	Kept
31.1	31.1	Permit requirements relating to nonattainment areas	Permit requirements relating to nonattainment areas	Kept, some language updated
31.2	31.2	Conformity of general federal actions to the Iowa state implementation plan or federal implementation plan - Rescinded	Reserved	Language removed
31.3	31.3	Nonattainment new source review requirements for areas designated nonattainment on or after May 18, 1998	Nonattainment new source review (NNSR) requirements for areas designated nonattainment	Kept, some language updated
31.4	31.4	Preconstruction review permit program	Preconstruction review permit program	Kept
31.5 - 31.8	31.5 - 31.8	Reserved	Reserved	Kept
31.9	31.9	Actuals PALs	Actuals PALs	Kept, some language updated
31.10	31.10	Validity of rules	Validity of rules	Kept
31.11 - 31.19	N/A	Reserved	N/A	Rescinded and removed
31.20	N/A	Special requirements for nonattainment areas designated before May 18, 1998	N/A	Rescinded and removed

32	N/A	AFO Field Study	N/A	Rescinded Ch. 32. (Reserved)
32.1	N/A	Animal feeding operations field study	N/A	Rescinded, reserved, and language removed
32.2	N/A	Definitions	N/A	Rescinded, reserved, and language removed
32.3	N/A	Exceedance of the health effects value (HEV) for hydrogen sulfide	N/A	Rescinded, reserved, and language removed
32.4	N/A	Exceedance of the health effects standard (HES) for hydrogen sulfide	N/A	Rescinded, reserved, and language removed
32.5	N/A	Iowa Air Sampling Manual	N/A	Rescinded, reserved, and language removed

33	33	Special regulations and construction permit requirements for major stationary sources—Prevention of significant deterioration (PSD) of air quality	Construction permit requirements for major stationary sources—Prevention of significant deterioration (PSD)	Kept
33.1	33.1	Purpose	Purpose	Kept, some language updated
33.2	33.2	Reserved	Reserved	Kept
33.3	33.3	Special construction permit requirements for major stationary sources in areas designated attainment or unclassified (PSD)	PSD construction permit requirements for major stationary sources	Kept, some language updated
33.4 - 33.8	33.4 - 33.8	Reserved	Reserved	Kept
33.9	33.9	Plantwide applicability limitations (PALs)	Plantwide applicability limitations (PALs)	Kept, some language updated
33.10	33.10	Exceptions to adoption by reference	Exceptions to adoption by reference	Kept, some language updated

Previous Chapter Number (Prior to 5/15/2024)	Current Chapter Number	Previous Title and Description (Prior to 5/15/2024)	Current Title and Description	Actions Taken
34	N/A	Emissions Trading-CAIR-CAMR	N/A	Rescinded Ch. 34. (Reserved)
34.1	N/A	Purpose	N/A	Rescinded, reserved, and language removed
34.2 - 34.199	N/A	Reserved	N/A	Rescinded, reserved, and language removed
34.200	N/A	Provisions for air emissions trading and other requirements for the Clean Air Interstate Rule (CAIR) - rescinded	N/A	Rescinded, reserved, and language removed
34.201	N/A	CAIR NOx annual trading program general provisions - rescinded	N/A	Rescinded, reserved, and language removed
34.202	N/A	CAIR designated representative for CAIR NOx sources - rescinded	N/A	Rescinded, reserved, and language removed
34.203	N/A	Permits - rescinded	N/A	Rescinded, reserved, and language removed
34.204	N/A	Reserved	N/A	Rescinded, reserved, and language removed
34.205	N/A	CAIR NOx allowance allocations - rescinded	N/A	Rescinded, reserved, and language removed
34.206	N/A	CAIR NOx allowance tracking system - rescinded	N/A	Rescinded, reserved, and language removed
34.207	N/A	CAIR NOx allowance transfers - rescinded	N/A	Rescinded, reserved, and language removed
34.208	N/A	Monitoring and reporting - rescinded	N/A	Rescinded, reserved, and language removed
34.209	N/A	CAIR NOx opt-in units - rescinded	N/A	Rescinded, reserved, and language removed
34.210	N/A	CAIR SO2 trading program - rescinded	N/A	Rescinded, reserved, and language removed
34.211 - 34.219	N/A	Reserved	N/A	Rescinded, reserved, and language removed
34.220	N/A	CAIR NOx ozone season trading program - rescinded	N/A	Rescinded, reserved, and language removed
34.221	N/A	CAIR NOx ozone season trading program general provisions - rescinded	N/A	Rescinded, reserved, and language removed
34.222	N/A	CAIR designated representative for CAIR NOx ozone season sources - rescinded	N/A	Rescinded, reserved, and language removed
34.223	N/A	CAIR NOx ozone season permits - rescinded	N/A	Rescinded, reserved, and language removed
34.224	N/A	Reserved	N/A	Rescinded, reserved, and language removed
34.225	N/A	CAIR NOx ozone season allowance allocations - rescinded	N/A	Rescinded, reserved, and language removed
34.226	N/A	CAIR NOx ozone season allowance tracking system - rescinded	N/A	Rescinded, reserved, and language removed
34.227	N/A	CAIR NOx ozone season allowance transfers - rescinded	N/A	Rescinded, reserved, and language removed
34.228	N/A	CAIR NOx ozone season monitoring and reporting - rescinded	N/A	Rescinded, reserved, and language removed
34.229	N/A	CAIR NOx ozone season opt-in units - rescinded	N/A	Rescinded, reserved, and language removed
34.230 - 34.299	N/A	Reserved	N/A	Rescinded, reserved, and language removed
34.300	N/A	Provisions for air emissions trading and other requirements for the Clean Air Mercury Rule (CAMR) - rescinded	N/A	Rescinded, reserved, and language removed
34.301	N/A	Mercury (Hg) budget trading program general provisions - rescinded	N/A	Rescinded, reserved, and language removed
34.302	N/A	Hg designated representative for Hg budget sources - rescinded	N/A	Rescinded, reserved, and language removed
34.303	N/A	General Hg budget trading program permit requirements - rescinded	N/A	Rescinded, reserved, and language removed
34.304	N/A	Hg allowance allocations - rescinded	N/A	Rescinded, reserved, and language removed
34.305	N/A	Hg allowance tracking system - rescinded	N/A	Rescinded, reserved, and language removed

AQB Rule Tracking Crosswalk

34.306	N/A	Hg allowance transfers - rescinded	N/A	Rescinded, reserved, and language removed
Previous Chapter Number (Prior to 5/15/2024)	Current Chapter Number	Previous Title and Description (Prior to 5/15/2024)	Current Title and Description	Actions Taken
34.307	N/A	Monitoring and reporting - rescinded	N/A	Rescinded, reserved, and language removed
34.308	N/A	Performance specifications - rescinded	N/A	Rescinded, reserved, and language removed

35	N/A	Grant Assistance Programs	N/A	Rescinded Ch. 35. (Reserved)
35.1	N/A	Purpose	N/A	Rescinded, reserved, and language removed
35.2	N/A	Definitions	N/A	Rescinded, reserved, and language removed
35.3	N/A	Role of the department of natural resources	N/A	Rescinded, reserved, and language removed
35.4	N/A	Eligible projects	N/A	Rescinded, reserved, and language removed
35.5	N/A	Forms	N/A	Rescinded, reserved, and language removed
35.6	N/A	Project selection	N/A	Rescinded, reserved, and language removed
35.7	N/A	Funding sources	N/A	Rescinded, reserved, and language removed
35.8	N/A	Type of financial assistance	N/A	Rescinded, reserved, and language removed
35.9	N/A	Term of loans	N/A	Rescinded, reserved, and language removed
35.10	N/A	Reduced award	N/A	Rescinded, reserved, and language removed
35.11	N/A	Fund disbursement limitations	N/A	Rescinded, reserved, and language removed
35.12	N/A	Applicant cost share	N/A	Rescinded, reserved, and language removed
35.13	N/A	Eligible costs	N/A	Rescinded, reserved, and language removed
35.14	N/A	Ineligible costs	N/A	Rescinded, reserved, and language removed
35.15	N/A	Written agreement	N/A	Rescinded, reserved, and language removed
35.16	N/A	Financial assistance denial	N/A	Rescinded, reserved, and language removed