

**Iowa Department of Natural Resources
Title V Operating Permit**

**Name of Permitted Facility: Magellan Pipeline Company, LP –
Iowa City Terminal**

Facility Location: 912 1st Street, Coralville, IA 52241

Air Quality Operating Permit Number: 03-TV-010R3

Expiration Date: August 5, 2024

Permit Renewal Application Deadline: February 5, 2024

EIQ Number: 92-5490

Facility File Number: 52-02-006

Responsible Official

Name: Jeff Myers

Title: Director of Operations

Mailing Address: 13424 West 98th Street, Shawnee Mission, KS 66215

Phone #: (913) 310-7730

Permit Contact Person for the Facility

Name: Kendall Mordhorst

Title: Sr. Air Specialist

Mailing Address: One Williams Center MD OTC 8, Tulsa, OK 74172

Phone #: (918) 574-7479

This permit is issued in accordance with 567 Iowa Administrative Code Chapter 22, and is issued subject to the terms and conditions contained in this permit.

For the Director of the Department of Natural Resources

Lori Hanson, Supervisor of Air Operating Permits Section

Date

Table of Contents

I. Facility Description and Equipment List	4
II. Plant - Wide Conditions.....	6
III. Emission Point Specific Conditions	9
IV. General Conditions.....	28
G1. Duty to Comply	
G2. Permit Expiration	
G3. Certification Requirement for Title V Related Documents	
G4. Annual Compliance Certification	
G5. Semi-Annual Monitoring Report	
G6. Annual Fee	
G7. Inspection of Premises, Records, Equipment, Methods and Discharges	
G8. Duty to Provide Information	
G9. General Maintenance and Repair Duties	
G10. Recordkeeping Requirements for Compliance Monitoring	
G11. Evidence used in establishing that a violation has or is occurring.	
G12. Prevention of Accidental Release: Risk Management Plan Notification and Compliance Certification	
G13. Hazardous Release	
G14. Excess Emissions and Excess Emissions Reporting Requirements	
G15. Permit Deviation Reporting Requirements	
G16. Notification Requirements for Sources That Become Subject to NSPS and NESHAP Regulations	
G17. Requirements for Making Changes to Emission Sources That Do Not Require Title V Permit Modification	
G18. Duty to Modify a Title V Permit	
G19. Duty to Obtain Construction Permits	
G20. Asbestos	
G21. Open Burning	
G22. Acid Rain (Title IV) Emissions Allowances	
G23. Stratospheric Ozone and Climate Protection (Title VI) Requirements	
G24. Permit Reopenings	
G25. Permit Shield	
G26. Severability	
G27. Property Rights	
G28. Transferability	
G29. Disclaimer	
G30. Notification and Reporting Requirements for Stack Tests or Monitor Certification	
G31. Prevention of Air Pollution Emergency Episodes	
G32. Contacts List	
V. Appendix A: Links to NSPS/NESHAP Regulations	42

Abbreviations

acfm.....	actual cubic feet per minute
CFR.....	Code of Federal Regulation
CE	control equipment
CEM.....	continuous emission monitor
°F.....	degrees Fahrenheit
EIQ.....	emissions inventory questionnaire
EP	emission point
EU	emission unit
gr./dscf	grains per dry standard cubic foot
IAC.....	Iowa Administrative Code
IDNR.....	Iowa Department of Natural Resources
MVAC.....	motor vehicle air conditioner
NAICS.....	North American Industry Classification System
NSPS.....	new source performance standard
ppmv	parts per million by volume
lb./hr	pounds per hour
lb./MMBtu	pounds per million British thermal units
SCC.....	Source Classification Codes
scfm.....	standard cubic feet per minute
SIC	Standard Industrial Classification
TPY.....	tons per year
USEPA.....	United States Environmental Protection Agency

Pollutants

PM.....	particulate matter
PM ₁₀	particulate matter ten microns or less in diameter
SO ₂	sulfur dioxide
NO _x	nitrogen oxides
VOC.....	volatile organic compound
CO.....	carbon monoxide
HAP.....	hazardous air pollutant

I. Facility Description and Equipment List

Facility Name: Magellan Pipeline Company, LP – Iowa City Terminal
 Permit Number: 03-TV-010R3

Facility Description: Refined Petroleum Pipeline (SIC 4613)

Equipment List

Emission Point Number	Emission Unit Number	Emission Unit Description	DNR Construction Permit Number
1	1	Truck Loading Rack	96-A-1030-S1
2	2	Domed External Floating Roof Tank #402 (266,480 gallons)	NA
3	3	Domed External Floating Roof Tank #403 (265,186 gallons)	NA
4	4	Domed External Floating Roof Tank #407 (252,662 gallons)	NA
5	5	Domed External Floating Roof Tank #423 (266,480 gallons)	NA
6	6	Domed External Floating Roof Tank #424 (266,480 gallons)	NA
7	7	Domed External Floating Roof Tank #623 (740,222 gallons)	NA
8	8	Domed External Floating Roof Tank #624 (713,786 gallons)	NA
9	9	Domed External Floating Roof Tank #631 (713,786 gallons)	NA
10	10	Domed External Floating Roof Tank #632 (712,728 gallons)	NA
11	11	Domed External Floating Roof Tank #641 (845,968 gallons)	NA
12	12	Domed External Floating Roof Tank #642 (888,266 gallons)	NA
13	13	Domed External Floating Roof Tank #645 (740,222 gallons)	NA
14	14	Domed External Floating Roof Tank #655 (888,266 gallons)	NA
17	17	Internal Floating Roof Tank #1358 (1,697,811 gallons)	NA
18	18	Internal Floating Roof Tank #1359 (1,697,811 gallons)	NA
19	19	Internal Floating Roof Tank #1360 (1,697,811 gallons)	NA
22	22	Internal Floating Roof Tank #1363 (1,697,811 gallons)	NA
23	23	Internal Floating Roof Tank #1364 (1,697,811 gallons)	NA
25	25	Internal Floating Roof Tank #1366 (1,697,811 gallons)	NA
26	26	Internal Floating Roof Tank #1367 (1,697,811 gallons)	NA
28	28	Internal Floating Roof Tank #1390 (1,697,811 gallons)	NA
31	31	Facility Fugitives	NA
41	41	Floating Roof Landings	NA

Insignificant Activities Equipment List

Insignificant Emission Unit Number	Insignificant Emission Unit Description
15 ^{(1),(2)}	Spherical Tank #903 (266,639 gallons)
16 ^{(1),(2)}	Spherical Tank #1001 (660,090 gallons)
20 ^{(1),(2)}	Vertical Fixed Roof Tank #1361 (1,697,811 gallons)
21 ^{(1),(2)}	Vertical Fixed Roof Tank #1362 (1,612,920 gallons)
24 ^{(1),(2)}	Vertical Fixed Roof Tank #1365 (1,697,811 gallons)
27 ^{(1),(2)}	Vertical Fixed Roof Tank #1389 (1,697,811 gallons)
29 ^{(1),(2)}	Vertical Fixed Roof Tank #1436 (2,284,114 gallons)
30 ⁽²⁾	Relief Tank (29,600 gallons)
32a	Additive Tank #1 (1,003 gallons)
32b	Additive Tank #2 (2,538 gallons)
32c	Additive Tank #3 (4,022 gallons)
32d	Additive Tank #4 (2,540 gallons)
32e	Additive Tank #5 (4,162 gallons)
32f	Additive Tank #6 (400 gallons)
32g	Additive Tank #7 (8,000 gallons)
32h	Additive Tank #8 (3,000 gallons)
32i	Additive Tank #9 (1,040 gallons)
32j	Additive Tank #10 (2,000 gallons)
32k	Additive Tank #11 (180 gallons)
32l	Additive Tank #12 (1,330 gallons)
32m	Additive Tank #13 (358 gallons)
32n	Additive Tank #14 (358 gallons)
32o	Additive Tank #15 – Lubricity (4,000 gallons)
32p	Additive Tank #16 (1,040 gallons)
32q	Additive Tank #17 (1,062 gallons)
32r	Additive Tank #138 (4,000 gallons)
33	Sump Tanks (oil/water separator)
34	7 NG Furnaces (100,000 Btu/hr each)
37 ⁽²⁾	Pigging/Emergency Use Flare
39 ⁽²⁾	Q Grade Filter Drainage
40 ⁽²⁾	Butane Truck Unloading, Sample Tee Purging, and Routine Maintenance
42 ⁽²⁾	Ethanol Offloading Skid

⁽¹⁾ These tanks are not used to store gasoline at this time. If they are used to store gasoline, they will be subject to NESHAP - 40 CFR 63 subpart BBBB and become significant emission units.

⁽²⁾ Emission Units qualify for Small Unit Exemption under 567 IAC 22.1(2)"w". Records shall be kept in accordance with 567 IAC 22.1(2)"w"(3).

II. Plant-Wide Conditions

Facility Name: Magellan Pipeline Company, LP – Iowa City Terminal

Permit Number: 03-TV-010R3

Permit conditions are established in accord with 567 Iowa Administrative Code rule 22.108

Permit Duration

The term of this permit is: Five (5) years.

Commencing on: August 6, 2019

Ending on: August 5, 2024

Amendments, modifications and reopenings of the permit shall be obtained in accordance with 567 Iowa Administrative Code rules 22.110 - 22.114. Permits may be suspended, terminated, or revoked as specified in 567 Iowa Administrative Code Rules 22.115.

Emission Limits

Unless specified otherwise in the Source Specific Conditions, the following limitations and supporting regulations apply to all emission points at this plant:

Opacity (visible emissions): 40% opacity

Authority for Requirement: 567 IAC 23.3(2)"d"

Sulfur Dioxide (SO₂): 500 parts per million by volume

Authority for Requirement: 567 IAC 23.3(3)"e"

Particulate Matter:

No person shall cause or allow the emission of particulate matter from any source in excess of the emission standards specified in this chapter, except as provided in 567 – Chapter 24. For sources constructed, modified or reconstructed on or after July 21, 1999, the emission of particulate matter from any process shall not exceed an emission standard of 0.1 grain per dry standard cubic foot of exhaust gas, except as provided in 567 – 21.2(455B), 23.1(455B), 23.4(455B) and 567 – Chapter 24.

For sources constructed, modified or reconstructed prior to July 21, 1999, the emission of particulate matter from any process shall not exceed the amount determined from Table I, or amount specified in a permit if based on an emission standard of 0.1 grain per standard cubic foot of exhaust gas or established from standards provided in 23.1(455B) and 23.4(455B).

Authority for Requirement: 567 IAC 23.3(2)"a"

Fugitive Dust: Attainment and Unclassified Areas - A person shall take reasonable precautions to prevent particulate matter from becoming airborne in quantities sufficient to cause a nuisance as defined in Iowa Code section 657.1 when the person allows, causes or permits any materials

to be handled, transported or stored or a building, its appurtenances or a construction haul road to be used, constructed, altered, repaired or demolished, with the exception of farming operations or dust generated by ordinary travel on unpaved roads. Ordinary travel includes routine traffic and road maintenance activities such as scarifying, compacting, transporting road maintenance surfacing material, and scraping of the unpaved public road surface. (the preceding sentence is State Only) All persons, with the above exceptions, shall take reasonable precautions to prevent the discharge of visible emissions of fugitive dusts beyond the lot line of the property on which the emissions originate. The public highway authority shall be responsible for taking corrective action in those cases where said authority has received complaints of or has actual knowledge of dust conditions which require abatement pursuant to this subrule. Reasonable precautions may include, but not be limited to, the following procedures.

1. Use, where practical, of water or chemicals for control of dusts in the demolition of existing buildings or structures, construction operations, the grading of roads or the clearing of land.
2. Application of suitable materials, such as but not limited to asphalt, oil, water or chemicals on unpaved roads, material stockpiles, race tracks and other surfaces which can give rise to airborne dusts.
3. Installation and use of containment or control equipment, to enclose or otherwise limit the emissions resulting from the handling and transfer of dusty materials, such as but not limited to grain, fertilizer or limestone.
4. Covering, at all times when in motion, open-bodied vehicles transporting materials likely to give rise to airborne dusts.
5. Prompt removal of earth or other material from paved streets or to which earth or other material has been transported by trucking or earth-moving equipment, erosion by water or other means.
6. Reducing the speed of vehicles traveling over on-property surfaces as necessary to minimize the generation of airborne dusts.

Authority for Requirement: 567 IAC 23.3(2)"c"

40 CFR 60 Subpart A Requirements

This facility is an affected source and these *General Provisions* apply to the facility. The affected unit is EU 1. Applicable requirements are incorporated in the Emission Point Specific conditions. See Appendix for a link to the Standard.

Authority for Requirement: 40 CFR 60 Subpart A
567 IAC 23.1(2)

40 CFR 60 Subpart XX Requirements

Truck Loading Rack, EU 1 is subject to the New Source Performance Standards (NSPS) Subpart XX – Standards of Performance for *Bulk Gasoline Terminals*. Applicable subpart XX requirements are incorporated into this permit. See the Appendix for a link to the Standard.

Authority for Requirement: 40 CFR 60 Subpart XX
567 IAC 23.1(2)"pp"

40 CFR 63 Subpart A Requirements

This facility is an affected source and these *General Provisions* apply to the facility. All emission units at this facility are affected units. Applicable requirements are incorporated in the Emission Point Specific conditions. See Appendix for a link to the Standard.

Authority for Requirements: 40 CFR 63 Subpart A
567 IAC 23.1(4)

40 CFR 63 Subpart BBBBBB Requirements

All emission units at this facility are subject to the National Emission Standards for Hazardous Air Pollutants (NESHAP) Subpart BBBBBB - *Source Category: Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities*. The facility is responsible for compliance with the most current version of the regulation. Applicable subpart BBBBBB requirements are incorporated into this permit. See the Appendix for a link to the Standard.

Authority for Requirements: 40 CFR 63 Subpart BBBBBB
567 IAC 23.1(4)"eb"

III. Emission Point-Specific Conditions

Facility Name: Magellan Company, LP – Iowa City Terminal
Permit Number: 03-TV-010R3

Emission Point ID Number: 1

Associated Equipment

Associated Emission Unit ID Number: 1
Emissions Control Equipment ID Number: CE-01
Emissions Control Equipment Description: Vapor Combustion Unit

Emission Unit vented through this Emission Point: 1
Emission Unit Description: Truck Loading System
Raw Material/Fuel: Gasoline, Ethanol, and Distillates
Rated Capacity: 96,000 gallons/hr

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity
Emission Limit(s): 40%⁽¹⁾
Authority for Requirement: DNR Construction Permit 96-A-1030-S1
567 IAC 23.3(2)"d"

Pollutant: Particulate Matter (PM) – State
Emission Limit(s): 0.1 gr/dscf
Authority for Requirement: DNR Construction Permit 96-A-1030-S1
567 IAC 23.3(2)"a"

Pollutant: Particulate Matter (PM) – State
Emission Limit(s): 0.03 lb/hr
Authority for Requirement: DNR Construction Permit 96-A-1030-S1

Pollutant: Sulfur Dioxide (SO₂)
Emission Limit(s): 500 ppmv
Authority for Requirement: DNR Construction Permit 96-A-1030-S1
567 IAC 23.3(3)"e"

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 35 mg/L

Authority for Requirement: DNR Construction Permit 96-A-1030-S1
40 CFR Part 60 Subpart XX
567 IAC 23.1(2)"pp"

- (1) An exceedance of the indicator opacity of "no visible emissions" will require the owner or operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the Department may require additional proof to demonstrate compliance (e.g., stack testing).

Operational Limits & Reporting and Recordkeeping Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.

PRODUCT and VOC LIMITS REQUIREMENTS

- A. The owner or operator may use the Truck Loading System (EU-1) to load any of the following products: gasoline, denatured ethanol, jet kerosene, and other distillate fuels into trucks.
- i. The owner or operator shall retain on-site Safety Data Sheets of all materials handled at the Truck Loading System (EU-1).
- B. Per 40 CFR Part 60, Subpart XX – *Standards of Performance for Bulk Gasoline Terminals*, emissions to the atmosphere from Emission Point 1 shall not exceed 35 milligrams of total organic compounds per liter of gasoline loaded.
- i. The owner or operator shall install and operate a vapor processing system¹ to ensure compliance with the required VOC emission limit.

HAP CONTENT LIMITS REQUIREMENTS

- C. The *vapor phase* Single HAP composition of the gasoline loaded at the Truck Loading System (EU-1) shall not exceed 3.65 percent by weight.
- D. The *vapor phase* Total HAP composition of the gasoline loaded at the Truck Loading System (EU-1) shall not exceed 9.49 percent by weight.
- E. The owner or operator shall conduct sampling of all the gasoline grades loaded at the Truck Loading System (EU-1) to determine the liquid phase Single HAP and Total HAP content, in weight percent, for the following compounds:

¹ Per 40 CFR §60.501, "*vapor processing system*" means all equipment used for recovering or oxidizing total organic compounds vapors displaced from the affected facility. The Truck Loading System (EU-1) at the Iowa City Terminal is equipped with a Vapor Combustion Unit that oxidizes organic vapors displaced during product loading.

- i. Benzene, ethylbenzene, hexane, toluene, 2,2,4-trimethylpentane, and xylenes.
- F. The owner or operator shall conduct liquid phase sampling using ASTM Method D6729 (*Detailed Hydrocarbon Analysis*) of all the gasoline grades loaded at the Truck Loading System (EU-1) for at least two calendar years after the issuance date (4/16/2018) of the construction permit 96-A-1030-S1.
- i. The owner or operator shall retain on-site the results from the most recent gasoline sampling.
- G. The owner or operator shall calculate and record the vapor phase Single HAP and Total HAP content, in weight percent for the HAPs listed in Condition E.i. using:
- i. The highest liquid phase HAP content determined during the most recent gasoline sampling;
 - ii. An average loading temperature of 50 degrees Fahrenheit; and
 - iii. A vapor phase HAP calculation method approved by the Department.

NSPS REQUIREMENTS

- H. The owner or operator shall comply with the applicable requirements in 40 CFR Part 60, Subpart XX [§60.500 - §60.506], including those not specifically mentioned in this permit.
- i. The owner or operator shall comply with the requirements in 40 CFR §60.502, including, but not limited to the following:
 - 1. The owner or operator shall equip the total of all loading racks with a vapor collection system designed to collect the total organic compounds vapors displaced from tank trucks during product loading.
 - 2. The owner or operator shall design each vapor collection system to prevent any total organic compounds vapors collected at one loading rack from passing to another loading rack.
 - 3. Loading of liquid products into gasoline tank trucks shall be limited to vapor-tight gasoline tank trucks as defined in 40 CFR §60.501.
 - a) The owner or operator shall ensure the vapor tightness of the gasoline tank trucks by following the procedures in 40 CFR §60.502(e).
 - 4. The owner or operator shall act to assure that loadings of gasoline tank trucks at the affected facility are made only into tanks equipped with vapor collection equipment that is compatible with the terminal's vapor collection system.

5. The owner or operator shall act to assure that the terminal's and the tank truck's vapor collection systems are connected during each loading of a gasoline tank truck at the affected emission unit.
 6. The vapor collection and liquid loading equipment shall be designed and operated to prevent gauge pressure in the delivery tank from exceeding 450 mm of water during product loading.
 - a) Per 40 CFR §60.503(d), the owner or operator shall determine compliance with the delivery tank gauge pressure limitation by installing and operating a pressure measurement device as described in §60.503(d)(1).
 7. No pressure-vacuum vent in the bulk gasoline terminal's vapor collection system shall begin to open at a system pressure of less than 450 mm of water.
 8. Each calendar month, the vapor collection system, the vapor processing system, and each loading rack handling gasoline shall be inspected during the loading of gasoline tank trucks for total organic compounds liquid vapor leaks. Detection methods incorporating sight, sound, or smell are acceptable.
 - a) Each detection leak shall be recorded and the source of the leak repaired within 15 calendar days after it is detected.
- ii. The owner or operator shall comply with the applicable reporting and recordkeeping requirements described in 40 CFR §60.505.

NESHAP REQUIREMENTS

- I. The owner or operator shall comply with the applicable requirements in 40 CFR Part 60, Subpart BBBBBB [§63.11080 - §63.11100], including those not specifically mentioned in this permit.
 - i. Per 40 CFR §63.11085(a), the owner or operator shall, at all times, operate and maintain any affected source in a manner consistent with safety and good air pollution control practices for minimizing emissions. Determination of whether such operation and maintenance procedures are being used will be based on information available to the Department, which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source.
 - ii. Per 40 CFR §63.11088(a), the owner or operator shall meet each applicable emission limit and management practice in Table 2 to Subpart BBBBBB of Part 63.

- iii. Per 40 CFR §63.11089, the owner or operator shall perform a monthly leak inspection of all equipment in gasoline service, as defined in §63.11100. For this inspection, detection methods incorporating sight, sound, and smell are acceptable.
 - 1.The owner or operator shall maintain a logbook indicating each detection of a liquid or vapor leak.
 - 2.When a leak is detected, the owner or operator shall make an initial attempt at repair it as soon as practicable, but no later than five calendar days after the leak is detected.
 - 3.The owner or operator shall complete the repair or replacement of leaking equipment within 15 calendar days after detection of each leak.
 - 4.Delay of repair of leaking equipment shall be allowed if the repair is not feasible within 15 days.
- iv. Per 40 CFR §63.11092(a), the owner or operator shall comply with the applicable testing and monitoring requirements listed in §63.11092(a) through §63.11092(d).
 - 1.Per 40 CFR §63.11092(d), the owner or operator shall operate the vapor processing system in a manner not to exceed or not to go below, as appropriate, the operating parameter determined using the procedures in §63.11092.
- v. The owner or operator shall comply with the applicable notification, recordkeeping, and reporting requirements described in 40 CFR §63.11093, §63.11094, and §63.11095, respectively.

VAPOR COMBUSTION UNIT OPERATION REQUIREMENTS

- J. The pilot associated with the Vapor Combustion Unit shall only use natural gas or propane.
- K. The owner or operator shall inspect and maintain the Vapor Combustion Unit according to the facility's (Plant No. 52-02-006) operation and maintenance plan.
 - i. Pursuant to 567 IAC 22.3(3), the owner or operator shall keep a log of all maintenance and inspection activities performed on the vapor processing system Vapor Combustion Unit. This log shall include, but shall not limited to:
 - 1.The date that any inspection and/or maintenance was performed on the control equipment;
 - 2.Any issues identified during the inspection;
 - 3.Any issues addressed during the maintenance activities and the date each issue was resolved; and

4. Identification of the staff member performing the maintenance or inspection.

Authority for Requirement: DNR Construction Permit 96-A-1030-S1

NESHAP and NSPS Applicability

This emission unit is subject to Subparts A (*General Provisions*; 40 CFR §60.1 – 40 CFR §60.19) and XX (*Standards of Performance for Bulk Gasoline Terminals*; 40 CFR §60.500 – 40 CFR §60.506) of the New Source Performance Standards (NSPS).

Authority for Requirement: DNR Construction Permit 96-A-1030-S1
40 CFR 60 Subpart XX
567 IAC 23.1(2)"pp"

This unit is subject to the requirements of 40 CFR Part 63, Subpart BBBBBB – National Emission Standards for Hazardous Air Pollutants for *Source Category: Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities* (§§ 63.11080 through 63.11100). In accordance with §63.11082, the facility meets the definition of an existing bulk gasoline terminal. The unit is also subject to the applicable requirements of the General Provisions (§§ 63.1 through 63.15) per Table 3 to Part 63, Subpart BBBBBB.

Authority for Requirement: DNR Construction Permit 96-A-1030-S1
40 CFR 63 Subpart BBBBBB
567 IAC 23.1(4)"eb"

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 40

Stack Opening, (inches, dia.): 96

Exhaust Flow Rate (scfm): 26,333

Exhaust Temperature (°F): 1,800

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 96-A-1030-S1

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within thirty (30) days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Monitoring Requirements (40 CFR 63.11092(b)):

(b) Each owner or operator of a bulk gasoline terminal subject to the provisions of this subpart shall install, calibrate, certify, operate, and maintain, according to the manufacturer's specifications, a continuous monitoring system (CMS) while gasoline vapors are displaced to the vapor processor systems, as specified in paragraphs (b)(1) through (5) of this section. For each facility conducting a performance test under paragraph (a)(1) of this section, and for each facility utilizing the provisions of paragraphs (a)(2) or (a)(3) of this section, the CMS must be installed by January 10, 2011.

(1) For each performance test conducted under paragraph (a)(1) of this section, the owner or operator shall determine a monitored operating parameter value for the vapor processing system using the procedures specified in paragraphs (b)(1)(i) through (iv) of this section. During the performance test, continuously record the operating parameter as specified under paragraphs (b)(1)(i) through (iv) of this section.

...

(iii) Where a thermal oxidation system other than a flare is used, the owner or operator shall monitor the operation of the system as specified in paragraphs (b)(1)(iii)(A) or (B) of this section. (A) A continuous parameter monitoring system (CPMS) capable of measuring temperature shall be installed in the firebox or in the ductwork immediately downstream from the firebox in a position before any substantial heat exchange occurs.

(B) As an alternative to paragraph (b)(1)(iii)(A) of this section, you may choose to meet the requirements listed in paragraphs (b)(1)(iii)(B)(1) and (2) of this section.

(1) The presence of a thermal oxidation system pilot flame shall be monitored using a heat-sensing device, such as an ultraviolet beam sensor or a thermocouple, installed in proximity to the pilot light to indicate the presence of a flame. The heat-sensing device shall send a positive parameter value to indicate that the pilot flame is on, or a negative parameter value to indicate that the pilot flame is off.

(2) Develop and submit to the Administrator a monitoring and inspection plan that describes the owner or operator's approach for meeting the requirements in paragraphs (b)(1)(iii)(B)(2)(i) through (v) of this section.

(i) The thermal oxidation system shall be equipped to automatically prevent gasoline loading operations from beginning at any time that the pilot flame is absent.

(ii) The owner or operator shall verify, during each day of operation of the loading rack, the proper operation of the assist-air blower and the vapor line valve. Verification shall be through visual observation, or through an automated alarm or shutdown system that monitors system operation. A manual or electronic record of the start and end of a shutdown event may be used.

(iii) The owner or operator shall perform semi-annual preventive maintenance inspections of the thermal oxidation system, including the automated alarm or shutdown system for those units so equipped, according to the recommendations of the manufacturer of the system.

(iv) The monitoring plan developed under paragraph (2) of this section shall specify conditions that would be considered malfunctions of the thermal oxidation system during the inspections or automated monitoring performed under paragraphs (b)(1)(iii)(B)(2)(ii) and (iii) of this section,

describe specific corrective actions that will be taken to correct any malfunction, and define what the owner or operator would consider to be a timely repair for each potential malfunction.

(v) The owner or operator shall document any system malfunction, as defined in the monitoring and inspection plan, and any activation of the automated alarm or shutdown system with a written entry into a log book or other permanent form of record. Such record shall also include a description of the corrective action taken and whether such corrective actions were taken in a timely manner, as defined in the monitoring and inspection plan, as well as an estimate of the amount of gasoline loaded during the period of the malfunction.

...

(3) Determine an operating parameter value based on the parameter data monitored during the performance test, supplemented by engineering assessments and the manufacturer's recommendations.

(4) Provide for the Administrator's approval the rationale for the selected operating parameter value, monitoring frequency, and averaging time, including data and calculations used to develop the value and a description of why the value, monitoring frequency, and averaging time demonstrate continuous compliance with the emission standard in §63.11088(a).

...

(c) For performance tests performed after the initial test required under paragraph (a) of this section, the owner or operator shall document the reasons for any change in the operating parameter value since the previous performance test.

(d) Each owner or operator of a bulk gasoline terminal subject to the provisions of this subpart shall comply with the requirements in paragraphs (d)(1) through (4) of this section.

(1) Operate the vapor processing system in a manner not to exceed or not to go below, as appropriate, the operating parameter value for the parameters described in paragraph (b)(1) of this section.

(2) In cases where an alternative parameter pursuant to paragraph (b)(1)(iv) or paragraph (b)(5)(i) of this section is approved, each owner or operator shall operate the vapor processing system in a manner not to exceed or not to go below, as appropriate, the alternative operating parameter value.

(3) Operation of the vapor processing system in a manner exceeding or going below the operating parameter value, as appropriate, shall constitute a violation of the emission standard in §63.11088(a), except as specified in paragraph (d)(4) of this section.

(4) For the monitoring and inspection, as required under paragraphs (b)(1)(i)(B)(2) and (b)(1)(iii)(B)(2) of this section, malfunctions that are discovered shall not constitute a violation of the emission standard in §63.11088(a) if corrective actions as described in the monitoring and inspection plan are followed. The owner or operator must:

(i) Initiate corrective action to determine the cause of the problem within 1 hour;

(ii) Initiate corrective action to fix the problem within 24 hours;

(iii) Complete all corrective actions needed to fix the problem as soon as practicable consistent with good air pollution control practices for minimizing emissions;

(iv) Minimize periods of start-up, shutdown, or malfunction; and

(v) Take any necessary corrective actions to restore normal operation and prevent the recurrence of the cause of the problem.

...

(f) The annual certification test for gasoline cargo tanks shall consist of the test methods specified in paragraphs (f)(1) or (f)(2) of this section. Affected facilities that are subject to subpart XX of 40 CFR part 60 may elect, after notification to the subpart XX delegated authority, to comply with paragraphs (f)(1) and (2) of this section.

(1) *EPA Method 27, Appendix A-8, 40 CFR part 60.* Conduct the test using a time period (t) for the pressure and vacuum tests of 5 minutes. The initial pressure (Pi) for the pressure test shall be 460 millimeters (mm) of water (18 inches of water), gauge. The initial vacuum (Vi) for the vacuum test shall be 150 mm of water (6 inches of water), gauge. The maximum allowable pressure and vacuum changes (Δp , Δv) for all affected gasoline cargo tanks is 3 inches of water, or less, in 5 minutes.

Authority for Requirement: 40 CFR 63 Subpart BBBBBB
567 IAC 23.1(4)"eb"

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

The CAM plan requirements are satisfied by complying with 40 CFR 63 Subpart BBBBBB monitoring requirements mentioned above.

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: See Table 1

Associated Equipment

Associated Emission Unit ID Numbers: See Table 1

Table 1

EP	EU	Emission Unit Description	Raw Material/ Fuel⁽¹⁾	Storage Capacity	Engineered Capacity⁽²⁾
2	2	Domed External Floating Roof Tank #402	Natural Gasoline or Gasoline	266,480 gallons	235,410 gallons
3	3	Domed External Floating Roof Tank #403	Natural Gasoline or Gasoline	265,186 gallons	235,368 gallons
4	4	Domed External Floating Roof Tank #407	Natural Gasoline or Gasoline	252,662 gallons	221,802 gallons
5	5	Domed External Floating Roof Tank #423	Natural Gasoline or Gasoline	266,480 gallons	235,368 gallons
6	6	Domed External Floating Roof Tank #424	Natural Gasoline or Gasoline	266,480 gallons	234,906 gallons
7	7	Domed External Floating Roof Tank #623	Natural Gasoline or Gasoline	740,222 gallons	625,590 gallons
8	8	Domed External Floating Roof Tank #624	Natural Gasoline or Gasoline	713,786 gallons	623,196 gallons
9	9	Domed External Floating Roof Tank #631	Natural Gasoline or Gasoline	713,786 gallons	626,850 gallons
10	10	Domed External Floating Roof Tank #632	Natural Gasoline or Gasoline	712,728 gallons	615,846 gallons
11	11	Domed External Floating Roof Tank #641	Natural Gasoline or Gasoline	845,968 gallons	625,086 gallons
12	12	Domed External Floating Roof Tank #642	Natural Gasoline or Gasoline	888,266 gallons	740,208 gallons
13	13	Domed External Floating Roof Tank #645	Natural Gasoline or Gasoline	740,222 gallons	619,374 gallons
14	14	Domed External Floating Roof Tank #655	Natural Gasoline or Gasoline	888,266 gallons	694,512 gallons

⁽¹⁾ Tanks may be in Natural Gasoline/Gasoline or other less volatile product service.

⁽²⁾ Engineered capacity is based on the maximum height of the floating roof allowed by the facility due to high level alarms and engineering controls.

Applicable Requirements

(The following requirements apply to the emission units identified in Table 1)

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from these emission points shall not exceed the levels specified below.

None at this time.

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Process throughput:

1. These tanks shall store natural gasoline, or other liquid with a lower vapor pressure.

Authority for Requirements: 567 IAC 22.108(14)

Reporting and Recordkeeping

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.

1. The type of liquid and vapor pressure of the liquid stored in each tank.

Authority for Requirements: 567 IAC 22.108(3)

NESHAP and NSPS Applicability

These units are subject to the requirements of 40 CFR Part 63, Subpart BBBBBB – National Emission Standards for Hazardous Air Pollutants for *Source Category: Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities* (§§ 63.11080 through 63.11100). In accordance with §63.11082, the facility meets the definition of an existing bulk gasoline terminal. These units are also subject to the applicable requirements of the General Provisions (§§ 63.1 through 63.15) per Table 3 to Part 63, Subpart BBBBBB.

NESHAP Subpart BBBBBB Requirements

1. The owner/operator of this equipment shall comply with the operational limits and requirements listed below when in gasoline service.

Table 1 to Subpart BBBBBB of Part 63—Applicability Criteria, Emission Limits, and Management Practices for Storage Tanks

If you own or operate . . .	Then you must . . .
2. A gasoline storage tank with a capacity of greater than or equal to 75 m ³ and not meeting any of the criteria specified in item 1 of this Table	(b) Equip each internal floating roof gasoline storage tank according to the requirements in § 60.112b(a)(1) of this chapter, except for the secondary seal requirements under § 60.112b(a)(1)(ii)(B) and the requirements in § 60.112b(a)(1)(iv) through (ix) of this chapter; or

	(d) Equip and operate each internal and external floating roof gasoline storage tank according to the applicable requirements in §63.1063(a)(1) and (b), except for the secondary seal requirements under §63.1063(a)(1)(i)(C) and (D), and equip each external floating roof gasoline storage tank according to the requirements of §63.1063(a)(2) if such storage tank does not currently meet the requirements of §63.1063(a)(1).
--	--

2. The owner or operator shall meet the applicable recordkeeping and reporting standards of 40 CFR §63.11094 and 40 CFR §63.11095.
3. The owner or operator shall meet the applicable testing and monitoring requirements in accordance with 40 CFR§63.11092(e).
4. The owner or operator shall meet the applicable notification requirements in accordance with 40 CFR §63.11093.

Authority for Requirements: 40 CFR 63 Subpart BBBBBB
567 IAC 23.1(4)"eb"

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: See Table 2

Associated Equipment

Associated Emission Unit ID Numbers: See Table 2

Table 2

EP	EU	Emission Unit Description	Raw Material/ Fuel⁽¹⁾	Storage Capacity	Engineered Capacity⁽²⁾
17	17	Internal Floating Roof Tank #1358	Natural Gasoline or Gasoline	1,697,811 gallons	1,580,926 gallons
18	18	Internal Floating Roof Tank #1359	Natural Gasoline or Gasoline	1,697,811 gallons	1,570,254 gallons
19	19	Internal Floating Roof Tank #1360	Natural Gasoline or Gasoline	1,697,811 gallons	1,543,920 gallons
22	22	Internal Floating Roof Tank #1363	Natural Gasoline or Gasoline	1,697,811 gallons	1,571,136 gallons
23	23	Internal Floating Roof Tank #1364	Natural Gasoline or Gasoline	1,697,811 gallons	1,151,052 gallons
25	25	Internal Floating Roof Tank #1366	Natural Gasoline or Gasoline	1,697,811 gallons	1,544,382 gallons
26	26	Internal Floating Roof Tank #1367	Natural Gasoline or Gasoline	1,697,811 gallons	1,570,548 gallons
28	28	Internal Floating Roof Tank #1390	Natural Gasoline or Gasoline	1,697,811 gallons	1,526,826 gallons

⁽¹⁾ Tanks may be in Natural Gasoline/Gasoline or other less volatile product service.

⁽²⁾ Engineered capacity is based on the maximum height of the floating roof allowed by the facility due to high level alarms and engineering controls.

Applicable Requirements

(The following requirements apply to the emission units identified in Table 2)

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from these emission points shall not exceed the levels specified below.

None at this time.

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Process throughput:

1. These tanks shall store natural gasoline, or other liquid with a lower vapor pressure.

Authority for Requirements: 567 IAC 22.108(14)

Reporting and Recordkeeping

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.

1. The type of liquid and vapor pressure of the liquid stored in each tank.

Authority for Requirements: 567 IAC 22.108(3)

NESHAP and NSPS Applicability

These units are subject to the requirements of 40 CFR Part 63, Subpart BBBBBB – National Emission Standards for Hazardous Air Pollutants for *Source Category: Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities* (§§ 63.11080 through 63.11100). In accordance with §63.11082, the facility meets the definition of an existing bulk gasoline terminal. These units are also subject to the applicable requirements of the General Provisions (§§ 63.1 through 63.15) per Table 3 to Part 63, Subpart BBBBBB.

NESHAP Subpart BBBBBB Requirements

1. The owner/operator of this equipment shall comply with the operational limits and requirements listed below when in gasoline service.

Table 1 to Subpart BBBBBB of Part 63—Applicability Criteria, Emission Limits, and Management Practices for Storage Tanks

If you own or operate . . .	Then you must . . .
2. A gasoline storage tank with a capacity of greater than or equal to 75 m ³ and not meeting any of the criteria specified in item 1 of this Table	(b) Equip each internal floating roof gasoline storage tank according to the requirements in §60.112b(a)(1) of this chapter, except for the secondary seal requirements under §60.112b(a)(1)(ii)(B) and the requirements in §60.112b(a)(1)(iv) through (ix) of this chapter; or
	(d) Equip and operate each internal and external floating roof gasoline storage tank according to the applicable requirements in §63.1063(a)(1) and (b), except for the secondary seal requirements under §63.1063(a)(1)(i)(C) and (D), and equip each external floating roof gasoline storage tank according to the requirements of §63.1063(a)(2) if such storage tank does not currently meet the requirements of §63.1063(a)(1).

2. The owner or operator shall meet the applicable recordkeeping and reporting standards of 40 CFR §63.11094 and 40 CFR §63.11095.

3. The owner or operator shall meet the applicable testing and monitoring requirements in accordance with 40 CFR §63.11092(e).
4. The owner or operator shall meet the applicable notification requirements in accordance with 40 CFR §63.11093.

Authority for Requirement: 40 CFR 63 Subpart BBBBBB
567 IAC 23.1(4)"eb"

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 31

Associated Equipment

Associated Emission Unit ID Number: 31

Emission Unit vented through this Emission Point: 31

Emission Unit Description: Valves, Pumps, Flanges, and Equipment Leaks

Raw Material/Fuel: Gasoline, Ethanol, and Distillate Fuel

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

None at this time.

Operational Limits & Reporting and Recordkeeping Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.

1. The owner or operator shall meet the applicable recordkeeping and reporting standards of §63.11094(e), §63.11095(a)(3), and §63.11095(b)(5).

Authority for Requirement: 40 CFR Part 63 Subpart BBBBBB
567 IAC 23.1(4)"eb"

NESHAP and NSPS Applicability

This unit is subject to the requirements of 40 CFR Part 63, Subpart BBBBBB – National Emission Standards for Hazardous Air Pollutants for *Source Category: Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities* (§§ 63.11080 through 63.11100). In accordance with §63.11082, the facility meets the definition of an existing bulk gasoline terminal. The unit is also subject to the applicable requirements of the General Provisions (§§ 63.1 through 63.15) per Table 3 to Part 63, Subpart BBBBBB.

NESHAP Subpart BBBBBB Requirements

1. Equipment at the facility "in gasoline service" is subject to applicable requirements for equipment leak inspections in accordance with 40 CFR Part 63.11089.
2. The owner or operator shall meet the applicable notification requirements in accordance with and 40 CFR 63.11093. The owner or operator shall meet the applicable notification requirements in accordance with 40 CFR 63.11093.

Authority for Requirement: 40 CFR Part 63 Subpart BBBBBB
567 IAC 23.1(4)"eb"

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 41

Associated Equipment

Associated Emission Unit ID Numbers: 41

Emission Unit vented through this Emission Point: 41

Emission Unit Description: Floating Roof Landing Losses for Emission Units 2-14, 17-19, 22-23, 25-26, and 28

Raw Material/Fuel: Gasoline

Rated Capacity: NA

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

None at this time.

Operational Limits & Reporting and Recordkeeping Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below. All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner.

1. The owner or operator shall meet the applicable recordkeeping and reporting standards of 40 CFR Part 63 Subpart BBBBBB as defined for the respected tank.
2. For each roof landing, record the tank number, product stored before and after each landing event, and the start and stop dates of the landing.

Authority for Requirement: 567 IAC 22.108(3)

NESHAP and NSPS Applicability

This unit is subject to the requirements of 40 CFR Part 63, Subpart BBBBBB – National Emission Standards for Hazardous Air Pollutants for *Source Category: Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities* (§§ 63.11080 through 63.11100). In accordance with §63.11082, the facility meets the definition of an existing bulk gasoline terminal. The unit is also subject to the applicable requirements of the General Provisions (§§ 63.1 through 63.15) per Table 3 to Part 63, Subpart BBBBBB.

NESHAP Subpart BBBBBB Requirements

1. The owner or operator shall meet the applicable requirements of 40 CFR Part 63 Subpart BBBBBB as defined for the respected tank.

Authority for Requirement: 40 CFR Part 63 Subpart BBBBBB
567 IAC 23.1(4)"eb"

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

IV. General Conditions

This permit is issued under the authority of the Iowa Code subsection 455B.133(8) and in accordance with 567 Iowa Administrative Code chapter 22.

G1. Duty to Comply

1. The permittee must comply with all conditions of the Title V permit. Any permit noncompliance constitutes a violation of the Act and is grounds for enforcement action; for a permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application. *567 IAC 22.108(9)"a"*
2. Any compliance schedule shall be supplemental to, and shall not sanction noncompliance with, the applicable requirements on which it is based. *567 IAC 22.105 (2)"h"(3)*
3. Where an applicable requirement of the Act is more stringent than an applicable requirement of regulations promulgated under Title IV of the Act, both provisions shall be enforceable by the administrator and are incorporated into this permit. *567 IAC 22.108 (1)"b"*
4. Unless specified as either "state enforceable only" or "local program enforceable only", all terms and conditions in the permit, including provisions to limit a source's potential to emit, are enforceable by the administrator and citizens under the Act. *567 IAC 22.108 (14)*
5. It shall not be a defense for a permittee, in an enforcement action, that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. *567 IAC 22.108 (9)"b"*
6. For applicable requirements with which the permittee is in compliance, the permittee shall continue to comply with such requirements. For applicable requirements that will become effective during the permit term, the permittee shall meet such requirements on a timely basis. *567 IAC 22.108(15)"c"*

G2. Permit Expiration

1. Except as provided in rule 567—22.104(455B), permit expiration terminates a source's right to operate unless a timely and complete application for renewal has been submitted in accordance with rule 567—22.105(455B). *567 IAC 22.116(2)*
2. To be considered timely, the owner, operator, or designated representative (where applicable) of each source required to obtain a Title V permit shall submit on forms or electronic format specified by the Department to the Air Quality Bureau, Iowa Department of Natural Resources, Air Quality Bureau, Wallace State Office Building, 502 E 9th St., Des Moines, IA 50319-0034, two copies (three if your facility is located in Linn or Polk county) of a complete permit application, at least 6 months but not more than 18 months prior to the date of permit expiration. An additional copy must also be sent to U.S. EPA Region VII, Attention: Chief of Air Permitting & Standards Branch, 11201 Renner Blvd., Lenexa, KS 66219. Additional copies to local programs or EPA are not required for application materials submitted through the electronic format specified by the Department. The application must include all emission points, emission units, air pollution control equipment, and monitoring devices at the facility. All emissions generating activities, including fugitive emissions, must be included. The definition of a complete application is as indicated in 567 IAC 22.105(2). *567 IAC 22.105*

G3. Certification Requirement for Title V Related Documents

Any application, report, compliance certification or other document submitted pursuant to this permit shall contain certification by a responsible official of truth, accuracy, and completeness. All certifications shall state that, based on information and belief formed after reasonable

inquiry, the statements and information in the document are true, accurate, and complete. 567 IAC 22.107 (4)

G4. Annual Compliance Certification

By March 31 of each year, the permittee shall submit compliance certifications for the previous calendar year. The certifications shall include descriptions of means to monitor the compliance status of all emissions sources including emissions limitations, standards, and work practices in accordance with applicable requirements. The certification for a source shall include the identification of each term or condition of the permit that is the basis of the certification; the compliance status; whether compliance was continuous or intermittent; the method(s) used for determining the compliance status of the source, currently and over the reporting period consistent with all applicable department rules. For sources determined not to be in compliance at the time of compliance certification, a compliance schedule shall be submitted which provides for periodic progress reports, dates for achieving activities, milestones, and an explanation of why any dates were missed and preventive or corrective measures. The compliance certification shall be submitted to the administrator, director, and the appropriate DNR Field office. 567 IAC 22.108 (15)"e"

G5. Semi-Annual Monitoring Report

By March 31 and September 30 of each year, the permittee shall submit a report of any monitoring required under this permit for the 6 month periods of July 1 to December 31 and January 1 to June 30, respectively. All instances of deviations from permit requirements must be clearly identified in these reports, and the report must be signed by a responsible official, consistent with 567 IAC 22.107(4). The semi-annual monitoring report shall be submitted to the director and the appropriate DNR Field office. 567 IAC 22.108 (5)

G6. Annual Fee

1. The permittee is required under subrule 567 IAC 22.106 to pay an annual fee based on the total tons of actual emissions of each regulated air pollutant. Beginning July 1, 1996, Title V operating permit fees will be paid on July 1 of each year. The fee shall be based on emissions for the previous calendar year.
2. The fee amount shall be calculated based on the first 4,000 tons of each regulated air pollutant emitted each year. The fee to be charged per ton of pollutant will be available from the department by June 1 of each year. The Responsible Official will be advised of any change in the annual fee per ton of pollutant.
3. The emissions inventory shall be submitted annually by March 31 with forms specified by the department documenting actual emissions for the previous calendar year.
4. The fee shall be submitted annually by July 1 with forms specified by the department.
5. If there are any changes to the emission calculation form, the department shall make revised forms available to the public by January 1. If revised forms are not available by January 1, forms from the previous year may be used and the year of emissions documented changed. The department shall calculate the total statewide Title V emissions for the prior calendar year and make this information available to the public no later than April 30 of each year.
6. Phase I acid rain affected units under section 404 of the Act shall not be required to pay a fee for emissions which occur during the years 1993 through 1999 inclusive.
7. The fee for a portable emissions unit or stationary source which operates both in Iowa and out of state shall be calculated only for emissions from the source while operating in Iowa.
8. Failure to pay the appropriate Title V fee represents cause for revocation of the Title V permit as indicated in 567 IAC 22.115(1)"d".

G7. Inspection of Premises, Records, Equipment, Methods and Discharges

Upon presentation of proper credentials and any other documents as may be required by law, the permittee shall allow the director or the director's authorized representative to:

1. Enter upon the permittee's premises where a Title V source is located or emissions-related activity is conducted, or where records must be kept under the conditions of the permit;
2. Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
3. Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
4. Sample or monitor, at reasonable times, substances or parameters for the purpose of ensuring compliance with the permit or other applicable requirements. *567 IAC 22.108 (15)"b"*

G8. Duty to Provide Information

The permittee shall furnish to the director, within a reasonable time, any information that the director may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee also shall furnish to the director copies of records required to be kept by the permit, or for information claimed to be confidential, the permittee shall furnish such records directly to the administrator of EPA along with a claim of confidentiality. *567 IAC 22.108 (9)"e"*

G9. General Maintenance and Repair Duties

The owner or operator of any air emission source or control equipment shall:

1. Maintain and operate the equipment or control equipment at all times in a manner consistent with good practice for minimizing emissions.
2. Remedy any cause of excess emissions in an expeditious manner.
3. Minimize the amount and duration of any excess emission to the maximum extent possible during periods of such emissions. These measures may include but not be limited to the use of clean fuels, production cutbacks, or the use of alternate process units or, in the case of utilities, purchase of electrical power until repairs are completed.
4. Schedule, at a minimum, routine maintenance of equipment or control equipment during periods of process shutdowns to the maximum extent possible. *567 IAC 24.2(1)*

G10. Recordkeeping Requirements for Compliance Monitoring

1. In addition to any source specific recordkeeping requirements contained in this permit, the permittee shall maintain the following compliance monitoring records, where applicable:

- a. The date, place and time of sampling or measurements
- b. The date the analyses were performed.
- c. The company or entity that performed the analyses.
- d. The analytical techniques or methods used.
- e. The results of such analyses; and
- f. The operating conditions as existing at the time of sampling or measurement.
- g. The records of quality assurance for continuous compliance monitoring systems (including but not limited to quality control activities, audits and calibration drifts.)

2. The permittee shall retain records of all required compliance monitoring data and support information for a period of at least 5 years from the date of compliance monitoring sample, measurement report or application. Support information includes all calibration and maintenance records and all original strip chart recordings for continuous compliance monitoring, and copies of all reports required by the permit.

3. For any source which in its application identified reasonably anticipated alternative operating scenarios, the permittee shall:
 - a. Comply with all terms and conditions of this permit specific to each alternative scenario.
 - b. Maintain a log at the permitted facility of the scenario under which it is operating.
 - c. Consider the permit shield, if provided in this permit, to extend to all terms and conditions under each operating scenario. *567 IAC 22.108(4), 567 IAC 22.108(12)*

G11. Evidence used in establishing that a violation has or is occurring.

Notwithstanding any other provisions of these rules, any credible evidence may be used for the purpose of establishing whether a person has violated or is in violation of any provisions herein.

1. Information from the use of the following methods is presumptively credible evidence of whether a violation has occurred at a source:
 - a. A monitoring method approved for the source and incorporated in an operating permit pursuant to 567 Chapter 22;
 - b. Compliance test methods specified in 567 Chapter 25; or
 - c. Testing or monitoring methods approved for the source in a construction permit issued pursuant to 567 Chapter 22.
2. The following testing, monitoring or information gathering methods are presumptively credible testing, monitoring, or information gathering methods:
 - a. Any monitoring or testing methods provided in these rules; or
 - b. Other testing, monitoring, or information gathering methods that produce information comparable to that produced by any method in subrule 21.5(1) or this subrule. *567 IAC 21.5(1)-567 IAC 21.5(2)*

G12. Prevention of Accidental Release: Risk Management Plan Notification and Compliance Certification

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Act, the permittee shall notify the department of this requirement. The plan shall be filed with all appropriate authorities by the deadline specified by EPA. A certification that this risk management plan is being properly implemented shall be included in the annual compliance certification of this permit. *567 IAC 22.108(6)*

G13. Hazardous Release

The permittee must report any situation involving the actual, imminent, or probable release of a hazardous substance into the atmosphere which, because of the quantity, strength and toxicity of the substance, creates an immediate or potential danger to the public health, safety or to the environment. A verbal report shall be made to the department at (515) 725-8694 and to the local police department or the office of the sheriff of the affected county as soon as possible but not later than six hours after the discovery or onset of the condition. This verbal report must be followed up with a written report as indicated in 567 IAC 131.2(2). *567 IAC Chapter 131-State Only*

G14. Excess Emissions and Excess Emissions Reporting Requirements

1. Excess Emissions. Excess emission during a period of startup, shutdown, or cleaning of control equipment is not a violation of the emission standard if the startup, shutdown or cleaning is accomplished expeditiously and in a manner consistent with good practice for minimizing emissions. Cleaning of control equipment which does not require the shutdown of the process equipment shall be limited to one six-minute period per one-hour period. An incident of excess emission (other than an incident during startup, shutdown or cleaning of control equipment) is a

violation. If the owner or operator of a source maintains that the incident of excess emission was due to a malfunction, the owner or operator must show that the conditions which caused the incident of excess emission were not preventable by reasonable maintenance and control measures. Determination of any subsequent enforcement action will be made following review of this report. If excess emissions are occurring, either the control equipment causing the excess emission shall be repaired in an expeditious manner or the process generating the emissions shall be shutdown within a reasonable period of time. An expeditious manner is the time necessary to determine the cause of the excess emissions and to correct it within a reasonable period of time. A reasonable period of time is eight hours plus the period of time required to shut down the process without damaging the process equipment or control equipment. A variance from this subrule may be available as provided for in Iowa Code section 455B.143. In the case of an electric utility, a reasonable period of time is eight hours plus the period of time until comparable generating capacity is available to meet consumer demand with the affected unit out of service, unless, the director shall, upon investigation, reasonably determine that continued operation constitutes an unjustifiable environmental hazard and issue an order that such operation is not in the public interest and require a process shutdown to commence immediately.

2. Excess Emissions Reporting

a. Initial Reporting of Excess Emissions. An incident of excess emission (other than an incident of excess emission during a period of startup, shutdown, or cleaning) shall be reported to the appropriate field office of the department within eight hours of, or at the start of the first working day following the onset of the incident. The reporting exemption for an incident of excess emission during startup, shutdown or cleaning does not relieve the owner or operator of a source with continuous monitoring equipment of the obligation of submitting reports required in 567-subrule 25.1(6). An initial report of excess emission is not required for a source with operational continuous monitoring equipment (as specified in 567-subrule 25.1(1)) if the incident of excess emission continues for less than 30 minutes and does not exceed the applicable emission standard by more than 10 percent or the applicable visible emission standard by more than 10 percent opacity. The initial report may be made by electronic mail (E-mail), in person, or by telephone and shall include as a minimum the following:

- i. The identity of the equipment or source operation from which the excess emission originated and the associated stack or emission point.
- ii. The estimated quantity of the excess emission.
- iii. The time and expected duration of the excess emission.
- iv. The cause of the excess emission.
- v. The steps being taken to remedy the excess emission.
- vi. The steps being taken to limit the excess emission in the interim period.

b. Written Reporting of Excess Emissions. A written report of an incident of excess emission shall be submitted as a follow-up to all required initial reports to the department within seven days of the onset of the upset condition, and shall include as a minimum the following:

- i. The identity of the equipment or source operation point from which the excess emission originated and the associated stack or emission point.
- ii. The estimated quantity of the excess emission.
- iii. The time and duration of the excess emission.
- iv. The cause of the excess emission.

v. The steps that were taken to remedy and to prevent the recurrence of the incident of excess emission.

vi. The steps that were taken to limit the excess emission.

vii. If the owner claims that the excess emission was due to malfunction, documentation to support this claim. *567 IAC 24.1(1)-567 IAC 24.1(4)*

3. Emergency Defense for Excess Emissions. For the purposes of this permit, an "emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the source, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the source to exceed a technology-based emission limitation under the permit due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include non-compliance, to the extent caused by improperly designed equipment, lack of preventive maintenance, careless or improper operation or operator error. An emergency constitutes an affirmative defense to an action brought for non-compliance with technology based limitations if it can be demonstrated through properly signed contemporaneous operating logs or other relevant evidence that:

- a. An emergency occurred and that the permittee can identify the cause(s) of the emergency;
- b. The facility at the time was being properly operated;
- c. During the period of the emergency, the permittee took all reasonable steps to minimize levels of emissions that exceeded the emissions standards or other requirements of the permit; and
- d. The permittee submitted notice of the emergency to the director by certified mail within two working days of the time when the emissions limitations were exceeded due to the emergency. This notice fulfills the requirement of paragraph 22.108(5)"b." – See G15. This notice must contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken.

In any enforcement proceeding, the permittee seeking to establish the occurrence of an emergency has the burden of proof. This provision is in addition to any emergency or upset provision contained in any applicable requirement. *567 IAC 22.108(16)*

G15. Permit Deviation Reporting Requirements

A deviation is any failure to meet a term, condition or applicable requirement in the permit. Reporting requirements for deviations that result in a hazardous release or excess emissions have been indicated above (see G13 and G14). Unless more frequent deviation reporting is specified in the permit, any other deviation shall be documented in the semi-annual monitoring report and the annual compliance certification (see G4 and G5). *567 IAC 22.108(5)"b"*

G16. Notification Requirements for Sources That Become Subject to NSPS and NESHAP Regulations

During the term of this permit, the permittee must notify the department of any source that becomes subject to a standard or other requirement under 567-subrule 23.1(2) (standards of performance of new stationary sources) or section 111 of the Act; or 567-subrule 23.1(3) (emissions standards for hazardous air pollutants), 567-subrule 23.1(4) (emission standards for hazardous air pollutants for source categories) or section 112 of the Act. This notification shall be submitted in writing to the department pursuant to the notification requirements in 40 CFR Section 60.7, 40 CFR Section 61.07, and/or 40 CFR Section 63.9. *567 IAC 23.1(2), 567 IAC 23.1(3), 567 IAC 23.1(4)*

G17. Requirements for Making Changes to Emission Sources That Do Not Require Title V Permit Modification

1. Off Permit Changes to a Source. Pursuant to section 502(b)(10) of the CAAA, the permittee may make changes to this installation/facility without revising this permit if:
 - a. The changes are not major modifications under any provision of any program required by section 110 of the Act, modifications under section 111 of the act, modifications under section 112 of the act, or major modifications as defined in 567 IAC Chapter 22.
 - b. The changes do not exceed the emissions allowable under the permit (whether expressed therein as a rate of emissions or in terms of total emissions);
 - c. The changes are not modifications under any provisions of Title I of the Act and the changes do not exceed the emissions allowable under the permit (whether expressed therein as a rate of emissions or as total emissions);
 - d. The changes are not subject to any requirement under Title IV of the Act (revisions affecting Title IV permitting are addressed in rules 567—22.140(455B) through 567 - 22.144(455B));.
 - e. The changes comply with all applicable requirements.
 - f. For each such change, the permitted source provides to the department and the administrator by certified mail, at least 30 days in advance of the proposed change, a written notification, including the following, which must be attached to the permit by the source, the department and the administrator:
 - i. A brief description of the change within the permitted facility,
 - ii. The date on which the change will occur,
 - iii. Any change in emission as a result of that change,
 - iv. The pollutants emitted subject to the emissions trade
 - v. If the emissions trading provisions of the state implementation plan are invoked, then Title V permit requirements with which the source shall comply; a description of how the emissions increases and decreases will comply with the terms and conditions of the Title V permit.
 - vi. A description of the trading of emissions increases and decreases for the purpose of complying with a federally enforceable emissions cap as specified in and in compliance with the Title V permit; and
 - vii. Any permit term or condition no longer applicable as a result of the change.
2. Such changes do not include changes that would violate applicable requirements or contravene federally enforceable permit terms and conditions that are monitoring (including test methods), record keeping, reporting, or compliance certification requirements. *567 IAC 22.110(2)*
3. Notwithstanding any other part of this rule, the director may, upon review of a notice, require a stationary source to apply for a Title V permit if the change does not meet the requirements of subrule 22.110(1). *567 IAC 22.110(3)*
4. The permit shield provided in subrule 22.108(18) shall not apply to any change made pursuant to this rule. Compliance with the permit requirements that the source will meet using the emissions trade shall be determined according to requirements of the state implementation plan authorizing the emissions trade. *567 IAC 22.110(4)*

5. No permit revision shall be required, under any approved economic incentives, marketable permits, emissions trading and other similar programs or processes, for changes that are provided for in this permit. *567 IAC 22.108(11)*

G18. Duty to Modify a Title V Permit

1. Administrative Amendment.

- a. An administrative permit amendment is a permit revision that does any of the following:
 - i. Correct typographical errors
 - ii. Identify a change in the name, address, or telephone number of any person identified in the permit, or provides a similar minor administrative change at the source;
 - iii. Require more frequent monitoring or reporting by the permittee; or
 - iv. Allow for a change in ownership or operational control of a source where the director determines that no other change in the permit is necessary, provided that a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new permittee has been submitted to the director.
- b. The permittee may implement the changes addressed in the request for an administrative amendment immediately upon submittal of the request. The request shall be submitted to the director.
- c. Administrative amendments to portions of permits containing provisions pursuant to Title IV of the Act shall be governed by regulations promulgated by the administrator under Title IV of the Act.

2. Minor Title V Permit Modification.

- a. Minor Title V permit modification procedures may be used only for those permit modifications that satisfy all of the following:
 - i. Do not violate any applicable requirement;
 - ii. Do not involve significant changes to existing monitoring, reporting or recordkeeping requirements in the Title V permit;
 - iii. Do not require or change a case by case determination of an emission limitation or other standard, or an increment analysis;
 - iv. Do not seek to establish or change a permit term or condition for which there is no corresponding underlying applicable requirement and that the source has assumed in order to avoid an applicable requirement to which the source would otherwise be subject. Such terms and conditions include any federally enforceable emissions caps which the source would assume to avoid classification as a modification under any provision under Title I of the Act; and an alternative emissions limit approved pursuant to regulations promulgated under section 112(i)(5) of the Act;
 - v. Are not modifications under any provision of Title I of the Act; and
 - vi. Are not required to be processed as significant modification under rule 567 - 22.113(455B).
- b. An application for minor permit revision shall be on the minor Title V modification application form and shall include at least the following:
 - i. A description of the change, the emissions resulting from the change, and any new applicable requirements that will apply if the change occurs;

- ii. The permittee's suggested draft permit;
 - iii. Certification by a responsible official, pursuant to 567 IAC 22.107(4), that the proposed modification meets the criteria for use of minor permit modification procedures and a request that such procedures be used; and
 - iv. Completed forms to enable the department to notify the administrator and the affected states as required by 567 IAC 22.107(7).
- c. The permittee may make the change proposed in its minor permit modification application immediately after it files the application. After the permittee makes this change and until the director takes any of the actions specified in 567 IAC 22.112(4) "a" to "c", the permittee must comply with both the applicable requirements governing the change and the proposed permit terms and conditions. During this time, the permittee need not comply with the existing permit terms and conditions it seeks to modify. However, if the permittee fails to comply with its proposed permit terms and conditions during this time period, the existing permit terms and conditions it seeks to modify may be enforced against the facility.

3. Significant Title V Permit Modification.

Significant Title V modification procedures shall be used for applications requesting Title V permit modifications that do not qualify as minor Title V modifications or as administrative amendments. These include but are not limited to all significant changes in monitoring permit terms, every relaxation of reporting or recordkeeping permit terms, and any change in the method of measuring compliance with existing requirements. Significant Title V modifications shall meet all requirements of 567 IAC Chapter 22, including those for applications, public participation, review by affected states, and review by the administrator, as those requirements that apply to Title V issuance and renewal.

The permittee shall submit an application for a significant permit modification not later than three months after commencing operation of the changed source unless the existing Title V permit would prohibit such construction or change in operation, in which event the operation of the changed source may not commence until the department revises the permit. *567 IAC 22.111-567 IAC 22.113*

G19. Duty to Obtain Construction Permits

Unless exempted in 567 IAC 22.1(2) or to meet the parameters established in 567 IAC 22.1(1)"c", the permittee shall not construct, install, reconstruct or alter any equipment, control equipment or anaerobic lagoon without first obtaining a construction permit, or conditional permit, or permit pursuant to rule 567 IAC 22.8, or permits required pursuant to rules 567 IAC 22.4, 567 IAC 22.5, 567 IAC 31.3, and 567 IAC 33.3 as required in 567 IAC 22.1(1). A permit shall be obtained prior to the initiation of construction, installation or alteration of any portion of the stationary source or anaerobic lagoon. *567 IAC 22.1(1)*

G20. Asbestos

The permittee shall comply with 567 IAC 23.1(3)"a", and 567 IAC 23.2(3)"g" when activities involve asbestos mills, surfacing of roadways, manufacturing operations, fabricating, insulating, waste disposal, spraying applications, demolition and renovation operations (*567 IAC 23.1(3)"a"*); training fires and controlled burning of a demolished building (*567 IAC 23.2*).

G21. Open Burning

The permittee is prohibited from conducting open burning, except as provided in 567 IAC 23.2. *567 IAC 23.2 except 23.2(3)"j"; 567 IAC 23.2(3)"j" - State Only*

G22. Acid Rain (Title IV) Emissions Allowances

The permittee shall not exceed any allowances that it holds under Title IV of the Act or the regulations promulgated there under. Annual emissions of sulfur dioxide in excess of the number of allowances to emit sulfur dioxide held by the owners and operators of the unit or the designated representative of the owners and operators is prohibited. Exceedences of applicable emission rates are prohibited. "Held" in this context refers to both those allowances assigned to the owners and operators by USEPA, and those allowances supplementally acquired by the owners and operators. The use of any allowance prior to the year for which it was allocated is prohibited. Contravention of any other provision of the permit is prohibited. 567 IAC 22.108(7)

G23. Stratospheric Ozone and Climate Protection (Title VI) Requirements

1. The permittee shall comply with the standards for labeling of products using ozone-depleting substances pursuant to 40 CFR Part 82, Subpart E:
 - a. All containers in which a class I or class II substance is stored or transported, all products containing a class I substance, and all products directly manufactured with a class I substance must bear the required warning statement if it is being introduced into interstate commerce pursuant to § 82.106.
 - b. The placement of the required warning statement must comply with the requirements pursuant to § 82.108.
 - c. The form of the label bearing the required warning statement must comply with the requirements pursuant to § 82.110.
 - d. No person may modify, remove, or interfere with the required warning statement except as described in § 82.112.
2. The permittee shall comply with the standards for recycling and emissions reduction pursuant to 40 CFR Part 82, Subpart F, except as provided for MVACs in Subpart B:
 - a. Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to § 82.156.
 - b. Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to § 82.158.
 - c. Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to § 82.161.
 - d. Persons disposing of small appliances, MVACs, and MVAC-like appliances must comply with reporting and recordkeeping requirements pursuant to § 82.166. ("MVAC-like appliance" as defined at § 82.152)
 - e. Persons owning commercial or industrial process refrigeration equipment must comply with the leak repair requirements pursuant to § 82.156.
 - f. Owners/operators of appliances normally containing 50 or more pounds of refrigerant must keep records of refrigerant purchased and added to such appliances pursuant to § 82.166.
3. If the permittee manufactures, transforms, imports, or exports a class I or class II substance, the permittee is subject to all the requirements as specified in 40 CFR part 82, Subpart A, Production and Consumption Controls.
4. If the permittee performs a service on motor (fleet) vehicles when this service involves ozone-depleting substance refrigerant (or regulated substitute substance) in the motor vehicle air conditioner (MVAC), the permittee is subject to all the applicable requirements as specified in 40 CFR part 82, Subpart B, Servicing of Motor Vehicle Air Conditioners. The term "motor vehicle" as used in Subpart B does not include a vehicle in which final assembly of the vehicle

has not been completed. The term "MVAC" as used in Subpart B does not include the air-tight sealed refrigeration system used as refrigerated cargo, or system used on passenger buses using HCFC-22 refrigerant,

5. The permittee shall be allowed to switch from any ozone-depleting or greenhouse gas generating substances to any alternative that is listed in the Significant New Alternatives Program (SNAP) promulgated pursuant to 40 CFR part 82, Subpart G, Significant New Alternatives Policy Program. *40 CFR part 82*

G24. Permit Reopenings

1. This permit may be modified, revoked, reopened, and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition. *567 IAC 22.108(9)"c"*

2. Additional applicable requirements under the Act become applicable to a major part 70 source with a remaining permit term of 3 or more years. Revisions shall be made as expeditiously as practicable, but not later than 18 months after the promulgation of such standards and regulations.

a. Reopening and revision on this ground is not required if the permit has a remaining term of less than three years;

b. Reopening and revision on this ground is not required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions have been extended pursuant to 40 CFR 70.4(b)(10)(i) or (ii) as amended to May 15, 2001.

c. Reopening and revision on this ground is not required if the additional applicable requirements are implemented in a general permit that is applicable to the source and the source receives approval for coverage under that general permit. *567 IAC 22.108(17)"a"*, *567 IAC 22.108(17)"b"*

3. A permit shall be reopened and revised under any of the following circumstances:

a. The department receives notice that the administrator has granted a petition for disapproval of a permit pursuant to 40 CFR 70.8(d) as amended to July 21, 1992, provided that the reopening may be stayed pending judicial review of that determination;

b. The department or the administrator determines that the Title V permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of the Title V permit;

c. Additional applicable requirements under the Act become applicable to a Title V source, provided that the reopening on this ground is not required if the permit has a remaining term of less than three years, the effective date of the requirement is later than the date on which the permit is due to expire, or the additional applicable requirements are implemented in a general permit that is applicable to the source and the source receives approval for coverage under that general permit. Such a reopening shall be complete not later than 18 months after promulgation of the applicable requirement.

d. Additional requirements, including excess emissions requirements, become applicable to a Title IV affected source under the acid rain program. Upon approval by the administrator, excess emissions offset plans shall be deemed to be incorporated into the permit.

e. The department or the administrator determines that the permit must be revised or

revoked to ensure compliance by the source with the applicable requirements. *567 IAC 22.114(1)*

4. Proceedings to reopen and reissue a Title V permit shall follow the procedures applicable to initial permit issuance and shall effect only those parts of the permit for which cause to reopen exists. *567 IAC 22.114(2)*

5. A notice of intent shall be provided to the Title V source at least 30 days in advance of the date the permit is to be reopened, except that the director may provide a shorter time period in the case of an emergency. *567 IAC 22.114(3)*

G25. Permit Shield

1. The director may expressly include in a Title V permit a provision stating that compliance with the conditions of the permit shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that:

a. Such applicable requirements are included and are specifically identified in the permit;
or

b. The director, in acting on the permit application or revision, determines in writing that other requirements specifically identified are not applicable to the source, and the permit includes the determination or a concise summary thereof.

2. A Title V permit that does not expressly state that a permit shield exists shall be presumed not to provide such a shield.

3. A permit shield shall not alter or affect the following:

a. The provisions of Section 303 of the Act (emergency orders), including the authority of the administrator under that section;

b. The liability of an owner or operator of a source for any violation of applicable requirements prior to or at the time of permit issuance;

c. The applicable requirements of the acid rain program, consistent with Section 408(a) of the Act;

d. The ability of the department or the administrator to obtain information from the facility pursuant to Section 114 of the Act. *567 IAC 22.108 (18)*

G26. Severability

The provisions of this permit are severable and if any provision or application of any provision is found to be invalid by this department or a court of law, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected by such finding. *567 IAC 22.108 (8)*

G27. Property Rights

The permit does not convey any property rights of any sort, or any exclusive privilege. *567 IAC 22.108 (9)"d"*

G28. Transferability

This permit is not transferable from one source to another. If title to the facility or any part of it is transferred, an administrative amendment to the permit must be sought consistent with the requirements of *567 IAC 22.111(1)*. *567 IAC 22.111 (1)"d"*

G29. Disclaimer

No review has been undertaken on the engineering aspects of the equipment or control equipment other than the potential of that equipment for reducing air contaminant emissions. *567 IAC 22.3(3)"c"*

G30. Notification and Reporting Requirements for Stack Tests or Monitor Certification

The permittee shall notify the department's stack test contact in writing not less than 30 days before a required test or performance evaluation of a continuous emission monitor is performed to determine compliance with applicable requirements of 567 – Chapter 23 or a permit condition. Such notice shall include the time, the place, the name of the person who will conduct the test and other information as required by the department. If the owner or operator does not provide timely notice to the department, the department shall not consider the test results or performance evaluation results to be a valid demonstration of compliance with applicable rules or permit conditions. Upon written request, the department may allow a notification period of less than 30 days. At the department's request, a pretest meeting shall be held not later than 15 days prior to conducting the compliance demonstration. A testing protocol shall be submitted to the department no later than 15 days before the owner or operator conducts the compliance demonstration. A representative of the department shall be permitted to witness the tests. Results of the tests shall be submitted in writing to the department's stack test contact in the form of a comprehensive report within six weeks of the completion of the testing. Compliance tests conducted pursuant to this permit shall be conducted with the source operating in a normal manner at its maximum continuous output as rated by the equipment manufacturer, or the rate specified by the owner as the maximum production rate at which the source shall be operated. In cases where compliance is to be demonstrated at less than the maximum continuous output as rated by the equipment manufacturer, and it is the owner's intent to limit the capacity to that rating, the owner may submit evidence to the department that the source has been physically altered so that capacity cannot be exceeded, or the department may require additional testing, continuous monitoring, reports of operating levels, or any other information deemed necessary by the department to determine whether such source is in compliance.

Stack test notifications, reports and correspondence shall be sent to:

Stack Test Review Coordinator
Iowa DNR, Air Quality Bureau
Wallace State Office Building
502 E 9th St.
Des Moines, IA 50319-0034
(515) 725-9545

Within Polk and Linn Counties, stack test notifications, reports and correspondence shall also be directed to the supervisor of the respective county air pollution program.

567 IAC 25.1(7)"a", 567 IAC 25.1(9)

G31. Prevention of Air Pollution Emergency Episodes

The permittee shall comply with the provisions of 567 IAC Chapter 26 in the prevention of excessive build-up of air contaminants during air pollution episodes, thereby preventing the occurrence of an emergency due to the effects of these contaminants on the health of persons.

567 IAC 26.1(1)

G32. Contacts List

The current address and phone number for reports and notifications to the EPA administrator is:

Iowa Compliance Officer
Air Branch
Enforcement and Compliance Assurance Division
U.S. EPA Region 7
11201 Renner Blvd.
Lenexa, KS 66219
(913) 551-7020

The current address and phone number for reports and notifications to the department or the Director is:

Chief, Air Quality Bureau
Iowa Department of Natural Resources
Wallace State Office Building
502 E 9th St.
Des Moines, IA 50319-0034
(515) 725-8200

Reports or notifications to the DNR Field Offices or local programs shall be directed to the supervisor at the appropriate field office or local program. Current addresses and phone numbers are:

Field Office 1

909 West Main – Suite 4
Manchester, IA 52057
(563) 927-2640

Field Office 2

2300-15th St., SW
Mason City, IA 50401
(641) 424-4073

Field Office 3

1900 N. Grand Ave.
Spencer, IA 51301
(712) 262-4177

Field Office 4

1401 Sunnyside Lane
Atlantic, IA 50022
(712) 243-1934

Field Office 5

502 E 9th St.
Des Moines, IA 50319
(515) 725-0268

Field Office 6

1023 West Madison Street
Washington, IA 52353-1623
(319) 653-2135

Polk County Public Works Dept.

Air Quality Division
5885 NE 14th St.
Des Moines, IA 50313
(515) 286-3351

Linn County Public Health

Air Quality Branch
501 13th St., NW
Cedar Rapids, IA 52405
(319) 892-6000

V. Appendix A – Links to NSPS/NESHAP Regulations

- A. 40 CFR 60 Subpart A – *General Provisions*
<https://www.ecfr.gov/cgi-bin/text-idx?node=sp40.7.60.a>
- B. 40 CFR 60 Subpart XX - Standards of Performance for *Bulk Gasoline Terminals*
<https://www.ecfr.gov/cgi-bin/text-idx?node=sp40.7.60.xx>
- C. 40 CFR 63 Subpart A – *General Provisions*
<https://www.ecfr.gov/cgi-bin/text-idx?node=sp40.7.63.a>
- D. 40 CFR 63 Subpart BBBBBB - National Emission Standards for Hazardous Air Pollutants for *Source Category: Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities*
<https://www.ecfr.gov/cgi-bin/text-idx?node=sp40.7.63.bbbbb>