

**Iowa Department of Natural Resources
Title V Operating Permit**

**Name of Permitted Facility: Georgia-Pacific Gypsum LLC,
Fort Dodge, IA**

Facility Location: 2374 Mill Road, Fort Dodge, IA 50501

Air Quality Operating Permit Number: 99-TV-035R2

Expiration Date: July 5, 2017

Permit Renewal Application Deadline: January 5, 2017

EIQ Number: 92-2162

Facility File Number: 94-01-010

Responsible Official

Name: Jerry Lunn

Title: Plant Manager

Mailing Address: 2374 Mill Road, Fort Dodge, IA 50501

Phone #: (515) 573-2176

Permit Contact Person for the Facility

Name: Doug Bahr

Title: Environmental Coordinator

Mailing Address: 2374 Mill Road, Fort Dodge, IA 50501

Phone #: (515) 573-2176

This permit is issued in accordance with 567 Iowa Administrative Code Chapter 22, and is issued subject to the terms and conditions contained in this permit.

For the Director of the Department of Natural Resources

Douglas A. Campbell, Supervisor of Air Operating Permits Section

Date

Table of Contents

I. Facility Description and Equipment List	4
II. Plant - Wide Conditions.....	7
III. Emission Point Specific Conditions	9
IV. General Conditions.....	64
G1. Duty to Comply	
G2. Permit Expiration	
G3. Certification Requirement for Title V Related Documents	
G4. Annual Compliance Certification	
G5. Semi-Annual Monitoring Report	
G6. Annual Fee	
G7. Inspection of Premises, Records, Equipment, Methods and Discharges	
G8. Duty to Provide Information	
G9. General Maintenance and Repair Duties	
G10. Recordkeeping Requirements for Compliance Monitoring	
G11. Evidence used in establishing that a violation has or is occurring.	
G12. Prevention of Accidental Release: Risk Management Plan Notification and Compliance Certification	
G13. Hazardous Release	
G14. Excess Emissions and Excess Emissions Reporting Requirements	
G15. Permit Deviation Reporting Requirements	
G16. Notification Requirements for Sources That Become Subject to NSPS and NESHAP Regulations	
G17. Requirements for Making Changes to Emission Sources That Do Not Require Title V Permit Modification	
G18. Duty to Modify a Title V Permit	
G19. Duty to Obtain Construction Permits	
G20. Asbestos	
G21. Open Burning	
G22. Acid Rain (Title IV) Emissions Allowances	
G23. Stratospheric Ozone and Climate Protection (Title VI) Requirements	
G24. Permit Reopenings	
G25. Permit Shield	
G26. Severability	
G27. Property Rights	
G28. Transferability	
G29. Disclaimer	
G30. Notification and Reporting Requirements for Stack Tests or Monitor Certification	
G31. Prevention of Air Pollution Emergency Episodes	
G32. Contacts List	
V. Appendix A: Compliance Assurance Monitoring Plan	77

Abbreviations

acfm.....	actual cubic feet per minute
CFR.....	Code of Federal Regulation
CE.....	control equipment
CEM.....	continuous emission monitor
°F.....	degrees Fahrenheit
EIQ.....	emissions inventory questionnaire
EP.....	emission point
EU.....	emission unit
gr./dscf.....	grains per dry standard cubic foot
gr./100 cf.....	grains per one hundred cubic feet
IAC.....	Iowa Administrative Code
IDNR.....	Iowa Department of Natural Resources
Msf.....	1,000 square feet
MVAC.....	motor vehicle air conditioner
NAICS.....	North American Industry Classification System
NSPS.....	new source performance standard
ppmv.....	parts per million by volume
lb./hr.....	pounds per hour
lb./MMBtu.....	pounds per million British thermal units
SCC.....	Source Classification Codes
scfm.....	standard cubic feet per minute
SIC.....	Standard Industrial Classification
TPY.....	tons per year
USEPA.....	United States Environmental Protection Agency

Pollutants

PM.....	particulate matter
PM ₁₀	particulate matter ten microns or less in diameter
SO ₂	sulfur dioxide
NO _x	nitrogen oxides
VOC.....	volatile organic compound
CO.....	carbon monoxide
HAP.....	hazardous air pollutant

I. Facility Description and Equipment List

Facility Name: Georgia-Pacific Gypsum LLC, Fort Dodge, IA
 Permit Number: 99-TV-035R2

Facility Description: Gypsum Wallboard Manufacturing (SIC 3275)

Equipment List

Emission Point Number	Emission Unit Number	Emission Unit Description	IDNR Construction Permit Number
1	1	Unpaved Road Traffic	NA
2	2	Uncrushed Gypsum Ore Outdoor Stockpile	NA
3	3	Reclaim Gypsum Outdoor Stockpile	NA
4	4	Uncrushed Ore Transfer to Primary Crusher Hopper	NA
	5	Vibratory Pan Feeder Transfer to Primary Crusher	NA
9	6	Primary Crushing	98-A-811-S1
	8	Screening	
	9	Secondary Crushing	
	7	Bulk Material Conveying	
	10	Bulk Material Conveying	
	11	Bulk Material Conveying	
9A	6	Primary Crushing (Uncaptured)	NA
9B	8	Screening (Uncaptured)	NA
	9	Secondary Crushing (Uncaptured)	NA
9C	7	Bulk Material Conveying (Uncaptured) Two material transfers onto belt from crusher	NA
9D	10	Bulk Material Conveying (Uncaptured) Three material transfers post secondary crusher	NA
9E	11	Bulk Material Conveying (Uncaptured) Baghouse fines – Screw to Conveyor Belt	NA
9F	12	Bulk Material Conveying (Uncaptured) Transfer of Screened Gypsum to Belt	NA
53	12RU	Radial Stacker Conveyor	99-A-401
	102	Belt Conveyor from Blend Building	
12RU	12RU	Radial Stacker Conveyor (Uncaptured)	NA
12	13	Crushed Gypsum Ore Pile Outdoor	NA
13	14	Gypsum Ore Pile Indoor	NA
28D	61	Accelerator Bin & Feed System	99-A-140
28J	46A	Stucco Storage Bin Northwest	78-A-185
28K	46B	Stucco Storage Bin Southwest	NA
28L	48A	Stucco Storage Bin Northeast	NA
28M	48B	Stucco Storage Bin Southeast	NA

Equipment List (Cont.)

Emission Point Number	Emission Unit Number	Emission Unit Description	IDNR Construction Permit Number
29	50	Baghouse Heater	89-A-131
	52	Gypsum Conveyor	
	74	Gypsum Blender	
	75	Gypsum Pin Mixer	
32 33 34 35 36 37	82	Board Drying Kiln	02-A-889-S1 02-A-890-S1 02-A-891-S1 99-A-298-S2 02-A-892-S1 02-A-893-S1
	83		
	84		
	85		
	86		
	87		
	117	DENS In-Line Coating	
	I100	Edge/Code Printer	
40	88A	End Trimmer	76-A-250-S1 00-A-677-S2
41	88B	End Trimmer	
50	89	Riser Cutter	
43	91	Bulk Unloading of Gypsum Dust (Wheelabrator Alley)	NA
49	67	Starch Bin	89-A-197
	68	Starch Bin	
50A	19	Reclaim/Recycle Conveyor	00-A-206-S1
	110	Reclaim Storage Area	
	111	Steele Feeder	
51C	58	Ball Mill	98-A-600
	59	Ball Mill	
	60	Ball Mill	
52	31	Landplaster Storage Bin & Feed	98-A-601
55	101	High Angle Conveyor	99-A-402
	103	Raw Gypsum Bin	
56	104	Chain Feeder	99-A-403
	105	Ball Race Mill	
	106	Hot Gas Generator	
57	107	Closed Aeroslide	99-A-404-S1
	108	Stucco Cooler	
	109	Bulk Stucco Loadout	
59A	112	Portable Trommel Screen	01-A-1113-S1
	114	Portable Reclaim Conveyor	
60A	115A	Maxi-Grinder	02-A-360
60	115B	Diesel Engine	02-A-361
61	118	DENS Off-line Coating	02-A-894-S1
61A	I101	Edge Printer	04-A-061
62	119	Holtec Saw	02-A-895-S1

Insignificant Activities Equipment List

Insignificant Emission Unit Number	Insignificant Emission Unit Description
I51	Blender Baghouse Fines Transfer to Hopper
I53	Stucco Transfer to Bypass Bin
I54	Stucco Transfer to Bypass Bin
I57	Lignosite Transfer into Bin
I69	Transfer of Recycle Paper into Hydropulper
I76	Paper Unrolling and Feeding
I77	Gas Flame Heating of Paper
I99	Cold Cleaning of Maintenance Parts
I110	Natural Gas Space Heating (0.24 MMBtu/hr.)
I12	Trommel Screen Diesel Engine (48 hp)
I113	Diesel Storage Tank (500 gallons)
I114	Propane Storage Tank (1,000 gallons) & Filling Activities
I115	Gasoline Storage Tank (500 gallons)
I116	Reclaim Wastewater Holding Basin (3,000 gallons)
I117	Mobile Vacuum Truck
I200	Cold Cleaning of Maintenance Parts
I201	DENS Gold Edge Painting
I208	Bulk Truck Loadout of Wheelabrator Baghouse Fines
I209	Bulk Truck Loadout of Holtec Baghouse Fines
I210	Paper Screen Fines Transfer to Bin
I211	Riser Cyclone Fines Transfer to Bin
I212	Riser Machine Baghouse Fines Transfer to Bin
I213	End Trim/Riser Machine Cyclone Fines Transfer to Indoor Pile
I214	End Trim/Riser Machine Baghouse Fines Transfer to Indoor Pile
I216	Blend Building Fugitive Emissions
I217	Material Belt Transfers into Transfer Bin
I218	Transfer from HAC Belt to Rock Bin

Insignificant Activities Equipment List (Small Unit Exemption) ⁽¹⁾

Insignificant Emission Unit Number	Insignificant Emission Unit Description
I215	Riser Machine

⁽¹⁾ Emission Units qualify for Small Unit Exemption under 567 IAC 22.1(2)"w". Records shall be kept in accordance with 567 IAC 22.1(2)"w"(3).

II. Plant-Wide Conditions

Facility Name: Georgia-Pacific Gypsum LLC, Fort Dodge, IA
Permit Number: 99-TV-035R2

Permit conditions are established in accord with 567 Iowa Administrative Code rule 22.108

Permit Duration

The term of this permit is: Five (5) years from permit issuance
Commencing on: July 6, 2012
Ending on: July 5, 2017

Amendments, modifications and reopenings of the permit shall be obtained in accordance with 567 Iowa Administrative Code rules 22.110 - 22.114. Permits may be suspended, terminated, or revoked as specified in 567 Iowa Administrative Code Rules 22.115.

Emission Limits

Unless specified otherwise in the Source Specific Conditions, the following limitations and supporting regulations apply to all emission points at this plant:

Opacity (visible emissions): 40% opacity
Authority for Requirement: 567 IAC 23.3(2)"d"

Sulfur Dioxide (SO₂): 500 parts per million by volume
Authority for Requirement: 567 IAC 23.3(3)"e"

Particulate Matter:

No person shall cause or allow the emission of particulate matter from any source in excess of the emission standards specified in this chapter, except as provided in 567 – Chapter 24. For sources constructed, modified or reconstructed after July 21, 1999, the emission of particulate matter from any process shall not exceed an emission standard of 0.1 grain per dry standard cubic foot of exhaust gas, except as provided in 567 – 21.2(455B), 23.1(455B), 23.4(455B) and 567 – Chapter 24.

For sources constructed, modified or reconstructed prior to July 21, 1999, the emission of particulate matter from any process shall not exceed the amount determined from Table I, or amount specified in a permit if based on an emission standard of 0.1 grain per standard cubic foot of exhaust gas or established from standards provided in 23.1(455B) and 23.4(455B).
Authority for Requirement: 567 IAC 23.3(2)"a"

Fugitive Dust: Attainment and Unclassified Areas - No person shall allow, cause or permit any materials to be handled, transported or stored; or a building, its appurtenances or a construction haul road to be used, constructed, altered repaired or demolished, with the exception of farming operations or dust generated by ordinary travel on unpaved public roads, without taking reasonable precautions to prevent particulate matter in quantities sufficient to create a nuisance, as defined in Iowa Code section 657.1, from becoming airborne. All persons, with the above exceptions, shall take reasonable precautions to prevent the discharge of visible emissions of fugitive dusts beyond the lot line of the property on which the emissions originate. The highway authority shall be responsible for taking corrective action in those cases where said authority has received complaints of or has actual knowledge of dust conditions which require abatement pursuant to this subrule. Reasonable precautions may include, but not limited to, the following procedures.

1. Use, where practical, of water or chemicals for control of dusts in the demolition of existing buildings or structures, construction operations, the grading of roads or the clearing of land.
2. Application of suitable materials, such as but not limited to asphalt, oil, water or chemicals on unpaved roads, material stockpiles, race tracks and other surfaces which can give rise to airborne dusts.
3. Installation and use of containment or control equipment, to enclose or otherwise limit the emissions resulting from the handling and transfer of dusty materials, such as but not limited to grain, fertilizers or limestone.
4. Covering at all times when in motion, open-bodied vehicles transporting materials likely to give rise to airborne dusts.
5. Prompt removal of earth or other material from paved streets or to which earth or other material has been transported by trucking or earth-moving equipment, erosion by water or other means.

Authority for Requirement: 567 IAC 23.3(2)"c"

Compliance Plan

The owner/operator shall comply with the applicable requirements listed below. The compliance status is based on information provided by the applicant.

For those applicable requirements which become effective during the permit term, Georgia-Pacific Gypsum LLC, Fort Dodge, IA shall comply with such requirements in a timely manner.

Authority for Requirement: 567 IAC 22.108(15)

III. Emission Point-Specific Conditions

Facility Name: Georgia-Pacific Gypsum LLC, Fort Dodge, IA
Permit Number: **99-TV-035R2**

Emission Point ID Number: 1

Associated Equipment

Emission Unit	Emission Unit Description	Raw Material	Rated Capacity	Construction Permit
1	Unpaved Road Traffic	Vehicle Traffic	NA	NA

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Fugitive Dust

Emission Limit: No person shall allow, cause or permit any materials to be handled, transported or stored; or a building, its appurtenances or a construction haul road to be used, constructed, altered, repaired or demolished, without taking reasonable precautions to prevent a nuisance. All persons shall take reasonable precautions to prevent the discharge of visible emissions of fugitive dusts beyond the lot line of the property on which the emissions originate.

Authority for Requirement: 567 IAC 23.3(2)"c"

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Numbers: 2 & 3

Associated Equipment

Emission Point	Emission Unit	Emission Unit Description	Raw Material	Rated Capacity	Construction Permit
2	2	Uncrushed Gypsum Ore Outdoor Stockpile	Gypsum Ore	68.75 tons/hr.	NA
3	3	Reclaim Gypsum Outdoor Stockpile	Gypsum Ore	50 tons/hr.	NA

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Fugitive Dust

Emission Limit: No person shall allow, cause or permit any materials to be handled, transported or stored; or a building, its appurtenances or a construction haul road to be used, constructed, altered, repaired or demolished, without taking reasonable precautions to prevent a nuisance. All persons shall take reasonable precautions to prevent the discharge of visible emissions of fugitive dusts beyond the lot line of the property on which the emissions originate.

Authority for Requirement: 567 IAC 23.3(2)"c"

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 4

Associated Equipment

Emission Unit	Emission Unit Description	Raw Material	Rated Capacity	Construction Permit
4	Uncrushed Ore Transfer to Primary Crusher Hopper	Gypsum	125 tons/hr.	NA
5	Vibratory Pan Feeder Transfer to Primary Crusher	Gypsum	125 tons/hr.	NA

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Fugitive Dust

Emission Limit: No person shall allow, cause or permit any materials to be handled, transported or stored; or a building, its appurtenances or a construction haul road to be used, constructed, altered, repaired or demolished, without taking reasonable precautions to prevent a nuisance. All persons shall take reasonable precautions to prevent the discharge of visible emissions of fugitive dusts beyond the lot line of the property on which the emissions originate.

Authority for Requirement: 567 IAC 23.3(2)"c"

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 9**Associated Equipment**

Emission Unit	Emission Unit Description	Control Equipment	Raw Material	Rated Capacity	Construction Permit
6	Primary Crushing	CE1: Baghouse	Gypsum	125 tons/hr.	98-A-811-S1
8	Screening		Gypsum	125 ton/hr.	
9	Secondary Crushing		Gypsum	125 tons/hr.	
7	Bulk Material Conveying		Gypsum	175 tons/hr.	
10	Bulk Material Conveying		Gypsum	50 tons/hr.	
11	Bulk Material Conveying		Gypsum	0.68 tons/hr.	
12	Bulk Material Conveying		Gypsum	165 tons/hr.	

Applicable Requirements**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 7%

Authority for Requirement: Iowa DNR Construction Permit 98-A-811-S1
567 IAC 23.1(2)"bbb"
40 CFR 60.672

Pollutant: Particulate Matter

Emission Limit(s): 0.022 gr/dscf

Authority for Requirement: Iowa DNR Construction Permit 98-A-811-S1
567 IAC 23.1(2)"bbb"
40 CFR 60.672

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

This source is subject to 40 CFR 60 Subpart A (General Provisions) and 40 CFR 60 Subpart OOO (Standards of Performance for Nonmetallic Mineral Processing Plants). The above emission units cannot be operated without the baghouse.

Authority for Requirement: Iowa DNR Construction Permit 98-A-811-S1
567 IAC 23.1(2)"bbb"
40 CFR 60 Subparts A & OOO

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 31

Stack Opening, (feet): 1.67 x 2.5

Exhaust Flow Rate (scfm): 16,000

Exhaust Temperature (°F): 70

Discharge Style: Vertical, Unobstructed

Authority for Requirement: Iowa DNR Construction Permit 98-A-811-S1

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No
(See Appendix A)

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Numbers: 9A, 9B, 9C, 9D, 9E, 9F

Associated Equipment

Emission Point	Emission Unit	Emission Unit Description	Control Equipment	Raw Material	Rated Capacity	Construction Permit
9A	6	Primary Crushing (Uncaptured)	NA	Gypsum	125 tons/hr.	NA
9B	8	Screening (Uncaptured)	CE17: Dust Suppression	Gypsum	125 ton/hr.	NA
	9	Secondary Crushing (Uncaptured)		Gypsum	125 tons/hr.	NA
9C	7	Bulk Material Conveying (Uncaptured) Two material transfers onto belt from crusher		Gypsum	175 tons/hr.	NA
9D	10	Bulk Material Conveying (Uncaptured) Three material transfers post secondary crusher		Gypsum	50 tons/hr.	NA
9E	11	Bulk Material Conveying (Uncaptured) Baghouse fines – Screw to Conveyor Belt		Gypsum	0.68 tons/hr.	NA
9F	12	Bulk Material Conveying (Uncaptured) Transfer of Screened Gypsum to Belt		Gypsum	165 tons/hr.	NA

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

EU's 6, 8, 9, 7

Pollutant: Opacity

Emission Limit(s): 10%

Authority for Requirement: 567 IAC 23.1(2)"bbb"
40 CFR 60.672

EU's 10, 11, 12

Pollutant: Opacity

Emission Limit(s): 10%

Authority for Requirement: 567 IAC 23.1(2)"bbb"
40 CFR 60 Subpart 000

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Emission units 10, 11, and 12 are subject to 40 CFR 60 Subpart A (General Provisions) and 40 CFR 60 Subpart OOO (Standards of Performance for Nonmetallic Mineral Processing Plants). The above emission units cannot be operated without the baghouse.

Authority for Requirement: 567 IAC 23.1(2)"bbb"
40 CFR 60 Subparts A & OOO

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Opacity:

Visible emissions shall be observed on a weekly basis to ensure that none when the emission unit on this emission point is at or near full capacity. If visible emissions are observed corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 22 observation will be required. If an opacity of 10% is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from observation of the violation.

If weather conditions prevent the observer from conducting an observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Maintain a written record of the observation and any action resulting from the observation for a minimum of five years.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 53**Associated Equipment**

Emission Unit	Emission Unit Description	Control Equipment	Raw Material	Rated Capacity	Construction Permit
12RU	Radial Stacker Conveyor	CE22: Baghouse	Gypsum	165 tons/hr.	99-A-401
102	Belt Conveyor from Blend Building		Gypsum	165 tons/hr.	

Applicable Requirements**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 7%⁽¹⁾

Authority for Requirement: Iowa DNR Construction Permit 99-A-401
567 IAC 23.1(2)"bbb"
40 CFR 60.672

Pollutant: PM-10

Emission Limit(s): 0.13 lb/hr.

Authority for Requirement: Iowa DNR Construction Permit 99-A-401

Pollutant: Particulate Matter

Emission Limit(s): 0.022 gr/dscf

Authority for Requirement: Iowa DNR Construction Permit 99-A-401
567 IAC 23.1(2)"bbb"
40 CFR 60.672

⁽¹⁾ An exceedance of the indicator opacity of (0%) will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

This source is subject to 40 CFR 60 Subpart A (General Provisions) and 40 CFR 60 Subpart OOO (Standards of Performance for Nonmetallic Mineral Processing Plants).

Authority for Requirement: Iowa DNR Construction Permit 99-A-401
567 IAC 23.1(2)"bbb"
40 CFR 60 Subparts A & OOO

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

- Stack Height, (ft, from the ground): 25
- Stack Opening, (inches, dia.): 12
- Exhaust Flow Rate (scfm): 1500
- Exhaust Temperature (°F): Ambient
- Discharge Style: NA
- Authority for Requirement: Iowa DNR Construction Permit 99-A-401

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Opacity:

Visible emissions shall be observed on a weekly basis to ensure that none when the emission unit on this emission point is at or near full capacity. If visible emissions are observed corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity >7% is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from observation of the violation.

If weather conditions prevent the observer from conducting an observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Maintain a written record of the observation and any action resulting from the observation for a minimum of five years.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source’s compliance with the applicable requirements.

The data pertaining to the plan shall be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 12RU

Associated Equipment

Emission Unit	Emission Unit Description	Raw Material	Rated Capacity	Construction Permit
12RU	Radial Stacker Conveyor (Uncaptured)	Gypsum	165 tons/hr.	NA

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 10%

Authority for Requirement: 567 IAC 23.1(2)"bbb"
40 CFR 60 Subpart OOO

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

This source is subject to 40 CFR 60 Subpart A (General Provisions) and 40 CFR 60 Subpart OOO (Standards of Performance for Nonmetallic Mineral Processing Plants).

Authority for Requirement: 567 IAC 23.1(2)"bbb"
40 CFR 60 Subparts A & OOO

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Opacity:

Visible emissions shall be observed on a weekly basis to ensure that none when the emission unit on this emission point is at or near full capacity. If visible emissions are observed corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 22 observation will be required. If an opacity 10% is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from observation of the violation.

If weather conditions prevent the observer from conducting an observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Maintain a written record of the observation and any action resulting from the observation for a minimum of five years.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 12

Associated Equipment

Emission Unit	Emission Unit Description	Control Equipment	Raw Material	Rated Capacity	Construction Permit
13	Crushed Gypsum Ore Pile Outdoor	CE17: Dust Suppression	Gypsum	165 tons/hr.	NA

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Fugitive Dust

Emission Limit: No person shall allow, cause or permit any materials to be handled, transported or stored; or a building, its appurtenances or a construction haul road to be used, constructed, altered, repaired or demolished, without taking reasonable precautions to prevent a nuisance. All persons shall take reasonable precautions to prevent the discharge of visible emissions of fugitive dusts beyond the lot line of the property on which the emissions originate.

Authority for Requirement: 567 IAC 23.3(2)"c"

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 13

Associated Equipment

Emission Unit	Emission Unit Description	Control Equipment	Raw Material	Rated Capacity	Construction Permit
14	Gypsum Ore Pile Indoor	CE17: Dust Suppression	Gypsum	165 tons/hr.	NA

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Fugitive Dust

Emission Limit: No person shall allow, cause or permit any materials to be handled, transported or stored; or a building, its appurtenances or a construction haul road to be used, constructed, altered, repaired or demolished, without taking reasonable precautions to prevent a nuisance. All persons shall take reasonable precautions to prevent the discharge of visible emissions of fugitive dusts beyond the lot line of the property on which the emissions originate.

Authority for Requirement: 567 IAC 23.3(2)"c"

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 28D (Vents Internally)

Associated Equipment

Emission Unit	Emission Unit Description	Control Equipment	Raw Material	Rated Capacity	Construction Permit
61	Accelerator Bin & Feed System	CE4: Baghouse	Accelerator	9 tons/hr.	99-A-140

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): No owner or operator shall cause to be discharged into the atmosphere from:

- (a) Fugitive emissions from the building openings (except for vents as defined in §60.671) must not exceed 7 percent opacity
- (b) Any vent of any building in which the emission unit (EU 61 - Accelerator Storage Bin & Feed System) listed in this permit (99-A-140) vents into emissions which exceed:
 - Particulate matter in excess of 0.05 grams/dscm (0.022 grains/dscf).
 - Opacity greater than 7 %.

Authority for Requirement: Iowa DNR Construction Permit 99-A-140
567 IAC 23.1(2)"bbb"
40 CFR 60.672

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

This unit is subject to 40 CFR 60 Subpart A (General Provisions) and 40 CFR 60 Subpart OOO (Standards of Performance for Nonmetallic Mineral Processing Plants).

Authority for Requirement: Iowa DNR Construction Permit 99-A-140
567 IAC 23.1(2)"bbb"
40 CFR 60.672

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Opacity:

The facility shall check the opacity of building openings weekly during a period when the emission unit on this emission point is at or near full capacity and record the reading. Maintain a written record of the observation and any action resulting from the observation for a minimum of five years. The facility shall use EPA Method 22.

If visible emissions, other than emissions from a vent as defined in 40 CFR 60.671, are observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions.

If visible emissions are observed from a vent, a Method 9 reading must be performed by a certified smoke reader. If an opacity > 7% is observed from the vent, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the applicable requirements.

The data pertaining to the plan shall be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 28J

Associated Equipment

Emission Unit	Emission Unit Description	Control Equipment	Raw Material	Rated Capacity	Construction Permit
46A	Stucco Storage Bin Northwest	CE18: Baghouse	Stucco	65 tons/hr.	78-A-185

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 40 %

Authority for Requirement: 567 IAC 23.3(2)"d"

Pollutant: Particulate Matter

Emission Limit(s): 0.1 gr/dscf.

Authority for Requirement: Iowa DNR Construction Permit 78-A-185
567 IAC 23.3(2)"a"

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the applicable requirements.

The data pertaining to the plan shall be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Numbers: 28K, 28L, 28M

Associated Equipment

Emission Point	Emission Unit	Emission Unit Description	Control Equipment	Raw Material	Rated Capacity	Construction Permit
28K	46B	Stucco Storage Bin Southwest	CE19: Baghouse	Stucco	65 tons/hr.	NA
28L	48A	Stucco Storage Bin Northeast	CE20: Baghouse	Stucco	65 tons/hr.	NA
28M	48B	Stucco Storage Bin Southeast	CE21: Baghouse	Stucco	65 tons/hr.	NA

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from each emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 40 %

Authority for Requirement: 567 IAC 23.3(2)"d"

Pollutant: Particulate Matter

Emission Limit(s): 0.1 gr/scf

Authority for Requirement: 567 IAC 23.3(2)"a"

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

**Facility Maintained Operation & Maintenance Plan Required?
(Required for CE19, CE20, and CE21)** Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the applicable requirements.

The data pertaining to the plan shall be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 29

Associated Equipment

Emission Unit	Emission Unit Description	Control Equipment	Raw Material	Rated Capacity	Construction Permit
50	Baghouse Heater	NA	Natural Gas	1.52 MMBtu/hr.	89-A-131
52	Gypsum Conveyor	CE6: Baghouse	Stucco	65 tons/hr.	
74	Gypsum Blender		Stucco	65 tons/hr.	
75	Gypsum Pin Mixer		Stucco	65 tons/hr.	

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 40 %

Authority for Requirement: 567 IAC 23.3(2)"d"

Pollutant: Particulate Matter

Emission Limit(s): 0.1 gr/scf

Authority for Requirement: 567 IAC 23.3(2)"a"

Pollutant: Sulfur Dioxide (SO₂)

Emission Limit(s): 500 ppmv

Authority for Requirement: 567 IAC 23.3(3)"e"

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No
(See Appendix A)

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Numbers: 32, 33, 34, 35, 36, 37

Associated Equipment

Emission Unit*	Emission Unit Description	Raw Material	Rated Capacity	Construction Permit
82	Board Drying Kiln	Natural Gas	113.5 MMBtu/hr.	See Below
83				See Below
84				See Below
85				See Below
86				See Below
87				See Below
117	DENS In-Line Coating	Coatings	3.28 gallons/msf	See Below
I100	Edge/Code Printer	Ink	0.00034 gallons/msf	See Below

* All of these emission units are exhausted through each of the emission points listed above. Each emission point is listed below with its corresponding construction permit.

Emission Point	Construction Permit
32	02-A-889-S1
33	02-A-890-S1
34	02-A-891-S1
35	99-A-298-S2
36	02-A-892-S1
37	02-A-893-S1

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from each emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 40 %⁽¹⁾

Authority for Requirement: Iowa DNR Construction Permits 02-A-889-S1, 02-A-890-S1, 02-A-891-S1, 99-A-298-S2, 02-A-892-S1, 02-A-893-S1
567 IAC 23.3(2)"d"

Pollutant: Particulate Matter

Emission Limit(s): 0.1 gr/dscf

Authority for Requirement: Iowa DNR Construction Permits 02-A-889-S1, 02-A-890-S1, 02-A-891-S1, 99-A-298-S2, 02-A-892-S1, 02-A-893-S1
567 IAC 23.3(2)"a"

Pollutant: Sulfur Dioxide (SO₂)

Emission Limit(s): 500 ppmv

Authority for Requirement: 567 IAC 23.3(3)"e"

Pollutant: Single HAP

Emission Limit(s): 9.4 tons/yr.^{(2), (3)}

Authority for Requirement: Iowa DNR Construction Permits 02-A-889-S1, 02-A-890-S1, 02-A-891-S1, 99-A-298-S2, 02-A-892-S1, 02-A-893-S1

Pollutant: Total HAP

Emission Limit(s): 24.4 tons/yr.^{(2), (3)}

Authority for Requirement: Iowa DNR Construction Permits 02-A-889-S1, 02-A-890-S1, 02-A-891-S1, 99-A-298-S2, 02-A-892-S1, 02-A-893-S1

⁽¹⁾ An exceedance of the indicator opacity of (25%) will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

⁽²⁾ Limit applies to total emissions from the wallboard line.

⁽³⁾ Standard is a 12-month rolling total.

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Process throughput:

1. Dens In-Line Coating (Prime) and Dens In-Line Spray Unit (Gold) are limited to a total of 50,000 msf of Dens coated/ink applied product per rolling 12-month period.
2. Dens in-Line Coating (Prime) and Dens In-Line Spray Unit (Gold) are limited to the application of a coating containing a maximum VOC content of 0.3 lb/gal.
3. Dens In-Line Spray Unit (Gold) and Edge Printer #1 (EUI100) are limited to the application of inks containing a maximum VOC content of 7.0 lb/gal.
4. Board Drying Kiln (EU82-EU87) is limited to firing on natural gas fuel only.

Reporting & Record keeping:

Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. Record on a monthly basis, the total amount of DENS coated/ink applied product manufactured in Dens In-line Coating (Prime) and Dens In-Line Spray Unit (Gold) in ft². Calculate and record rolling 12-month totals.
2. Record the VOC content of all coating/inks/VOC-containing materials applied in Dens In-Line Coating (Prime), Dens In-Line Spray Unit (Gold) and Edge Printer #1 (EUI100) in lbs/gallon.
3. Record on a monthly basis in tons, the Total HAP emissions from Dens-In-Line Coating (Prime), Dens In-Line Spray Unit (Gold) and Edge Printer #1 (EUI100) combined.
4. Record on a monthly basis in tons, the Individual HAP emissions from Dens-In Line Coating (Prime), Dens In-Line Spray Unit (Gold) and Edge Printer #1 (EUI100) combined.
5. Retain Material Safety Data Sheets (MSDS) of all materials used in Dens In-Line Coating (Prime), Dens In-Line Spray Unit (Gold) and Edge Printer #1 (EUI100).

Authority for Requirement: Iowa DNR Construction Permits 02-A-889-S1, 02-A-890-S1, 02-A-891-S1, 99-A-298-S2, 02-A-892-S1, 02-A-893-S1

Emission Point Characteristics

Emission points 32, 33, 34, 35, 36, and 37 shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 30

Stack Opening, (inches, dia.): 36

Exhaust Flow Rate (scfm): 8900

Exhaust Temperature (°F): 300

Discharge Style: Vertical, Obstructed

Authority for Requirement: Iowa DNR Construction Permits 02-A-889-S1, 02-A-890-S1,
02-A-891-S1, 99-A-298-S2, 02-A-892-S1, 02-A-893-S1

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 40, 41, 50 (Back Up System)

Associated Equipment

Emission Unit*	Emission Unit Description	Control Equipment	Raw Material	Rated Capacity	Construction Permit
88A	End Trimmer	CE9: Baghouse (EP 40) CE10: Baghouse (EP 41)	Gypsum Board	38 msf/hr.	See Below
88B	End Trimmer	CE12: Baghouse (EP 50)	Gypsum Board	38 msf/hr.	See Below

* All of these emission units may be vented through the emission points listed above. Emissions from emission unit 88A are typically vented through emission points 40 and 41 with emission point 50 as a back-up. Emissions from emission unit 88B typically vent through emission point 50.

Emission Point	Construction Permit
40	76-A-250-S1
41	
50	00-A-677-S2

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from these emission points shall not exceed the levels specified below.

EP's 40 & 41

Pollutant: Opacity

Emission Limit(s): 40 %

Authority for Requirement: 567 IAC 23.3(2)"d"

Pollutant: Particulate Matter

Emission Limit(s): 0.1 gr/scf

Authority for Requirement: Iowa DNR Construction Permit 76-A-250-S1
567 IAC 23.3(2)"a"

EP 50

Pollutant: Opacity

Emission Limit(s): 40 %⁽¹⁾

Authority for Requirement: Iowa DNR Construction Permit 00-A-677-S2
567 IAC 23.3(2)"d"

Pollutant: Particulate Matter

Emission Limit(s): 0.1 gr/dscf

Authority for Requirement: Iowa DNR Construction Permit 00-A-677-S2
567 IAC 23.3(2)"a"

⁽¹⁾ An exceedance of the indicator opacity of (10%) will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Emission Point Characteristics

Emission Point 50 shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 54

Stack Opening, (inches): 16 x 18

Exhaust Flow Rate (scfm): 10,800

Exhaust Temperature (°F): Ambient

Discharge Style: Vertical, Unobstructed

Authority for Requirement: Iowa DNR Construction Permit 00-A-677-S2

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No
(Required for Emission Point 40 (CE9), 41 (CE10), and 50 (CE12), see Appendix A)

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 43

Associated Equipment

Emission Unit	Emission Unit Description	Raw Material	Rated Capacity	Construction Permit
91	Bulk Unloading of Gypsum Dust (Wheelabrator Alley)	Gypsum Dust	0.43 tons/hr.	NA

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Fugitive Dust

Emission Limit: No person shall allow, cause or permit any materials to be handled, transported or stored; or a building, its appurtenances or a construction haul road to be used, constructed, altered, repaired or demolished, without taking reasonable precautions to prevent a nuisance. All persons shall take reasonable precautions to prevent the discharge of visible emissions of fugitive dusts beyond the lot line of the property on which the emissions originate.

Authority for Requirement: 567 IAC 23.3(2)"c"

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 49

Associated Equipment

Emission Unit	Emission Unit Description	Control Equipment	Raw Material	Rated Capacity	Construction Permit
67	Starch Bin	CE8: Baghouse	Starch	50 tons/hr.	89-A-197
68	Starch Bin		Starch	50 tons/hr.	

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 40 %

Authority for Requirement: 567 IAC 23.3(2)"d"

Pollutant: Particulate Matter

Emission Limit(s): 0.1 gr/dscf

Authority for Requirement: Iowa DNR Construction Permit 89-A-197
567 IAC 23.3(2)"a"

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the applicable requirements.

The data pertaining to the plan shall be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 50A

Associated Equipment

Emission Unit	Emission Unit Description	Raw Material	Rated Capacity	Construction Permit
19	Reclaim/Recycle Conveyor	Gypsum	15 tons/hr.	00-A-206-S1
110	Reclaim Storage Area	Gypsum	100 tons/hr.	
111	Steele Feeder	Gypsum	15 tons/hr.	

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 10%

Authority for Requirement: Iowa DNR Construction Permit 00-A-206-S1
567 IAC 23.1(2)"bbb"
40 CFR 60.672

Pollutant: Fugitive Dust

Emission Limit: No person shall allow, cause or permit any materials to be handled, transported or stored; or a building, its appurtenances or a construction haul road to be used, constructed, altered, repaired or demolished, without taking reasonable precautions to prevent a nuisance. All persons shall take reasonable precautions to prevent the discharge of visible emissions of fugitive dusts beyond the lot line of the property on which the emissions originate.

Authority for Requirement: 567 IAC 23.3(2)"c"

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Process throughput:

1. The maximum capacity of the feeder and the belt conveyor is limited to 15 tons per hour.
2. The maximum capacity of the storage area is limited to 10,000 tons.

NSPS:

Emission Units 110 and 111 are subject to 40 CFR 60 Subpart A (General Provisions) and 40 CFR 60 Subpart OOO (Standards of Performance for Nonmetallic Mineral Processing Plants).

Authority for Requirement: Iowa DNR Construction Permit 00-A-206-S1
567 IAC 23.1(2)"bbb"
40 CFR 60 Subparts A & OOO

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): NA

Stack Opening, (inches, dia.): NA

Exhaust Flow Rate (scfm): NA

Exhaust Temperature (°F): Ambient

Discharge Style: NA

Authority for Requirement: Iowa DNR Construction Permit 00-A-206-S1

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Opacity:

Visible emissions shall be observed on a weekly basis to ensure that none when the emission unit on this emission point is at or near full capacity. If visible emissions are observed corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 22 observation will be required. If an opacity 10% is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from observation of the violation.

If weather conditions prevent the observer from conducting an observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 51C (Vents Internally)

Associated Equipment

Emission Unit	Emission Unit Description	Raw Material	Rated Capacity	Construction Permit
58	Ball Mill	Landplaster	0.45 tons/hr.	98-A-600
59	Ball Mill	Landplaster	0.45 tons/hr.	
60	Ball Mill	Landplaster	0.45 tons/hr.	

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): No owner or operator shall cause to be discharged into the atmosphere from:

- (a) Fugitive emissions from the building openings (except for vents as defined in §60.671) must not exceed 7 percent opacity
- (b) Any vent of any building enclosing the sources (Ball Mills 1, 2, and 3) listed in this permit (98-A-600) emissions which exceed:
 - Particulate matter in excess of 0.05 grams/dscm (0.02 grains/dscf).
 - Opacity greater than 7 %.

Authority for Requirement: Iowa DNR Construction Permit 98-A-600
567 IAC 23.1(2)"bbb"
40 CFR 60.672

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

These sources are subject to 40 CFR 60 Subpart A (General Provisions) and 40 CFR 60 Subpart OOO (Standards of Performance for Nonmetallic Mineral Processing Plants).

Authority for Requirement: Iowa DNR Construction Permit 98-A-600
567 IAC 23.1(2)"bbb"
40 CFR 60.672

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Opacity:

The facility shall check the opacity weekly during a period when the emission unit on this emission point is at or near full capacity and record the reading. Maintain a written record of the observation and any action resulting from the observation for a minimum of five years. The facility shall use EPA Method 22.

If visible emissions, other than emissions from a vent as defined in 40 CFR 60.671, are observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions.

If visible emissions are observed from a vent, a Method 9 reading must be performed by a certified smoke reader. If an opacity > 7% is observed from the vent, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 52

Associated Equipment

Emission Unit	Emission Unit Description	Control Equipment	Raw Material	Rated Capacity	Construction Permit
31	Landplaster Storage Bin & Feed	CE16: Baghouse	Landplaster	9.975tons/hr.	98-A-601

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 7%

Authority for Requirement: Iowa DNR Construction Permit 98-A-601
567 IAC 23.1(2)"bbb"
40 CFR 60.672

Pollutant: Particulate Matter

Emission Limit(s): 0.022 gr/dscf

Authority for Requirement: Iowa DNR Construction Permit 98-A-601
567 IAC 23.1(2)"bbb"
40 CFR 60.672

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

This source is subject to 40 CFR 60 Subpart A (General Provisions) and 40 CFR 60 Subpart OOO (Standards of Performance for Nonmetallic Mineral Processing Plants).

Authority for Requirement: Iowa DNR Construction Permit 98-A-601
567 IAC 23.1(2)"bbb"
40 CFR 60.672

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

- Stack Height, (ft, from the ground): 50
- Stack Opening, (inches, dia.): 12
- Exhaust Flow Rate (scfm): 300
- Exhaust Temperature (°F): 70
- Discharge Style: Vertical, Unobstructed
- Authority for Requirement: Iowa DNR Construction Permit 98-A-601

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Opacity:

Visible emissions shall be observed on a weekly basis to ensure that none when the emission unit on this emission point is at or near full capacity. If visible emissions are observed corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity >7 % is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from observation of the violation.

If weather conditions prevent the observer from conducting an observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Maintain a written record of the observation and any action resulting from the observation for a minimum of five years.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source’s compliance with the applicable requirements.

The data pertaining to the plan shall be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 55 (Vents Internally)

Associated Equipment

Emission Unit	Emission Unit Description	Control Equipment	Raw Material	Rated Capacity	Construction Permit
101	High Angle Conveyor	CE23: Baghouse	Gypsum	125 tons/hr.	99-A-402
103	Raw Gypsum Bin		Gypsum	125 tons/hr.	

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 7%⁽¹⁾

Authority for Requirement: Iowa DNR Construction Permit 99-A-402
567 IAC 23.1(2)"bbb"
40 CFR 60.672

Pollutant: PM-10

Emission Limit(s): 0.09 lb/hr.

Authority for Requirement: Iowa DNR Construction Permit 99-A-402

Pollutant: Particulate Matter

Emission Limit(s): 0.022 gr/dscf

Authority for Requirement: Iowa DNR Construction Permit 99-A-402
567 IAC 23.1(2)"bbb"
40 CFR 60.672

⁽¹⁾ An exceedance of the indicator opacity of (0%) will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

This source is subject to 40 CFR 60 Subpart A (General Provisions) and 40 CFR 60 Subpart OOO (Standards of Performance for Nonmetallic Mineral Processing Plants).

Authority for Requirement: Iowa DNR Construction Permit 99-A-402
567 IAC 23.1(2)"bbb"
40 CFR 60 Subpart OOO

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 47.5

Stack Opening, (inches, dia.): 12

Exhaust Flow Rate (scfm): 1000

Exhaust Temperature (°F): Ambient

Discharge Style: NA

Authority for Requirement: Iowa DNR Construction Permit 99-A-402

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Opacity:

Visible emissions shall be observed on a weekly basis to ensure that none when the emission unit on this emission point is at or near full capacity. If visible emissions are observed corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If corrective action does not return the observation to no visible emissions, then a Method 9 observation will be required. If an opacity >7 % is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from observation of the violation.

If weather conditions prevent the observer from conducting an observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Maintain a written record of the observation and any action resulting from the observation for a minimum of five years.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the applicable requirements.

The data pertaining to the plan shall be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility's implementation of its obligation to operate according to good air pollution control practice.

Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 56

Associated Equipment

Emission Unit	Emission Unit Description	Control Equipment	Raw Material	Rated Capacity	Construction Permit
104	Chain Feeder	CE24: CP Mill North Baghouse	Gypsum	50 tons/hr.	99-A-403
105	Ball Race Mill		Gypsum	50 tons/hr.	
106	Hot Gas Generator	CE25: CP Mill South Baghouse	Natural Gas	0.0476 MMcf/hr (48.6 MMBtu/hr)	

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 10%

Authority for Requirement: Iowa DNR Construction Permit 99-A-403
567 IAC 23.1(2)"ppp"
40 CFR 60.732(b)

Pollutant: Opacity

Emission Limit(s): 7%

Authority for Requirement: 567 IAC 23.1(2)"bbb"
40 CFR 60.672

Pollutant: PM-10

Emission Limit(s): 4.5 lb/hr.

Authority for Requirement: Iowa DNR Construction Permit 99-A-403

Pollutant: Particulate Matter

Emission Limit(s): 0.04 gr/scf

Authority for Requirement: Iowa DNR Construction Permit 99-A-403
567 IAC 23.1(2)"ppp"
40 CFR 60.732(a)

Pollutant: Particulate Matter

Emission Limit(s): 0.022 gr/dscf

Authority for Requirement: 567 IAC 23.1(2)"bbb"
40 CFR 60.672

Pollutant: Sulfur Dioxide (SO₂)

Emission Limit(s): 500 ppmv

Authority for Requirement: 567 IAC 23.3(3)"e"

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Process throughput:

1. The Hot Gas Generator (EU-106) shall only use Natural Gas.

Reporting & Record keeping:

Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. Record the dates of any filter bag replacements for CE-24 or CE-25.

This source is subject to 40 CFR 60 Subpart A (General Provisions) and 40 CFR 60 Subpart OOO (Standards of Performance for Nonmetallic Mineral Processing Plants).

Authority for Requirement: 567 IAC 23.1(2)"bbb"
40 CFR 60 Subparts A & OOO

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 105

Stack Opening, (inches, dia.): 54

Exhaust Flow Rate (scfm): 35,000

Exhaust Temperature (°F): 300

Discharge Style: Vertical, Unobstructed

Authority for Requirement: Iowa DNR Construction Permit 99-A-403

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Stack Testing:

Pollutant – PM₁₀

Stack Test to be Completed by – 7/5/2014

Test Method – 40 CFR 51, Appendix M, 201A with 202, or approved alternative.

Authority for Requirement - 567 IAC 22.108(3)

Pollutant – Particulate Matter

Stack Test to be Completed by – 7/5/2014

Test Method - 40 CFR Part 60 App. A, Method 5

Authority for Requirement - 567 IAC 22.108(3)

The owner of this equipment or the owner's authorized agent shall provide written notice to the Director, not less than 30 days before a required stack test or performance evaluation of a continuous emission monitor. Results of the test shall be submitted in writing to the Director in the form of a comprehensive report within 6 weeks of the completion of the testing. 567 IAC 25.1(7)

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No
(See Appendix A)

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 57

Associated Equipment

Emission Unit	Emission Unit Description	Control Equipment	Raw Material	Rated Capacity	Construction Permit
107	Closed Aeroslide	CE26: Baghouse	Gypsum	50 tons/hr.	99-A-404-S1
108	Stucco Cooler		Gypsum	50 tons/hr.	
109	Stucco Truck Loading		Gypsum	50 tons/hr.	

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 7%⁽¹⁾

Authority for Requirement: Iowa DNR Construction Permit 99-A-404-S1
567 IAC 23.1(2)"bbb"
40 CFR 60.672

Pollutant: PM-10

Emission Limit(s): 4.46 lb/hr.

Authority for Requirement: Iowa DNR Construction Permit 99-A-404-S1

Pollutant: Particulate Matter

Emission Limit(s): 0.022 gr/dscf

Authority for Requirement: 567 IAC 23.1(2)"bbb"
40 CFR 60.672

⁽¹⁾ An exceedance of the indicator opacity of (0%) will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

This source is subject to 40 CFR 60 Subpart A (General Provisions) and 40 CFR 60 Subpart OOO (Standards of Performance for Nonmetallic Mineral Processing Plants).

Authority for Requirement: Iowa DNR Construction Permit 99-A-404-S1
567 IAC 23.1(2)"bbb"
40 CFR 60 Subparts A & OOO

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 56
Stack Opening, (inches, dia.): 54
Exhaust Flow Rate (scfm): 52,000
Exhaust Temperature (°F): 200
Discharge Style: Vertical Unobstructed
Authority for Requirement: Iowa DNR Construction Permit 99-A-404-S1

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No
(See Appendix A)

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 59A

Associated Equipment

Emission Unit	Emission Unit Description	Raw Material	Rated Capacity	Construction Permit
112	Portable Trommel Screen	Gypsum	50 tons/hr.	01-A-1113-S1
114	Portable Reclaim Conveyor	Gypsum	100 tons/hr.	

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): No owner or operator shall cause to be discharged into the atmosphere from:

- (a) Fugitive emissions from the building openings (except for vents as defined in §60.671) must not exceed 7 percent opacity
- (b) Any vent of any building enclosing the sources listed in this permit emissions which exceed:
 - Opacity greater than 10 %.

Authority for Requirement: Iowa DNR Construction Permit 01-A-1113-S1
567 IAC 23.1(2)"bbb"
40 CFR 60.672

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Hours of operation:

1. The portable screening operation (EU114) is limited to 2500 hours of operation per rolling 12-month period.

Reporting & Record keeping:

Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. Record on a monthly basis, hours of operation of Screening (EU114) Operation.
Calculate and record rolling 12-month totals.

NSPS:

This source is subject to 40 CFR 60 Subpart A (General Provisions) and 40 CFR 60 Subpart OOO (Standards of Performance for Nonmetallic Mineral Processing Plants).

Authority for Requirement: Iowa DNR Construction Permit 01-A-1113-S1
567 IAC 23.1(2)"bbb"
40 CFR 60 Subpart OOO

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Opacity:

The facility shall check the opacity weekly during a period when the emission unit on this emission point is at or near full capacity and record the reading. Maintain a written record of the observation and any action resulting from the observation for a minimum of five years. The facility shall use EPA Method 22. If an opacity >10% is observed, this would be a violation and corrective action will be taken as soon as possible, but no later than eight hours from the observation of visible emissions. If weather conditions prevent the observer from conducting an opacity observation, the observer shall note such conditions on the data observation sheet. At least three attempts shall be made to retake opacity readings at approximately 2-hour intervals throughout the day. If all observation attempts for a week have been unsuccessful due to weather, an observation shall be made the next operating day where weather permits.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 60A

Associated Equipment

Emission Unit	Emission Unit Description	Raw Material	Rated Capacity	Construction Permit
115A	Maxi-Grinder	Gypsum	100 tons/hr.	02-A-360

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): No owner or operator shall cause to be discharged into the atmosphere from:

- (a) Fugitive emissions from the building openings (except for vents as defined in §60.671) must not exceed 7 percent opacity
- (b) Any vent of any building enclosing the sources listed in this permit emissions which exceed:
 - Opacity greater than 10 %.

Authority for Requirement: Iowa DNR Construction Permit 02-A-360
567 IAC 23.1(2)"bbb"
40 CFR 60.672

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Hours of operation:

- 1. The portable grinding and screening operation (EU 115) shall not operate more than 2500 hours per rolling 12-month period.

Reporting & Record keeping:

Records shall be kept on site for at least five years and shall be available for inspection by the Department.

- 1. Record on a monthly basis the hours of operation of the portable grinding and screening operation (EU 115). Calculate and record rolling 12-month totals.

NSPS:

This source is subject to 40 CFR 60 Subpart A (General Provisions) and 40 CFR 60 Subpart OOO (Standards of Performance for Nonmetallic Mineral Processing Plants).

Authority for Requirement: Iowa DNR Construction Permit 02-A-360
567 IAC 23.1(2)"bbb"
40 CFR 60 Subparts A & OOO

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 60

Associated Equipment

Emission Unit	Emission Unit Description	Raw Material	Rated Capacity	Construction Permit
115B	Diesel Engine	Diesel Fuel	460 horsepower	02-A-361

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 40%⁽¹⁾

Authority for Requirement: Iowa DNR Construction Permit 02-A-361

Pollutant: PM-10

Emission Limit(s): 0.72 lb/hr.

Authority for Requirement: Iowa DNR Construction Permit 02-A-361

Pollutant: Particulate Matter

Emission Limit(s): 0.72 lb/hr.

Authority for Requirement: Iowa DNR Construction Permit 02-A-361

Pollutant: Sulfur Dioxide (SO₂)

Emission Limit(s): 2.5 lb/MMBtu

Authority for Requirement: Iowa DNR Construction Permit 02-A-361
567 IAC 23.3(3)"b"(2)

⁽¹⁾ An exceedance of the indicator opacity of (20%) will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Hours of operation:

1. The 460 Hp Diesel Engine (EU 115B) shall not operate more than 2500 hours per rolling 12-month period.

Process throughput:

1. The 460 Hp Diesel Engine (EU 115B) is limited to firing diesel fuel containing a sulfur content less than or equal to 0.05 percent by weight.

Reporting & Record keeping:

Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. Record on a monthly basis the hours of operation of the 460 Hp Diesel Engine (EU 115B). Calculate and record rolling 12-month totals.
2. Retain supplier's certification of sulfur content in diesel fuel fired in the 460 Hp Diesel Engine (EU 115B).

Authority for Requirement: Iowa DNR Construction Permit 02-A-361

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 16

Stack Opening, (inches, dia.): 4

Exhaust Flow Rate (acfm): 3535

Exhaust Temperature (°F): 1166

Discharge Style: Vertical, Unobstructed

Authority for Requirement: Iowa DNR Construction Permit 02-A-361

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 61

Associated Equipment

Emission Unit	Emission Unit Description	Raw Material	Rated Capacity	Construction Permit
118	DENS Off-line Coating	Product Coating	30.972 gallons/hr.	02-A-894-S1

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 40 %⁽¹⁾

Authority for Requirement: Iowa DNR Construction Permit 02-A-894-S1
567 IAC 23.3(2)"d"

Pollutant: Particulate Matter

Emission Limit(s): 0.01 gr/scf

Authority for Requirement: Iowa DNR Construction Permit 02-A-894-S1
567 IAC 23.4(13)

Pollutant: Single HAP

Emission Limit(s): 9.4 tons/yr.^{(2), (3)}

Authority for Requirement: Iowa DNR Construction Permit 02-A-894-S1

Pollutant: Total HAP's

Emission Limit(s): 24.4 tons/yr.^{(2), (3)}

Authority for Requirement: Iowa DNR Construction Permit 02-A-894-S1

⁽¹⁾ An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

⁽²⁾ Limit applies to total emissions from the wallboard line.

⁽³⁾ Standard is a 12-month rolling total.

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Process throughput:

- 1. DENS Off-line Coating (EU118) Line is limited to using coatings with a maximum VOC content of 0.1 pounds per gallon.

Reporting & Record keeping:

Records shall be kept on site for at least five years and shall be available for inspection by the Department.

- 1. Record the VOC content of all materials used in Dens Off-Line Coating Line (EU118) in pounds per gallon.
- 2. Record on a monthly basis in tons, the total HAP emissions from Dens Off-line Coating line (EU118).
- 3. Record on a monthly basis in tons, the individual HAP emissions from Dens Off-line Coating Line (EU118).
- 4. Retain Material Safety Data Sheets (MSDS) of all materials used in Dens Off-line Coating Line (EU118).

Authority for Requirement: Iowa DNR Construction Permit 02-A-894-S1

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 16' 2"

Stack Opening, (inches, dia.): 26

Exhaust Flow Rate (scfm): 600

Exhaust Temperature (°F): 100

Discharge Style: Obstructed, Vertical or Horizontal

Authority for Requirement: Iowa DNR Construction Permit 02-A-894-S1

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 61A

Associated Equipment

Emission Unit	Emission Unit Description	Raw Material	Rated Capacity	Construction Permit
1101	Edge Printer	Ink	0.257 gallons/hr.	04-A-061

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 40 %⁽¹⁾

Authority for Requirement: Iowa DNR Construction Permit 04-A-061
567 IAC 23.3(2)"d"

Pollutant: Particulate Matter

Emission Limit(s): 0.01 gr/scf

Authority for Requirement: Iowa DNR Construction Permit 04-A-061
567 IAC 23.4(13)

Pollutant: Single HAP

Emission Limit(s): 9.4 tons/yr.^{(2), (3)}

Authority for Requirement: Iowa DNR Construction Permit 04-A-061

Pollutant: Total HAP's

Emission Limit(s): 24.4 tons/yr.^{(2), (3)}

Authority for Requirement: Iowa DNR Construction Permit 04-A-061

⁽¹⁾ An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

⁽²⁾ Limit applies to total emissions from the wallboard line.

⁽³⁾ Standard is a 12-month rolling total.

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Process throughput:

- 1. Edge Printer #2 (EUI101) is limited to the application of inks containing a maximum VOC content of 7.0 lb/gal.

Reporting & Record keeping:

Records shall be kept on site for at least five years and shall be available for inspection by the Department.

- 1. Record the VOC content of all materials used in Edge Printer #2 (EUI101) in pounds per gallon.
- 2. Record on a monthly basis in tons, the Total HAP emissions from Edge Printer #2 (EUI101).
- 3. Record on a monthly basis in tons, the Individual HAP emissions from Edge Printer #2 (EUI101).
- 4. Retain Material Safety Data Sheets (MSDS) of all materials used in Edge Printer #2 (EUI101).

Authority for Requirement: Iowa DNR Construction Permit 04-A-061

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No

Authority for Requirement: 567 IAC 22.108(3)

Emission Point ID Number: 62

Associated Equipment

Emission Unit	Emission Unit Description	Control Equipment	Raw Material	Rated Capacity	Construction Permit
119	Holtec Saw	CE27: Baghouse	Gypsum Board	8,000 sf/hr.	02-A-895-S1

Applicable Requirements

Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

The emissions from this emission point shall not exceed the levels specified below.

Pollutant: Opacity

Emission Limit(s): 40 %⁽¹⁾

Authority for Requirement: Iowa DNR Construction Permit 02-A-895-S1
567 IAC 23.3(2)"d"

Pollutant: Particulate Matter

Emission Limit(s): 0.02 gr/scf

Authority for Requirement: Iowa DNR Construction Permit 02-A-895-S1

⁽¹⁾ An exceedance of the indicator opacity of 10% will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Operational Limits & Requirements

The owner/operator of this equipment shall comply with the operational limits and requirements listed below.

Control equipment parameters:

1. Maintain baghouse (CE27) according to manufacturers specifications and maintenance schedule.

Reporting & Record keeping:

Records shall be kept on site for at least five years and shall be available for inspection by the Department.

1. Record all maintenance (if any) on baghouse (CE27).

Authority for Requirement: Iowa DNR Construction Permit 02-A-895-S1

Emission Point Characteristics

The emission point shall conform to the specifications listed below.

Stack Height, (ft, from the ground): 16' 2"

Stack Opening, (inches, dia.): 24

Exhaust Flow Rate (scfm): 10,000

Exhaust Temperature (°F): Ambient

Discharge Style: Vertical, Unobstructed

Authority for Requirement: Iowa DNR Construction Permit 02-A-895-S1

The temperature and flow rate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point design characteristics are different than the values stated above, the owner/operator must notify the Department and obtain a permit amendment, if required.

Monitoring Requirements

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

Agency Approved Operation & Maintenance Plan Required? Yes No

Facility Maintained Operation & Maintenance Plan Required? Yes No

Compliance Assurance Monitoring (CAM) Plan Required? Yes No
(See Appendix A)

Authority for Requirement: 567 IAC 22.108(3)

IV. General Conditions

This permit is issued under the authority of the Iowa Code subsection 455B.133(8) and in accordance with 567 Iowa Administrative Code chapter 22.

G1. Duty to Comply

1. The permittee must comply with all conditions of the Title V permit. Any permit noncompliance constitutes a violation of the Act and is grounds for enforcement action; for a permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application. *567 IAC 22.108(9)"a"*
2. Any compliance schedule shall be supplemental to, and shall not sanction noncompliance with, the applicable requirements on which it is based. *567 IAC 22.105 (2)"h"(3)*
3. Where an applicable requirement of the Act is more stringent than an applicable requirement of regulations promulgated under Title IV of the Act, both provisions shall be enforceable by the administrator and are incorporated into this permit. *567 IAC 22.108 (1)"b"*
4. Unless specified as either "state enforceable only" or "local program enforceable only", all terms and conditions in the permit, including provisions to limit a source's potential to emit, are enforceable by the administrator and citizens under the Act. *567 IAC 22.108 (14)*
5. It shall not be a defense for a permittee, in an enforcement action, that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. *567 IAC 22.108 (9)"b"*

G2. Permit Expiration

1. Except as provided in rule 567—22.104(455B), permit expiration terminates a source's right to operate unless a timely and complete application for renewal has been submitted in accordance with rule 567—22.105(455B). *567 IAC 22.116(2)*
2. To be considered timely, the owner, operator, or designated representative (where applicable) of each source required to obtain a Title V permit shall submit on forms or electronic format specified by the Department to the Air Quality Bureau, Iowa Department of Natural Resources, Air Quality Bureau, 7900 Hickman Rd, Suite #1, Windsor Heights, Iowa 50324, two copies (three if your facility is located in Linn or Polk county) of a complete permit application, at least 6 months but not more than 18 months prior to the date of permit expiration. An additional copy must also be sent to EPA Region VII, Attention: Chief of Air Permits, 901 N. 5th St., Kansas City, KS 66101. Additional copies to local programs or EPA are not required for application materials submitted through the electronic format specified by the Department. The application must include all emission points, emission units, air pollution control equipment, and monitoring devices at the facility. All emissions generating activities, including fugitive emissions, must be included. The definition of a complete application is as indicated in 567 IAC 22.105(2). *567 IAC 22.105*

G3. Certification Requirement for Title V Related Documents

Any application, report, compliance certification or other document submitted pursuant to this permit shall contain certification by a responsible official of truth, accuracy, and completeness. All certifications shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete. *567 IAC 22.107 (4)*

G4. Annual Compliance Certification

By March 31 of each year, the permittee shall submit compliance certifications for the previous calendar year. The certifications shall include descriptions of means to monitor the compliance status of all emissions sources including emissions limitations, standards, and work practices in accordance with applicable requirements. The certification for a source shall include the identification of each term or condition of the permit that is the basis of the certification; the

compliance status; whether compliance was continuous or intermittent; the method(s) used for determining the compliance status of the source, currently and over the reporting period consistent with all applicable department rules. For sources determined not to be in compliance at the time of compliance certification, a compliance schedule shall be submitted which provides for periodic progress reports, dates for achieving activities, milestones, and an explanation of why any dates were missed and preventive or corrective measures. The compliance certification shall be submitted to the administrator, director, and the appropriate DNR Field office. *567 IAC 22.108 (15)"e"*

G5. Semi-Annual Monitoring Report

By March 31 and September 30 of each year, the permittee shall submit a report of any monitoring required under this permit for the 6 month periods of July 1 to December 31 and January 1 to June 30, respectively. All instances of deviations from permit requirements must be clearly identified in these reports, and the report must be signed by a responsible official, consistent with *567 IAC 22.107(4)*. The semi-annual monitoring report shall be submitted to the director and the appropriate DNR Field office. *567 IAC 22.108 (5)*

G6. Annual Fee

1. The permittee is required under subrule *567 IAC 22.106* to pay an annual fee based on the total tons of actual emissions of each regulated air pollutant. Beginning July 1, 1996, Title V operating permit fees will be paid on July 1 of each year. The fee shall be based on emissions for the previous calendar year.
2. The fee amount shall be calculated based on the first 4,000 tons of each regulated air pollutant emitted each year. The fee to be charged per ton of pollutant will be available from the department by June 1 of each year. The Responsible Official will be advised of any change in the annual fee per ton of pollutant.
3. The following forms shall be submitted annually by March 31 documenting actual emissions for the previous calendar year.
 - a. Form 1.0 "Facility Identification";
 - b. Form 4.0 "Emissions unit-actual operations and emissions" for each emission unit;
 - c. Form 5.0 "Title V annual emissions summary/fee"; and
 - d. Part 3 "Application certification."
4. The fee shall be submitted annually by July 1. The fee shall be submitted with the following forms:
 - a. Form 1.0 "Facility Identification";
 - b. Form 5.0 "Title V annual emissions summary/fee";
 - c. Part 3 "Application certification."
5. If there are any changes to the emission calculation form, the department shall make revised forms available to the public by January 1. If revised forms are not available by January 1, forms from the previous year may be used and the year of emissions documented changed. The department shall calculate the total statewide Title V emissions for the prior calendar year and make this information available to the public no later than April 30 of each year.
6. Phase I acid rain affected units under section 404 of the Act shall not be required to pay a fee for emissions which occur during the years 1993 through 1999 inclusive.
7. The fee for a portable emissions unit or stationary source which operates both in Iowa and out of state shall be calculated only for emissions from the source while operating in Iowa.
8. Failure to pay the appropriate Title V fee represents cause for revocation of the Title V permit as indicated in *567 IAC 22.115(1)"d"*.

G7. Inspection of Premises, Records, Equipment, Methods and Discharges

Upon presentation of proper credentials and any other documents as may be required by law, the permittee shall allow the director or the director's authorized representative to:

1. Enter upon the permittee's premises where a Title V source is located or emissions-related activity is conducted, or where records must be kept under the conditions of the permit;
2. Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
3. Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
4. Sample or monitor, at reasonable times, substances or parameters for the purpose of ensuring compliance with the permit or other applicable requirements. *567 IAC 22.108 (15)"b"*

G8. Duty to Provide Information

The permittee shall furnish to the director, within a reasonable time, any information that the director may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee also shall furnish to the director copies of records required to be kept by the permit, or for information claimed to be confidential, the permittee shall furnish such records directly to the administrator of EPA along with a claim of confidentiality. *567 IAC 22.108 (9)"e"*

G9. General Maintenance and Repair Duties

The owner or operator of any air emission source or control equipment shall:

1. Maintain and operate the equipment or control equipment at all times in a manner consistent with good practice for minimizing emissions.
2. Remedy any cause of excess emissions in an expeditious manner.
3. Minimize the amount and duration of any excess emission to the maximum extent possible during periods of such emissions. These measures may include but not be limited to the use of clean fuels, production cutbacks, or the use of alternate process units or, in the case of utilities, purchase of electrical power until repairs are completed.
4. Schedule, at a minimum, routine maintenance of equipment or control equipment during periods of process shutdowns to the maximum extent possible. *567 IAC 24.2(1)*

G10. Recordkeeping Requirements for Compliance Monitoring

1. In addition to any source specific recordkeeping requirements contained in this permit, the permittee shall maintain the following compliance monitoring records, where applicable:
 - a. The date, place and time of sampling or measurements
 - b. The date the analyses were performed.
 - c. The company or entity that performed the analyses.
 - d. The analytical techniques or methods used.
 - e. The results of such analyses; and
 - f. The operating conditions as existing at the time of sampling or measurement.
 - g. The records of quality assurance for continuous compliance monitoring systems (including but not limited to quality control activities, audits and calibration drifts.)
2. The permittee shall retain records of all required compliance monitoring data and support information for a period of at least 5 years from the date of compliance monitoring sample, measurement report or application. Support information includes all calibration and maintenance records and all original strip chart recordings for continuous compliance monitoring, and copies of all reports required by the permit.
3. For any source which in its application identified reasonably anticipated alternative operating scenarios, the permittee shall:
 - a. Comply with all terms and conditions of this permit specific to each alternative scenario.
 - b. Maintain a log at the permitted facility of the scenario under which it is operating.
 - c. Consider the permit shield, if provided in this permit, to extend to all terms and conditions under each operating scenario. *567 IAC 22.108(4), 567 IAC 22.108(12)*

G11. Evidence used in establishing that a violation has or is occurring.

Notwithstanding any other provisions of these rules, any credible evidence may be used for the purpose of establishing whether a person has violated or is in violation of any provisions herein.

1. Information from the use of the following methods is presumptively credible evidence of whether a violation has occurred at a source:
 - a. A monitoring method approved for the source and incorporated in an operating permit pursuant to 567 Chapter 22;
 - b. Compliance test methods specified in 567 Chapter 25; or
 - c. Testing or monitoring methods approved for the source in a construction permit issued pursuant to 567 Chapter 22.
2. The following testing, monitoring or information gathering methods are presumptively credible testing, monitoring, or information gathering methods:
 - a. Any monitoring or testing methods provided in these rules; or
 - b. Other testing, monitoring, or information gathering methods that produce information comparable to that produced by any method in subrule 21.5(1) or this subrule. *567 IAC 21.5(1)-567 IAC 21.5(2)*

G12. Prevention of Accidental Release: Risk Management Plan Notification and Compliance Certification

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Act, the permittee shall notify the department of this requirement. The plan shall be filed with all appropriate authorities by the deadline specified by EPA. A certification that this risk management plan is being properly implemented shall be included in the annual compliance certification of this permit. *567 IAC 22.108(6)*

G13. Hazardous Release

The permittee must report any situation involving the actual, imminent, or probable release of a hazardous substance into the atmosphere which, because of the quantity, strength and toxicity of the substance, creates an immediate or potential danger to the public health, safety or to the environment. A verbal report shall be made to the department at (515) 281-8694 and to the local police department or the office of the sheriff of the affected county as soon as possible but not later than six hours after the discovery or onset of the condition. This verbal report must be followed up with a written report as indicated in 567 IAC 131.2(2). *567 IAC Chapter 131-State Only*

G14. Excess Emissions and Excess Emissions Reporting Requirements

1. Excess Emissions. Excess emission during a period of startup, shutdown, or cleaning of control equipment is not a violation of the emission standard if the startup, shutdown or cleaning is accomplished expeditiously and in a manner consistent with good practice for minimizing emissions. Cleaning of control equipment which does not require the shutdown of the process equipment shall be limited to one six-minute period per one-hour period. An incident of excess emission (other than an incident during startup, shutdown or cleaning of control equipment) is a violation. If the owner or operator of a source maintains that the incident of excess emission was due to a malfunction, the owner or operator must show that the conditions which caused the incident of excess emission were not preventable by reasonable maintenance and control measures. Determination of any subsequent enforcement action will be made following review of this report. If excess emissions are occurring, either the control equipment causing the excess emission shall be repaired in an expeditious manner or the process generating the emissions shall be shutdown within a reasonable period of time. An expeditious manner is the time necessary to determine the cause of the excess emissions and to correct it within a reasonable period of time. A reasonable period of time is eight hours plus the period of time required to shut down the process without damaging the process equipment or control equipment. In the case of an electric

utility, a reasonable period of time is eight hours plus the period of time until comparable generating capacity is available to meet consumer demand with the affected unit out of service, unless, the director shall, upon investigation, reasonably determine that continued operation constitutes an unjustifiable environmental hazard and issue an order that such operation is not in the public interest and require a process shutdown to commence immediately.

2. Excess Emissions Reporting

a. Oral Reporting of Excess Emissions. An incident of excess emission (other than an incident of excess emission during a period of startup, shutdown, or cleaning) shall be reported to the appropriate field office of the department within eight hours of, or at the start of the first working day following the onset of the incident. The reporting exemption for an incident of excess emission during startup, shutdown or cleaning does not relieve the owner or operator of a source with continuous monitoring equipment of the obligation of submitting reports required in 567-subrule 25.1(6). An oral report of excess emission is not required for a source with operational continuous monitoring equipment (as specified in 567-subrule 25.1(1)) if the incident of excess emission continues for less than 30 minutes and does not exceed the applicable emission standard by more than 10 percent or the applicable visible emission standard by more than 10 percent opacity. The oral report may be made in person or by telephone and shall include as a minimum the following:

- i. The identity of the equipment or source operation from which the excess emission originated and the associated stack or emission point.
- ii. The estimated quantity of the excess emission.
- iii. The time and expected duration of the excess emission.
- iv. The cause of the excess emission.
- v. The steps being taken to remedy the excess emission.
- vi. The steps being taken to limit the excess emission in the interim period.

b. Written Reporting of Excess Emissions. A written report of an incident of excess emission shall be submitted as a follow-up to all required oral reports to the department within seven days of the onset of the upset condition, and shall include as a minimum the following:

- i. The identity of the equipment or source operation point from which the excess emission originated and the associated stack or emission point.
- ii. The estimated quantity of the excess emission.
- iii. The time and duration of the excess emission.
- iv. The cause of the excess emission.
- v. The steps that were taken to remedy and to prevent the recurrence of the incident of excess emission.
- vi. The steps that were taken to limit the excess emission.
- vii. If the owner claims that the excess emission was due to malfunction, documentation to support this claim. 567 IAC 24.1(1)-567 IAC 24.1(4)

3. Emergency Defense for Excess Emissions. For the purposes of this permit, an “emergency” means any situation arising from sudden and reasonably unforeseeable events beyond the control of the source, including acts of God, which requires immediate corrective action to restore normal operation, and that causes the source to exceed a technology-based emission limitation under the permit due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include non-compliance, to the extent caused by improperly designed equipment, lack of preventive maintenance, careless or improper operation or operator error. An emergency constitutes an affirmative defense to an action brought for non-compliance with

technology based limitations if it can be demonstrated through properly signed contemporaneous operating logs or other relevant evidence that:

- a. An emergency occurred and that the permittee can identify the cause(s) of the emergency;
- b. The facility at the time was being properly operated;
- c. During the period of the emergency, the permittee took all reasonable steps to minimize levels of emissions that exceeded the emissions standards or other requirements of the permit; and
- d. The permittee submitted notice of the emergency to the director by certified mail within two working days of the time when the emissions limitations were exceeded due to the emergency. This notice must contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken. *567 IAC 22.108(16)*

G15. Permit Deviation Reporting Requirements

A deviation is any failure to meet a term, condition or applicable requirement in the permit. Reporting requirements for deviations that result in a hazardous release or excess emissions have been indicated above (see G13 and G14). Unless more frequent deviation reporting is specified in the permit, any other deviation shall be documented in the semi-annual monitoring report and the annual compliance certification (see G4 and G5). *567 IAC 22.108(5)"b"*

G16. Notification Requirements for Sources That Become Subject to NSPS and NESHAP Regulations

During the term of this permit, the permittee must notify the department of any source that becomes subject to a standard or other requirement under 567-subrule 23.1(2) (standards of performance of new stationary sources) or section 111 of the Act; or 567-subrule 23.1(3) (emissions standards for hazardous air pollutants), 567-subrule 23.1(4) (emission standards for hazardous air pollutants for source categories) or section 112 of the Act. This notification shall be submitted in writing to the department pursuant to the notification requirements in 40 CFR Section 60.7, 40 CFR Section 61.07, and/or 40 CFR Section 63.9. *567 IAC 23.1(2), 567 IAC 23.1(3), 567 IAC 23.1(4)*

G17. Requirements for Making Changes to Emission Sources That Do Not Require Title V Permit Modification

1. Off Permit Changes to a Source. Pursuant to section 502(b)(10) of the CAAA, the permittee may make changes to this installation/facility without revising this permit if:
 - a. The changes are not major modifications under any provision of any program required by section 110 of the Act, modifications under section 111 of the act, modifications under section 112 of the act, or major modifications as defined in 567 IAC Chapter 22.
 - b. The changes do not exceed the emissions allowable under the permit (whether expressed therein as a rate of emissions or in terms of total emissions);
 - c. The changes are not modifications under any provisions of Title I of the Act and the changes do not exceed the emissions allowable under the permit (whether expressed therein as a rate of emissions or as total emissions);
 - d. The changes are not subject to any requirement under Title IV of the Act.
 - e. The changes comply with all applicable requirements.
 - f. For such a change, the permitted source provides to the department and the administrator by certified mail, at least 30 days in advance of the proposed change, a written notification, including the following, which must be attached to the permit by the source, the department and the administrator:
 - i. A brief description of the change within the permitted facility,
 - ii. The date on which the change will occur,
 - iii. Any change in emission as a result of that change,

- iv. The pollutants emitted subject to the emissions trade
- v. If the emissions trading provisions of the state implementation plan are invoked, then Title V permit requirements with which the source shall comply; a description of how the emissions increases and decreases will comply with the terms and conditions of the Title V permit.
- vi. A description of the trading of emissions increases and decreases for the purpose of complying with a federally enforceable emissions cap as specified in and in compliance with the Title V permit; and
- vii. Any permit term or condition no longer applicable as a result of the change. *567 IAC 22.110(1)*

2. Such changes do not include changes that would violate applicable requirements or contravene federally enforceable permit terms and conditions that are monitoring (including test methods), record keeping, reporting, or compliance certification requirements. *567 IAC 22.110(2)*

3. Notwithstanding any other part of this rule, the director may, upon review of a notice, require a stationary source to apply for a Title V permit if the change does not meet the requirements of subrule 22.110(1). *567 IAC 22.110(3)*

4. The permit shield provided in subrule 22.108(18) shall not apply to any change made pursuant to this rule. Compliance with the permit requirements that the source will meet using the emissions trade shall be determined according to requirements of the state implementation plan authorizing the emissions trade. *567 IAC 22.110(4)*

5. No permit revision shall be required, under any approved economic incentives, marketable permits, emissions trading and other similar programs or processes, for changes that are provided for in this permit. *567 IAC 22.108(11)*

G18. Duty to Modify a Title V Permit

1. Administrative Amendment.

a. An administrative permit amendment is a permit revision that is required to do any of the following:

- i. Correct typographical errors
- ii. Identify a change in the name, address, or telephone number of any person identified in the permit, or provides a similar minor administrative change at the source;
- iii. Require more frequent monitoring or reporting by the permittee; or
- iv. Allow for a change in ownership or operational control of a source where the director determines that no other change in the permit is necessary, provided that a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new permittee has been submitted to the director.

b. The permittee may implement the changes addressed in the request for an administrative amendment immediately upon submittal of the request. The request shall be submitted to the director.

c. Administrative amendments to portions of permits containing provisions pursuant to Title IV of the Act shall be governed by regulations promulgated by the administrator under Title IV of the Act.

2. Minor Permit Modification.

a. Minor permit modification procedures may be used only for those permit modifications that do any of the following:

- i. Do not violate any applicable requirements
- ii. Do not involve significant changes to existing monitoring, reporting or

recordkeeping requirements in the Title V permit.

iii. Do not require or change a case by case determination of an emission limitation or other standard, or increment analysis.

iv. Do not seek to establish or change a permit term or condition for which there is no corresponding underlying applicable requirement and that the source has assumed in order to avoid an applicable requirement to which the source would otherwise be subject. Such terms and conditions include any federally enforceable emissions caps which the source would assume to avoid classification as a modification under any provision under Title I of the Act; and an alternative emissions limit approved pursuant to regulations promulgated under section 112(i)(5) of the Act.;

v. Are not modifications under any provision of Title I of the Act; and

vi. Are not required to be processed as significant modification.

b. An application for minor permit revision shall be on the minor Title V modification application form and shall include at least the following:

i. A description of the change, the emissions resulting from the change, and any new applicable requirements that will apply if the change occurs.

ii. The permittee's suggested draft permit

iii. Certification by a responsible official, pursuant to 567 IAC 22.107(4), that the proposed modification meets the criteria for use of a minor permit modification procedures and a request that such procedures be used; and

iv. Completed forms to enable the department to notify the administrator and the affected states as required by 567 IAC 22.107(7).

c. The permittee may make the change proposed in its minor permit modification application immediately after it files the application. After the permittee makes this change and until the director takes any of the actions specified in 567 IAC 22.112(4) "a" to "c", the permittee must comply with both the applicable requirements governing the change and the proposed permit terms and conditions. During this time, the permittee need not comply with the existing permit terms and conditions it seeks to modify. However, if the permittee fails to comply with its proposed permit terms and conditions during this time period, existing permit term terms and conditions it seeks to modify may subject the facility to enforcement action.

3. Significant Permit Modification. Significant Title V modification procedures shall be used for applications requesting Title V permit modifications that do not qualify as minor Title V modifications or as administrative amendments. These include but are not limited to all significant changes in monitoring permit terms, every relaxation of reporting or recordkeeping permit terms, and any change in the method of measuring compliance with existing requirements. Significant Title V modifications shall meet all requirements of 567 IAC Chapter 22, including those for applications, public participation, review by affected states, and review by the administrator, and those requirements that apply to Title V issuance and renewal. 567 IAC 22.111-567 IAC 22.113 The permittee shall submit an application for a significant permit modification not later than three months after commencing operation of the changed source unless the existing Title V permit would prohibit such construction or change in operation, in which event the operation of the changed source may not commence until the department revises the permit. 567 IAC 22.105(1)"a"(4)

G19. Duty to Obtain Construction Permits

Unless exempted under 567 IAC 22.1(2), the permittee must not construct, install, reconstruct, or alter any equipment, control equipment or anaerobic lagoon without first obtaining a construction permit, conditional permit, or permit pursuant to 567 IAC 22.8, or permits required

pursuant to 567 IAC 22.4 and 567 IAC 22.5. Such permits shall be obtained prior to the initiation of construction, installation or alteration of any portion of the stationary source. 567 IAC 22.1(1)

G20. Asbestos

The permittee shall comply with 567 IAC 23.1(3)"a", and 567 IAC 23.2(3)"g" when activities involve asbestos mills, surfacing of roadways, manufacturing operations, fabricating, insulating, waste disposal, spraying applications, demolition and renovation operations, training fires and controlled burning of a demolished building. 567 IAC 23.1(3)"a", and 567 IAC 23.2

G21. Open Burning

The permittee is prohibited from conducting open burning, except as may be allowed by 567 IAC 23.2. 567 IAC 23.2 *except* 23.2(3)"j"; 567 IAC 23.2(3)"j" - *State Only*

G22. Acid Rain (Title IV) Emissions Allowances

The permittee shall not exceed any allowances that it holds under Title IV of the Act or the regulations promulgated there under. Annual emissions of sulfur dioxide in excess of the number of allowances to emit sulfur dioxide held by the owners and operators of the unit or the designated representative of the owners and operators is prohibited. Exceedences of applicable emission rates are prohibited. "Held" in this context refers to both those allowances assigned to the owners and operators by USEPA, and those allowances supplementally acquired by the owners and operators. The use of any allowance prior to the year for which it was allocated is prohibited. Contravention of any other provision of the permit is prohibited. 567 IAC 22.108(7)

G23. Stratospheric Ozone and Climate Protection (Title VI) Requirements

1. The permittee shall comply with the standards for labeling of products using ozone-depleting substances pursuant to 40 CFR Part 82, Subpart E:

- a. All containers in which a class I or class II substance is stored or transported, all products containing a class I substance, and all products directly manufactured with a class I substance must bear the required warning statement if it is being introduced into interstate commerce pursuant to § 82.106.
- b. The placement of the required warning statement must comply with the requirements pursuant to § 82.108.
- c. The form of the label bearing the required warning statement must comply with the requirements pursuant to § 82.110.
- d. No person may modify, remove, or interfere with the required warning statement except as described in § 82.112.

2. The permittee shall comply with the standards for recycling and emissions reduction pursuant to 40 CFR Part 82, Subpart F, except as provided for MVACs in Subpart B:

- a. Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to § 82.156.
- b. Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to § 82.158.
- c. Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to § 82.161.
- d. Persons disposing of small appliances, MVACs, and MVAC-like appliances must comply with reporting and recordkeeping requirements pursuant to § 82.166. ("MVAC-like appliance" as defined at § 82.152)
- e. Persons owning commercial or industrial process refrigeration equipment must comply with the leak repair requirements pursuant to § 82.156.
- f. Owners/operators of appliances normally containing 50 or more pounds of refrigerant must keep records of refrigerant purchased and added to such appliances pursuant to § 82.166.

3. If the permittee manufactures, transforms, imports, or exports a class I or class II substance, the permittee is subject to all the requirements as specified in 40 CFR part 82, Subpart A, Production and Consumption Controls.

4. If the permittee performs a service on motor (fleet) vehicles when this service involves ozone-depleting substance refrigerant (or regulated substitute substance) in the motor vehicle air conditioner (MVAC), the permittee is subject to all the applicable requirements as specified in 40 CFR part 82, Subpart B, Servicing of Motor Vehicle Air Conditioners. The term "motor vehicle" as used in Subpart B does not include a vehicle in which final assembly of the vehicle has not been completed. The term "MVAC" as used in Subpart B does not include the air-tight sealed refrigeration system used as refrigerated cargo, or system used on passenger buses using HCFC-22 refrigerant,

5. The permittee shall be allowed to switch from any ozone-depleting substance to any alternative that is listed in the Significant New Alternatives Program (SNAP) promulgated pursuant to 40 CFR part 82, Subpart G, Significant New Alternatives Policy Program. *40 CFR part 82*

G24. Permit Reopenings

1. This permit may be modified, revoked, reopened, and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition. *567 IAC 22.108(9)"c"*

2. Additional applicable requirements under the Act become applicable to a major part 70 source with a remaining permit term of 3 or more years. Revisions shall be made as expeditiously as practicable, but not later than 18 months after the promulgation of such standards and regulations.

a. Reopening and revision on this ground is not required if the permit has a remaining term of less than three years;

b. Reopening and revision on this ground is not required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions have been extended pursuant to 40 CFR 70.4(b)(10)(i) or (ii) as amended to May 15, 2001.

c. Reopening and revision on this ground is not required if the additional applicable requirements are implemented in a general permit that is applicable to the source and the source receives approval for coverage under that general permit. *567 IAC 22.108(17)"a", 567 IAC 22.108(17)"b"*

3. A permit shall be reopened and revised under any of the following circumstances:

a. The department receives notice that the administrator has granted a petition for disapproval of a permit pursuant to 40 CFR 70.8(d) as amended to July 21, 1992, provided that the reopening may be stayed pending judicial review of that determination;

b. The department or the administrator determines that the Title V permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of the Title V permit;

c. Additional applicable requirements under the Act become applicable to a Title V source, provided that the reopening on this ground is not required if the permit has a remaining term of less than three years, the effective date of the requirement is later than the date on which the permit is due to expire, or the additional applicable requirements are implemented in a general permit that is applicable to the source and the source receives approval for coverage under that general permit. Such a reopening shall be complete not later than 18 months after promulgation of the applicable requirement.

d. Additional requirements, including excess emissions requirements, become applicable

to a Title IV affected source under the acid rain program. Upon approval by the administrator, excess emissions offset plans shall be deemed to be incorporated into the permit.

e. The department or the administrator determines that the permit must be revised or revoked to ensure compliance by the source with the applicable requirements. *567 IAC 22.114(1)*

4. Proceedings to reopen and reissue a Title V permit shall follow the procedures applicable to initial permit issuance and shall effect only those parts of the permit for which cause to reopen exists. *567 IAC 22.114(2)*

G25. Permit Shield

1. The director may expressly include in a Title V permit a provision stating that compliance with the conditions of the permit shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that:

a. Such applicable requirements are included and are specifically identified in the permit; or

b. The director, in acting on the permit application or revision, determines in writing that other requirements specifically identified are not applicable to the source, and the permit includes the determination or a concise summary thereof.

2. A Title V permit that does not expressly state that a permit shield exists shall be presumed not to provide such a shield.

3. A permit shield shall not alter or affect the following:

a. The provisions of Section 303 of the Act (emergency orders), including the authority of the administrator under that section;

b. The liability of an owner or operator of a source for any violation of applicable requirements prior to or at the time of permit issuance;

c. The applicable requirements of the acid rain program, consistent with Section 408(a) of the Act;

d. The ability of the department or the administrator to obtain information from the facility pursuant to Section 114 of the Act. *567 IAC 22.108 (18)*

G26. Severability

The provisions of this permit are severable and if any provision or application of any provision is found to be invalid by this department or a court of law, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected by such finding. *567 IAC 22.108 (8)*

G27. Property Rights

The permit does not convey any property rights of any sort, or any exclusive privilege. *567 IAC 22.108 (9)"d"*

G28. Transferability

This permit is not transferable from one source to another. If title to the facility or any part of it is transferred, an administrative amendment to the permit must be sought to determine transferability of the permit. *567 IAC 22.111 (1)"d"*

G29. Disclaimer

No review has been undertaken on the engineering aspects of the equipment or control equipment other than the potential of that equipment for reducing air contaminant emissions. *567 IAC 22.3(3)"c"*

G30. Notification and Reporting Requirements for Stack Tests or Monitor Certification

The permittee shall notify the department's stack test contact in writing not less than 30 days before a required test or performance evaluation of a continuous emission monitor is performed to determine compliance with applicable requirements of 567 – Chapter 23 or a permit condition.

For the department to consider test results a valid demonstration of compliance with applicable rules or a permit condition, such notice shall be given. Such notice shall include the time, the place, the name of the person who will conduct the test and other information as required by the department. Unless specifically waived by the department's stack test contact, a pretest meeting shall be held not later than 15 days prior to conducting the compliance demonstration. The department may accept a testing protocol in lieu of a pretest meeting. A representative of the department shall be permitted to witness the tests. Results of the tests shall be submitted in writing to the department's stack test contact in the form of a comprehensive report within six weeks of the completion of the testing. Compliance tests conducted pursuant to this permit shall be conducted with the source operating in a normal manner at its maximum continuous output as rated by the equipment manufacturer, or the rate specified by the owner as the maximum production rate at which the source shall be operated. In cases where compliance is to be demonstrated at less than the maximum continuous output as rated by the equipment manufacturer, and it is the owner's intent to limit the capacity to that rating, the owner may submit evidence to the department that the source has been physically altered so that capacity cannot be exceeded, or the department may require additional testing, continuous monitoring, reports of operating levels, or any other information deemed necessary by the department to determine whether such source is in compliance.

Stack test notifications, reports and correspondence shall be sent to:

Stack Test Review Coordinator
Iowa DNR, Air Quality Bureau
7900 Hickman Road, Suite #1
Windsor Heights, IA 50324
(515) 242-6001

Within Polk and Linn Counties, stack test notifications, reports and correspondence shall also be directed to the supervisor of the respective county air pollution program.

567 IAC 25.1(7)"a", 567 IAC 25.1(9)

G31. Prevention of Air Pollution Emergency Episodes

The permittee shall comply with the provisions of 567 IAC Chapter 26 in the prevention of excessive build-up of air contaminants during air pollution episodes, thereby preventing the occurrence of an emergency due to the effects of these contaminants on the health of persons.

567 IAC 26.1(1)

G32. Contacts List

The current address and phone number for reports and notifications to the EPA administrator is:

Chief of Air Permits
EPA Region 7
Air Permits and Compliance Branch
901 N. 5th Street
Kansas City, KS 66101
(913) 551-7020

The current address and phone number for reports and notifications to the department or the Director is:

Chief, Air Quality Bureau
Iowa Department of Natural Resources
7900 Hickman Road, Suite #1
Windsor Heights, IA 50324
(515) 242-5100

Reports or notifications to the DNR Field Offices or local programs shall be directed to the supervisor at the appropriate field office or local program. Current addresses and phone numbers are:

Field Office 1

909 West Main – Suite 4
Manchester, IA 52057
(563) 927-2640

Field Office 2

2300-15th St., SW
Mason City, IA 50401
(641) 424-4073

Field Office 3

1900 N. Grand Ave.
Spencer, IA 51301
(712) 262-4177

Field Office 4

1401 Sunnyside Lane
Atlantic, IA 50022
(712) 243-1934

Field Office 5

401 SW 7th Street, Suite I
Des Moines, IA 50309
(515) 725-0268

Field Office 6

1023 West Madison Street
Washington, IA 52353-1623
(319) 653-2135

Polk County Public Works Dept.

Air Quality Division
5885 NE 14th St.
Des Moines, IA 50313
(515) 286-3351

Linn County Public Health Dept.

Air Pollution Control Division
501 13th St., NW
Cedar Rapids, IA 52405
(319) 892-6000

Appendix A: Compliance Assurance Monitoring Plan

COMPLIANCE ASSURANCE MONITORING (CAM) PLAN BAGHOUSES FOR PARTICULATE (PM/PM10) CONTROL

I. Background

A. Emissions Unit

Description: Baghouses for PM/PM₁₀ Control (See CAM Applicability Table)
Identification: EP9, EP29, EP40, EP41, EP50, EP56, EP57, EP62

B. Applicable Regulation, Emission Limit and Pre-CAM Monitoring Requirements

Regulation: See CAM Applicability Table
CAM Emission Limits: See CAM Applicability Table
Pre-CAM Monitoring: Weekly Visible Emissions Observations / Pressure Drops

C. Control Technology, Capture System, Bypass, Potential-to-Emit (PTE)

Controls: Baghouses
Capture System: Closed Dust Systems or Hood Collection Points
Bypass: None of these units are configured to allow bypass of the control device
PTE Before Control: See CAM Applicability Table
PTE After Control: See CAM Applicability Table

II. Monitoring Approach

A. Indicators

Presence of visible emissions is the primary indicator for these sources. Normal process operations will not produce conditions that adversely affect the function of the baghouses, so no process operational parameters will be monitored. For those equipped baghouses, pressure drop across the filters will be monitored on a weekly basis as a secondary operating parameter.

B. Measurement Approach & Frequency

A trained employee familiar with normal process operations and the appearance of the exhaust from each source is responsible for observing and recording visible emissions observations on a daily basis. Pressure drop across the baghouse is recorded on a weekly basis as a means to judge the dust "cake" on the bags and verify that the bags are not being unduly worn.

C. Indicator Range

The presence of any visible emissions would be considered an excursion and trigger the operator to take corrective actions.

D. Performance Criteria

Data Representativeness: The presence of any visible emissions from a properly maintained and operating baghouse is an appropriate indicator that a bag rupture or leak is occurring and that corrective action is necessary.

QA/QC Practices and Criteria: Employees performing visible emissions observations are trained on observing the source under the appropriate conditions (e.g lighting, sun position, etc.) and have a detailed understanding of the proper operation of the affected sources. The records of the emissions observations are periodically reviewed by the facility environmental coordinator to verify that the notations are being kept properly.

III. Response to Excursions

Upon observing visible emissions, an operator will check the pressure drop, pulsing system, and the baghouse housing. If these checks do not allow the operator to correct the visible emissions, maintenance will be notified immediately. A complete maintenance inspection will be initiated within 12 hours of the observation and the necessary repairs will be made as soon as judged practical by facility management and environmental staff.